


Amrit Science Campus
Thamel, Kathmandu
AFFILIATED WITH TU



Simulation and Modeling 5th Semester Lab Report 2082



Submitted By:

Bishnu Chalise

Roll no: 79010174

Section: A

Shift: Morning

Internal Examiner

Submitted To:

Arjun Gautam

Simulation and
Modeling Professor

-ASCOL

External Examiner

Index

S.N.	Labs	Date	Signature
1.	Implementation of Bubble , Selection and Insertion Sort :		
2.	Implementation of Merge Sort :		
3.	Implementation of Quick Sort :		
4.	Implementation of Randomized Quick Sort		
5.	Implementation of 0/1 Knapsack problem using Dynamic approach		
6.	Implementation Of Matrix chain Multiplication Problem		
7.	Implementation of String Editing		
8.	Program for Floyd Warshall Algorithm		
9.	Program for Dijkstra's single source shortest path		
10.	Program to solve fractional Knapsack Problem		
11.	Program to solve N Queen Problem using backtracking		
12.	Kruskal's algorithm to find Minimum Spanning Tree of a given connected, undirected graph		
13.	Program for Prim's Minimum		
14.	Implementation of Subset sum problem		
15.	Implementation of job sequence in deadlines		

Lab 1 : Implementation of Bubble , Selection and Insertion Sort

Bubble Sort

Source Code :

```
#include <stdio.h>
```

```
int main() {
    int arr[] = {64, 25, 12, 22, 11};
    int n = sizeof(arr) / sizeof(arr[0]), step_count = 0;

    printf("Before: ");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    putchar('\n');
    for (int i = 0; i < n; i++) {
        int swapped = 0;
        for (int j = 0; j < n - i - 1; j++) {
            step_count++;
            if (arr[j] > arr[j + 1]) {
                int temp = arr[j];
                arr[j] = arr[j + 1];
                arr[j + 1] = temp;
                swapped = 1;
            }
        }
        if (!swapped)
            break;
    }

    printf("After:");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    printf("\nSteps: %d\n", step_count);

    return 0;
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='1a'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Before: 64 25 12 22 11
After:11 12 22 25 64
Steps: 10
```

Selection Sort :

Source Code :

```
#include <stdio.h>


int main() {
    int arr[] = {64, 25, 12, 22, 11};
    int n = sizeof(arr) / sizeof(arr[0]), step_count = 0;

    printf("Before: ");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    putchar('\n');
    for (int i = 0; i < n - 1; i++) {
        int min = i;
        for (int j = i + 1; j < n; j++) {
            step_count++;
            if (arr[j] < arr[min])
                min = j;
        }
        if (min != i) {
            int t = arr[i];
            arr[i] = arr[min];
            arr[min] = t;
        }
    }

    printf("After:");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    printf("\nSteps: %d\n", step_count);

    return 0;
}
```

OUTPUT:



```
rudy@rudy:~/bishnu-chalise$ n='1b'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Before: 64 25 12 22 11
After: 11 12 22 25 64
Steps: 10
```

Insertion sort :

Source Code :

```
#include <stdio.h>

int main() {
    int arr[] = {64, 25, 12, 22, 11};
    int n = sizeof(arr) / sizeof(arr[0]), step_count = 0;

    printf("Before: ");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    putchar('\n');
    for (int i = 1; i < n; i++) {
        int key = arr[i], j = i - 1;
        while (j >= 0 && arr[j] > key) {
            step_count++;
            arr[j + 1] = arr[j];
            j--;
        }
        if (j >= 0)
            step_count++;
        arr[j + 1] = key;
    }

    printf("After: ");
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    printf("\nSteps: %d\n", step_count);

    return 0;
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='1c'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Before: 64 25 12 22 11
After: 11 12 22 25 64
Steps: 10
```

Lab2 : Implementation of Merge Sort

Source Code :

```
#include <stdio.h>

int step_count = 0;

void merge(int a[], int l, int m, int r) {
    int n1 = m - l + 1, n2 = r - m;
    int L[n1], R[n2];
    for (int i = 0; i < n1; i++)
        L[i] = a[l + i];
    for (int i = 0; i < n2; i++)
        R[i] = a[m + 1 + i];
    int i = 0, j = 0, k = l;
    while (i < n1 && j < n2) {
        step_count++;
        if (L[i] <= R[j])
            a[k++] = L[i++];
        else
            a[k++] = R[j++];
    }
    while (i < n1)
        a[k++] = L[i++];
    while (j < n2)
        a[k++] = R[j++];
}

void merge_sort(int a[], int l, int r) {
    if (l < r) {
        int m = (l + r) / 2;
        merge_sort(a, l, m);
        merge_sort(a, m + 1, r);
        merge(a, l, m, r);
    }
}

int main() {
    int a[] = {64, 25, 12, 22, 11};
    int n = sizeof(a) / sizeof(a[0]);

    printf("Before: ");
    for (int i = 0; i < n; i++)
        printf("%d ", a[i]);
    putchar('\n');
```

```
merge_sort(a, 0, n - 1);

printf("After: ");
for (int i = 0; i < n; i++)
    printf("%d ", a[i]);
printf("\nSteps: %d\n", step_count);

return 0;
}
```

OUTPUT:



```
o rudy@rudy:~/bishnu-chalise$ n='2'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Before: 64 25 12 22 11
After: 11 12 22 25 64
Steps: 6
```

Lab3 : Implementation of Quick Sort :

```
#include <stdio.h>
```

```
int step_count = 0;
```

```
int partition(int a[], int low, int high) {  
    int p = a[high], i = low - 1;  
    for (int j = low; j < high; j++) {  
        step_count++;  
        if (a[j] < p) {  
            int t = a[++i];  
            a[i] = a[j];  
            a[j] = t;  
        }  
    }  
    int t = a[i + 1];  
    a[i + 1] = a[high];  
    a[high] = t;  
    return i + 1;  
}
```

```
void quick_sort(int a[], int low, int high) {  
    if (low < high) {  
        int pi = partition(a, low, high);  
        quick_sort(a, low, pi - 1);  
        quick_sort(a, pi + 1, high);  
    }  
}
```

```
int main() {  
    int a[] = {64, 25, 12, 22, 11};  
    int n = sizeof(a) / sizeof(a[0]);  
  
    printf("Before: ");  
    for (int i = 0; i < n; i++)  
        printf("%d ", a[i]);  
    putchar('\n');
```



```
quick_sort(a, 0, n - 1);

printf("After: ");
for (int i = 0; i < n; i++)
    printf("%d ", a[i]);
printf("\nSteps: %d\n", step_count);

return 0;
}
```

OUTPUT:

```
rudy@rudy:~/Desktop/5sem/bishnu-chalise/daa$ n='3'; gcc files/${n}.c -o /tmp/a.out &&
/tmp/a.out && ssc output/${n}.png
Before: 64 25 12 22 11
After: 11 12 22 25 64
Steps: 9
█
```

Lab4 : Implementation of Randomized Quick Sort

```
#include <stdio.h>
#include <stdlib.h>

int step_count = 0;

int partition(int a[], int l, int h) {
    int p = a[h], i = l - 1;
    for (int j = l; j < h; j++) {
        step_count++;
        if (a[j] < p) {
            int t = a[++i];
            a[i] = a[j];
            a[j] = t;
        }
    }
    int t = a[i + 1];
    a[i + 1] = a[h];
    a[h] = t;
    return i + 1;
}

int rand_partition(int a[], int l, int h) {
    int r = l + rand() % (h - l + 1);
    int t = a[r];
    a[r] = a[h];
    a[h] = t;
    return partition(a, l, h);
}

void quick_sort(int a[], int l, int h) {
    if (l < h) {
        int pi = rand_partition(a, l, h);
        quick_sort(a, l, pi - 1);
        quick_sort(a, pi + 1, h);
    }
}

int main() {
    int a[] = {64, 25, 12, 22, 11};
    int n = sizeof(a) / sizeof(a[0]);

    printf("Before: ");
    for (int i = 0; i < n; i++)
```

```
    printf("%d ", a[i]);  
    putchar('\n');  
  
    quick_sort(a, 0, n - 1);  
  
    printf("After: ");  
    for (int i = 0; i < n; i++)  
        printf("%d ", a[i]);  
    printf("\nSteps: %d\n", step_count);  
  
    return 0;  
}
```

OUTPUT:

```
rudy@rudy:~/Desktop/5sem/bishnu-chalise/daa$ n='4'; gcc files/${n}.c -o /tmp/a.out &&  
./tmp/a.out && ssc output/${n}.png  
Before: 64 25 12 22 11  
After: 11 12 22 25 64  
Steps: 6  
□
```

Lab5 : implementation of 0/1 Knapsack problem using Dynamic approach

```
#include <stdio.h>
```

```
int max(int a, int b) { return a > b ? a : b; }
```

```
int main() {
    int n, cap;
    printf("Enter number of items and capacity: ");
    scanf("%d %d", &n, &cap);
    int w[n], p[n], dp[n + 1][cap + 1];

    printf("Enter weights: ");
    for (int i = 0; i < n; i++)
        scanf("%d", &w[i]);
    printf("Enter profits: ");
    for (int i = 0; i < n; i++)
        scanf("%d", &p[i]);

    for (int i = 0; i <= n; i++)
        for (int j = 0; j <= cap; j++) {
            if (i == 0 || j == 0)
                dp[i][j] = 0;
            else if (w[i - 1] <= j)
                dp[i][j] = max(p[i - 1] + dp[i - 1][j - w[i - 1]], dp[i - 1][j]);
            else
                dp[i][j] = dp[i - 1][j];
        }

    printf("Table:\n");
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= cap; j++)
            printf("%2d ", dp[i][j]);
        putchar('\n');
    }

    printf("Max Profit: %d\n", dp[n][cap]);
    return 0;
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='5'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter number of items and capacity: 4 5
Enter weights: 2 3 4 5
Enter profits: 3 4 5 6
Table:
0 0 0 0 0 0
0 0 3 3 3 3
0 0 3 4 4 7
0 0 3 4 5 7
0 0 3 4 5 7
Max Profit: 7
```

Lab 6: implementation Of Matrix chain Multiplication Problem

```
#include <stdio.h>
```

```
int main() {
    int n, step = 0;
    printf("Enter number of matrices: ");
    scanf("%d", &n);
    int d[n + 1];
    printf("Enter dimensions: ");
    for (int i = 0; i <= n; i++)
        scanf("%d", &d[i]);

    int m[n][n];
    for (int i = 0; i < n; i++)
        m[i][i] = 0;

    for (int L = 2; L <= n; L++) {
        for (int i = 0; i <= n - L; i++) {
            int j = i + L - 1;
            m[i][j] = 1e9;
            for (int k = i; k < j; k++) {
                step++;
                int cost = m[i][k] + m[k + 1][j] + d[i] * d[k + 1] * d[j + 1];
                if (cost < m[i][j])
                    m[i][j] = cost;
            }
        }
    }

    printf("Table:\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++)
            if (j < i)
                printf(" - ");
            else
                printf("%3d ", m[i][j]);
        putchar('\n');
    }

    printf("Min Multiplications: %d\n", m[0][n - 1]);
    printf("Steps: %d\n", step);
    return 0;
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='6'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter number of matrices: 4
Enter dimensions: 10 20 30 40 50
Table:
  0 6000 18000 38000
-  0 24000 64000
- -  0 60000
- - -  0
Min Multiplications: 38000
Steps: 10
```

Lab 7 : Implementation of Dynamic Programming based C++ program to find minimum number operations to convert str1 to str2

```
#include <stdio.h>
#include <string.h>

int min(int a, int b, int c) {
    return a < b ? (a < c ? a : c) : (b < c ? b : c);
}

int main() {
    char str1[100], str2[100];
    printf("Enter first string: ");
    scanf("%s", str1);
    printf("Enter second string: ");
    scanf("%s", str2);

    int m = strlen(str1), n = strlen(str2);
    int dp[m + 1][n + 1];

    for (int i = 0; i <= m; i++)
        dp[i][0] = i;
    for (int j = 0; j <= n; j++)
        dp[0][j] = j;

    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {
            if (str1[i - 1] == str2[j - 1])
                dp[i][j] = dp[i - 1][j - 1];
            else
                dp[i][j] = 1 + min(dp[i - 1][j - 1], dp[i - 1][j], dp[i][j - 1]);
        }
    }

    printf("Minimum operations: %d\n", dp[m][n]);
    return 0;
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='7'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter first string: cafe
Enter second string: leaf
Minimum operations: 3
█
```


Lab 8: Program for Floyd Warshall Algorithm

```
#include <stdio.h>
```

```
int main() {
```

```
    int n, step = 0;
```

```
    printf("Enter number of vertices: ");
```

```
    scanf("%d", &n);
```

```
    int dist[n][n];
```

```
    printf("Enter the adjacency matrix (use a large number for infinity):\n");
```

```
    for (int i = 0; i < n; i++)
```

```
        for (int j = 0; j < n; j++)
```

```
            scanf("%d", &dist[i][j]);
```

```
    for (int k = 0; k < n; k++) {
```

```
        for (int i = 0; i < n; i++) {
```

```
            for (int j = 0; j < n; j++) {
```

```
                step++;
```

```
                if (dist[i][j] > dist[i][k] + dist[k][j])
```

```
                    dist[i][j] = dist[i][k] + dist[k][j];
```

```
            }
```

```
        }
```

```
    }
```

```
    printf("Shortest paths matrix:\n");
```

```
    for (int i = 0; i < n; i++) {
```

```
        for (int j = 0; j < n; j++)
```

```
            printf("%4d ", dist[i][j]);
```

```
        putchar('\n');
```

```
    }
```

```
    printf("Steps: %d\n", step);
```

```
    return 0;
```

```
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='8'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter number of vertices: 4
Enter the adjacency matrix (use a large number for infinity):
0 3 999 7
8 0 2 999
5 999 0 1
2 999 3 0
Shortest paths matrix:
  0   3   5   6
  5   0   2   3
  3   6   0   1
  2   5   3   0
Steps: 64
```

Lab 9: program for Dijkstra's single source shortest path

```
#include <limits.h>
```

```
#include <stdio.h>
```

```
#define INF INT_MAX
```

```
int min_distance(int dist[], int spt_set[], int n) {  
    int min = INF, min_index;  
    for (int v = 0; v < n; v++) {  
        if (spt_set[v] == 0 && dist[v] <= min) {  
            min = dist[v];  
            min_index = v;  
        }  
    }  
    return min_index;  
}
```

```
int main() {  
    int n, source, step = 0;  
    printf("Enter number of vertices: ");  
    scanf("%d", &n);
```

```
    int graph[n][n], dist[n], spt_set[n];
```

```
    printf("Enter the adjacency matrix (use a large number for infinity):\n");  
    for (int i = 0; i < n; i++)  
        for (int j = 0; j < n; j++)  
            scanf("%d", &graph[i][j]);
```

```
    printf("Enter the source vertex (0-based index): ");  
    scanf("%d", &source);
```

```
    for (int i = 0; i < n; i++) {  
        dist[i] = INF;  
        spt_set[i] = 0;  
    }  
    dist[source] = 0;
```

```
    for (int count = 0; count < n - 1; count++) {  
        int u = min_distance(dist, spt_set, n);  
        spt_set[u] = 1;
```

```
        for (int v = 0; v < n; v++) {  
            step++;
```

```

        if (!spt_set[v] && graph[u][v] != INF && dist[u] != INF &&
            dist[u] + graph[u][v] < dist[v]) {
            dist[v] = dist[u] + graph[u][v];
        }
    }
}

printf("Shortest distances from source vertex %d:\n", source);
for (int i = 0; i < n; i++) {
    if (dist[i] == INF)
        printf("Vertex %d: INF\n", i);
    else
        printf("Vertex %d: %d\n", i, dist[i]);
}

printf("Steps: %d\n", step);
return 0;
}

```

OUTPUT:

```

o rudy@rudy:~/bishnu-chalise$ n='9'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter number of vertices: 5
Enter the adjacency matrix (use a large number for infinity):
0 10 999 30 999
10 0 50 999 10
999 50 0 10 60
30 999 10 0 40
999 10 60 40 0
Enter the source vertex (0-based index): 0
Shortest distances from source vertex 0:
Vertex 0: 0
Vertex 1: 10
Vertex 2: 40
Vertex 3: 30
Vertex 4: 20
Steps: 20

```

Lab 10 : Program to solve fractional Knapsack Problem Source Co

```
#include <stdio.h>
```

```
typedef struct {  
    int weight;  
    int value;  
    float ratio;  
} Item;
```

```
int main() {  
    int n, capacity, step = 0;  
    printf("Enter number of items and capacity of knapsack: ");  
    scanf("%d %d", &n, &capacity);
```

```
    Item items[n];  
    for (int i = 0; i < n; i++) {  
        printf("Enter weight and value for item %d: ", i + 1);  
        scanf("%d %d", &items[i].weight, &items[i].value);  
        items[i].ratio = (float)items[i].value / items[i].weight;  
    }
```

```
    for (int i = 0; i < n - 1; i++) {  
        for (int j = i + 1; j < n; j++) {  
            step++;  
            if (items[i].ratio < items[j].ratio) {  
                Item temp = items[i];  
                items[i] = items[j];  
                items[j] = temp;  
            }  
        }  
    }
```

```
    int totalValue = 0;  
    float totalWeight = 0.0;
```

```
    for (int i = 0; i < n; i++) {  
        if (totalWeight + items[i].weight <= capacity) {  
            totalWeight += items[i].weight;  
            totalValue += items[i].value;  
        } else {  
            int remainingWeight = capacity - totalWeight;  
            totalValue += items[i].value * ((float)remainingWeight / items[i].weight);  
            break;  
        }  
    }
```

```
    }  
}  
  
printf("Maximum value in Knapsack = %d\n", totalValue);  
printf("Steps: %d\n", step);  
return 0;  
}
```

OUTPUT:

```
o rudy@rudy:~/bishnu-chalise$ n='10'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png  
Enter number of items and capacity of knapsack: 4 50  
Enter weight and value for item 1: 10 60  
Enter weight and value for item 2: 20 100  
Enter weight and value for item 3: 30 120  
Enter weight and value for item 4: 40 240  
Maximum value in Knapsack = 300  
Steps: 6  
█
```

Lab 11: program to solve N Queen Problem using backtracking

```
#include <stdio.h>
```

```
int step = 0;
```

```
int is_safe(int board[][10], int row, int col, int n) {  
    for (int i = 0; i < row; i++) {  
        if (board[i][col] == 1)  
            return 0;  
        if (col - (row - i) >= 0 && board[i][col - (row - i)] == 1)  
            return 0;  
        if (col + (row - i) < n && board[i][col + (row - i)] == 1)  
            return 0;  
    }  
    return 1;  
}
```

```
int solve_nqueens(int board[][10], int row, int n) {  
    step++;  
    if (row == n)  
        return 1;  
  
    for (int col = 0; col < n; col++) {  
        if (is_safe(board, row, col, n)) {  
            board[row][col] = 1;  
            if (solve_nqueens(board, row + 1, n))  
                return 1;  
            board[row][col] = 0;  
        }  
    }  
    return 0;  
}
```

```
int main() {  
    int n;  
    printf("Enter the value of N: ");  
    scanf("%d", &n);  
  
    int board[10][10] = {0};  
  
    if (solve_nqueens(board, 0, n)) {  
        printf("Solution:\n");  
        for (int i = 0; i < n; i++) {  
            for (int j = 0; j < n; j++) {
```

```

        printf("%d ", board[i][j]);
    }
    printf("\n");
}
printf("Steps: %d\n", step);
} else {
    printf("No solution exists\n");
}

return 0;
}

```

OUTPUT:

```

o rudy@rudy:~/bishnu-chalise$ n='11'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter the value of N: 4
Solution:
0 1 0 0
0 0 0 1
1 0 0 0
0 0 1 0
Steps: 9

```

Lab12 : Kruskal's algorithm to find Minimum Spanning Tree of a connected, undirected graph

```
#include <stdio.h>
#include <stdlib.h>
```

```
#define MAX 10
```

```
typedef struct {
    int u, v, weight;
} Edge;
```

```
int parent[MAX], rank[MAX];
```

```
int find(int i) {
    if (parent[i] != i)
        parent[i] = find(parent[i]);
    return parent[i];
}
```

```
void union_set(int u, int v) {
    int root_u = find(u);
    int root_v = find(v);
```

```
    if (root_u != root_v) {
        if (rank[root_u] > rank[root_v]) {
            parent[root_v] = root_u;
        } else if (rank[root_u] < rank[root_v]) {
            parent[root_u] = root_v;
        } else {
            parent[root_v] = root_u;
            rank[root_u]++;
        }
    }
}
```

```
int compare(const void *a, const void *b) {
    return ((Edge *)a)->weight - ((Edge *)b)->weight;
}
```

```
int main() {
    int n, m, total_weight = 0, steps = 0;
```

```
    printf("Enter the number of vertices and edges: ");
```



```

scanf("%d %d", &n, &m);

Edge edges[m];

for (int i = 0; i < n; i++) {
    parent[i] = i;
    rank[i] = 0;
}

printf("Enter the edges (u v weight):\n");
for (int i = 0; i < m; i++) {
    scanf("%d %d %d", &edges[i].u, &edges[i].v, &edges[i].weight);
}

qsort(edges, m, sizeof(Edge), compare);

printf("Minimum Spanning Tree (MST) edges:\n");
for (int i = 0; i < m; i++) {
    steps++;
    int u = edges[i].u;
    int v = edges[i].v;
    int weight = edges[i].weight;

    if (find(u) != find(v)) {
        union_set(u, v);
        total_weight += weight;
        printf("%d - %d: %d\n", u, v, weight);
    }
}

printf("Total weight of MST: %d\n", total_weight);
printf("Steps: %d\n", steps);

return 0;
}

```

OUTPUT:

```

• rudy@rudy:~/bishnu-chalise$ n='12'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter the number of vertices and edges: 4 5
Enter the edges (u v weight):
0 1 10
0 2 6
0 3 5
1 3 15
2 3 4
Minimum Spanning Tree (MST) edges:
2 - 3: 4
0 - 3: 5
0 - 1: 10
Total weight of MST: 19
Steps: 5

```

Lab 13 :program for Prim's Minimum spanning tree

```
#include <limits.h>
#include <stdio.h>
```

```
#define MAX 10
```

```
int minKey(int key[], int mstSet[], int n) {
    int min = INT_MAX, minIndex;
    for (int v = 0; v < n; v++) {
        if (mstSet[v] == 0 && key[v] < min) {
            min = key[v];
            minIndex = v;
        }
    }
    return minIndex;
}
```

```
void primMST(int graph[MAX][MAX], int n) {
    int parent[n];
    int key[n];
    int mstSet[n];
    int totalWeight = 0, steps = 0;
```

```
    for (int i = 0; i < n; i++) {
        key[i] = INT_MAX;
        mstSet[i] = 0;
    }
```

```
    key[0] = 0;
    parent[0] = -1;
```

```
    for (int count = 0; count < n - 1; count++) {
        int u = minKey(key, mstSet, n);
        mstSet[u] = 1;
        steps++;
```

```
        for (int v = 0; v < n; v++) {
            if (graph[u][v] && mstSet[v] == 0 && graph[u][v] < key[v]) {
                key[v] = graph[u][v];
                parent[v] = u;
            }
        }
    }
}
```

```

printf("Minimum Spanning Tree (MST) edges:\n");
for (int i = 1; i < n; i++) {
    printf("%d - %d: %d\n", parent[i], i, graph[i][parent[i]]);
    totalWeight += graph[i][parent[i]];
}

printf("Total weight of MST: %d\n", totalWeight);
printf("Steps: %d\n", steps);
}

int main() {
    int n;

    printf("Enter the number of vertices: ");
    scanf("%d", &n);

    int graph[MAX][MAX];
    printf("Enter the adjacency matrix of the graph:\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    primMST(graph, n);

    return 0;
}

```

OUTPUT:

```

o rudy@rudy:~/bishnu-chalise$ n='13'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter the number of vertices: 5
Enter the adjacency matrix of the graph:
0 2 0 6 0
2 0 3 8 5
0 3 0 0 7
6 8 0 9 0
0 5 7 0 0
Minimum Spanning Tree (MST) edges:
0 - 1: 2
1 - 2: 3
0 - 3: 6
1 - 4: 5
Total weight of MST: 16
Steps: 4

```

Lab 14 : implementation of Subset sum problem

```
#include <stdio.h>
```

```
#define MAX 20
```

```
int count = 0;
```

```
void findSubsetSum(int set[], int n, int target, int index, int current[],
                  int current_size) {
    if (index == n) {
        int sum = 0;
        for (int i = 0; i < current_size; i++) {
            sum += current[i];
        }
        if (sum == target) {
            count++;
            printf("Subset %d: {", count);
            for (int i = 0; i < current_size; i++) {
                printf("%d", current[i]);
                if (i < current_size - 1)
                    printf(", ");
            }
            printf("}\n");
        }
        return;
    }
}
```

```
    current[current_size] = set[index];
```

```
    findSubsetSum(set, n, target, index + 1, current, current_size + 1);
```

```
    findSubsetSum(set, n, target, index + 1, current, current_size);
}
```

```
int main() {
```

```
    int set[MAX], n, target, current[MAX];
```

```
    printf("Enter the number of elements in the set: ");
```

```
    scanf("%d", &n);
```

```
    printf("Enter the elements of the set:\n");
```

```
    for (int i = 0; i < n; i++) {
```

```
        scanf("%d", &set[i]);
```

```
    }
```

```
printf("Enter the target sum: ");
scanf("%d", &target);

printf("Subsets that sum to %d:\n", target);
findSubsetSum(set, n, target, 0, current, 0);

printf("Total subsets found: %d\n", count);

return 0;
}
```

OUTPUT:

```
● rudy@rudy:~/bishnu-chalise$ n='14'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter the number of elements in the set: 5
Enter the elements of the set:
3 34 4 12 5
Enter the target sum: 9
Subsets that sum to 9:
Subset 1: {4, 5}
Total subsets found: 1
```

Lab 15: implementation of job sequence in deadlines

```
#include <stdio.h>
#include <stdlib.h>

#define MAX 100

typedef struct {
    int id;
    int deadline;
    int profit;
} Job;

int compare(const void *a, const void *b) {
    return ((Job *)b)->profit - ((Job *)a)->profit;
}

void jobSequencing(Job jobs[], int n) {
    int result[MAX];
    int slot[MAX];
    int totalProfit = 0, count = 0;

    for (int i = 0; i < n; i++) {
        slot[i] = -1;
    }

    qsort(jobs, n, sizeof(Job), compare);

    for (int i = 0; i < n; i++) {
        for (int j = jobs[i].deadline - 1; j >= 0; j--) {
            if (slot[j] == -1) {
                slot[j] = i;
                totalProfit += jobs[i].profit;
                count++;
                break;
            }
        }
    }

    printf("Job Sequence that maximizes profit:\n");
    for (int i = 0; i < n; i++) {
        if (slot[i] != -1) {
            printf("Job %d with profit %d, Deadline %d\n", jobs[slot[i]].id,
                jobs[slot[i]].profit, jobs[slot[i]].deadline);
        }
    }
}
```

```

    }
}
printf("Total Profit: %d\n", totalProfit);
printf("Total Jobs Scheduled: %d\n", count);
}

int main() {
    int n;

    printf("Enter the number of jobs: ");
    scanf("%d", &n);

    Job jobs[n];

    printf("Enter job details (ID, Deadline, Profit):\n");
    for (int i = 0; i < n; i++) {
        jobs[i].id = i + 1;
        scanf("%d %d", &jobs[i].deadline, &jobs[i].profit);
    }

    jobSequencing(jobs, n);

    return 0;
}

```

OUTPUT:

```

o rudy@rudy:~/bishnu-chalise$ n='15'; gcc ${n}.c -o /tmp/a.out && /tmp/a.out && ssc ${n}.png
Enter the number of jobs: 5
Enter job details (ID, Deadline, Profit):
2 100
1 19
2 27
1 25
3 15
Job Sequence that maximizes profit:
Job 3 with profit 27, Deadline 2
Job 1 with profit 100, Deadline 2
Job 5 with profit 15, Deadline 3
Total Profit: 142
Total Jobs Scheduled: 3

```