4

Coloured Line



Table of contents



- Problem definition
- Observations
- Hypothesis 1 Refraction and difraction
- Measurements for hypothesis 1
- Hypothesis 2 Repeated reflection
- Measurements for hypothesis 2
- Summary

Problem definition


- EN: When a compact disc or DVD is illuminated with light coming from a filament lamp in such a way that only rays with large angles of incidence are selected, a clear green line can be observed. The colour varies upon slightly changing the angle of the disc. Explain and investigate this phenomenon.
- CZ: Když osvítíme kompaktní disk nebo DVD světlem z žárovky s wolframovým vláknem tak, že jsou vybrány pouze paprsky s velkým úhlem dopadu, můžeme pozorovat jasnou zelenou čáru. Její barva se mění s nepatrnými změnami úhlu náklonu disku. Vysvětlete a prozkoumejte tento jev.
- Frequently used terminology:
 - Pitch (p) distance between two data lines
 - Pit/Land lowered/heightened areas of the data line
 - PC layer transparent polycarbonate layer

Assumptions

- In microscopic situations we assume the quasiparallelity of light rays coming out of the light source
- In macroscopic situations we ignore the thickness of the disc itself and we approximate the light source as a point light shining radially



Fig. 1: Construction of CDs [1]



Observations




- Many optical phenomena, mainly colorful lines and curves can be seen on DVDs or CDs
- Our goal is to explain some of these optical phenomena

Fig. 2: Examples of optical phenomena [2]




Fig. 3: Comparison of construction of CDs and DVDs [3]



Hyp. 1 - Refraction and difraction



In the scenario, where we assume two quasiparallel rays of light entering the PC layer via the top, phase shift of the difracted beams occurs. If this phase shift is a k – multiple of the wavelength λ , the light undergoes constructive interference and persists. If it is a $\left(k+\frac{1}{2}\right)$ -multiple, the light undergoes destructive interference and perishes.



Hyp. 1 - Refraction and difraction



Summary


- The phase shift at the refraction points depend on the entrance/viewing angle (α and β respectively)
- The total phase shift is then:

$$\Delta s = \Delta s_a - \Delta s_b = p \cdot (\cos \alpha - \cos \beta)$$

 The rest of the formulation for constructive interference:


$$k\lambda = p \cdot (\cos \alpha - \cos \beta)$$
 $k \in \mathbb{N}$

Fig. 4: Diagram of two quasiparallel rays of light



Measurements for hypothesis 1

- The angles α and β have been calculated from the relative positions of the light source, viewed disc and camera
- Measured for a total of 6 points
- Mostly a qualitative measurement






Fig. 5: Diagram of the experiment

Measurements for hypothesis 1



Fig. 6: Photos of the measured points






Fig. 7: Measurement results



Hyp. 2 - Repeated reflection



In the scenario, where a ray enters the PC layer of the disc via the side, the ray can experience multiple reflections within that layer. During each reflection some part of it's energy may be emmited. These reflections will be spaced evenly.





 To calculate the distance of two neighboring emmission points (or bands) denoted l, we firstly calculate the angle of travel of the ray using Snell's law. The rest is done using simple trigonometry:


$$\alpha' = \arcsin\left(\sin(\alpha) \cdot \frac{n_0}{n_{PC}}\right) \quad \tan(\alpha') = \frac{2h}{l}$$

Introduction

$$l = \frac{2h}{\tan\left(\arcsin\left(\sin(\alpha) \cdot \frac{n_0}{n_{PC}}\right)\right)}$$

Fig. 8: Diagram of a ray being repeatedly reflected within the PC layer

Measurement





Measurements for hypothesis 2


GCh(D+1)

- The measurement was simple done by shining a light at the side of the CD from a know position
- From that the angle was calculated
- Ambient light was blocked using a shade, that greatly reduced the amount of light hitting the disc from the top
- Refractive index of the PC layer used [4]:

 $n_{PC} \approx 1.585$







Measurements for hypothesis 2



- Measurements done for two different configurations
- Both result fit the theory very well

Fig. 12: Measurements versus theory for hyp. 2 [ww] ₃ 0.2 α [rad] -----Theory Measurements

Fig. 10,11: Photos of the measured phenomena

Future improvements



- Quantitative measurements for hypothesis 1
- More measurements for hypothesis 1

Summary



 We were able to create a hypothesis for the behaviour of the lines. We came up with a formula for the color of such line at any given point and confirmed it qualitatively.

$$k\lambda = p \cdot (\cos \alpha - \cos \beta)$$
 $k \in \mathbb{N}$

 We have created a hypothesis for the banding artefacts. We came up with a formula for the distance of these bands and confirmed it quantitatively.

$$l = \frac{2h}{\tan\left(\arcsin\left(\sin(\alpha) \cdot \frac{n_0}{n_{PC}}\right)\right)}$$

Additional sources



- [1] Chris Mueller, 26.6.2015, w0h0N.gif, viewed 20.12.2022,
- https://engineering.stackexchange.com/questions/3324/why-is-it-more-reliable-to-use-the-land-pit-transition-in-a-cd-rom
- [2] Jon Abe, 10.9.2014, photo1.png, viewed 20.12.2022, https://joabe808.wordpress.com/2014/09/10/optics-cd-rainbow-reflection/
- [3] Cmglee, 6.6.2021, File:Comparison_CD_DVD_HDDVD_BD.svg, viewed 20.12.2022, https://en.wikipedia.org/wiki/Comparison_of_high-definition_optical_disc_formats
- [4] Trisha, 25.4.2012, DVD-Rainbow.jpg, zobrazeno 20.12.2022, https://inspirationlaboratories.com/how-to-make-a-rainbow/dvd-rainbow/

Other observed phenomena



