

Advanced Methods in Text Analytics

Transfer Learning



What is Transfer Learning?

- “Acquiring knowledge from one task or domain, and then applying it (*transferring* it) to solve a new task.” Jurafsky et al. 2025
- **Common approach** follows **two-steps** ([Howard and Ruder, 2018](#)):
 1. **Pre-training** a model on some tasks that “allows” model to learn rich representations
 2. **Fine-tuning** the learned representations (weights) in the context of a new downstream application
- Why is it called **pre-training**?
 - Train model for general use *before* using it on specific applications
- **Fine-tuning** refers to **further updating weights** of pre-trained model
 - Downstream task usually implies using a **downstream model** in combination with the pre-trained model
 - Updating weights **may result in “catastrophic forgetting”**
- Focus this week: pre-training tasks and architectures
 - Next week: fine-tuning methods and applications

But First, a Word on Tokenization

- Recall introduction lecture: **tokenization is important!**
 - Should we tokenize words? What are words?
 - Should we tokenize characters? What meaning do they encode?
- Nice sweet spot: tokenize subwords
 - E.g. *unlikeliest* -> *un-likely-est*
 - Each a morpheme, i.e. a meaning-bearing unit
- **Byte-Pair Encoding** ([Sennrich et al. 2016](#)): very common subword tokenizer, roughly as follows
 1. Starting vocabulary V is set of characters
 2. Find most common two-character subword, create token for it, add to V
 3. Keep finding common and longer subwords until k new tokens are created
- Thus, can handle unknown words by breaking them into characters
 - Variants exist, e.g. [WordPiece](#), [SentencePiece](#)
- Tokenization is the sole focus the next lecture slides

Outline

1. Pre-Training

1. Transformer-based language models
2. Masked Language Models
3. Causal (or Autoregressive) Language Models

2. Fine-Tuning


Pre-Training

Pre-Training Methods

- Take **skip-gram** as an **example of pre-training**
 - **Goal:** learn useful (static) representations
 - **Task:** predict whether two words are likely to be in context
- In other words, the **actual goal is not necessarily solving the task**
- There are **different tasks for pre-training**
 - Each a **different training objective**
 - Multi-task training possible, e.g. objective is linear combination of tasks
- **Most common pre-training tasks/approaches**
 - **Masked Language Models (MLMs)**
 - **Causal (or Autoregressive) Language Models (CLMs)**
- Different task -> usually different architecture and objective
 - MLM: **BERT**, encoder-only transformer
 - CLM: **GPTs**, decoder-only transformer
 - Other variants exist, all based on the transformer architecture
- **First: transformer-based LMs, then: MLMs and CLMs**


Encoder-Only and Decoder-Only

- Recall the transformer architecture
 - Encoder-decoder
- Some models use only the encoder
 - Input:** tokenized input sequence
 - Output:** contextualized input tokens
- Other models use only the decoder
 - Input:** start symbol, previous outputs
 - Output:** new generated word
- Both can be stacked



Recap: Self-Attention Layer (1)


- **Input:** sequence of n tokens
- **Output:** sequence of n *contextualized* tokens (here, **bidirectional**)



- Layer is parameterized by W^Q , W^K and W^V
 - Each a transformation for using tokens as: queries, keys, values
- Thus, **same words gets different representations based on context**
 - “They **broke** in tears when they heard they got the new **flat**.”
 - “They **broke** the world record by 2 seconds **flat**.”

Recap: Self-Attention Layer (2)

- Self-attention can also be causal
 - Token at time step t attends only to previous inputs ($< t$)




- Input and output still the same as any self-attention layer
 - But "**context**" of each output embedding is **only inputs from previous steps**
 - Recall that without positional embeddings, there is no "time"

The Language Modeling Head (1)

- A **transformer block/layer** typically outputs token representations
 - Transformer block/layer = self-attention + MLP (with residuals, layernorm)
- **Output embeddings are same size as input embeddings**
 - Can either be a sequence in encoder-only models
 - Or a single token per time-step in decoder-only models
- How do we turn these outputs into a language model?
 - Each representation fed to a "classification head" (a **downstream model**)
 - **Classification head**: softmax *layer* that projects to space of possible classes
 - **Language modeling head**: projects to vocabulary space
 - I.e. same mechanism used for language modeling with RNNs
- If the **task** is to **predict next word**:
 - Feed *contextualized* representation of input at time step t to LM head to predict word at time step $t + 1$
- Let's visualize this!


The Language Modeling Head (2)



- $h_N^L \in R^d$ is output embedding of block L at time step N
- Unembedding layer $U \in R^{d \times |V|}$ projects from d to $|V|$ (vocabulary space)
 - Output is logits, used as input to softmax *function* (no weights)
- Note that U is same size as initial (static) embedding layer $E \in R^{|V| \times d}$
 - Hence, we usually set to be $U = E^T$ (weight tying, [Press et al. 2017](#))
 - **Weight tying:** use same matrix as E and U , known to improve performance

Transformer-Based LMs

- All together:
 - (Static) input embeddings $E[w_i]$
 - Positional embeddings p_i (added)
 - L transformer layers (blocks)
 - Language model head
- For each **transformer layer/block**
 - **Input:** sequence of embeddings of size d
 - **Output:** sequence of embeddings of size d
- For **language model head**
 - **Input:** single embedding of size d
 - **Output:** probability of each token in vocab. V
- **Input to downstream model depends on task**
 - E.g. for sequence classification, we need to represent entire input sequence
 - For sequence labelling, each token representation is classified




Masked Language Models

Masked Language Models (1)

- Using information about the future in a sequence is often not suitable
 - E.g. in text generation, we use past generated words to generate new ones
 - We don't want to train a model to use information that isn't available at inference time
- But **often the entire input sequence is available during inference!**
 - E.g. in machine translation we get an entire document to translate
 - In dialogue scenarios, we get entire input from user at each turn
- And **looking at subsequent tokens can be useful for certain tasks**
 - Tasks that require labeling each sequence element (token-level classification)
 - E.g. part-of-speech tagging (adjectives come *before* nouns in English)
 - Generally, we obtain richer representations by using more context
- With transformers, **we control that in the self-attention layers**
 - If we can't look at future tokens: **causal self-attention**
 - If we can look at future tokens: **bidirectional self-attention**

Masked Language Models (2)


- Contextualized representations from **bidirectional self-attention layers** consider **context from both sides of each input word**



- Masked language modeling:** predicting masked words in input sequence
 - Masked words:** hidden, usually replaced with [MASK] token
 - Architecture:** we use *bidirectional* transformer encoders to train models to predict *masked* words in the input sequence
- What exactly does *masking* mean? The training approach should clarify!

Training Masked Language Models (1)


- Recall training RNNs
 - We predict the next word given previous ones
 - The loss corresponding to each input word is measured against next word in input sequence, final loss is average over all tokens



- Can we do that here?
 - No**, bidirectional self-attention looks at next word!
 - Task of predicting next word therefore trivial

Training Masked Language Models (2)

- Instead, **cloze task**, i.e. fill-in the blank ([Taylor, 1953](#))
 - “Turn ____ homework in.”
 - Many examples from same sentence: “Turn your _____ in.”




- **Loss averaged over masked tokens only**, all tokens "attended" to
 - Note: **self-supervision**, predict parts of input using rest of input
 - More details by discussing quintessential MLM: **BERT**

The BERT Model (1)

- **BERT: Bidirectional Encoder Representations from Transformers**
- Seminal work by [Devlin et al. 2018](#)
 - A clear success case is transfer learning
 - **Revolution:** jump in state-of-the-art performance in several NLP tasks
 - Defined masked language modeling as discussed today
- **Goal:** learn representations of language
 - Not predict masked words, i.e. not the task from training objective
 - Thus, similar to word embeddings, but now using transformers
- Their **general architecture:**
 - **Encoder-only** transformer
 - 12 stacked layers of transformer encoders, each with 12 attention heads
 - Hidden layers of size 728
 - Max input length: 512 tokens (recall: attention cost quadratic in this length)
- Overall: **100M parameters**


The BERT Model (2)



- Pre-training -> Fine-tuning framework
 - **Pre-training** designed to include both token level and sentence level tasks
 - **Fine-tuning** required minimal changes to pre-training architecture
- Let's discuss some of these important design choices

Pre-Training BERT (1)

- Two level representations
 - Both in same input sequence
- **Token level**
 - E_i inputs, T_i outputs
- **Sentence level**
 - **[CLS]**, **[SEP]** inputs
 - **C**, **T_[SEP]** outputs
- Thus, model “aware” of sentence pairs
 - Useful for downstream tasks
 - E.g. (question, answer) pairs
- **[CLS] token** meant for sequence classification
 - Final representation C used as sequence representation
- **[SEP] token** separates two input sentences



Pre-Training BERT (2)


- They (pre-)trained with **two self-supervised tasks**
 1. Masked language modeling (MLM), i.e. fill-in the blank
 2. Next sentence prediction (NSP), e.g. for QA, natural language inference
- **For MLM training objective:**
 - Replaced 15% of input tokens in training corpus
 - 80% of that time replaced with [MASK] token
 - 10% of that time replaced with another random token
 - 10% left unchanged
 - Output token T_i fed to softmax for classification, original word as target
 - Why all of this? Because [MASK] token never seen at inference time!
 - Model should not rely on signal from [MASK] token to make predictions
- **For next sentence prediction objective:**
 - Binary classification: next sentence or not? ([CLS] token to softmax layer)
 - 50% of examples were subsequent sentences in training corpus (positives)
 - 50% of examples had 2nd sentence be a randomly chosen one (negatives)

Pre-Training BERT (3)


- **Final loss:** combined loss of both MLM and NSP training objectives
- **Training corpus**
 - BooksCorpus: 800M words
 - English Wikipedia: 2.5B words
 - (Much less data than used for training large language models today)
- **Important:** training data must be full documents, not shuffled sentences (often a valid approach)
 - Why?
- **Tokenization:** WordPiece subword embeddings
 - Vocabulary size: 30K
 - Recall: subwords is nice balance between words and characters
- It took 40 epochs to converge model during training
 - With the hardware at the time (64 Google TPUs), that was 4 days

Fine-Tuning BERT (1)

- **Straightforward:** representations computed by BERT used as input for downstream model
 - Note: requires using entire model, not just its weights as word2vec
- Can handle **tasks** where **input is single sequence**, e.g. sequence labeling (NER) and sequence classification, or **pairs of sequences**, e.g. QA (SQuAD) or NLI (MNLI)
- Given input data, e.g. sequence to classify:
 - **Sequence** fed as **input** to BERT
 - **BERT output** passed to classification head (each token for sequence labeling, CLS token for sequence classification)
- **Let's visualize this!**



Fine-Tuning BERT (2)




- Here's an example for sequence labeling, i.e. we classify each token h_i^L ;
 - Downstream model is linear projection W_c to classification space C
 - During fine-tuning, W_c + all model parameters were updated
 - Fine-tuning model often took 1 hour (doable compared to pre-training)
- For sequence classification task, CLS token used as downstream input

Variations of BERT (1)

- BERT's architecture was highly influential
 - Spawned several variants of the original model
- **RoBERTa** ([Liu et al. 2019](#))
 - More than a variant, the result of a **reproduction study**
 - They **reimplemented, retrained**, did more **ablation**
 - **Proposed changes** such as:
 - (1) **Dynamic masking**, i.e. sampling tokens for masking for each input sequence during training (as opposed to once before entire training run)
 - (2) **Training without NSP** loss (no more sentence pairs)
- **SpanBERT** ([Joshi et al. 2020](#))
 - **Masked entire subsequences** instead of individual tokens (i.e. a span)
 - Marked masked span with special tokens (start-of-span, end-of-span)
 - Model trained on **additional objective** Span Boundary Objective (SBO)
 - They outperformed BERT in span-based tasks, e.g. span-based QA
 - This model was concurrent with RoBERTa

Variations of BERT (2)

- Sentence-BERT ([Reimers et al. 2019](#)): better **sentence embeddings**
- Siamese network architecture (here, two BERTs with shared weights)
 - **Pooling** BERT output vectors (MEAN/MAX) to get sentence embedding
 - **Training** (left): Feed sentence vectors to classification/regression head
 - **Inference** (right): for regression, cosine similarity between sentences



- **Results:** better sentence embeddings vs [CLS] token, other methods


Causal Language Models

Autoregressive Text Generation

- **Recall autoregressive generation:** word generated at each time-step is conditioned on word generated at previous time-step
- **Concrete steps:**
 1. Feed starting symbol $\langle s \rangle$, model produces softmax distribution over vocabulary
 2. Sample next word w_i from softmax distribution (using some sampling method)
 3. Add sampled word to previous input sequence, i.e. " $\langle s \rangle w_i$ ", feed to model
 4. Model produces new softmax distribution, sample next word w_{i+1} again
 5. Repeat steps 3-4 with latest sampled word until symbol $\langle /s \rangle$ is sampled
- **Sampling methods important part of generation**, as seen in tutorials
 - **Greedy decoding:** sample most probable word
 - **Top-k:** sample from top k words
 - **Top-p:** sample from words that make up top p probability mass
- More involved sampling methods exist
 - Before we look at causal language models, let's have a quick look at a very common and less simple sampling method in more detail

Beam Search (1)

- Say we have a pre-trained LM that can produce distributions for next word prediction
- Assume further our vocabulary is $V = \{yes, ok, </s>\}$
- In the following example, the **most probable sequence** is “ok ok </s>”
 - But **greedy sampling would fail** to predict it, it would first choose “yes”



Beam Search (2)

- The previous example illustrates that when we want the **most probable sequence**, shortsighted approaches may not be suitable
 - Shortsighted: only considering the probability of the next word
- **Beam Search:**
 - **Iteratively sample top k** most probable words (i.e. also greedy)
 - The **score of each possible word** is based on the probabilities of the previously sampled words, i.e. **consider the probability of the sequence**
- Score of sequence of y_i words given some input x , e.g. in translation, is:


$$\begin{aligned} \text{score}(y) &= \log P(y|x) \\ &= \log (P(y_1|x)P(y_2|y_1,x)P(y_3|y_1,y_2,x)...P(y_t|y_1,...,y_{t-1},x)) \\ &= \sum_{i=1}^t \log P(y_i|y_1,...,y_{i-1},x) \end{aligned}$$

- We normalize by sequence length to avoid favoring shorter sequences:

$$\text{score}(y) = \log P(y|x) = \frac{1}{t} \sum_{i=1}^t \log P(y_i|y_1,...,y_{i-1},x)$$

Beam Search (3)

- At each time step:
 - Select top k probably words from distribution over vocabulary
 - Predict next word with each of the k top words, i.e. $k \times V$ probabilities
 - Each next word is scored by its probability times the probability of its path
 - We pick the top k most probable paths, and continue the process




Beam Search (4)

- **Beam search is widely used** in text-generation applications:
 - E.g. machine translation, summarization
 - Generally applications where we compare different output sequences
- However, it has **shortcomings**
 - Cost intensive
 - Size of beam, i.e. value of k , still greedy, can miss better solutions
 - Sampled sequences often similar to one another ([Li and Jurafsky, 2016](#))
- Variants have been proposed, e.g. [diverse beam search](#)
 - Divides sampled sequences into different sampling groups
 - Promotes diversity between sequences in different sampling groups
- Still, **beam search remains a very common sampling method**

Causal Language Models


- **Causal language modeling:** given sequence of words, predict next word
 - **Context window/prompt:** given input sequence words
 - **Architecture:** we use causal self-attention in transformers (only look back)



- Text autoregressively generated with CLMs generally based on:
 - **Model predictions**, i.e. softmax over V
 - **Size of context window** (quadratic cost in self-attention using transformers)
 - **Sampling strategy/heuristic** (beam search a common one)
- Let's see how to train a CLM using transformers.
 - Then we'll go over some seminal transformer-based CLMs

Training Causal Language Models

- **Teacher forcing** does apply here:
 - Construct training sequences from given corpus in self-supervised manner
 - Given sequence, *force* each subsequence as input, next word as target
 - Compute loss between model's prediction and target word
 - Average loss over all predictions in given sequence
 - **Note:** computing loss for each word is independent, parallelizable



Generative Pre-Trained Transformer

- That is what GPT stands for ([Radford et al. 2018](#))
- Published at time when pre-training & fine-tuning framework was new
 - Unclear what tasks to pre-train on
 - Unclear how to use learned representations in downstream models
 - Some of this still unclear, but pragmatic success with some architectures, e.g. BERT, GPT
- **GPT: autoregressive language modeling is a useful pre-training task**
- **Goal:** “...learn universal representations that transfer with little adaptation to a wide range of tasks.”
 - So, transfer learning, important to avoid task-specific customization
- Two-step process:
 - **Pre-train** on large corpus in self-supervised manner
 - **Fine-tune** model on downstream tasks in supervised manner
 - Supervised downstream tasks need not be related to pre-training corpus (again, transfer learning)

GPT Architecture, Training, Fine-Tuning


- Their **general architecture (117M parameters)**:
 - **Decoder-only** transformer (i.e. no self-attention layer attending to encoder)
 - 12 layers of transformer decoders, each with 12 attention heads
 - Hidden layers of size 728, position-independent MLP of size 3072
 - Max input length: 512 tokens (attention cost quadratic in this length)
- So, architecture **quite similar to BERT**, except decoder-only
 - In fact, BERT heavily borrowed from GPT, as claimed by the BERT authors
- **Pre-Training**
 - **Self-supervised** causal language modeling on **BooksCorpus**
 - **Tokenization**: byte pair encoding (vocabulary size: 40K)
- **Fine-tuning**
 - Task inputs fed to pre-trained model to produce final representation $\mathbf{h}_N^L$, i.e. representation of token N in layer L , $\mathbf{h}_N^L$ then fed to classification head
 - They fine-tuned *all parameters* using the classification objective + the CLM objective

GPT Variants

- **GPT-2** ([Radford et al. 2019](#)): mostly same architecture as GPT-1
 - Moved around/added more layer normalization (more in LLMs lecture)
 - Initialized weights passed by residual layers (scaled them down)
 - Vocabulary expanded to 50K
 - Context window expanded from 512 to 1024 (again, quadratic cost)
 - Largest variant: **1.5B parameters**
 - **Their language model was able to do** NLP tasks such as **QA, machine translation** and **summarization** without training/tuning for it (**zero-shot**)
- **GPT-3** ([Brown et al. 2020](#)): same as GPT-2
 - Used [sparse attention](#), cost from $O(n^2)$ to $O(n\sqrt{n})$ where n is input length
 - **Corpus**: Common Crawl dataset (1 trillion words)
 - Largest variant: **175B parameters**
 - Achieved **great performance in few-shot tasks described in prompts**
- We'll discuss these **zero-shot/few-shot** settings in future **LLMs lecture**.

Other Transformer-Based Models

- **T5** ([Raffel et al. 2020](#)): explored different training objectives, datasets
 - **Encoder-decoder** architecture, so cross attention from decoder to encoder!
 - They cast all tasks as text-to-text for this purpose, e.g. *sts* is sentence similarity, model trained to generate one of possible classes



- **Electra** ([Clark et al. 2020](#)): **different task**, predict whether word was replaced randomly or not, so binary classification, not masking
 - More efficient training, competitive with larger models on some datasets

Which Architecture is Best?

- **No golden rule**
 - Encoder-decoder better?
 - Encoder-only?
 - Decoder-only?
- What about all **other design decisions**?
 - Which positional encodings?
 - Which tokenization approach?
- **Generally unclear**
 - Pragmatic evidence exists, e.g. studies like RoBERTa, T5
 - But results change as training/models/data change or scale up

The BERT Legacy

- **Large language models (LLMs)** currently hugely successful
 - They are almost exclusively transformer-based **decoder-only** models
 - I.e. they generate tokens one step at a time
- However, **for many applications, encoder-only models are arguably more suitable**
 - E.g. classification tasks where input is token/sequence representation, retrieval where input is query/document representation
 - Evidence of this: BERT-like models are some of the most popular models in [HuggingFace Hub](#) (vast repository of pre-trained models)
- Recently, BERT has received a "modern touch"
 - Mostly an update after all the lessons from pre-training decoder-only LLMs
- [ModernBERT \(2024\)](#): introduces improvements mostly for speed
 - E.g. different positional embeddings, [alternating attention](#) (not all layers attend to entire input sequence), multilingual variant [released in 2005](#)
- [NeoBERT \(2025\)](#): concurrent with ModernBERT, similar improvements


Summary: Pre-Training

- **Transfer learning:**
 1. **Pre-training:** train model on some task(s) that “allows” model to learn rich representations, usually from large amounts of text. Representations then useful in downstream applications
 2. **Fine-tuning:** update learned representations (weights) in context of new downstream application, usually using new downstream model/component, e.g. a classification head
- **Pre-training now mostly done with transformer-based models**
- Different kinds of **pre-training objectives**, two dominant ones
 - Masked language modeling (**MLM**)
 - Causal language modeling (**CLM**)
- Different kinds of **architectures**
 - **Encoder-only**, typically used for training MLMs
 - **Decoder-only**, typically used for training CLMs
 - **Encoder-decoder**, cross-attention (decoder also attends to encoder outputs)

Fine-Tuning


What is Fine-Tuning?

- Traditionally, updating weights of pre-trained model when training on **new** downstream task
 - Resulting **contextualized representations** *tuned* to the **new task**
 - **New** = not used/seen during pre-training
- Downstream task usually implies additional **downstream model**
 - Downstream model usually comes with its separate weights
 - These weights *must be trained* (e.g. **classification head** in image below)



To Update or Not to Update (1)


- Updating pre-trained weights **may result in “catastrophic forgetting”**
 - Encoded information during pre-training lost/replaced



- Pre-training can be very expensive
 - E.g. META AI's [Llama3](#) CLM (400B parameters) trained with 16.000 GPUs
 - Catastrophic forgetting can potentially undo some/much of that effort
 - Understanding how specific knowledge is stored in weights is open question

To Update or Not to Update (2)

- “Freezing” (some or all) pre-trained weights means not updating them
 - Still referred to as fine-tuning, because we use a downstream model



- Definition unclear, so **relevant questions when discussing fine-tuning**:
 - Freezing or not freezing weights? Same or different training objective?
 - Which downstream model? How does it interact with pre-trained model?
 - How are downstream examples constructed/fed to model?
- This section: downstream tasks, basic/parameter efficient fine-tuning

Types of Downstream Tasks

- Two main types:
 - **Sequence classification:** predict label for entire input sequence
 - **Sequence labeling:** predict label for each input token
- **In each case, we need to:**
 1. Get general information encoded in pre-trained model
 2. Use this information with downstream model designed for downstream application
- 1. **How to get information encoded in pre-trained model?**
 - Depends on downstream task
 - Generally, we use some of the representations in the model, e.g. tokens in any (usually last) encoder layers
 - **No golden rules**, open question is what each layer encodes, usability for different tasks, e.g. multilingual transformers
- 2. **How to use pre-trained information with downstream models?**
 - Again, depends on application (let's see some cases)


Sequence Classification (1)

- **Example:** Say we are interested in **sentiment classification**
 - **Three labels:** positive, negative, neutral
- **We have:**
 - A good mount of input sequences and corresponding sentiment labels
 - A pre-trained transformer LM
- **How can we use these resources to solve this task?**
 - In other words, how do we use this pre-trained model to solve this task?
 - Is it clear why we think this is a good idea in the first place?
- **Usually: we get single sentence representation from model**
 - Then feed this representation to a classifier that predicts 1 of three possible labels.
 - Downstream classifier usually referred to as **classification head**
- **How can we get a sentence representation?**
 - And what types of architecture can our classifier head have?

Sequence Classification (2)

- How to get a **sentence representation** from our **transformer**?
 - **[CLS] token** if available, e.g. in BERT
 - **Mean pooling** over (contextualized) output tokens (as in T5)
- What types of **architectures** can we use **for our classifier head**?
 - No general restrictions
 - Simple/common approach? **Softmax layer** (linear layer + softmax function)
- In the case of our sentiment classification task
 - Let $\mathbf{y} \in \mathbf{R}^d$ be the sentence embedding we use, e.g. CLS token
 - Then, our classifier is $\mathbf{y}_{CLS} = \text{Softmax}(\mathbf{W}_C \mathbf{y})$, parameterized by $\mathbf{W}_C \in \mathbf{R}^{3 \times d}$
- But the classifier can be more involved
 - E.g. fully-connected FNN with as many layers/architecture you want
 - As usual, the more parameters, the more data required for training
- Let's visualize this!

Sequence Classification (3)




- We assume an architecture where $[CLS]$ token is available
- Recall: **we need labeled data** for our task to train W_C (not pre-trained), i.e. no more self-supervision, but loss is still typically cross entropy

Pair-Wise Sequence Classification

- **Some problems** involve **classifying two sentences**
 - Logical entailment: does one sentence entail the other?
 - Paraphrase detection: is one sentence paraphrasing the other?
- Common such task: **natural language inference (NLI)**
 - Given two sentences, identify relation between the two
 - E.g. entails, contradicts, neutral
- How can we **fine-tune a pre-trained transformer for NLI?**
 - Feed single representation for entire input sequence to classifier head
 - Input sequence includes pair of sentences, [SEP] token
 - Any other way?
- Again, **no golden rules!**
 - E.g. feed each sentence separately, concatenate representations for classifier input
 - Different approaches may have different impact on pre-trained weights during fine-tuning

Sequence Labeling

- **Example:** Say we are interested in **part-of-speech (POS) tagging**
 - Each input token gets **one of k labels**, e.g. verb, noun, modifier, etc.
- **How do we fine-tune a classifier for this approach?**
 - Classifier head fed each output token for prediction, i.e. $y_i = \text{Softmax}(W_K z_i)$ where z_i is contextualized representation of token i



How Feasible is Fine-Tuning?


- **Pre-training** a (large) language model is **expensive**
 - BERT (2018) had 100M parameters, LLMs today in the billions/trillions
- **Is fine-tuning LMs less costly than pre-training?**
 - Not necessarily, still tuning the entire pre-trained model
 - E.g. fine-tuning with same objective -> continued pre-training
 - *Store copy of tuned model for each task you tune it for!*
 - But, usually requires less time/data due to pre-trained "bootstrap"
- **Do you need to fine-tune entire pre-trained LM?**
 - Perhaps just train a few layers, perhaps the last layers only?
 - Recall concept of hierarchical representations
 - We can choose what to freeze!
- That is the basic idea behind **parameter efficient fine-tuning (PEFT)**
 - This name used in NLP community, relatively new
 - Similar approaches already used in Computer Vision before that

Parameter Efficient Fine-Tuning

- What if you have **small amount of data**?
 - Or **not enough compute power** to continue training a large transformer
 - Lots of weights -> lots of data for training, lots of compute power
- **PEFT**: fine-tune small subset of pre-trained weights
- **Advantages**
 - Requires less data, compute power
 - Less prone to overfitting to whatever data you have
- **Disadvantages**
 - Usually worse performance than standard fine-tuning
- Different approaches suggested in recent years
 - Let's go over some of the most popular ones


Adapters (1)

- Used by [Rebuffi et al.](#) for computer vision tasks in 2017
- [Houlsby et al. \(2019\)](#) proposed it in NLP, applied it to transformers
- **Main idea:** insert adapter modules in transformer block, tune adapter weights only during fine-tuning
- **Adapter layer:** tunable layer added to transformer block, originally two, one after self-attention layer and another after projection layer




Adapters (2)

- **Adapter layer should not have many parameters**
 - Thus, easier/less expensive to tune
 - Originally, between 0.5 and 8% of pre-trained model
- **Components in adapter layer**
 - Projection layer down to *bottleneck* dimension m
 - Non-linearity
 - Projection up to original input size d
- **# parameters:** $2md + m + d$
 - Two projections + output biases
- **Bottleneck size:** controls trade-off between model performance and parameter efficiency




Adapters (3)

- **Important:** initialization should result in (close to) identity function
 - Why?
- Training needs to **continue** in fine-tuning process
 - We start with a working forward pass!
 - Random *init* would break that function!
- **Residual connection inside adapter layer serves this purpose**
 - Initialize adapter weights to zero
 - Then you get identity
- **Recall residual connections** add input back to output
 - Let $y = f(x)$ be the operator.
 - With residual connection, $y = f(x) + x$
 - Thus operator is identity if $f(x) = 0$




Adapters (4)

- Other architectures possible
- [Bapna et al. \(2019\)](#) use only single adapter layer after projection layer
- [Pffeifer et al. \(2021\)](#) proposed to **combine several task-specific adapters**
 - Task-specific adapters combined with **attention mechanism**
 - Allows classifier to use **information from several different tasks in non-destructive manner**
 - No catastrophic forgetting compared to fine-tuning same adapter on new task




Low-Rank Adaptation (1)

- **LoRA:** Low-rank adaptation ([Hu et al. 2021](#))
- Similar to adapters, adds trainable modules to transformer block
- Specifically, **two projection layers parallel** to projection layer in transformer
- Perspective: updated weight $\mathbf{W}'$ during fine-tuning is $\mathbf{W}' = \mathbf{W}_O + \Delta\mathbf{W}_O$
 - Simulate this effect by freezing $\mathbf{W}_O$, adding parallel projections $\mathbf{AB}$
 - Thus, $\mathbf{W}' = \mathbf{W}_O + \mathbf{AB}$
- $\mathbf{A}$ projects down to small size
 - Thus, $\mathbf{AB}$ is low-rank factorization of $\Delta\mathbf{W}_O$
- As with adapters, initialization must be identity
 - They achieve this by setting $\mathbf{B} = \mathbf{0}$, so that $\mathbf{AB} = \mathbf{0}$



Low-Rank Adaptation (2)


- Downside to *all adapters* in general?
 - (Slightly) higher inference costs
 - We add more parameters!
- LoRA designed to prevent this
 - Once adapter is learned, original W_O can be updated by *merging back* AB
 - That is, final weight $W = W_O + AB$
 - Thus, **no additional inference costs**
 - But catastrophic forgetting possible
- Generally, **adapters have trade-offs**
 - **CON:** increased inference cost
 - **PRO:** prevent catastrophic forgetting, original model frozen, adapters can always be removed (gives rise to [modular deep learning](#))



Prompt Tuning (1)

- PEFT method, different from adapters, proposed by [Lester et al. \(2021\)](#)
- **GPT-3**: performs well on new tasks using **in-context learning**
 - In-context learning: describe task and provide few examples in prompt
 - **Advantage?** No fine-tuning! Same frozen model used for different tasks!
 - **Problem?** Approach sensitive to prompt, gives rise to *prompt design*
- **Main idea**: prepend task-specific tokens to input sequences (prompt)

- Then, during fine-tuning, only new task-specific tokens are updated
- Each task A, B, C gets new task token **A, B, C**
- Prepend task examples with task tokens, e.g. prepend **A** to a1, a2
- Tune only task tokens
- At inference, use new tokens in same way



Prompt Tuning (2)

- As with T5 model, they cast tasks as text-to-text
 - **Normally:** downstream classification is $p(y/X)$ where X is input sequence (prompt) and y is single class label, e.g. 0 or 1 if binary
 - **Text-to-text:** we have $p(Y/X)$, where Y is generated output sequence that represent class label, e.g. "neutral" for sentiment analysis
 - **Fine-tuning:** $p_{\theta}(Y/X)$ where θ is pre-trained model parameters we tune
- **Prompting:** prepend tokens P to input sequence
 - Normally, P made up of known tokens from pre-trained embedding layer
 - E.g. P = "Summarize the following article into a single sentence"
 - Performance sensitive to chosen prompt, may require prompt design
- **Prompt tuning:** add fixed prompt P per task using special new tokens
 - θ_P = new tokens added to vocabulary
 - Then: $p_{\theta;\theta_P}(Y/[P,X])$ but we only tune θ_P
 - Fixed prompt removes need for prompt design
- Similar approaches: prefix tuning by [Li et al. \(2021\)](#), P-Tuning by [Liu et al. \(2022\)](#)

Another Perspective on Tasks

- We can classify downstream tasks as follows:
 - Sequence classification
 - Sequence labeling
 - Etc.
- We can also **classify tasks based on available data, usually:**
 - **Few shot:** few examples available
 - **Zero shot:** no examples available (just text description)
- These definitions are not so consistent in the literature
 - More details in future LLM lecture

Summary: Fine-Tuning

- Difficult to define
 - Generally, using pre-trained model PT on new task not seen during training
 - May or may not imply updating pre-trained model parameters θ_{PT}
 - Usually includes use of downstream model DM, e.g. classification head
 - Parameters of downstream model θ_{DM} are definitely trained
- **Relevant questions when discussing fine-tuning:**
 - Freezing or not freezing weights? Same or different training objective?
 - Which downstream model? How does it interact with pre-trained model?
 - How are downstream examples constructed/fed to model?
- **Parameter Efficient Fine-Tuning (PEFT)**
 - Updating all model parameters θ_{PT} can be prohibitively expensive
 - PEFT: tune only subset of parameters of θ_{PT} , or new added parameters θ_{FT}
- Most common PEFT approaches: **adapters, LoRA**

References

- Speech and Language Processing, Jurafsky et al., 2024
 - Chapters 10 and 11
- Natural Language Processing: A Machine Learning Perspective, Zhang et al., 2021
 - Chapter 17
- References linked in corresponding slides