Mining Massive Datasets

Lecture 09

Artur Andrzejak

http://pvs.ifi.uni-heidelberg.de



Note on Slides

A substantial part of these slides come (either verbatim or in a modified form) from the book Mining of Massive Datasets by Jure Leskovec, Anand Rajaraman, Jeff Ullman (Stanford University). For more information, see the website accompanying the book: http://www.mmds.org.

Online Algorithms

Classic model of algorithms


- You get to see the entire input, then compute some function of it
- In this context, "offline algorithm"

Online Algorithms

- You get to see the input one piece at a time, and need to make irrevocable decisions along the way
- Similar to the data stream model

Online Bipartite Matching


Example: Bipartite Matching



Nodes: Boys and Girls; Edges: Preferences


Goal: Match boys to girls so that maximum number of preferences is satisfied

Example: Bipartite Matching



M = {(1,a),(2,b),(3,d)} is a matching Cardinality of matching = |M| = 3

Example: Bipartite Matching



Perfect matching ... all vertices of the graph are matched **Maximum matching** ... a matching that contains the largest possible number of matches

Matching Algorithm


- Problem: Find a maximum matching for a given bipartite graph
 - A perfect one if it exists
- There is a polynomial-time offline algorithm based on augmenting paths (Hopcroft & Karp 1973, see http://en.wikipedia.org/wiki/Hopcroft-Karp algorithm)
- But what if we do not know the entire graph upfront?

Online Graph Matching Problem

- Initially, we are given the set boys
- In each round, one girl's choices are revealed
 - That is, girl's edges are revealed
- At that time, we have to decide to either:
 - Pair the girl with a boy
 - Do not pair the girl with any boy
- Example of application:

Assigning tasks to servers

Online Graph Matching: Example



Greedy Algorithm


- Greedy algorithm for the online graph matching problem:
 - Pair the new girl with any eligible boy
 - If there is none, do not pair girl
- How good is the algorithm?

Competitive Ratio

• For input I, suppose greedy produces matching M_{greedy} while an optimal matching is M_{opt}

(what is greedy's worst performance over all possible inputs I)

Worst-case Scenario



Web Advertising

History of Web Advertising


- Banner ads (1995-2001)
 - Initial form of web advertising
 - Popular websites charged
 X\$ for every 1,000
 "impressions" of the ad
 - Called "CPM" rate (Cost per thousand impressions)
 - Modeled similar to TV, magazine ads
- **CPM**...cost per *mille Mille*...thousand in Latin
- From untargeted to demographically targeted
- Low click-through rates
 - Low return of investment for advertisers



Performance-based Advertising

- Introduced by Overture around 2000
 - Advertisers bid on search keywords
 - When someone searches for that keyword, the highest bidder's ad is shown
 - Advertiser is charged only if the ad is clicked on
- Similar model adopted by Google with some changes around 2002
 - Called Adwords

Ads vs. Search Results



CHECK24: Handyvertrag - CHECK24.de

Anzeige www.check24.de/Handyvertrag *

4,7 ★★★★ Bewertung für check24.de

Jetzt günstigen **Handyvertrag** finden Exklusiv bis 150€ Cashback on Top TÜV "sehr gut" · 100% Kostenlos · Exklusive Angebote · Top-Handys uvm. Service- und Beratungsleistungen exzellent – ServiceRating.de

CHECK24: mit Smartphone CHECK24: Galaxy S5 ab 0 €
CHECK24: Allnet ab 11,36€ CHECK24: Mobilfunktarife

Handyvertrag BASE all-in - BASE.de

Anzeige www.base.de/ ▼

4,4 ★★★★ Bewertung für base.de

Allnet Flat nur noch 25€ im Monat. Aktions-Vorteil exklusiv online! Exklusive Online Vorteile · Versand & Retoure gratis · Voller Käuferschutz Bestes Preis-Leistungsverhältnis 2014 – Teltarif

Galaxy S5 Aktion - i Phone5s Angebot - Surf Aktion bis 01.02.

Handyvertrag inkl. Handy - Günstig wie nie - jetzt bestellen Anzeige www.preis24.de/Handyvertrag *

Ohne Versand- und Anschlusskosten.

Deals aus der TV Werbung · Mit Rufnummern-Mitnahme · Keine Versandkosten. iPhone 6 plus + Vertrag - iPhone 6 mit Vertrag - Alles Flat für 19,95 €

(i) Anzeigen (i)

Handyvertrag nur 4,95€

www.deutschlandsim.de/ ▼
4,6 ★★★★ Bewertung für Anbieter
100 Min + 100 SMS + 300 MB Internet
Hole Dir das Top-Angebot!

o2 Allnet-Flat Vertrag www.o2online.de/Handyvertrag *

Die o2 Allnet-Verträge: Jetzt mit Highspeed LTE schon ab 19,99€ mtl.!

Handyvertrag LTE ONE 7,95

smartmobil.de/Handy-Vertrag-LTE-ONE ▼ 4,7 ★★★★ Bewertung für Anbieter
Handy Full-Flat + 4G LTE-Highspeed.
All-Net-Flat: alle Netze + Internet

iPhone 5s günstig

www.blue-deals.de/iPhone_5s ▼
Das iPhone 5s mit Allnet-Flat und
1 GB Internet für 34,99 € mtl.

Web 2.0

- Performance-based advertising works!
 - Multi-billion-dollar industry
- Interesting problem:
 What ads to show for a given query?
 - (Today's lecture)
- If I am an advertiser, which search terms should I bid on and how much should I bid?
 - (Not focus of today's lecture)

Adwords Problem

- A stream of queries arrives at the search engine: q_1 , q_2 , ...
- Several advertisers bid on each query
- When query q_i arrives, search engine must pick a subset of advertisers whose ads are shown
- Goal: Maximize search engine's revenues
 - Simple solution: Instead of raw bids, use the "expected revenue per click" (i.e., Bid*CTR)
- Clearly we need an online algorithm!

The Adwords Innovation

Advertiser	Bid	CTR	Bid * CTR
A	\$1.00	1%	1 cent
В	\$0.75	2%	1.5 cents
С	\$0.50	2.5%	1.125 cents
		Click through rate	Expected revenue

The Adwords Innovation

Advertiser	Bid	CTR	Bid * CTR
В	\$0.75	2%	1.5 cents
C	\$0.50	2.5%	1.125 cents
A	\$1.00	1%	1 cent

Adwords Problem

Given:

- 1. A set of bids by advertisers for search queries
- 2. A click-through rate for each advertiser-query pair
- 3. A budget for each advertiser (say for 1 month)
- 4. A limit on the number of ads to be displayed with each search query
- Respond to each search query with a set of advertisers such that:
 - 1. The size of the set is no larger than the limit on the number of ads per query
 - 2. Each advertiser has bid on the search query
 - 3. Each advertiser has enough budget left to pay for the ad if it is clicked upon

Complications: Budget

- Two complications:
 - Budget
 - CTR of an ad is unknown
- Each advertiser has a limited budget
 - Search engine guarantees that the advertiser
 will not be charged more than their daily budget

Complications: CTR

- CTR: Each ad has a different likelihood of being clicked
 - Advertiser 1 bids \$2, click probability = 0.1
 - Advertiser 2 bids \$1, click probability = 0.5
 - Clickthrough rate (CTR) is measured historically
 - Very hard problem: Exploration vs. exploitation
 Exploit: Should we keep showing an ad for which we have good estimates of click-through rate
 or

Explore: Shall we show a brand new ad to get a better sense of its click-through rate

Greedy Algorithm

Our setting: Simplified environment

- There is 1 ad shown for each query
- All advertisers have the same budget B
- All ads are equally likely to be clicked
- Value of each ad is the same (=1)

Simplest algorithm is greedy:

- For a query pick any advertiser who has bid 1 for that query
- Competitive ratio of greedy is 1/2

Bad Scenario for Greedy

- Two advertisers A and B
 - A bids on query x, B bids on x and y
 - Both have budgets of \$4
- Query stream: x x x x y y y y
 - Worst case greedy choice: B B B B _ _ _ _
 - Optimal: AAAABBBBB
 - Competitive ratio = ½
- This is the worst case!
 - Note: Greedy algorithm is deterministic it always resolves draws in the same way

BALANCE Algorithm [MSVV]

- BALANCE Algorithm by Mehta, Saberi,
 Vazirani, and Vazirani
- Algorithm:
 - For each query, assign it to an advertiser with the largest <u>unspent</u> budget (i.e. largest <u>BALANCE</u>).
 - Break ties arbitrarily (but in a deterministic way)


Example: BALANCE

- Two advertisers A and B
 - A bids on query x, B bids on x and y
 - Both have budgets of \$4
- Query stream: x x x x y y y y
- BALANCE choice: A B A B B B _ _
 - Optimal: A A A A B B B B
- In general: For BALANCE on 2 advertisers
 Competitive ratio = ¾

Analyzing BALANCE

- Consider simple case (w.l.o.g.):
 - 2 advertisers, A_1 and A_2 , each with budget B (≥ 1)
 - Optimal solution exhausts both advertisers' budgets
- BALANCE must exhaust at least one advertiser's budget:
 - If not, we can allocate more queries
 - Whenever BALANCE makes a mistake (both advertisers bid on the query), advertiser's unspent budget only decreases
 - Since optimal exhausts both budgets, one will for sure get exhausted
 - Assume BALANCE exhausts A₂'s budget, but allocates x queries fewer than the optimal
 - Revenue: *BAL = 2B x*

Analyzing Balance




BALANCE: General Result

- In the general case, worst competitive ratio
 of BALANCE is 1–1/e = approx. 0.63
 - Interestingly, no online algorithm has a better competitive ratio!
- Let's see the worst case example that gives this ratio

Worst case for BALANCE

- N advertisers: A₁, A₂, ... A_N
 - Each with budget B > N
- Queries:
 - N·B queries appear in N rounds of B queries each
- Bidding:
 - Round 1 queries: bidders A₁, A₂, ..., A_N
 - Round 2 queries: bidders $A_2, A_3, ..., A_N$
 - Round i queries: bidders A_i , ..., A_N
- Optimum allocation:
 - Allocate round i queries to A_i
 - Optimum revenue N·B

BALANCE Allocation



BALANCE assigns each of the queries in round 1 to $\bf N$ advertisers. After $\bf k$ rounds, sum of allocations to each of advertisers $\bf A_k,...,\bf A_N$ is

$$S_k = S_{k+1} = \dots = S_N = \sum_{i=1}^k \frac{B}{N-i+1}$$

If we find the smallest k such that $S_k \ge B$, then after k rounds we cannot allocate any queries to any advertiser

BALANCE: Analysis

B/1 B/2 B/3 ... B/(N-(k-1)) ... B/(N-1) B/N

$$S_{k} = B$$

1/1 1/2 1/3 ... 1/(N-(k-1)) ... 1/(N-1) 1/N

 $S_{k} = S_{k} = S_{k} = S_{k}$

BALANCE: Analysis

- Fact: $H_n = \sum_{i=1}^n 1/i \approx \ln(n)$ for large n
 - Result due to Euler

1/1 1/2 1/3 ... 1/(N-(k-1)) ... 1/(N-1) 1/N

$$ln(N)$$
 $S_k = 1$

- $S_k = 1 \text{ implies: } H_{N-k} = ln(N) 1 = ln(\frac{N}{e})$
- We also know: $H_{N-k} = ln(N-k)$
- So: $N k = \frac{N}{e}$
- Then: $k = N(1 \frac{1}{e})$

N terms sum to ln(N). Last k terms sum to 1. First N-k terms sum to ln(N-k) but also to ln(N)-1

BALANCE: Analysis

- So after the first k=N(1-1/e) rounds, we cannot allocate a query to any advertiser
- Revenue = B·N (1-1/e)
- Competitive ratio = 1-1/e

General Version of the Problem

- Arbitrary bids and arbitrary budgets!
- Consider we have 1 query q, advertiser i
 - Bid = x_i
 - Budget = b_i
- In a general setting BALANCE can be terrible
 - Consider two advertisers A₁ and A₂
 - **A**₁: bid = x_1 = 1, b_1 = 110
 - A_2 : bid = x_2 = 10, b_2 = 100
 - Consider we see 10 instances of q
 - BALANCE always selects A₁ and earns 10
 - Optimal earns 100

Generalized BALANCE

- Arbitrary bids: consider query q, bidder i
 - Bid = x_i
 - Budget = b_i
 - Amount spent so far = m_i
 - Fraction of budget left over f_i = 1-m_i/b_i
 - Define $\psi_i(q) = x_i(1-e^{-f_i})$
- Generalized Algorithm: Allocate query q to bidder i with largest value of $\psi_i(q)$
- Same competitive ratio (1-1/e)

Thank you.

Questions?