# Mining massive Datasets WS 2017/18

## **Problem Set 8**

Rudolf Chrispens, Marvin Klaus, Daniela Schacherer

December 18, 2017

## Exercise 01

a) The probability that C1 and C2 are matched?

Quastionnaires Count = b (  $Q_1,\,\dots\,,\,Q_b$  )

QuestionCount = r

QuestionCountSum = b \* r

Propability for one Questionair that it matsches:  $p^r$ 

Probability for one Questionair that it doesn't match:  $(1-p)^r$ 

Probability that at least one Q. Matches:  $1 - (1 - p)^r$ 

b) The probability that exactly two (no matter which) questionnaires match, i.e. have the same answers for both C1 and C2.

binomial coefficient

formula:

$$\binom{b}{2}*(p^r)^2*(1-(p^r))^{b-2}$$

## Exercise 02

siehe  $Ex8_2_3$ 

#### Exercise 03

siehe  $Ex8_2_3$ 

#### Exercise 04

• BALANCE Algorithm:

For each query, assign it to an advertiser with the largest unspent budget (i.e. largest BAL-ANCE) A(x,y) B(x,z)

Worst Case Szenarios:

- a) xyyy  $AA_{-}$  (since there are 3 y no optimal solution possible, A has only 2 dollars.)
- b) xyyx AA\_B (optimal solution is possible but not certain BAAB)
- c) yyxx AABB (Optimal)
- d) xzyz BBA<sub>-</sub> (optimal solution is possible but not certain ABAB)
- Since we used the worst case possible query assignment with the balance Algorithm we can show that only c) would give an optimal solution. All the other queries have situations where an optimal solution is not certain. c's optimal solution is because A and B cant steal from each other, because their budget is empty before the other can take anything from their common x.

## Exercise 05

- budget: 3 / ties in favor of lower index
- $A_1(Q_1,Q_2)$   $A_2(Q_2,Q_3)$   $A_3(Q_3,Q_4)$   $A_4(Q_1,Q_4)$
- Query:  $Q_1, Q_2, Q_3, Q_3, Q_1, Q_2, Q_3, Q_1, Q_4, Q_1, Q_4$
- a) What is the sequence of advertisers that the BALANCE algorithm will yield?

$$A_1, A_2, A_3, A_2, A_4, A_1, A_3, A_4, A_3, A_1, A_4$$

What is the competitive ratio for this instance?

$$Competitive\ ratio = min_{(}all\ possible\ inputs) \frac{|M_{(}greedy)|}{(|M_{(}opt|))}) \frac{11}{11} = 1$$

b) Rearrange the sequence of queries so that BALANCE results in a worse competitive ratio.

```
Query: Q_1, Q_1, Q_1, Q_1, Q_4, Q_4, Q_2, Q_2, Q_3, Q_3, Q_3

A_1, A_4, A_1, A_4, A_3, A_3, A_2, A_2, A_2, A_3, \dots

\frac{10}{11} = 0,9090909091
```

### Exercise 06

siehe Ex8\_6.py

- a) see  $Ex8_6a.py$
- b) see  $Ex8\_6b.py$

I had a problem while overwriting the old data. The error code was:

It is possible the underlying files have been updated. You can explicitly

- $\hookrightarrow$  invalidate the cache in Spark by running 'REFRESH TABLE tableName'
- $\hookrightarrow$  command in SQL or by recreating the Dataset/DataFrame involved.

I guess spark had problems with my filesystem (maybe access rights), but I don't know exactly. The solution was to write in a temp folder, delete the old one and rename the temp folder.

c) see  $Ex8\_6c.py$ 

## Exercise 07

MISSING