

# Predicting Protein Organelle Localization with Transfer Learning

Ruge Zhao,<sup>1</sup> Siyi Tang<sup>2</sup>

<sup>1</sup> Department of Statistics, Stanford University

<sup>2</sup> Department of Electrical Engineering, Stanford University

Stanford

## Motivation

- Advances in high-throughput microscopy images aid understanding of complex protein functions in human cells
- Accurate image classifications required for large-scale cell images provided by Human Protein Atlas (HPA) [1]
- Machine learning algorithms proven to be effective in automating the classification [2-4]

## Goal

- Predict protein organelle localization labels in human cell samples
- Explore effectiveness of transfer learning

## Data

- 31072 samples, 28 classes
- Each sample represented by 4 channels (RGBY)
- Each sample labeled with  $\geq 1$  protein organelle locations
- Imbalanced classes (e.g. 12885 vs 11)
- Train/validation/test sets: 24858/3107/3107




Fig. 1: Four channels of two cell samples

## Preprocessing

- Standardized with respect to train set
- Data augmentation: random rotate, flip, lighting

## Baseline

- 28 one-vs-all classifiers
- Logistic regression (LR) & random forest (RF)




Fig. 2: Overview of preprocessing and transfer learning

## Transfer learning of ResNet50

ResNet50 pre-trained on ImageNet dataset

### Initializing network weights

- RGB: initialized with pre-trained weights
- Y: initialized with pre-trained R weights

### Loss functions

- Binary cross-entropy (BCE) loss
- Focal loss [5]

$$L_{BCE}(p_t) = -\log(p_t)$$

$$L_{FL}(p_t) = -(1 - p_t)^\gamma \log(p_t)$$

where  $p_t = p$  if  $y = 1$ , else  $p_t = (1 - p)$ ;  
 $y \in \{0,1\}$ : true label;  $p \in [0,1]$ : predicted prob.

- Focal loss equivalent to BCE loss when  $\gamma = 0$

### Training of the network

- Freeze all layers except last, train for 1 epoch
- Unfreeze all layers and train until overfit

### Choosing optimal learning rate

- Picked learning rate where loss is low but still clearly decreasing




Fig. 3: Learning rate vs training loss

### Differential learning rates

- Later layers need more fine-tuning to capture dataset-specific features
- Higher learning rate for later layers

### Training with stochastic gradient descent with restarts (SGDR) [6]

- Learning rate annealing during each cycle, and restarts learning rate at next cycle
- Encourages to find “smooth” rather than “spiky” local minimum




Fig. 4: Learning rate vs number of iterations during training with SGDR

## Results

### Baseline

- LR performed better than RF
- Best baseline model: macro F1 = 0.12

### Transfer learning models

- Best model without SGDR: Focal loss with  $\gamma=0.2$
- With SGDR:
  - SGDR improved macro F1
  - Focal loss and BCE loss had comparable performance.




Fig. 5: Performance comparison on test data: macro F1




Fig. 6: Performance comparison on test data: ROC AUC

## Conclusion and future work

- ResNet pre-trained on ImageNet data has learned transferable features applicable to the HPA dataset
- Transfer learning model outperformed traditional machine learning models

### Future work

- Experiment with highest resolution for all models
- Reweigh / resample majority and minority classes

## References

- [1] D. P. Sullivan, C. F. Winsnes, L. Akesson, M. Hjelmare, M. Wiking, R. Schutten, L. Campbell, H. Leifsson, S. Rhodes, A. Nordgren, K. Smith, B. Revaz, B. Finnbogason, A. Szantner, and E. Lundberg, “Deep learning is combined with massive-scale citizen science to improve large-scale image classification,” *Nature Biotechnology*, vol. 36, p. 820, aug 2018.
- [2] J. Li, L. Xiong, J. Schneider, and R. F. Murphy, “Protein subcellular location pattern classification in cellular images using latent discriminative models,” *Bioinformatics*, vol. 28, no. 12, pp. i32–i39, 2012.
- [3] O. Z. Kraus, J. L. Ba, and B. J. Frey, “Classifying and segmenting microscopy images with deep multiple instance learning,” *Bioinformatics*, vol. 32, no. 12, pp. i52–i59, 2016.
- [4] T. Pärnmaa and L. Parts, “Accurate classification of protein subcellular localization from high-throughput microscopy images using deep learning,” *G3: Genes, Genomes, Genetics*, vol. 7, no. 5, pp. 1385–1392, 2017.
- [5] T. Lin, P. Goyal, R. B. Girshick, K. He, and P. Dollár, “Focal loss for dense object detection,” in *IEEE International Conference on Computer Vision, ICCV 2017, Venice, Italy, October 22–29, 2017*, 2017, pp. 2999–3007.
- [6] I. Loshchilov and F. Hutter, “Sgdr: Stochastic gradient descent with warm restarts,” *arXiv preprint arXiv:1608.03983v5*, 2016.
- [7] lafoss, “Kaggle kernel,” <https://www.kaggle.com/lafoss/pretrained-resnet34-with-rgb-0-460-public-lb>, 2018.