#### 打地鼠困境

#### A Whac-A-Mole Dilemma 🚉:



<sup>†</sup>Zhiheng Li<sup>2</sup> <sup>‡</sup>Ivan Evtimov<sup>1</sup> Albert Gordo<sup>1</sup> Caner Hazirbas<sup>1</sup> Tal Hassner<sup>1</sup> Cristian Canton Ferrer<sup>1</sup> Chenliang Xu<sup>2</sup> <sup>‡</sup>Mark Ibrahim<sup>1</sup>


<sup>1</sup>Meta AI <sup>2</sup>University of Rochester

{ivanevtimov, agordo, hazirbas, thassner, ccanton, marksibrahim}@meta.com {zhiheng.li, chenliang.xu}@rochester.edu

Rui Hu 2023.1.7

#### Motivation

- Most existing works design and evaluate methods under the tenuous assumption that a single shortcut is present in the data.
- Existing methods struggle in a Whac-A-Mole game, i.e., where mitigating one shortcut amplifies reliance on others.




# New Datasets for Multi-Shortcut Mitigation

- UrbanCars Dataset
  - Target: the car's body type
  - Shortcut: background & cooccurring object

	Common BG Common CoObj	Uncommon BG Common CoObj			
Frequency	90.25% 4.75%		4.75%	0.25%	
urban car	•				
country car			STOP		

- ImageNet-Watermark
  - Target: object
  - Shortcut: texture & background & watermark



#### Ubiquitous reliance on the watermark shortcut

- Models of different architectures, augmentations, regularizations and pretraining supervision rely on the watermark as a shortcut.
  - models with larger architectures or extra training data can decrease reliance on the watermark shortcut.
  - CLIP with zero-shot transfer is least affected by watermark shortcuts.

					捷径捷径拉	建径 捷格捷径证务	捷径扩	<b>建径捷径进</b> 径
			Predic	ction: goldfish	w/W	atermark: carton	w/ Waterr	mark: pencil sharpener → carton
method	architecture	(pre)training data	IN-1k Acc↑	$P(\hat{y} = \text{carton})$ (%)	IN-W Gap↑	$\Delta P(\hat{y} = \text{carton}) \ (\%) \downarrow$	Carton Gap ↓	$\Delta P(\hat{y} = \text{carton} \mid y = \text{carton}) (\%) \downarrow$
Supervised	ResNet-50 [30]	IN-1k [17]	76.1	0.07	-26.7	+7.56	+40	+42.46
MoCov3 [13] (LP)	ResNet-50	IN-1k	74.6	0.08	-20.7	+2.94	+44	+44.37
Style Transfer [26]	ResNet-50	SIN [26]	60.1	0.10	-17.3	+4.91	+52	+50.06
Mixup [93]	ResNet-50	IN-1k	76.1	0.07	-18.6	+3.43	+38	+39.78
CutMix [92]	ResNet-50	IN-1k	78.5	0.09	-14.8	+1.92	+22	+29.61
Cutout [19,96]	ResNet-50	IN-1k	77.0	0.08	-18.0	+2.93	+32	+38.06
AugMix [35]	ResNet-50	IN-1k	77.5	0.09	-16.8	+2.61	+36	+34.44
Supervised	RG-32gf	IN-1k	80.8	0.09	-14.1	+3.74	+32	+33.43
SEER [27] (FT)	RG-32gf [67]	IG-1B [27]	83.3	0.09	-6.5	+0.56	+18	+24.26
Supervised	ViT-B/32 [21]	IN-1k	75.9	0.09	-8.7	+1.20	+34	+34.31
Uniform Soup [89] (FT)	ViT-B/32	WIT [66]	79.9	0.09	-7.9	+0.32	+24	+23.87
Greedy Soup [89] (FT)	ViT-B/32	WIT	81.0	0.09	-6.5	+0.35	+16	+23.87
Supervised	ViT-L/16	IN-1k	79.6	0.08	-6.2	+0.82	+34	+32.57
CLIP [66] (zero-shot)	ViT-L/14	WIT	76.5	0.06	-4.4	+0.01	+12	+1.75
CLIP (zero-shot)	ViT-L/14	LAION-400M [74]	72.7	0.05	-4.9	+0.03	+12	+13.76
MAE [29] (FT)	ViT-H/14	IN-1k	86.9	0.08	-3.5	+0.43	+30	+29.59
SWAG [79] (LP)	ViT-H/14	IG-3.6B [79]	85.7	0.09	-4.9	+0.19	+8	+12.80
SWAG (FT)	ViT-H/14	IG-3.6B	88.5	0.09	-3.1	+0.35	+18	+20.25
CLIP (zero-shot)	ViT-H/14	LAION-2B [73]	77.9	0.06	-3.6	+0.03	+16	+12.01
	average		78.6	0.08	-10.7	+1.74	+26.7	+27.96

# Benchmark Methods and Settings

 We comprehensively evaluate shortcut mitigation methods across four categories based on the level of shortcut information required.

Category	Summary	<b>Shortcut Information</b>	Methods	
1	Standard Aug- mentation and Regularization	None	Mixup [93], Cutout [19,96], CutMix [92], AugMix [35], SD [63]	
2	Targeted Augmentation for Mitigating Shortcuts	Types of shortcuts (w/o shortcut labels)	CF+F Aug [11], Style Transfer (TXT Aug) [26], BG Aug [71,91], WMK Aug	
3	Using Shortcut Labels	Image-level ground- truth shortcut label	gDRO [72], DI [87], SUBG [38], DFR [45]	
4	Inferring Pseudo Shortcut Labels	Image-level pseudo shortcut label	LfF [60], JTT [58], EIIL [15], DebiAN [53]	

#### Analytic Experiment on New Dataset

- Standard training relies on multiple shortcuts.
- Standard augmentation and regularization methods can mitigate some shortcuts (e.g., texture) but amplify others.
- Augmentations tackling a specific type of shortcut (e.g., style transfer for texture shortcut) can amplify other shortcuts (e.g., watermark).

			shortcut reliance	
	I.D. Acc	BG Gap↑	CoObj Gap↑	BG+CoObj Gap 1
ERM	97.6	-15.3	-11.2	-69.2
Mixup	98.3	-12.6	-9.3	-61.8
CutMix	96.6	-45.0 (×2.94 🚇)	-4.8	-86.5
Cutout	97.8	-15.8 (×1.03 🚇)	-10.4	-71.4
AugMix	98.2	-10.3	-12.1 (×1.08 🚇)	-70.2
SD	97.3	-15.0	-3.6	-36.1
CF+F Aug	96.8	-16.0 (×1.04 🚇)	+0.4	-19.4
LfF	97.2	-11.6	-18.4 (×1.64 🚇)	-63.2
JTT (E=1)	95.9	-8.1	-13.3 (×1.18 🚇)	-40.1
EIIL (E=1)	95.5	-4.2	-24.7 (×2.21 🚇)	-44.9
JTT (E=2)	94.6	-23.3 (×1.52 🚇)	-5.3	-52.1
EIIL (E=2)	95.5	-21.5 (×1.40 🚇)	-6.8	-49.6
DebiAN	98.0	-14.9	-10.5	-69.0
LLE (ours)	96.7	-2.1	-2.7	-5.9

		shortcut reliance							
	IN-1k	Watermark IN-W Gap ↑	(WTM) Carton Gap↓	Tex SIN Gap↑	ture (TXT) IN-R Gap↑	Background (BG IN-9 Gap ↑			
ERM	76.39	-25.40	+30	-69.43	-56.22	-5.19			
Mixup	76.17	-24.87	+34 (×1.13 🖺)	-68.18	-55.79	-5.60 (×1.08 🚇)			
CutMix	75.90	-25.78 (×1.01 🚇)	+32 (×1.06 🚇)	-69.31	-56.36	-5.65 (×1.09 🚇)			
Cutout	76.40	-25.11	+32 (×1.06 🖺)	-69.39	-55.93	-5.35 (×1.03 🖺)			
AugMix	76.23	-23.41	+38 (×1.26 🖺)	-68.51	-54.91	-5.85 (×1.13 🖺)			
SD	76.39	-26.03 (×1.02 🖺)	+30	-69.42	-56.36	-5.33 (×1.03 🚇)			
WTM Aug	76.32	-5.78	+14	-69.31	-56.22	-5.34 (×1.03 🚇)			
TXT 🖥 Aug	75.94	-25.93 (×1.02 🚇)	+36 (×1.20 🚇)	-63.99	-53.24	-5.66 (×1.09 🛢)			
BG 🖺 Aug	76.03	-25.01	+36 (×1.20 🖺)	-68.41	-54.51	-4.67			
LfF	76.35	-26.19 (×1.03 🖺)	+36 (×1.20 🖺)	-69.34	-56.02	-5.61 (×1.08 🖺)			
JTT	76.33	-26.40 (×1.04 🖺)	+32 (×1.06 🖺)	-69.48	-56.30	-5.55 (×1.07 🖺)			
EIIL	71.55	-33.48 (×1.31 🗒)	+24	-66.04	-61.35 (×1.09 🚇)	-6.42 (×1.24 🗒)			
DebiAN	76.33	-26.40 (×1.04 🖺)	+36 (×1.20 🖺)	-69.37	-56.29	-5.53 (×1.07 ♠)			
LLE (ours)	76.25	-6.18	+10	-61.00	-54.89	-3.82			

## Analytic Experiment on New Dataset

- Methods using shortcut labels mitigate the labeled shortcut but amplifies the unlabeled one.
- Methods inferring pseudo shortcut labels still amplify shortcuts. (previous page)
  - Because ERM learns different shortcuts asynchronously during training, making it hard to infer labels of all shortcuts for mitigation.

	shortcu	at label		shortcut reliance			
	Train	Val	I.D. Acc	BG Gap↑	CoObj Gap↑	BG+CoObj Gap↑	
ERM	Х	BG+CoObj	97.6	-15.3	-11.2	-69.2	
gDRO	BG+CoObj	BG+CoObj	91.6	-10.9	-3.6	-16.4	
DI	BG+CoObj	BG+CoObj	89.0	-2.2	-1.0	+0.4	
SUBG	BG+CoObj	BG+CoObj	71.1	-4.7	-0.3	-6.3	
DFR	BG+CoObj	BG+CoObj	89.7	-10.7	-6.9	-45.2	
ERM	Х	BG	97.8	-14.6	-11.3	-68.5	
gDRO	BG 🖢	BG	96.0	-4.2	-26.9 (×2.39 📵)	-56.5	
DI	BG 퉅	BG	94.7	+2.2	-27.0 (×2.40 🚇)	-25.2	
SUBG	BG 🖆	BG	92.6	+1.3	-36.4 (×3.24 🗓)	-35.8	
DFR	BG \overline 🔭	BG	97.4	-9.8	-13.6 (×1.21 🚇)	-58.9	
ERM	Х	CoObj	97.6	-15.4	-11.0	-68.8	
gDRO	CoObj 🖢	CoObj	95.7	-31.4 (×2.03 🚇)	-0.5	-54.9	
DI	CoObj 🖢	CoObj	94.2	-36.1 (×2.34 🚇)	+2.8	-35.8	
SUBG	CoObj 🖢	CoObj	93.1	-60.2 (×3.90 🚇)	+2.5	-62.4	
DFR	CoObj 🔄	CoObj	97.4	$-19.1 \times 1.24$	-8.6	-64.9	




# Analytic Experiment on New Dataset

• Self-supervised and foundation models can mitigate some shortcuts but amplify others.

				shortcut reliance	;	
		Water	mark	Tex	ture	Background
	IN-1k	IN-W Gap↑	Carton Gap $\downarrow$	SIN Gap↑	IN-R Gap↑	IN-9 Gap↑
arch: RG-32gf						
ERM	80.88	-14.15	+32	-69.27	-52.43	-6.40
SEER (FT,IG-1B)	83.35	-6.50	+18	-73.04 (×1.05 🖺)	-50.42	-7.14 (×1.11 🖺)
arch: ViT-B/32						
ERM	75.92	-8.71	+34	-57.16	-49.45	-6.86
Uniform Soup (FT,WIT)	79.96	-7.90	+24	-59.67 (×1.04 🖺)	-27.51	-7.78 (×1.13 🖺)
Greedy Soup (FT,WIT)	81.01	-6.47	+16	-59.61 (×1.04 🖺)	-30.01	-7.21 (×1.05 🖺)
arch: ViT-B/16						
ERM	81.07	-6.69	+26	-62.60	-50.36	-5.36
SWAG (LP,IG-3.6B)	81.89	-7.76 (×1.16 🗓)	+18	-67.33 (×1.08 🖺)	-19.79	-10.39 (×1.94 🚇
SWAG (FT,IG-3.6B)	85.29	-5.43	+24	-66.99 (×1.07 🖺)	-29.55	-4.44
MoCov3 (LP)	76.65	-16.0 (×2.39 🖺)	+22	-63.36 (×1.01 🖺)	-56.86 (×1.12 🖺)	-7.80 (×1.45 🖺)
MAE (FT)	83.72	-4.60	+24	-65.20 (×1.04 🖺)	-47.10	-4.45
MAE+LLE (ours)	83.68	-2.48	+6	-58.78	-44.96	-3.70
arch: ViT-L/16 or 14						
ERM	79.65	-6.14	+34	-61.43	-53.17	-6.50
SWAG (LP,IG-3.6B)	85.13	-5.73	+6	-60.26	-10.17	-7.26 (×1.12 🖺)
SWAG (FT,IG-3.6B)	88.07	-3.16	+20	-63.45 (×1.03 🖺)	-12.29	-2.92
CLIP (zero-shot,WIT)	76.57	-4.47	+12	-61.27	-6.26	-3.68
CLIP (zero-shot,LAION)	72.77	-4.94	+12	-56.85	-8.43	-4.54
MAE (FT)	85.95	-4.36	+22	-62.48 (×1.02 🖺)	-36.46	-3.53
MAE+LLE (ours)	85.84	-1.74	+12	-56.32	-34.64	-2.77

# Method: Last Layer Ensemble

 We focus on mitigating multiple known shortcuts, i.e., the number and types of shortcuts are given, but shortcut labels are not.



#### Limitation

- Not all shortcuts can be data augmented.
- Need to know the type of shortcut.

#### Conclusion

• Studying the Whac-A-Mole dilemma of Large Pretrained Models in shortcut mitigation is meaningful.