

# QA·C 8.1 SOURCE CODE ANALYZER RELEASE NOTES

**July 2012** 

This document lists the QA·C Source Code Analyzer 8.1 application release notes.





## **IMPORTANT NOTICE**

#### **DISCLAIMER OF WARRANTY**

The staff of Programming Research Ltd have taken due care in preparing this document which is believed to be accurate at the time of printing. However, no liability can be accepted for errors or omissions nor should this document be considered as an expressed or implied warranty that the products described perform as specified within.

## **COPYRIGHT NOTICE**

This document is copyrighted and may not, in whole or in part, be copied, reproduced, disclosed, transferred, translated, or reduced to any form, including electronic medium or machine-readable form, or transmitted by any means, electronic or otherwise, unless Programming Research Ltd consents in writing in advance.

#### **TRADEMARKS**

PRQA, the PRQA logo, and QA·C are registered trademarks of Programming Research Ltd. Windows is a registered trademark of Microsoft Corporation.

#### **CONTACTING PROGRAMMING RESEARCH LTD**

For technical support, contact your nearest Programming Research Ltd authorized distributor or you can contact Programming Research's head office:

by telephone on +44 (0) 1 932 888 080 by fax on +44 (0) 1 932 888 081

or by e-mail on <a href="mailto:support@programmingresearch.com">support@programmingresearch.com</a> www.programmingresearch.com





# **Table of Contents**

1.	INTRODUCTION	4
	KEY ADDITIONAL FUNCTIONALITY	
	UNDERLYING TYPE / ESSENTIAL TYPE	
4.	CHANGES TO DATAFLOW METRICS GENERATION	5
5.	NEW MESSAGES	6
6.	REMOVED MESSAGES	14
7.	MESSAGES WITH MODIFIED BEHAVIOR	15
8	CR SUMMARY	19





#### 1. INTRODUCTION

The 8.1 release of QA·C features a revision of the arithmetic type conversion analysis to provide more intuitive, easier to understand messages. There are a number of incremental improvements in parsing extended keywords as well as new analysis messages and numerous bug fixes. In addition the dataflow engine has been enhanced to understand pointer aliasing and perform inter-function within a TU analysis.

#### 2. KEY ADDITIONAL FUNCTIONALITY

- · Parsing support for
  - C99 type \_Bool
  - C99 "inline" functions
  - GCC #include\_next syntax
  - Source files in UTF-8 encoding
  - Renesas compiler inline assembler syntax
  - · Renesas compiler default parameter value syntax
- Primary Analysis
  - Radical revisions to message system to improve analysis of expressions of arithmetic type
  - Improved enforcement of MISRA-C:2004 rules which use 'underlying type' concept
  - Other additional new analysis messages
  - Sundry bug-fixes
- Dataflow Analysis
  - Pointer alias analysis tracking the state of an object which is accessed via a pointer.
  - Inter-function dataflow analysis within a single translation unit.
  - Some additional analysis improvements.
- GUI Modifications

A set of dataflow configuration files is provided which support simpler control of dataflow analysis. In the Windows GUI, a dataflow level can be selected using the new Dataflow Level selector or via the Dataflow Settings dialog from the Configuration menu. Alternatively, the user can tailor the individual dataflow settings from this Dataflow Settings dialog by creating a user-defined configuration file. The Unix GUI provides access to the individual dataflow settings via a Dataflow Settings dialog which is accessible from the main toolbar.





### 3. UNDERLYING TYPE / ESSENTIAL TYPE

Version 8.1 of QA·C introduces an extensive range of new messages associated with type usage and type conversion. These messages are intended ultimately to supersede many pre-existing messages which are now classified as obsolete. (Messages classified as obsolete are generally removed after 2 full releases of the product).

The new type messages refer extensively to the concept of "essential type" – a term which is closely based on the principles of "underlying type" first introduced in MISRA-C:2004. Essential type is simply a way of capturing the essential nature of an expression in a way that avoids some of the unfortunate anomalies which exist in the C language. In many instances, the essential type of an expression is defined to be identical to its standard type – the type defined in the C language.

By adopting "essential type" concepts, a static analysis tool is able to provide:

- A message system which is more intuitive
- A more comprehensive enforcement of MISRA-C coding guidelines.
- A reduction in the incidence of noisy messages
- A full discussion of essential type principles and the new QA·C messages is provided in the QAC-8.1-EssentialTypeUsersGuide.pdf document supplied with this release.

#### 4. CHANGES TO DATAFLOW METRICS GENERATION

Metrics that are generated as part of the dataflow analysis have had their behaviour changed. When dataflow is disabled, either explicitly using -ed- or implicitly via a dataflow termination message (see Appendix B of the Dataflow Reference Guide), then in QA·C 8.1 no dataflow metrics will be written to the .met file. In QA·C 8.0 when dataflow was disabled the metrics appeared as 0 in the .met file. Furthermore, when QA·C 8.1 does generate the metrics they will be generated in a separate metric group from that of the metrics generated as part of the initial parser analysis.

#### The affected metrics are:

- STAV1 Average size of function statements (variant 1)
- STAV2 Average size of function statements (variant 2)
- STAV3 Average size of function statements (variant 3)
- STST1 Number of statements in function (variant 1)
- STST2 Number of statements in function (variant 2)
- STST3 Number of statements in function (variant 3)
- STRET Number of function return points
- STUNR Number of unreachable statements





# 5. NEW MESSAGES

The following table lists messages which are new in QA·C 8.1.

Msg	Message Text	CR
0318	Redundant type qualifier used in cast.	11300
0360	An expression of pointer type is being converted to type _Bool on assignment.	14059
0361	An expression of pointer type is being cast to type _Bool.	14059
0362	An expression of essentially Boolean type is being cast to a pointer.	14059
0570	This switch case label of 'essential type' '%1s', is not consistent with a controlling	14325
	expression of essential type '%2s'.	
0571	This switch case label of 'essential type' '%1s' is not consistent with a controlling	14325
	expression which has an essential type of higher rank (%2s).	
0572	This switch case label of 'essential type' '%1s' is not consistent with a controlling	14325
	expression which has an essential type of lower rank (%2s).	
1045	[E] Use of the #include_next preprocessing directive is a language extension.	13407
1046	[E] Function is being declared with default argument syntax. This is a language	13468
	extension.	
1047	[C] Function is being declared with default argument syntax after a previous call to the	13468
	function. This is not allowed.	
1048	[C] Default argument values are missing for some parameters in this function	13468
	declaration. This is not allowed.	
1055	[C99] The keyword 'inline' has been used.	10977
1056	[C99] The keyword '_Bool' has been used.	14059
1290	An integer constant of 'essentially signed' type is being converted to unsigned type on	11047
	assignment.	
1291	An integer constant of 'essentially unsigned' type is being converted to signed type on	11047
	assignment.	
1292	An integer constant of 'essentially signed' type is being converted to type char on	11047
	assignment.	
1293	An integer constant of 'essentially unsigned' type is being converted to type char on	11047
	assignment.	
1294	An integer constant of 'essentially signed' type is being converted to type _Bool on	11047
	assignment.	
1295	An integer constant of 'essentially unsigned' type is being converted to type _Bool on	11047
	assignment.	
1296	An integer constant of 'essentially signed' type is being converted to enum type on	11047
	assignment.	
1297	An integer constant of 'essentially unsigned' type is being converted to enum type on	11047
	assignment.	
1298	An integer constant of 'essentially signed' type is being converted to floating type on	11047
	assignment.	
1299	An integer constant of 'essentially unsigned' type is being converted to floating type on	11047
	assignment.	
1337	Function defined with a variable number of parameters.	13590
1800	The %1s operand (essential type: '%2s') will be implicitly converted to a floating type,	14284
	'%3s', in this arithmetic operation.	
1802	The %1s operand (essential type: '%2s') will be implicitly converted to a floating type,	14284
	'%3s', in this relational operation.	
1803	The %1s operand (essential type: '%2s') will be implicitly converted to a floating type,	14284
	'%3s', in this equality operation.	





The %1s operand (essential type: "\$2s") will be implicitly converted to a floating type, "\$3s", in this conditional operation.   14286	Msg	Message Text	CR
%35, in this conditional operation.			14284
1810   An operand of 'essentially character' type is being added to another operand of 'essentially character' type.   14286			
'essentially character' type.  1811 An operand of 'essentially character' type is being subtracted from an operand of 'essentially character' type is being subtracted from an operand of 'essentially character' type is being subtracted from an operand of 'essentially character' type is being balanced with an operand of 'essentially foating' type in this arithmetic operation.  1820 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1821 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1822 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1823 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1824 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1830 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this sonditional operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative	1810		14286
1811   An operand of 'essentially character' type is being subtracted from an operand of 'essentially signed' type.   14286			
'essentially signed' type.  1812 An operand of 'essentially character' type is being subtracted from an operand of 'essentially unsigned' type.  1813 An operand of 'essentially character' type is being balanced with an operand of 'essentially floating' type in this arithmetic operation.  1820 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1821 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1822 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1823 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1824 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1830 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional	1811		14286
An operand of 'essentially character' type is being subtracted from an operand of 'essentially unsigned' type.   14286		, , , , , , , , , , , , , , , , , , , ,	
"essentially loating" type in this arithmetic operation.  1820 The %1s operand is non-constant and "essentially signed" (%2s) but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1821 The %1s operand is non-constant and "essentially signed" (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1822 The %1s operand is non-constant and "essentially signed" (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1823 The %1s operand is non-constant and "essentially signed" (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1824 The %1s operand is non-constant and "essentially signed" (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1824 The %1s operand is non-constant and "essentially signed" (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1830 The %1s operand is constant, "essentially signed" (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, "essentially signed" (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1832 The %1s operand is constant, "essentially signed" (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, "essentially signed" (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, essentially signed" (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, essentially signed" (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1845 The %1s operand is constant, essentially signed" (%2s) and n	1812		14286
1813			
'essentially floating' type in this arithmetic operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  14285  1821 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1822 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1823 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1824 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1830 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1845 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1846 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1847 The %1s operand is constant, 'essenti	1813		14286
The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.   14285			
converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly con	1820	The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly	14281
The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1822 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1823 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1824 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1830 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly co	. 0_0	converted to an unsigned type (%3s) in this arithmetic operation.	
converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this platitity operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be imp	1821		
1822         The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this relational operation.         14285           1823         The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.         14285           1824         The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.         14285           1830         The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.         14285           1831         The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this invitational operation.         14285           1832         The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.         14285           1833         The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.         14285           1840         The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.         14285           1841         The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly conv	.02.		1.200
converted to an unsigned type (%3s) in this relational operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this plational operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this platicity operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this it is this operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly	1822		14285
The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this equality operation.   14285	.022		1.200
converted to an unsigned type (%3s) in this equality operation.  1824 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1830 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this inthis equality operation.  1851 The %1s operand i	1823		14285
1824 The %1s operand is non-constant and 'essentially signed' (%2s) but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1830 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1845 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed t	.020		1.200
converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s)	1824		14285
1830 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in th	1021		1.200
implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational	1830		14285
1831 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1845 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.			
implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1845 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will b	1831		14285
1832 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.			1.200
implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.	1832		14285
1833 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.			
implicitly converted to an unsigned type (%3s) in this equality operation.  1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.	1833		14285
1834 The %1s operand is constant, 'essentially signed' (%2s) and negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.			
implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.	1834		14285
1840 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this arithmetic operation.  1841 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  1842 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  1843 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285			
implicitly converted to an unsigned type (%3s) in this arithmetic operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.	1840		14285
The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.			
implicitly converted to an unsigned type (%3s) in this bitwise operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.	1841		14285
The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.			
implicitly converted to an unsigned type (%3s) in this relational operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.	1842		14285
The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.			
implicitly converted to an unsigned type (%3s) in this equality operation.  The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.	1843		14285
1844 The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will be implicitly converted to an unsigned type (%3s) in this conditional operation.  1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285			
implicitly converted to an unsigned type (%3s) in this conditional operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285	1844		14285
1850 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this arithmetic operation.  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285			
signed type (%3s) in this arithmetic operation.  14285  1851 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  1852 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285	1850		14281
The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285			14285
signed type (%3s) in this bitwise operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285  The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285	1851		14285
<ul> <li>The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this relational operation.</li> <li>The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.</li> <li>The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a</li> <li>The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a</li> </ul>			
signed type (%3s) in this relational operation.  1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285	1852		14285
1853 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285			
signed type (%3s) in this equality operation.  1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285	1853		14285
1854 The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to a 14285	1	, , , , , , , , , , , , , , , , , , , ,	
	1854		14285
	1		





Msg	Message Text	CR
1860	The operands of this arithmetic operator are of different 'essential signedness' but will	14285
	generate a result of type 'signed int'.	
1861	The operands of this bitwise operator are of different 'essential signedness' but will	14285
	generate a result of type 'signed int'.	
1862	The operands of this relational operator are of different 'essential signedness' but will	14285
	both be promoted to 'signed int' for comparison.	
1863	The operands of this equality operator are of different 'essential signedness' but will	14285
	both be promoted to 'signed int' for comparison.	
1864	The 2nd and 3rd operands of this conditional operator are of different 'essential	14285
	signedness'. The result will be in the promoted type 'signed int'.	
1880	The operands of this relational operator are expressions of different 'essential type'	14287
	categories (%1s and %2s).	
1881	The operands of this equality operator are expressions of different 'essential type'	14287
	categories (%1s and %2s).	
1882	The 2nd and 3rd operands of this conditional operator are expressions of different	14287
	'essential type' categories (%1s and %2s).	
1890	A composite expression of 'essentially signed' type (%1s) is being implicitly converted	14303
	to a wider signed type, '%2s'.	
1891	A composite expression of 'essentially unsigned' type (%1s) is being implicitly	14303
	converted to a wider unsigned type, '%2s'.	
1892	A composite expression of 'essentially floating' type (%1s) is being implicitly converted	14303
	to a wider floating type, '%2s'.	
1893	The 2nd and 3rd operands of this conditional operator are both 'essentially signed'	14303
	('%1s' and '%2s') but one is a composite expression of a narrower type than the other.	
1894	The 2nd and 3rd operands of this conditional operator are both 'essentially unsigned'	14303
	('%1s' and '%2s') but one is a composite expression of a narrower type than the other.	
1895	The 2nd and 3rd operands of this conditional operator are both 'essentially floating'	14303
	('%1s' and '%2s') but one is a composite expression of a narrower type than the other.	
2000	No 'else' clause exists for this 'if' statement.	11075
2109	Integral promotion : _Bool promoted to signed int.	14059
2119	Default argument promotion : _Bool promoted to signed int.	14059
2120	Integral promotion : unsigned bit-field promoted to signed int.	10391
2122	Integral promotion : unsigned bit-field promoted to unsigned int.	10391
2124	Integral promotion : signed bit-field promoted to signed int.	10391
2130	Default argument promotion: unsigned bit-field promoted to signed int.	10391
2132	Default argument promotion: unsigned bit-field promoted to unsigned int.	10391
2134	Default argument promotion: signed bit-field promoted to signed int.	10391
2756	Could not expand function call to '%1s' with maximum '-po df::inter' value.	13872
2757	Could not analyse function '%1s'. Try a smaller '-po df::inter' value?	13872
2845	Constant: Maximum number of characters to be written is larger than the target buffer	14409
	size.	
2846	Definite: Maximum number of characters to be written is larger than the target buffer	14409
	size.	
2847	Apparent: Maximum number of characters to be written is larger than the target buffer	14409
	size.	
2848	Suspicious: Maximum number of characters to be written is larger than the target	14409
	buffer size.	
2984	This operation is redundant. The value of the result is always '%1s'.	13640
2985	This operation is redundant. The value of the result is always that of the left-hand	13640
	operand.	





Msg	Message Text	CR
2986	This operation is redundant. The value of the result is always that of the right-hand	13640
	operand.	
3004	This integral constant expression is being interpreted as a NULL pointer constant.	14121
3236	[C] 'inline' may not be applied to function 'main'.	10977
3237	[C] inline function '%1s' has external linkage and is defining an object, '%2s', with static	10977
	storage duration.	
3238	[C] inline function '%1s' has external linkage and is referring to an object, '%2s', with	10977
	internal linkage.	
3239	[U] inline function '%1s' has external linkage, but is not defined within this translation	10977
	unit.	
3240	inline function '%s' is being defined with external linkage.	10977
3243	inline function '%s' is also an 'external definition'.	10977
3244	[C] 'inline' may only be used in the declaration of a function identifier.	10977
3491	Using conditional operator in a macro.	10947
3492	Using conditional operator outside a macro.	10947
3495	Using a conditional operator in place of a selection statement.	10947
4301	An expression of 'essentially Boolean' type (%1s) is being cast to character type '%2s'.	14231
4302	An expression of 'essentially Boolean' type (%1s) is being cast to enum type '%2s'.	14231
4303	An expression of 'essentially Boolean' type (%1s) is being cast to signed type '%2s'.	14231
4304	An expression of 'essentially Boolean' type (%1s) is being cast to unsigned type '%2s'.	14231
4305	An expression of 'essentially Boolean' type (%1s) is being cast to floating type '%2s'.	14231
4310	An expression of 'essentially character' type (%1s) is being cast to Boolean type, '%2s'.	14231
4312	An expression of 'essentially character' type (%1s) is being cast to enum type, '%2s'.	14231
4315	An expression of 'essentially character' type (%1s) is being cast to floating type, '%2s'.	14231
4320	An expression of 'essentially enum' type (%1s) is being cast to Boolean type, '%2s'.	14231
4322	An expression of 'essentially enum' type (%1s) is being cast to a different enum type, '%2s'.	14231
4325	An expression of 'essentially enum' type (%1s) is being cast to floating type, '%2s'.	14231
4330	An expression of 'essentially signed' type (%1s) is being cast to Boolean type '%2s'.	14231
4332	An expression of 'essentially signed' type (%1s) is being cast to enum type, '%2s'.	14231
4340	An expression of 'essentially unsigned' type (%1s) is being cast to Boolean type '%2s'.	14231
4342	An expression of 'essentially unsigned' type (%1s) is being cast to enum type '%2s'.	14231
4350	An expression of 'essentially floating' type (%1s) is being cast to Boolean type '%2s'.	14231
4351	An expression of 'essentially floating' type (%1s) is being cast to character type '%2s'.	14231
4352	An expression of 'essentially floating' type (%1s) is being cast to enum type, '%2s'.	14231
4390	A composite expression of 'essentially signed' type (%1s) is being cast to a wider	14146
	signed type, '%2s'.	
4391	A composite expression of 'essentially unsigned' type (%1s) is being cast to a wider unsigned type, '%2s'.	14146
4392	A composite expression of 'essentially floating' type (%1s) is being cast to a wider floating type, '%2s'.	14146
4393	A composite expression of 'essentially signed' type (%1s) is being cast to a different	14146
	type category, '%2s'.	
4394	A composite expression of 'essentially unsigned' type (%1s) is being cast to a different	14146
	type category, '%2s'.	
4395	A composite expression of 'essentially floating' type (%1s) is being cast to a different	14146
	type category, '%2s'.	
4397	An expression which is the result of a ~ or << operation has not been cast to its	11155
	essential type.	





Msg	Message Text	CR
4398	An expression which is the result of a ~ or << operation has been cast to a different	11155
	essential type category.	
4399	An expression which is the result of a ~ or << operation has been cast to a wider type.	11155
4401	An expression of 'essentially Boolean' type (%1s) is being converted to character type,	14234
	'%2s' on assignment.	
4402	An expression of 'essentially Boolean' type (%1s) is being converted to enum type,	14234
	'%2s' on assignment.	
4403	An expression of 'essentially Boolean' type (%1s) is being converted to signed type,	14234
	'%2s' on assignment.	
4404	An expression of 'essentially Boolean' type (%1s) is being converted to unsigned type,	14234
	'%2s' on assignment.	
4405	An expression of 'essentially Boolean' type (%1s) is being converted to floating type,	14234
	'%2s' on assignment.	
4410	An expression of 'essentially character' type (%1s) is being converted to Boolean type,	14234
	'%2s' on assignment.	1 120 1
4412	An expression of 'essentially character' type (%1s) is being converted to enum type,	14234
	'%2s' on assignment.	1 120 1
4413	An expression of 'essentially character' type (%1s) is being converted to signed type,	14234
	'%2s' on assignment.	1 120 1
4414	An expression of 'essentially character' type (%1s) is being converted to unsigned	14234
7717	type, '%2s' on assignment.	14204
4415	An expression of 'essentially character' type (%1s) is being converted to floating type,	14234
7710	'%2s' on assignment.	14204
4420	An expression of 'essentially enum' type (%1s) is being converted to Boolean type,	14234
1120	'%2s' on assignment.	14204
4421	An expression of 'essentially enum' type (%1s) is being converted to character type,	14234
7721	'%2s' on assignment.	14204
4422	An expression of 'essentially enum' type (%1s) is being converted to a different enum	14234
	type, '%2s' on assignment.	1 120 1
4423	An expression of 'essentially enum' type (%1s) is being converted to signed type,	14234
1.20	'%2s' on assignment.	
4424	An expression of 'essentially enum' type (%1s) is being converted to unsigned type,	14234
	'%2s' on assignment.	1 120 1
4425	An expression of 'essentially enum' type (%1s) is being converted to floating type,	14234
1.20	'%2s' on assignment.	1 120 1
4430	An expression of 'essentially signed' type (%1s) is being converted to Boolean type,	14234
	'%2s' on assignment.	
4431	An expression of 'essentially signed' type (%1s) is being converted to character type,	14234
	'%2s' on assignment.	
4432	An expression of 'essentially signed' type (%1s) is being converted to enum type,	14234
1102	'%2s' on assignment.	1 120 1
4434	A non-constant expression of 'essentially signed' type (%1s) is being converted to	14234
	unsigned type, '%2s' on assignment.	13036
4435	A non-constant expression of 'essentially signed' type (%1s) is being converted to	14234
	floating type, '%2s' on assignment.	'
4436	A constant expression of 'essentially signed' type (%1s) is being converted to	14234
	unsigned type, '%2s' on assignment.	'
4437	A constant expression of 'essentially signed' type (%1s) is being converted to floating	14234
	type, '%2s' on assignment.	1.201
4440	An expression of 'essentially unsigned' type (%1s) is being converted to Boolean type,	14234
	'%2s' on assignment.	207
	1 7020 on doorginnone.	1





Msg	Message Text	CR
4441	An expression of 'essentially unsigned' type (%1s) is being converted to character	14234
	type, '%2s' on assignment.	
4442	An expression of 'essentially unsigned' type (%1s) is being converted to enum type,	14234
	'%2s' on assignment.	
4443	A non-constant expression of 'essentially unsigned' type (%1s) is being converted to a	14234
	wider signed type, '%2s' on assignment.	
4445	An expression of 'essentially unsigned' type (%1s) is being converted to floating type,	14234
	'%2s' on assignment.	
4446	A non-constant expression of 'essentially unsigned' type (%1s) is being converted to	14234
	signed type, '%2s' on assignment.	
4447	A constant expression of 'essentially unsigned' type (%1s) is being converted to	14234
	signed type, '%2s' on assignment.	
4450	An expression of 'essentially floating' type (%1s) is being converted to Boolean type,	14234
1400	'%2s' on assignment.	14204
4451	An expression of 'essentially floating' type (%1s) is being converted to character type,	14234
1401	'%2s' on assignment.	14204
4452	An expression of 'essentially floating' type (%1s) is being converted to enum type,	14234
1402	'%2s' on assignment.	14204
4453	An expression of 'essentially floating' type (%1s) is being converted to signed type,	14234
7700	'%2s' on assignment.	14204
4454	An expression of 'essentially floating' type (%1s) is being converted to unsigned type,	14234
1101	'%2s' on assignment.	14204
4460	A non-constant expression of 'essentially signed' type (%1s) is being converted to	14236
4400	narrower signed type, '%2s' on assignment.	14200
4461	A non-constant expression of 'essentially unsigned' type (%1s) is being converted to	14236
1101	narrower unsigned type, '%2s' on assignment.	14200
4462	A non-constant expression of 'essentially floating' type (%1s) is being converted to	14236
1.02	narrower floating type, '%2s' on assignment.	1.200
4463	A constant expression of 'essentially signed' type (%1s) is being converted to narrower	14236
1100	signed type, '%2s' on assignment.	1 1200
4464	A constant expression of 'essentially unsigned' type (%1s) is being converted to	14236
1101	narrower unsigned type, '%2s' on assignment.	1 1200
4465	A constant expression of 'essentially floating' type (%1s) is being converted to	14236
1100	narrower floating type, '%2s' on assignment.	1 1200
4470	A non-constant expression of 'essentially signed' type (%1s) is being passed to a	14238
	function parameter of wider signed type, '%2s'.	1.200
4471	A non-constant expression of 'essentially unsigned' type (%1s) is being passed to a	14238
	function parameter of wider unsigned type, '%2s'.	1 1200
4472	A non-constant expression of 'essentially floating' type (%1s) is being passed to a	14238
7772	function parameter of wider floating type, '%2s'.	14200
4480	A non-constant expression of 'essentially signed' type (%1s) is being returned from a	14238
1100	function defined with a wider signed return type, '%2s'.	1 1200
4481	A non-constant expression of 'essentially unsigned' type (%1s) is being returned from	14238
4-01	a function defined with a wider unsigned return type, '%2s'.	14200
4482	A non-constant expression of 'essentially floating' type (%1s) is being returned from a	14238
7702	function defined with a wider floating return type, '%2s'.	17230
4490	A composite expression of 'essentially signed' type (%1s) is being converted to wider	14239
7730	signed type, '%2s' on assignment.	17233
4491	A composite expression of 'essentially unsigned' type (%1s) is being converted to	14239
7731	wider unsigned type, '%2s' on assignment.	17233
	wider ansigned type, 7023 on assignment.	1





Msg	Message Text	CR
4492	A composite expression of 'essentially floating' type (%1s) is being converted to wider	14239
	floating type, '%2s' on assignment.	
4498	An expression which is the result of a ~ or << operation has been converted to a	11155
	different essential type category on assignment.	
4499	An expression which is the result of a ~ or << operation has been converted to a wider	11155
	essential type on assignment.	
4500	An expression of 'essentially Boolean' type (%1s) is being used as an array subscript.	14034
	, , , , , , , , , , , , , , , , , , ,	14145
4501	An expression of 'essentially Boolean' type (%1s) is being used as the %2s operand of	14036
	this arithmetic operator (%3s).	14145
4502	An expression of 'essentially Boolean' type (%1s) is being used as the %2s operand of	14035
	this bitwise operator (%3s).	14145
4503	An expression of 'essentially Boolean' type (%1s) is being used as the left-hand	14034
1000	operand of this shift operator (%2s).	14145
4504	An expression of 'essentially Boolean' type (%1s) is being used as the right-hand	14034
	operand of this shift operator (%2s).	14145
4505	An expression of 'essentially Boolean' type (%1s) is being used as the %2s operand of	14034
	this relational operator (%3s).	14145
4507	An expression of 'essentially Boolean' type (%1s) is being used as the operand of this	14280
	increment/decrement operator (%2s).	
4510	An expression of 'essentially character' type (%1s) is being used as an array subscript.	14145
4511	An expression of 'essentially character' type (%1s) is being used as the %2s operand	14145
	of this arithmetic operator (%3s).	
4512	An expression of 'essentially character' type (%1s) is being used as the %2s operand	14145
	of this bitwise operator (%3s).	
4513	An expression of 'essentially character' type (%1s) is being used as the left-hand	14145
	operand of this shift operator (%2s).	
4514	An expression of 'essentially character' type (%1s) is being used as the right-hand	14145
	operand of this shift operator (%2s).	
4517	An expression of 'essentially character' type (%1s) is being used as the operand of this	14280
	increment/decrement operator (%2s).	
4518	An expression of 'essentially character' type (%1s) is being used as the %2s operand	14145
	of this logical operator (%3s).	
4519	An expression of 'essentially character' type (%1s) is being used as the first operand	14145
	of this conditional operator (%2s).	
4521	An expression of 'essentially enum' type (%1s) is being used as the %2s operand of	14145
	this arithmetic operator (%3s).	
4522	An expression of 'essentially enum' type (%1s) is being used as the %2s operand of	14145
	this bitwise operator (%3s).	
4523	An expression of 'essentially enum' type (%1s) is being used as the left-hand operand	14145
	of this shift operator (%2s).	
4524	An expression of 'essentially enum' type (%1s) is being used as the right-hand	14145
	operand of this shift operator (%2s).	
4527	An expression of 'essentially enum' type is being used as the operand of this	14280
	increment/decrement operator.	
4528	An expression of 'essentially enum' type (%1s) is being used as the %2s operand of	14145
	this logical operator (%3s).	
4529	An expression of 'essentially enum' type (%1s) is being used as the first operand of	14145
	this conditional operator (%2s).	
4532	An expression of 'essentially signed' type (%1s) is being used as the %2s operand of	14145
	this bitwise operator (%3s).	







Msg	Message Text	CR
4533	An expression of 'essentially signed' type (%1s) is being used as the left-hand operand of this shift operator (%2s).	14145
4534	An expression of 'essentially signed' type (%1s) is being used as the right-hand operand of this shift operator (%2s).	14145
4538	An expression of 'essentially signed' type (%1s) is being used as the %2s operand of this logical operator (%3s).	14145
4539	An expression of 'essentially signed' type (%1s) is being used as the first operand of this conditional operator (%2s).	14145
4542	A non-negative constant expression of 'essentially signed' type (%1s) is being used as the %2s operand of this bitwise operator (%3s).	14145
4543	A non-negative constant expression of 'essentially signed' type (%1s) is being used as the left-hand operand of this shift operator (%2s).	14145
4544	A non-negative constant expression of 'essentially signed' type (%1s) is being used as the right-hand operand of this shift operator (%2s).	14145
4548	A non-negative constant expression of 'essentially signed' type (%1s) is being used as the %2s operand of this logical operator (%3s).	14145
4549	A non-negative constant expression of 'essentially signed' type (%1s) is being used as the first operand of this conditional operator (%2s).	14145
4558	An expression of 'essentially unsigned' type (%1s) is being used as the %2s operand of this logical operator (%3s).	14145
4559	An expression of 'essentially unsigned' type (%1s) is being used as the first operand of this conditional operator (%2s).	14145
4568	An expression of 'essentially floating' type (%1s) is being used as the %2s operand of this logical operator (%3s).	14145
4569	An expression of 'essentially floating' type (%1s) is being used as the first operand of this conditional operator (%2s).	14145
4570	The operand of this ~ operator has an 'essential type' which is narrower than type 'int'.	11155
4571	The left-hand operand of this << operator has an 'essential type' which is narrower than type 'int'.	11155





# 6. REMOVED MESSAGES

Msg	Message Text	CR
4240	The value of an 'effectively Boolean' expression is being assigned to an object of type 'char'.	14033
4241	The value of an 'effectively Boolean' expression is being passed to a function parameter of type 'char'.	14033
4242	The value of an 'effectively Boolean' expression is being returned from a function with a return type of 'char'.	14033
4243	The value of an 'effectively Boolean' expression is being assigned to an object of floating type.	14033
4244	The value of an 'effectively Boolean' expression is being passed to a function parameter of floating type.	14033
4245	The value of an 'effectively Boolean' expression is being returned from a function with a floating return type.	14033





## 7. MESSAGES WITH MODIFIED BEHAVIOR

The following table summarises the messages whose behaviour has been modified as a result of a change in specification.

Msg	Message Text	CR
0268	[S] Comment open at end of translation unit.	14288
0336	Macro defined as an octal constant.	14442
0339	Octal constant used.	14442
0671	[C] Initializer for object of arithmetic type is not of arithmetic type.	14333
0672	[U] The initializer for a 'struct', 'union' or array is not enclosed in braces.	13875
0684	[C] Too many initializers.	13875
0693	Struct initializer is missing the optional {.	13875
0000	Struct Indunt of Indon't guite optional (.	14333
0818	[Q] Cannot find '%s' - Perhaps the appropriate search path was not given?	14506
1006	[E] This in-line assembler construct is a language extension. The code has been	11675
1000	ignored.	11070
1037	[E] Arrays of length zero are a language extension.	14011
1256	An integer constant suffixed with L is being converted to type signed or unsigned	11047
1230	long long on assignment.	11328
	long long on assignment.	14312
1257	An integer constant suffixed with L or LL is being converted to a type of lower	11047
1207	rank on assignment.	11328
	Tank on assignment.	14312
1264	A suffixed floating constant is being converted to a different floating type on	11047
1204	assignment.	14312
1265	An unsuffixed floating constant is being converted to a different floating type on	11047
1200	assignment.	14312
1266	A floating constant is being converted to integral type on assignment.	11047
1200	A housing constant is being converted to integral type on assignment.	14312
1276	An integer constant is being converted to floating type on assignment.	11047
1270	7 in integer constant to being converted to nearing type on assignment.	14312
1411	A constant expression of non-enum type is being passed as argument to a	14323
	function parameter of enum type.	
1412	A constant expression of non-enum type is being assigned to an object of enum	14323
	type.	
1413	A constant expression of non-enum type is being returned from a function with	14323
	an enum return type.	
1441	A non-constant expression of non-enum type is being passed as argument to a	14323
	function parameter of enum type.	
1442	A non-constant expression of non-enum type is being assigned to an object of	14323
	enum type.	
1443	A non-constant expression of non-enum type is being returned from a function	14323
	with an enum return type.	
1475	Range of possible enum values suggests this test is always true.	15536
1476	Range of possible enum values suggests this test is always false.	15536
1477	Object of enum type is being implicitly compared against zero in a controlling	15538
	expression.	
1478	Object of an enum type which does not include a zero value, is being implicitly	15538
	compared against zero in a controlling expression.	12300
2100	Integral promotion : unsigned char promoted to signed int.	11462





2210	Tab character encountered in this line.	11821
2214	Body of control statement is on the same line and is not enclosed within braces.	11867
2752	This '%1s' results in the function being too complex. Dataflow analysis continues	15537
2.02	with the next function.	10001
2755	Analysis time of function '%1s' has exceeded the configured maximum: '%2sms'.	14429
	Dataflow analysis continues with the next function.	
2801	Definite: Overflow in signed arithmetic operation.	14196
2813	Suspicious: Dereference of NULL pointer.	15519
2830	Constant: Division by zero.	12847
		14474
2832	Apparent: Division by zero.	14419
2834	Possible: Division by zero.	14419
2841	Definite: Dereference of an invalid pointer value.	14235
2890	Constant: Negative value implicitly converted to an unsigned type.	13517
		14624
2895	Constant: Negative value cast to an unsigned type.	13517
		14624
2900	Positive integer value truncated by implicit conversion to a smaller unsigned	13517
	type.	14624
2905	Positive integer value truncated by cast to a smaller unsigned type.	13517
		14624
2911	Definite: Wraparound in unsigned arithmetic operation.	14196
2931	Definite: Computing an invalid pointer value.	14235
2962	Apparent: Using value of uninitialized automatic object '%s'.	14365
2963	Suspicious: Using value of uninitialized automatic object '%s'.	14365
2972	Apparent: Passing address of uninitialized object '%s' to a function parameter declared as a pointer to const.	14365
2973	Suspicious: Passing address of uninitialized object '%s' to a function parameter declared as a pointer to const.	14365
2983	This assignment is redundant. The value of this object is never subsequently	13958
	used.	14211
		14212
2984	This operation is redundant. The value of the result is always '%1s'.	14228
2985	This operation is redundant. The value of the result is always that of the left-hand operand.	14228
2986	This operation is redundant. The value of the result is always that of the right-hand operand.	14228
2961	Definite: Using value of uninitialized automatic object '%s'.	14314
2995	The result of this logical operation is always 'true'.	14649
		15658
2996	The result of this logical operation is always 'false'.	14649
		15658
3001	Function has been declared with an empty parameter list.	13167
3103	Result of signed division or remainder operation may be implementation defined.	12847
3104	[S] #pragma '%s' has invalid arguments and has been ignored.	11675
3199	This assignment is redundant. The value of '%s' is never subsequently used.	11788
3212	This cast is redundant.	13516
3317	'#if' not matched by '#endif' in included file. This is probably an error.	12303
3318	'#else'/'#elif'/'#endif' in included file matched '#if' in parent file. This is probably	12303
20.0	an error.	





3447	'%s' is being declared with external linkage but this declaration is not in a header file.	13898
3799-	Implicit conversion: <b>x</b> to <b>y</b> .	14313
3807,	Where <b>x</b> is one of float, double, long double and <b>y</b> is one of char, signed char,	14313
3876,3877,	unsigned char, short, unsigned short, int, unsigned int, long, unsigned long, long	
3810-	long, unsigned long long.	
3818,	long, unsigned long long.	
3878,3879,		
3821-		
3829,		
3880,3881		
3999-	x value returned from y %s().	14313
4007.	Where <b>x</b> is one of float, double, long double and <b>y</b> is one of char, signed char,	14010
4076,4077,	unsigned char, short, unsigned short, int, unsigned int, long, unsigned long, long	
4010-	long, unsigned long long.	
4018,	iong, unoigned long long.	
4078,4079,		
4021-		
4029,		
4080,4081		
4810	Invalid annotation: tag '%1s' is not defined subsequently in this file.	13819
4811	The start of the range '%1s', starts and ends at the same location.	13819
4812	'%1s' not allowed here.	13819
4820	Annotation kind is expected.	13819
4821	Colon is expected.	13819
4822	Tag name is expected.	13819
4823	Annotation syntax error.	13819
4824	Invalid character in tag name.	13819
4825	Unexpected character.	13819
4826	Message specification is incomplete or missing.	13819
4827	Tag name is not allowed in the message specification of continuous suppression	13819
4021	annotation.	13019
4828	Invalid usage of predefined location tag.	13819
2778		15519
2793	Suspicious: Copy between overlapping objects.	
2803	Suspicious: Right hand operand of shift operator is negative or too large.  Suspicious: Overflow in signed arithmetic operation.	15519
	<u> </u>	15519
2813	Suspicious: Dereference of NULL pointer.	15519
2823	Suspicious: Arithmetic operation on NULL pointer.	15519
2833	Suspicious: Division by zero.	15519
2843	Suspicious: Dereference of an invalid pointer value.	15519
2853	Suspicious: Implicit conversion to a signed integer type of insufficient size.	15519
2858	Suspicious: Casting to a signed integer type of insufficient size.	15519
2863	Suspicious: Implementation-defined value resulting from left shift operation on	15519
2000	expression of signed type.	45540
2893	Suspicious: Negative value implicitly converted to an unsigned type.	15519
2898	Suspicious: Negative value cast to an unsigned type.	15519
2903	Suspicious: Positive integer value truncated by implicit conversion to a smaller	15519
0000	unsigned type.	45510
2908	Suspicious: Positive integer value truncated by cast to a smaller unsigned type.	15519
2913	Suspicious: Wraparound in unsigned arithmetic operation.	15519
2923	Suspicious: Left shift operation on expression of unsigned type results in loss of	15519
	high order bits.	







2933	Suspicious: Computing an invalid pointer value.	15519
2943	Suspicious: Result of implicit conversion is only representable in a two's complement implementation.	15519
2948	Suspicious: Result of cast is only representable in a two's complement implementation.	15519
2953	Suspicious: Negative value used in array subscript or pointer arithmetic operation.	15519





## 8. CR SUMMARY

The following table summarises the change requests (CRs) that have been implemented in QA·C 8.1. CRs have been categorised into 3 types (column "T"):

- **C** A significant change has been implemented to existing behaviour.
- **F** A fix of a bug or problem feature.
- **N** New functionality has been introduced.

Some CRs are associated with more than one category and, in some cases, the distinction between categories is a little indistinct. The classification should therefore be treated as a guide only.

CR	Т	Resolution
10391	Ν	New messages have been introduced to identify integral promotion and default
(1880)		argument promotion of bit-fields:
		2120: Integral promotion : unsigned bit-field promoted to signed int.
		2122: Integral promotion : unsigned bit-field promoted to unsigned int.
		2124: Integral promotion : signed bit-field promoted to signed int.
		2130: Default argument promotion : unsigned bit-field promoted to signed int.
		2132: Default argument promotion : unsigned bit-field promoted to unsigned int.
		2134:Default argument promotion: signed bit-field promoted to signed int.
10947	N	New messages have been introduced to identify use of the conditional operator:
(1147)		3491: Using conditional operator in a macro.
		3492: Using conditional operator outside a macro.
		3495: Using a conditional operator in place of a selection statement.
10977	Ν	'inline' functions as specified in the ISO:C99 standard are now fully supported and the
		semantic behaviour is addressed with the following messages.
		1055: [C99] The keyword 'inline' has been used.
		3236: [C] 'inline' may not be applied to function 'main'.
		3237: [C] inline function '%1s' has external linkage and is defining an object, '%2s', with
		static storage duration.
		3238: [C] inline function '%1s' has external linkage and is referring to an object, '%2s',
		with internal linkage.
		3239: [U] inline function '%1s' has external linkage, but is not defined within this
		translation unit.
		3240: inline function '%s' is being defined with external linkage.
		3243: inline function '%s' is also an 'external definition'.
		3244: [C] 'inline' may only be used in the declaration of a function identifier.
11047	C/	The set of messages associated with assignment of literal constants has been
	Ν	rationalised and extended.
		The messages identify situations where a literal constant undergoes type conversion in
		an initialisation, assignment, function argument or function return context.
		Note also:
		The text of the pre-existing messages has been modified.
		The pre-existing messages previously were not generated on function
		arguments. See CR 14312.
		The specification of messages 1256 and 1257 has been modified. See CR
		11328
		Pre-existing Messages:
		1256: An integer constant suffixed with L is being converted to type signed or unsigned
		long long on assignment.
		1257: An integer constant suffixed with L or LL is being converted to a type of lower
		rank on assignment.





CR	Т	Resolution
	•	1264: A suffixed floating constant is being converted to a different floating type on
		assignment.
		1265: An unsuffixed floating constant is being converted to a different floating type on
		assignment.
		1266: A floating constant is being converted to integral type on assignment.
		1276: An integer constant is being converted to floating type on assignment.
		New messages: 1290: An integer constant of 'essentially signed' type is being converted to unsigned
		type on assignment.
		1291: An integer constant of 'essentially unsigned' type is being converted to signed type on assignment.
		1292: An integer constant of 'essentially signed' type is being converted to type char on assignment.
		1293: An integer constant of 'essentially unsigned' type is being converted to type char on assignment.
		1294: An integer constant of 'essentially signed' type is being converted to type _Bool on assignment.
		1295: An integer constant of 'essentially unsigned' type is being converted to type _Bool on assignment.
		1296: An integer constant of 'essentially signed' type is being converted to enum type on assignment.
		1297: An integer constant of 'essentially unsigned' type is being converted to enum type on assignment.
		1298: An integer constant of 'essentially signed' type is being converted to floating type on assignment.
		1299: An integer constant of 'essentially unsigned' type is being converted to floating
44075		type on assignment.
11075	N	A new message has been introduced to identify an "if" statement which has no
		corresponding "else" clause.  2000: No 'else' clause exists for this 'if' statement.
11155	N	New messages have been introduced to support enforcement of MISRA-C:2004 Rule
11100	``	10.5.
		4397: An expression which is the result of a ~ or << operation has not been cast to its essential type.
		4398: An expression which is the result of a ~ or << operation has been cast to a different essential type category.
		4399: An expression which is the result of a ~ or << operation has been cast to a wider type.
		4498: An expression which is the result of a ~ or << operation has been converted to a
		different essential type category on assignment.
		4499: An expression which is the result of a ~ or << operation has been converted to a wider essential type on assignment.
		4570: The operand of this ~ operator has an 'essential type' which is narrower than type
		'int'.
		4571: The left-hand operand of this << operator has an 'essential type' which is
		narrower than type 'int'.
11278	F	This CR is not implemented however it is superseded following changes in QA-C 8.1.
		Message 4121 not generated when expected.
		4121: Cast of complex expression of integral type to wider type.
44000	<b>.</b>	This message has been superseded. See CR 14146.
11300	N	New QA·C message introduced to identify redundant type qualifiers in casts 0318: Redundant type qualifier used in cast.
	1	1 0





CR	Т	Resolution
11328	С	The specification and text of messages 1256 and 1257 has been modified. See also
		CR 11047 and CR 14312.
		Previously:
		1256: Suffixed integer constant implicitly converted to larger integer type on
		assignment.
		1257: Suffixed integer constant implicitly converted to smaller integer type on
		assignment.
		Message 1256 was generated when
		a) an L suffixed constant was converted to any type of higher rank or an unsigned
		type of the same rank (i.e. unsigned long)
		b) a U suffixed constant was converted to any type of higher rank
		c) a UL suffixed constant was converted to any type of higher rank
		Message 1257 was generated when
		a) an L suffixed constant being converted to any type of lower rank
		b) an LL suffixed constant being converted to any type of lower rank
		c) a U suffixed constant being converted to any type of lower rank or a signed
		type of the same rank (int)
		d) a UL suffixed constant being converted to any type of lower rank or a signed type of the same rank (long)
		e) a ULL suffixed constant being converted to any type of lower rank or a signed
		type of the same rank (long long)
		QA-C 8.1
		1256: An integer constant suffixed with L is being converted to type signed or unsigned
		long long on assignment.
		1257: An integer constant suffixed with L or LL is being converted to a type of lower rank on assignment.
		Message 1256 is now generated when
		a) an L suffixed constant is converted to type signed long long or unsigned long
		long
		b) a UL suffixed constant is converted to type signed long long or unsigned long
		long
		Message 1257 is now generated when
		an L suffixed constant is converted to any type of lower rank
		b) a UL suffixed constant is converted to any type of lower rank
		See also CR 11047.
11396	С	Handle UTF-8 Byte Order Mark (BOM) on Windows.
		This CR is implemented as part of CR 14176.
11405	F	This CR is not implemented however it is affected by changes in QA·C 8.1.
		The following messages have been superseded and are now classified as obsolete.  See CR 14303:
		4123: Implicit conversion: complex expression of type float to type double.
		4124: Implicit conversion: complex expression of type float to type long double.
		4125: Implicit conversion: complex expression of type double to type long double.





CR	Т	Resolution
11462	F	Integral promotion messages were generated incorrectly when performing pointer
		arithmetic or an array subscript operation. See also CR 12244.
		2100: Integral promotion : unsigned char promoted to signed int.
11675	N	Support is provided for parsing of source files which include functions containing inline
		assembler code as defined in Renesas compilers. These functions are declared in a
		#pragma statement of the form:
		#pragma inline_asm(func_name)
		1006: [E] This in-line assembler construct is a language extension. The code has been
		ignored.
		3104: [S] #pragma '%s' has invalid arguments and has been ignored.
11788	F	Message 3199 is now generated also in the case where an object is subject to a pre-
		increment or pre-decrement, and the value is not subsequently used.
		3199: This assignment is redundant. The value of '%s' is never subsequently used.
11821	С	Message 2210 is only generated when the option "–tabstop 0" is supplied.
		The text and specification of the message has been modified so that it is generated
		(once) on any line which includes a tab character anywhere within the line.
		Previously:
		2210: Tab character encountered at the beginning of a line.
		Now:
11007	_	2210: Tab character encountered in this line.
11867	F	A bug is fixed, so that the inclusion of a file whose last compound statement is a do
		while loop will no longer prevent the subsequent generation of message 2214 on the
		including file.
44004	_	2214: Body of control statement is on the same line and is not enclosed within braces.
11924	F	This CR is not implemented however it is superseded following changes in QA·C 8.1.
		Noisy instances of message 3760 are generated when comparing the value of an
		unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs
		12089, 13391 and 13410.
		3760: Implicit conversion: int to unsigned int.
12089	F	This CR is not implemented however it is superseded following changes in QA·C 8.1.
12009	ļ ·	Noisy instances of message 3760 are generated when comparing the value of an
		unsigned bitfield with an unsigned constant. Message 3760 is now classified as
		obsolete. New messages have been implemented under CR 14285. See also CRs
		11924, 13391 and 13410.
		3760: Implicit conversion: int to unsigned int.
12244	F	Integral promotion messages were generated incorrectly when performing pointer
		arithmetic or an array subscript operation. See also CR 11462.
12303	F	Message 3317 was not issued if the code at the end of the included file is located in an
		unreachable branch.
		Message 3318 was not issued if the included file contains a #elif or #else as well as the
		#endif.
		Message 3318 was not issued if the #else or #elif is in an included file but the #endif is
		in the parent file.
		3317: '#if' not matched by '#endif' in included file. This is probably an error.
		3318: '#else'/'#elif'/'#endif' in included file matched '#if' in parent file. This is probably
	<u> </u>	an error.
12824	F	Messages Browser now correctly handles UNC paths in the message help.
12847	F	Messages 586/2830 and 3103 were not issued in compound assignment operations.
		2830: Constant: Division by zero.
		3103: Result of signed division or remainder operation may be implementation defined.





12998   F   "OV" was generated instead of "OE" for the "space" field in the met file DEFINE record for an enumeration constant.   13036   F   Addressed under CR 14234. Assignment of a non-constant signed expression to an unsigned bit-field was not identified. Now identified with:	CR	Т	Resolution
for an enumeration constant.  Addressed under CR 14234. Assignment of a non-constant signed expression to an unsigned bit-field was not identified. Now identified with:  4/34: A non-constant expression of 'essentially signed' type (%1s) is being converted to unsigned type, '%2s' on assignment.  Message 3001 was not generated in the declaration of a function pointer with an empty parameter list.  3001: Function has been declared with an empty parameter list.  13322 F Inconsistent representation of pointer to void in met file.  The met file symbolic type code representation of a 'pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".  Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  13391 F This CR is not implemented however it is affected by changes in QA-C 8.1.  Noisy instances of message 3760 are generated when comparing the value of an unsigned biffield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is superseded following changes in QA-C 8.1.  Noisy instances of message 3760 are generated when comparing the value of an unsigned biffield with an unsigned constant. Message 3760 is now classified as obsolete. New messages foo are generated when comparing the value of an unsigned biffield with an unsigned constant. Message 3760 is now classified as obsolete. New messages and been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA-C 8.1.  Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is estential type '%2s'.  0597: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression in 'switch' statement.  13468  N Addressed und			
Addressed under CR 14234, Assignment of a non-constant signed expression to an unsigned bit-field was not identified. Now identified with:   4434: A non-constant expression of 'essentially signed' type (%1s) is being converted to unsigned type, %2s' on assignment.    13167		-	
unsigned bit-field was not identified. Now identified with:  4/34: A non-constant expression of 'essentially signed' type (%1s) is being converted to unsigned type, %2s' on assignment.    13167   F   Message 3001 was not generated in the declaration of a function pointer with an empty parameter list.   3001: Function has been declared with an empty parameter list.   3001: Function has been declared with an empty parameter list.   13322   F   Inconsistent representation of pointer to void in met file.   The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".   13378   C   Message Browser: In admin mode, the (-n, -nornsg) and (-o, -only) values were ignored.   13391   F   This CR is not implemented however it is affected by changes in QA-C 8.1.   Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.   3760: Implicit conversion: int to unsigned int.   This CR is not implemented however it is superseded following changes in QA-C 8.1.   Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.   3760: Implicit conversion: int to unsigned int.   This CR is not implemented however it is suffected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.   0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression in switch' statement.   13446	13036	F	
4434: A non-constant expression of 'essentially signed' type (%1s) is being converted to unsigned type, '%2s' on assignment.   13167   F   Message 3001 was not generated in the declaration of a function pointer with an empty parameter list. 3001: Function has been declared with an empty parameter list. 3001: Function has been declared with an empty parameter list. The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".   13378   C   Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.			
to unsigned type, "%2s' on assignment.    13167   F   Message 3001 was not generated in the declaration of a function pointer with an empty parameter list.     3001: Function has been declared with an empty parameter list.     13322   F   Inconsistent representation of pointer to void in met file.     The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p."     13378   C   Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.     13391   F   This CR is not implemented however it is affected by changes in QA-C 8.1.     Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.     3760: Implicit conversion: int to unsigned int.     13407   N   The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.     13410   F   This CR is not implemented however it is superseded following changes in QA-C 8.1.     Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.     3760: Implicit conversion: int to unsigned int.     13433   F   This CR is not implemented however it is affected by changes in QA-C 8.1.     Message 0597 is generated however it is affected by changes in QA-C 8.1.     Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.     0570: This switch case label of 'e			
13167   F   Message 3001 was not generated in the declaration of a function pointer with an empty parameter list. 3001: Function has been declared with an empty parameter list. 113322   F   Inconsistent representation of pointer to void in met file. The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.". 113378   C   Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.   F   This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410. 3760: Implicit conversion: int to unsigned int.   The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.   This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned biffield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391. 3760: Implicit conversion: int to unsigned int.   This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325. 0570: This switch case label of 'essential type' %1s', is not consistent with a controlling expression of essential type '%2s', is not consistent with a controlling expression in 'switch' statement.   N Addressed under CR 11047. Messages ha			
parameter list. 3001: Function has been declared with an empty parameter list.  13322 F Inconsistent representation of pointer to void in met file. The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".  13378 C Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  13391 F This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  13407 N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  13410 F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  13433 F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' "%1s', is not consistent with a controlling expression in 'switch' statement.  13468 N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  13468 N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The follo	13167	F	
13322 F Inconsistent representation of pointer to void in met file.  The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".  13378 C Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  13391 F This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  13407 N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  13410 F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' "%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  13446 N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument synta			
F Inconsistent representation of pointer to void in met file. The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".  13378 C Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  13391 F This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  The #include_next preprocessing directive is a language extension.  This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325. 0570: This switch case label of 'essential type' '%2s'. 0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented: 1046: [E] Function is being declared with default argument syntax. This is a language extension.			
The met file symbolic type code representation of a "pointer to void" was sometimes "g" and sometimes "p." It is now always represented as "p.".  C Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message 1045: [EI] Use of the #include_next preprocessing directive is a language extension.  This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924, 12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325. 0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:	13322	F	
and sometimes "p." It is now always represented as "p.".  13378 C Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  13391 F This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  13407 N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  13410 F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  13433 F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325. 0570: This switch case label of 'essential type' "%1s', is not consistent with a controlling expression in 'switch' statement.  13446 N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  13468 N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented: 1046: [E] Function is being declared with default argument syntax. This is a language extension.			
13378 C Message Browser: In admin mode, the (-n, -nomsg) and (-o, -only) values were ignored.  13391 F This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  13407 N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  13410 F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  13433 F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression in 'switch' statement.  13446 N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  13468 N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
Ignored.   Ignored.   This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.   3760: Implicit conversion: int to unsigned int.	13378	С	
F This CR is not implemented however it is affected by changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than ou).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [F] Use of the #include_next preprocessing directive is a language extension.  F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' "%1s', is not consistent with a controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.	13391	F	
unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  F This CR is not implemented however it is superseded following changes in QA·C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA·C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13410.  3760: Implicit conversion: int to unsigned int.  N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message: 1045: [E] Use of the #include_next preprocessing directive is a language extension.  F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
13407 N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message:  1045: [F] Use of the #include_next preprocessing directive is a language extension.  13410 F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  13433 F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  13446 N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  13468 N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
N The #include_next preprocessing directive supported by the GCC compiler is now supported. Use of this language extension is identified with message:  1045: [E] Use of the #include_next preprocessing directive is a language extension.  F This CR is not implemented however it is superseded following changes in QA-C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' "%1s', is not consistent with a controlling expression of essential type "%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			11924,12089 and 13410.
supported. Use of this language extension is identified with message:  1045: [E] Use of the #include_next preprocessing directive is a language extension.  This CR is not implemented however it is superseded following changes in QA·C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA·C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
13410 F This CR is not implemented however it is superseded following changes in QA·C 8.1. Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA·C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '9/2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.	13407	Ν	The #include_next preprocessing directive supported by the GCC compiler is now
F This CR is not implemented however it is superseded following changes in QA·C 8.1.  Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA·C 8.1.  Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			supported. Use of this language extension is identified with message:
Noisy instances of message 3760 are generated when comparing the value of an unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA·C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
unsigned bitfield with an unsigned constant. Message 3760 is now classified as obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391.  3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA-C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.	13410	F	
obsolete. New messages have been implemented under CR 14285. See also CRs 11924,12089 and 13391. 3760: Implicit conversion: int to unsigned int.  F This CR is not implemented however it is affected by changes in QA·C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
11924,12089 and 13391. 3760: Implicit conversion: int to unsigned int.  This CR is not implemented however it is affected by changes in QA·C 8.1. Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325. 0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'. 0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented: 1046: [E] Function is being declared with default argument syntax. This is a language extension.			
13433  F This CR is not implemented however it is affected by changes in QA·C 8.1.  Message 0597 is generated incorrectly when type char is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
F This CR is not implemented however it is affected by changes in QA·C 8.1.  Message 0597 is generated incorrectly when type <i>char</i> is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
Message 0597 is generated incorrectly when type <i>char</i> is configured as unsigned, the controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			3760: Implicit conversion: int to unsigned int.
controlling expression is of type char and the switch label is a character constant. The message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.	13433	F	
message has been superseded by message 0570. See CR 14325.  0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
<ul> <li>0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling expression of essential type '%2s'.</li> <li>0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.</li> <li>13446</li> <li>N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).</li> <li>13468</li> <li>N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:         <ul> <li>1046: [E] Function is being declared with default argument syntax. This is a language extension.</li> </ul> </li> </ul>			
expression of essential type '%2s'.  0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
<ul> <li>0597: Type of 'case' label expression is not consistent with type of controlling expression in 'switch' statement.</li> <li>13446  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).</li> <li>13468  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:         <ul> <li>1046: [E] Function is being declared with default argument syntax. This is a language extension.</li> </ul> </li> </ul>			
13446  N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
N Addressed under CR 11047. Messages have been implemented to identify when an object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			, , , , , , , , , , , , , , , , , , , ,
object of unsigned type is initialised with a constant of signed type (e.g. 0 rather than 0u).  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.	10110	N.I.	
0u).  13468  N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.	13446	IN	
N Support is now included for default argument syntax as defined in C++ and Renesas compilers. The following messages have been implemented:  1046: [E] Function is being declared with default argument syntax. This is a language extension.			
compilers. The following messages have been implemented: 1046: [E] Function is being declared with default argument syntax. This is a language extension.	13/68	NI	
1046: [E] Function is being declared with default argument syntax. This is a language extension.	13400	11	
extension.			
1047: [C] Function is being declared with default argument syntax after a previous call			
to the function. This is not allowed.			
1048: [C] Default argument values are missing for some parameters in this function			
declaration. This is not allowed.			
13516 C Message 3212 was previously generated when applying a cast which was of the same	13516	С	
type as the expression to which it was applied. Now the message is only generated if			
the 'essential type' of the expression also remains unchanged.			





CR	Т	Resolution
		3212: This cast is redundant.
13517	С	Noisy instances of messages 2890, 2895, 2900 and 2905 were generated when
		observing the requirements of MISRA-C:2004 Rule 10.5 – i.e. to apply a cast to the
		underlying type following a ~ or << operation.
		Messages 2890 and 2895 are no longer generated if the operand is essentially
		unsigned.
		Messages 2895 and 2905 are no longer generated unless the value represented in the
		essential type is truncated.
		2890: Constant: Negative value implicitly converted to an unsigned type.
		2895: Constant: Negative value cast to an unsigned type.
		2900: Positive integer value truncated by implicit conversion to a smaller unsigned type.
		2905: Positive integer value truncated by cast to a smaller unsigned type.
13527	F	The positioning of the message browser is improved to avoid situations where the
		window re-opens off screen after the screen configuration is changed.
13546	F	Windows GUI: there was a wrong application of a trailing backslash for a relative path
		at the current directory.
13590	N	A new message has been implemented to identify when a function is being defined with
		a variable number of parameters.
10010	<b>.</b>	1337: Function defined with a variable number of parameters.
13640	Ν	New messages have been implemented to identify when the result of an arithmetic
		operation is invariant.
		2984: This operation is redundant. The value of the result is always '%1s'.
		2985: This operation is redundant. The value of the result is always that of the left-hand
		operand.
		2986: This operation is redundant. The value of the result is always that of the right-
13709	С	hand operand. Improved checks are implemented for strings with formats passed to the C API (e.g. via
13709		sprintf, snprintf, strftime), based on calculation of minimum required buffer size.
13819	F	Annotation messages from QA · C did not have 'included from' information. As a result:
10010		(1) The messages were not displayed by errdsp for the first include and (2) The
		messages were not suppressed by the source level suppression.
		4810: Invalid annotation: tag '%1s' is not defined subsequently in this file.
		4811: The start of the range '%1s', starts and ends at the same location.
		4812: '%1s' not allowed here.
		4820: Annotation kind is expected.
		4821: Colon is expected.
		4822: Tag name is expected.
		4823: Annotation syntax error.
		4824: Invalid character in tag name.
		4825: Unexpected character.
		4826: Message specification is incomplete or missing.
		4827: Tag name is not allowed in the message specification of continuous suppression
		annotation.
		4828: Invalid usage of predefined location tag.
13872	N	Inter-function dataflow analysis is now conducted across all functions within a single
		translation unit. The following new messages have been introduced.
		2756: Could not expand function call to '%1s' with maximum '-po df::inter' value.
40075	_	2757: Could not analyse function '%1s'. Try a smaller '-po df::inter' value?
13875	F	QA-C was failing to parse certain forms of designated initializers.
		0672: [U] The initializer for a 'struct', 'union' or array is not enclosed in braces.
	<u> </u>	0684: [C] Too many initializers.





CR	Т	Resolution
		0693: Struct initializer is missing the optional {.
13898	F	Message 3408 was sometimes generated incorrectly on a function declaration.
		Message 3447 was not always generated when expected.
		3408: '%s' has external linkage and is being defined without any previous declaration.
		3447: '%s' is being declared with external linkage but this declaration is not in a header
		file.
13930	F	The message browser will no longer fail to obtain a licence when there are multiple servers and one of the servers is down.
13958	F	Message 2983 is no longer incorrectly generated when the address of a member is
13930	'	passed to
		an unknown function.
		2983: This assignment is redundant. The value of this object is never subsequently
		used.
13964	F	Messages that are hidden will remain hidden when the message browser is closed and
		re-opened.
14011	F	Thealignof operator was returning incorrect values.
		1037: [E] Arrays of length zero are a language extension.
14033	С	The following messages have been removed, since they have been superseded by messages 4401 and 4405 introduced in CR 14234:
		4240: The value of an 'effectively Boolean' expression is being assigned to an object of
		type 'char'.
		4241: The value of an 'effectively Boolean' expression is being passed to a function
		parameter of type 'char'.
		4242: The value of an 'effectively Boolean' expression is being returned from a function
		with a return type of 'char'.
		4243: The value of an 'effectively Boolean' expression is being assigned to an object of floating type.
		4244: The value of an 'effectively Boolean' expression is being passed to a function
		parameter of floating type.
		4245: The value of an 'effectively Boolean' expression is being returned from a function
		with a floating return type.
14034	N	New messages to identify misuse of an effectively Boolean expression in array
		subscript, relational and shift operations.
		4500: An expression of 'essentially Boolean' type (%1s) is being used as an array subscript.
		4503: An expression of 'essentially Boolean' type (%1s) is being used as the left-hand
		operand of this shift operator (%2s).
		4504: An expression of 'essentially Boolean' type (%1s) is being used as the right-hand
		operand of this shift operator (%2s).
		4505: An expression of 'essentially Boolean' type (%1s) is being used as the %2s
		operand of this relational operator (%3s).
14035	N	New messages to identify misuse of an effectively Boolean expression in bitwise
1	1	operations.
		4502: An expression of 'essentially Boolean' type (%1s) is being used as the %2s
	1	operand of this bitwise operator (%3s).
		[where %2s is either 'left-hand', 'right-hand' or, in the case of the bitwise complement
14036	N	operator is blank]  New messages to identify misuse of an effectively Boolean expression in arithmetic
14030	IN	operations.
		4501: An expression of 'essentially Boolean' type (%1s) is being used as the %2s
		operand of this arithmetic operator (%3s).
<u> </u>	1	1 optimise of the antimised operator (7000).





CR	Т	Resolution
		[where %1s is either "left-hand", "right-hand" or an empty string "" and %2s is the
		relevant operator]
14058	F	Motif GUI: The Auto Create Window was too tall and so was truncated in low resolution
		screens.
14059	N	Support has been added for parsing of type _Bool as specified in ISO:C99.
		The following new messages have been implemented:
		0360: An expression of pointer type is being converted to type _Bool on assignment.
		0361: An expression of pointer type is being cast to type _Bool.
		0362: An expression of essentially Boolean type is being cast to a pointer.
		1056: [C99] The keyword '_Bool' has been used.
		2109: Integral promotion : _Bool promoted to signed int. 2119: Default argument promotion : _Bool promoted to signed int.
14062	F	Motif GUI: Changed date format for file to match that of the Windows GUI.
14002	F	Dataflow was sometimes disabled for first function after exit from a header file.
14073	F	Windows GUI: A trailing '\' was required when specifying the starting directory for an
14073	'	Auto-create with sub-path output location.
14082	F	Motif GUI: Allow view source window size to be specified in the resource file (Japanese
1.002	1.	only).
14084	F	Windows GUI: Incorrect handling of trailing backslash for Auto Create in SJIS
		environments.
14121	N	A new message has been implemented to identify when an integral constant
		expression with value 0 is being interpreted as a null pointer constant.
		3004: This integral constant expression is being interpreted as a NULL pointer
		constant.
14145	N	New messages have been implemented to identify situations where the operand of an
		operator may be of inappropriate or unexpected type:
		4500: An expression of 'essentially Boolean' type (%1s) is being used as an array
		subscript.
		4501: An expression of 'essentially Boolean' type (%1s) is being used as the %2s
		operand of this arithmetic operator (%3s). 4502: An expression of 'essentially Boolean' type (%1s) is being used as the %2s
		operand of this bitwise operator (%3s).
		4503: An expression of 'essentially Boolean' type (%1s) is being used as the left-hand
		operand of this shift operator (%2s).
		4504: An expression of 'essentially Boolean' type (%1s) is being used as the right-hand
		operand of this shift operator (%2s).
		4505: An expression of 'essentially Boolean' type (%1s) is being used as the %2s
		operand of this relational operator (%3s).
		4510: An expression of 'essentially character' type (%1s) is being used as an array
		subscript.
		4511: An expression of 'essentially character' type (%1s) is being used as the %2s
		operand of this arithmetic operator (%3s).
1		4512: An expression of 'essentially character' type (%1s) is being used as the %2s
		operand of this bitwise operator (%3s). 4513: An expression of 'essentially character' type (%1s) is being used as the left-hand
		operand of this shift operator (%2s).
		4514: An expression of 'essentially character' type (%1s) is being used as the right-
		hand operand of this shift operator (%2s).
1		4518: An expression of 'essentially character' type (%1s) is being used as the %2s
		operand of this logical operator (%3s).
		4519: An expression of 'essentially character' type (%1s) is being used as the first





CR	Т	Resolution
		operand of this conditional operator (%2s).
		4521: An expression of 'essentially enum' type (%1s) is being used as the %2s operand
		of this arithmetic operator (%3s).
		4522: An expression of 'essentially enum' type (%1s) is being used as the %2s operand
		of this bitwise operator (%3s).
		4523: An expression of 'essentially enum' type (%1s) is being used as the left-hand
		operand of this shift operator (%2s).
		4524: An expression of 'essentially enum' type (%1s) is being used as the right-hand
		operand of this shift operator (%2s).
		4528: An expression of 'essentially enum' type (%1s) is being used as the %2s operand
		of this logical operator (%3s).
		4529: An expression of 'essentially enum' type (%1s) is being used as the first operand
		of this conditional operator (%2s).
		4532: An expression of 'essentially signed' type (%1s) is being used as the %2s
		operand of this bitwise operator (%3s).
		4533: An expression of 'essentially signed' type (%1s) is being used as the left-hand
		operand of this shift operator (%2s).
		4534: An expression of 'essentially signed' type (%1s) is being used as the right-hand
		operand of this shift operator (%2s).
		4538: An expression of 'essentially signed' type (%1s) is being used as the %2s
		operand of this logical operator (%3s).
		4539: An expression of 'essentially signed' type (%1s) is being used as the first
		operand of this conditional operator (%2s). 4542: A non-negative constant expression of 'essentially signed' type (%1s) is being
		used as the %2s operand of this bitwise operator (%3s).
		4543: A non-negative constant expression of 'essentially signed' type (%1s) is being
		used as the left-hand operand of this shift operator (%2s).
		4544: A non-negative constant expression of 'essentially signed' type (%1s) is being
		used as the right-hand operand of this shift operator (%2s).
		4548: A non-negative constant expression of 'essentially signed' type (%1s) is being
		used as the %2s operand of this logical operator (%3s).
		4549: A non-negative constant expression of 'essentially signed' type (%1s) is being
		used as the first operand of this conditional operator (%2s).
		4558: An expression of 'essentially unsigned' type (%1s) is being used as the %2s
		operand of this logical operator (%3s).
		4559: An expression of 'essentially unsigned' type (%1s) is being used as the first
		operand of this conditional operator (%2s).
		4568: An expression of 'essentially floating' type (%1s) is being used as the %2s
		operand of this logical operator (%3s).
		4569: An expression of 'essentially floating' type (%1s) is being used as the first
	L	operand of this conditional operator (%2s).
14146	N	New messages have been implemented to identify when a complex expression is being
		cast to a wider essential type:
		4390: A composite expression of 'essentially signed' type (%1s) is being cast to a wider
		signed type, '%2s'.
		4391: A composite expression of 'essentially unsigned' type (%1s) is being cast to a
		wider unsigned type, '%2s'.
		4392: A composite expression of 'essentially floating' type (%1s) is being cast to a
		wider floating type, '%2s'.
		4393: A composite expression of 'essentially signed' type (%1s) is being cast to a different type category, '%2s'.
		4394: A composite expression of 'essentially unsigned' type (%1s) is being cast to a
		+534. A composite expression or essentially unsigned type (7615) is being Cast to a





CR	Т	Resolution
		different type category, '%2s'.
		4395: A composite expression of 'essentially floating' type (%1s) is being cast to a
		different type category, '%2s'.
14176	С	Support has been implemented for parsing of files in UTF8 encoding.
14196	F	Dataflow generated false positive first iteration overflow/wraparound messages due to
		incorrect modelling of loops involving the != operator.
		2801: Definite: Overflow in signed arithmetic operation.
	<b>.</b>	2911: Definite: Wraparound in unsigned arithmetic operation.
14202	N	The Windows GUI is updated to support the inter-function analysis capability in
4.4000	N.	dataflow.
14203	N	The Motif GUI is updated to support the inter-function analysis capability in dataflow.
14211	F	Dataflow did not issue message 2983 if the last use of a variable was in a pre-
		increment or pre-decrement expression.
		2983: This assignment is redundant. The value of this object is never subsequently
14212	F	Used.  Dataflow message 2983 was not generated where the assignment took place in the
14212		middle or right hand operand of a ternary operator.
		2983: This assignment is redundant. The value of this object is never subsequently
		used.
14228	F	Determining loop directions for a loop variable in dataflow sometimes resulted in an
14220		incorrect result for complex conditional expressions.
		2984: This operation is redundant. The value of the result is always '%1s'.
		2985: This operation is redundant. The value of the result is always that of the left-hand
		operand.
		2986: This operation is redundant. The value of the result is always that of the right-
		hand operand.
14231	Ν	New messages have been implemented to identify certain cast operations to a different
		essential type:
		4301: An expression of 'essentially Boolean' type (%1s) is being cast to character type '%2s'.
		4302: An expression of 'essentially Boolean' type (%1s) is being cast to enum type
		'%2s'.
		4303: An expression of 'essentially Boolean' type (%1s) is being cast to signed type
		'%2s'.
		4304: An expression of 'essentially Boolean' type (%1s) is being cast to unsigned type '%2s'.
		4305: An expression of 'essentially Boolean' type (%1s) is being cast to floating type
		'%2s'.
		4310: An expression of 'essentially character' type (%1s) is being cast to Boolean type, '%2s'.
		4312: An expression of 'essentially character' type (%1s) is being cast to enum type,
		4320: An expression of 'essentially enum' type (%1s) is being cast to Boolean type,
		4322: An expression of essentially enum type (%1s) is being cast to a different enum type, '%2s'.
		4325: An expression of 'essentially enum' type (%1s) is being cast to floating type,
		1
		'%2s'. 4322: An expression of 'essentially enum' type (%1s) is being cast to a different enum type, '%2s'.





CD.	<b>-</b>	Desclution
CR	Т	Resolution
		'%2s'. 4332: An expression of 'essentially signed' type (%1s) is being cast to enum type, '%2s'.
		4340: An expression of 'essentially unsigned' type (%1s) is being cast to Boolean type '%2s'.
		4342: An expression of 'essentially unsigned' type (%1s) is being cast to enum type '%2s'.
		4350: An expression of 'essentially floating' type (%1s) is being cast to Boolean type '%2s'.
		4351: An expression of 'essentially floating' type (%1s) is being cast to character type '%2s'.
		4352: An expression of 'essentially floating' type (%1s) is being cast to enum type, '%2s'.
14234	N	New messages have been implemented to identify implicit conversions to a different essential type which occur in assigning operations (i.e. initialization, assignment, function arguments, functions returns):
		4401: An expression of 'essentially Boolean' type (%1s) is being converted to character type, '%2s' on assignment.
		4402: An expression of 'essentially Boolean' type (%1s) is being converted to enum type, '%2s' on assignment.
		4403: An expression of 'essentially Boolean' type (%1s) is being converted to signed type, '%2s' on assignment.
		4404: An expression of 'essentially Boolean' type (%1s) is being converted to unsigned type, '%2s' on assignment.
		4405: An expression of 'essentially Boolean' type (%1s) is being converted to floating type, '%2s' on assignment.
		4410: An expression of 'essentially character' type (%1s) is being converted to Boolean type, '%2s' on assignment.
		4412: An expression of 'essentially character' type (%1s) is being converted to enum type, '%2s' on assignment.
		4413: An expression of 'essentially character' type (%1s) is being converted to signed type, '%2s' on assignment.
		4414: An expression of 'essentially character' type (%1s) is being converted to unsigned type, '%2s' on assignment.
		4415: An expression of 'essentially character' type (%1s) is being converted to floating type, '%2s' on assignment.
		4420: An expression of 'essentially enum' type (%1s) is being converted to Boolean type, '%2s' on assignment.
		4421: An expression of 'essentially enum' type (%1s) is being converted to character type, '%2s' on assignment.
		4422: An expression of 'essentially enum' type (%1s) is being converted to a different enum type, '%2s' on assignment.
		4423: An expression of 'essentially enum' type (%1s) is being converted to signed type, '%2s' on assignment.
		4424: An expression of 'essentially enum' type (%1s) is being converted to unsigned type, '%2s' on assignment.
		4425: An expression of 'essentially enum' type (%1s) is being converted to floating type, '%2s' on assignment.
		4430: An expression of 'essentially signed' type (%1s) is being converted to Boolean type, '%2s' on assignment.
		4431: An expression of 'essentially signed' type (%1s) is being converted to character type, '%2s' on assignment.





CR	Т	Resolution
		4432: An expression of 'essentially signed' type (%1s) is being converted to enum type,
		'%2s' on assignment.
		4434: A non-constant expression of 'essentially signed' type (%1s) is being converted
		to unsigned type, '%2s' on assignment.
		4435: A non-constant expression of 'essentially signed' type (%1s) is being converted
		to floating type, '%2s' on assignment.
		4436: A constant expression of 'essentially signed' type (%1s) is being converted to
		unsigned type, '%2s' on assignment.
		4437: A constant expression of 'essentially signed' type (%1s) is being converted to
		floating type, '%2s' on assignment.
		4440: An expression of 'essentially unsigned' type (%1s) is being converted to Boolean
		type, '%2s' on assignment.
		4441: An expression of 'essentially unsigned' type (%1s) is being converted to character type, '%2s' on assignment.
		4442: An expression of 'essentially unsigned' type (%1s) is being converted to enum
		type, '%2s' on assignment.
		4443: A non-constant expression of 'essentially unsigned' type (%1s) is being
		converted to a wider signed type, '%2s' on assignment.
		4445: An expression of 'essentially unsigned' type (%1s) is being converted to floating
		type, '%2s' on assignment.
		4446: A non-constant expression of 'essentially unsigned' type (%1s) is being
		converted to signed type, '%2s' on assignment.
		4447: A constant expression of 'essentially unsigned' type (%1s) is being converted to
		signed type, '%2s' on assignment.
		4450: An expression of 'essentially floating' type (%1s) is being converted to Boolean
		type, '%2s' on assignment.
		4451: An expression of 'essentially floating' type (%1s) is being converted to character
		type, '%2s' on assignment.
		4452: An expression of 'essentially floating' type (%1s) is being converted to enum type, '%2s' on assignment.
		4453: An expression of 'essentially floating' type (%1s) is being converted to signed
		type, '%2s' on assignment.
		4454: An expression of 'essentially floating' type (%1s) is being converted to unsigned
		type, '%2s' on assignment.
14235	F	False positives 2841 and 2931 messages were generated when executing a loop
		controlled with a pointer variable where the operator used in the condition was !=.
		2841: Definite: Dereference of an invalid pointer value.
		2931: Definite: Computing an invalid pointer value.
14236	N	New messages have been implemented to identify implicit conversion of a non-constant
		expression to an essential type of the same type category but lower rank which occur in
		assigning operations (i.e. initialization, assignment, function arguments, functions
		returns): 4160: A non-constant expression of 'especially signed' type (%/1e) is being converted
		4460: A non-constant expression of 'essentially signed' type (%1s) is being converted
		to narrower signed type, '%2s' on assignment. 4461: A non-constant expression of 'essentially unsigned' type (%1s) is being
		converted to narrower unsigned type, '%2s' on assignment.
		4462: A non-constant expression of 'essentially floating' type (%1s) is being converted
		to narrower floating type, '%2s' on assignment.
		4463: A constant expression of 'essentially signed' type (%1s) is being converted to
		narrower signed type, '%2s' on assignment.
		4464: A constant expression of 'essentially unsigned' type (%1s) is being converted to
		narrower unsigned type, '%2s' on assignment.





CR	Т	Resolution
		4465: A constant expression of 'essentially floating' type (%1s) is being converted to
		narrower floating type, '%2s' on assignment.
14237	N	64 bit builds are provided for post-analysis and reports tools to extend the CMA
		analysis or report generation beyond the 3 GB Windows limit.
14238	N	New messages have been implemented to identify implicit widening type conversions
		occurring in function arguments and function return expressions:
		4470: A non-constant expression of 'essentially signed' type (%1s) is being passed to a
		function parameter of wider signed type, '%2s'.
		4471: A non-constant expression of 'essentially unsigned' type (%1s) is being passed to
		a function parameter of wider unsigned type, '%2s'. 4472: A non-constant expression of 'essentially floating' type (%1s) is being passed to a
		function parameter of wider floating type, '%2s'.
		4480: A non-constant expression of 'essentially signed' type (%1s) is being returned
		from a function defined with a wider signed return type, '%2s'.
		4481: A non-constant expression of 'essentially unsigned' type (%1s) is being returned
		from a function defined with a wider unsigned return type, '%2s'.
		4482: A non-constant expression of 'essentially floating' type (%1s) is being returned
		from a function defined with a wider floating return type, '%2s'.
14239	Ν	New messages have been implemented to identify implicit conversion of a composite
		expression to a wider type in assigning operations (i.e. initialization, assignment,
		function arguments, functions returns):
		4490: A composite expression of 'essentially signed' type (%1s) is being converted to
		wider signed type, '%2s' on assignment.
		4491: A composite expression of 'essentially unsigned' type (%1s) is being converted to wider unsigned type, '%2s' on assignment.
		4492: A composite expression of 'essentially floating' type (%1s) is being converted to
		wider floating type, '%2s' on assignment.
14273	F	Message Browser: fixed a failure when a message on line 0 was selected.
14280	N	New messages have been implemented to identify usage of an increment or decrement
		operator on an object of inappropriate type:
		4507: An expression of 'essentially Boolean' type (%1s) is being used as the operand of
		this increment/decrement operator (%2s).
		4517: An expression of 'essentially character' type (%1s) is being used as the operand
		of this increment/decrement operator (%2s).
		4527: An expression of 'essentially enum' type is being used as the operand of this
44004	-	increment/decrement operator.
14281	С	Compound assignment operations may be considered to consist of 2 distinct operations, a binary operation followed by an assignment operation. The messages
		associated with misuse of these operators will be generated for the corresponding
		compound assignment operations.
		1820: The %1s operand is non-constant and 'essentially signed' (%2s) but will be
		implicitly converted to an unsigned type (%3s) in this arithmetic operation.
		1850: The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to
		a signed type (%3s) in this arithmetic operation.
		etc.
14284	N	New messages have been implemented to identify operations which balance a floating
		operand with a signed or unsigned operand:
		1800: The %1s operand (essential type: '%2s') will be implicitly converted to a floating
		type, '%3s', in this arithmetic operation.
		1802: The %1s operand (essential type: '%2s') will be implicitly converted to a floating
		type, '%3s', in this relational operation.
		1803: The %1s operand (essential type: '%2s') will be implicitly converted to a floating





CR	Т	Resolution
		type, '%3s', in this equality operation.
		1804: The %1s operand (essential type: '%2s') will be implicitly converted to a floating
		type, '%3s', in this conditional operation.
14285	N	New messages have been implemented to identify operations which balance signed
		and unsigned operands:
		1820: The %1s operand is non-constant and 'essentially signed' (%2s) but will be
		implicitly converted to an unsigned type (%3s) in this arithmetic operation.
		1821: The %1s operand is non-constant and 'essentially signed' (%2s) but will be
		implicitly converted to an unsigned type (%3s) in this bitwise operation.
		1822: The %1s operand is non-constant and 'essentially signed' (%2s) but will be
		implicitly converted to an unsigned type (%3s) in this relational operation.
		1823: The %1s operand is non-constant and 'essentially signed' (%2s) but will be
		implicitly converted to an unsigned type (%3s) in this equality operation.
		1824: The %1s operand is non-constant and 'essentially signed' (%2s) but will be
		implicitly converted to an unsigned type (%3s) in this conditional operation.
		1830: The %1s operand is constant, 'essentially signed' (%2s) and negative but will be
		implicitly converted to an unsigned type (%3s) in this arithmetic operation.
		1831: The %1s operand is constant, 'essentially signed' (%2s) and negative but will be
		implicitly converted to an unsigned type (%3s) in this bitwise operation.
		1832: The %1s operand is constant, 'essentially signed' (%2s) and negative but will be
		implicitly converted to an unsigned type (%3s) in this relational operation.
		1833: The %1s operand is constant, 'essentially signed' (%2s) and negative but will be
		implicitly converted to an unsigned type (%3s) in this equality operation.
		1834: The %1s operand is constant, 'essentially signed' (%2s) and negative but will be
		implicitly converted to an unsigned type (%3s) in this conditional operation.  1840: The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will
		be implicitly converted to an unsigned type (%3s) in this arithmetic operation.
		1841: The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will
		be implicitly converted to an unsigned type (%3s) in this bitwise operation.
		1842: The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will
		be implicitly converted to an unsigned type (%3s) in this relational operation.
		1843: The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will
		be implicitly converted to an unsigned type (%3s) in this equality operation.
		1844: The %1s operand is constant, 'essentially signed' (%2s) and non-negative but will
		be implicitly converted to an unsigned type (%3s) in this conditional operation.
		1850: The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to
		a signed type (%3s) in this arithmetic operation.
		1851: The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to
		a signed type (%3s) in this bitwise operation.
		1852: The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to
		a signed type (%3s) in this relational operation.
		1853: The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to
		a signed type (%3s) in this equality operation.
		1854: The %1s operand is 'essentially unsigned' (%2s) but will be implicitly converted to
		a signed type (%3s) in this conditional operation.
		1860: The operands of this arithmetic operator are of different 'essential signedness'
		but will generate a result of type 'signed int'.
		1861: The operands of this bitwise operator are of different 'essential signedness' but
		will generate a result of type 'signed int'.  1862: The operands of this relational operator are of different 'essential signedness' but
		will both be promoted to 'signed int' for comparison.
		1863: The operands of this equality operator are of different 'essential signedness' but
	1	1000. The operation of this equality operator are of uniferent essential signethess but





CR	Т	Resolution
		will both be promoted to 'signed int' for comparison.
		1864: The 2nd and 3rd operands of this conditional operator are of different 'essential
		signedness'. The result will be in the promoted type 'signed int'.
14286	N	New messages have been implemented to identify certain operations which balance an
		operand of essentially character type:
		1810: An operand of 'essentially character' type is being added to another operand of
		'essentially character' type.
		1811: An operand of 'essentially character' type is being subtracted from an operand of
		'essentially signed' type.
		1812: An operand of 'essentially character' type is being subtracted from an operand of
		'essentially unsigned' type.
		1813: An operand of 'essentially character' type is being balanced with an operand of
		'essentially floating' type in this arithmetic operation.
14287	N	New messages have been implemented to identify specific operations which balance
		operands of different essential type category:
		1880: The operands of this relational operator are expressions of different 'essential
		type' categories (%1s and %2s).
		1881: The operands of this equality operator are expressions of different 'essential type'
		categories (%1s and %2s).  1882: The 2nd and 3rd operands of this conditional operator are expressions of
		different 'essential type' categories (%1s and %2s).
14288	F	QA-C failed under certain conditions when parsing a file which finished with an open
14200	-	comment.
		0268: [S] Comment open at end of translation unit.
14303	N	New messages required to identify balancing operations which result in the implicit
14303	'	conversion of a composite expression to a wider type.
		1890: A composite expression of 'essentially signed' type (%1s) is being implicitly
		converted to a wider signed type, '%2s'.
		1891: A composite expression of 'essentially unsigned' type (%1s) is being implicitly
		converted to a wider unsigned type, '%2s'.
		1892: A composite expression of 'essentially floating' type (%1s) is being implicitly
		converted to a wider floating type, '%2s'.
		1893: The 2nd and 3rd operands of this conditional operator are both 'essentially
		signed' ('%1s' and '%2s') but one is a composite expression of a narrower type
		than the other.
		1894: The 2nd and 3rd operands of this conditional operator are both 'essentially
		unsigned' ('%1s' and '%2s') but one is a composite expression of a narrower type
		than the other.
1		1895: The 2nd and 3rd operands of this conditional operator are both 'essentially
		floating' ('%1s' and '%2s') but one is a composite expression of a narrower type
14312	Е	than the other.
14312	F	Messages associated with assignment of literal constants were not generated for
		function arguments. See also CR 11047 and CR 11328.  1256: An integer constant suffixed with L is being converted to type signed or unsigned
		long long on assignment.
		1257: An integer constant suffixed with L or LL is being converted to a type of lower
		rank on assignment.
		1264: A suffixed floating constant is being converted to a different floating type on
1		assignment.
		1265: An unsuffixed floating constant is being converted to a different floating type on
		assignment.
		1266: A floating constant is being converted to integral type on assignment.





CR	Т	Resolution
	-	1276: An integer constant is being converted to floating type on assignment.
14313	F	'Standard' implicit conversion messages are no longer generated when a floating
		constant is assigned to an object of integer type.
		3799-3807,3876,3877,3810-3818,3878,3879,3821-3829,3880,3881: Implicit
		conversion: <b>x</b> to <b>y</b> .
		3999-4007,4076,4077,4010-4018,4078,4079,4021-4029,4080,4081: <b>x</b> value returned
		from <b>y</b> %s().
		Where <b>x</b> is one of <i>float</i> , <i>double</i> , <i>long double</i> and <b>y</b> is one of <i>char</i> , <i>signed char</i> ,
		unsigned char, short, unsigned short, int, unsigned int, long, unsigned long, long long,
		unsigned long long.
		These messages duplicated the function of message 1266.
4.404.4	_	1266: A floating constant is being converted to integral type on assignment.
14314	С	Dataflow no longer generates message 2961 for usage of an object that has no
		members.
14323	F	2961: Definite: Using value of uninitialized automatic object '%s'.  Incorrect messages were sometimes generated when assigning the value of a floating
14323	'	constant to an enum object:
		1411: A constant expression of non-enum type is being passed as argument to a
		function parameter of enum type.
		1412: A constant expression of non-enum type is being assigned to an object of enum
		type.
		1413: A constant expression of non-enum type is being returned from a function with an
		enum return type.
		1441: A non-constant expression of non-enum type is being passed as argument to a
		function parameter of enum type.
		1442: A non-constant expression of non-enum type is being assigned to an object of
		enum type.  1443: A non-constant expression of non-enum type is being returned from a function
		with an enum return type.
14325	N	New messages have been implemented to identify when the type of a switch case label
1.020	' '	is not consistent with the essential type of the controlling expression.
		0570: This switch case label of 'essential type' '%1s', is not consistent with a controlling
		expression of essential type '%2s'.
		0571: This switch case label of 'essential type' '%1s' is not consistent with a controlling
		expression which has an essential type of higher rank (%2s).
		0572: This switch case label of 'essential type' '%1s' is not consistent with a controlling
	<u> </u>	expression which has an essential type of lower rank (%2s).
14333	F	Incorrect error messages will no longer be generated on certain valid forms of
		designated initializers:
		0671: [C] Initializer for object of arithmetic type is not of arithmetic type. 0693: Struct initializer is missing the optional {.
14365	F	The implementation of dataflow messages which identify the use of uninitialized data
1-000	'	has been improved so that variable inter-dependency is now correctly modelled.
		2962: Apparent: Using value of uninitialized automatic object '%s'.
		2963: Suspicious: Using value of uninitialized automatic object '%s'.
		2972: Apparent: Passing address of uninitialized object '%s' to a function parameter
		declared as a pointer to const.
		2973: Suspicious: Passing address of uninitialized object '%s' to a function parameter
		declared as a pointer to const.
14409	F	New messages have been implemented to identify potential problems when supplying
		string arguments to standard library functions.
		2845: Constant: Maximum number of characters to be written is larger than the target





CR	Т	Resolution
		buffer size.
		2846: Definite: Maximum number of characters to be written is larger than the target buffer size.
		2847: Apparent: Maximum number of characters to be written is larger than the target
		buffer size.
		2848: Suspicious: Maximum number of characters to be written is larger than the target buffer size.
14419	F	Incorrect dataflow messages were generated for variables used in the right hand side of a logical operator in the condition of a branch statement.
		2832: Apparent: Division by zero.
		2834: Possible: Division by zero.
14429	F	When specifying large values for dataflow timeout where function_timeout was smaller
		than query_timeout, message 2755 was not always generated as expected.
		2755: Analysis time of function '%1s' has exceeded the configured maximum: '%2sms'.
		Dataflow analysis continues with the next function.
14442	F	Messages 0336 and 0339 were not generated for an octal constant which includes a
		Suffix.
		0336: Macro defined as an octal constant. 0339: Octal constant used.
14474	F	The evaluation of && and    operations in constant expressions was incorrect.
' ' ' '	'	2830: Constant: Division by zero.
14485	F	Memory usage when analysing deeply nested code in dataflow analysis has been
		reduced, thereby reducing the risk of failing to complete dataflow analysis.
14496	F	Memory usage has been modified to reduce the risk of analysis failure when analysing
		code with very large numbers of objects.
14501	F	The Windows GUI was not showing correct metrics values for file static entities when
14503	F	these metrics were calculated from the Cross-Module Analysis phase.  A bug is fixed which caused the Motif GUI to crash in some cases where files were
14505	-	added and deleted from projects.
14506	F	A bug has been fixed in the include file search algorithm.
		0818: [Q] Cannot find '%s' - Perhaps the appropriate search path was not given ?
14517	N	Implemented automatic retry to acquire a licence from the licence server in case of
		communication failure, to address cases of timeout due to slow connections.
14545	F	Modifications have been made to the x_print utility to allow printing on all supported Unix platforms.
14624	F	Noisy instances of messages 2890, 2895, 2900 and 2905 were generated when
		observing the requirements of MISRA-C:2004 Rule 10.5 – i.e. to apply a cast to the
		underlying type following a ~ or << operation.
		Messages 2890 and 2895 are no longer generated if the operand is essentially
		unsigned.
		Messages 2895 and 2905 are no longer generated unless the value represented in the
		essential type is truncated.
		2890: Constant: Negative value implicitly converted to an unsigned type.
		2895: Constant: Negative value cast to an unsigned type.
		2900: Positive integer value truncated by implicit conversion to a smaller unsigned type.
14625	+-	2905: Positive integer value truncated by cast to a smaller unsigned type.
14625 14639	F	The metrics description in the Windows and Unix metrics browser is improved.
14039	-	The -q (-quiet) option will suppress messages also from files included using angle brackets and located in the directories that are specified with the —i option.
14649	F	Dataflow was incorrectly modeling values if multiple calls to same function modify them
		via global pointers.





CR	Т	Resolution
		2995: The result of this logical operation is always 'true'.
		2996: The result of this logical operation is always 'false'.
14655	N	The Motif GUI is updated to support the UTF encoding option.
14657	N	The Windows GUI is updated to support the UTF encoding option.
15519	F	Dataflow suspicious messages will also be generated for variables that are modified
		within a loop body.
		2778: Suspicious: Copy between overlapping objects.
		2793: Suspicious: Right hand operand of shift operator is negative or too large.
		2803: Suspicious: Overflow in signed arithmetic operation.
		2813: Suspicious: Dereference of NULL pointer.
		2823: Suspicious: Arithmetic operation on NULL pointer. 2833: Suspicious: Division by zero.
		2843: Suspicious: Dereference of an invalid pointer value.
		2853: Suspicious: Implicit conversion to a signed integer type of insufficient size.
		2858: Suspicious: Casting to a signed integer type of insufficient size.
		2863: Suspicious: Implementation-defined value resulting from left shift operation on
		expression of signed type.
		2893: Suspicious: Negative value implicitly converted to an unsigned type.
		2898: Suspicious: Negative value cast to an unsigned type.
		2903: Suspicious: Positive integer value truncated by implicit conversion to a smaller
		unsigned type.
		2908: Suspicious: Positive integer value truncated by cast to a smaller unsigned type.
		2913: Suspicious: Wraparound in unsigned arithmetic operation.
		2923: Suspicious: Left shift operation on expression of unsigned type results in loss of
		high order bits.
		2933: Suspicious: Computing an invalid pointer value. 2943: Suspicious: Result of implicit conversion is only representable in a two's
		complement implementation.
		2948: Suspicious: Result of cast is only representable in a two's complement
		implementation.
		2953: Suspicious: Negative value used in array subscript or pointer arithmetic
		operation.
15536	F	Messages 1475 and 1476 are no longer classified as obsolete.
		1475: Range of possible enum values suggests this test is always true.
		1476: Range of possible enum values suggests this test is always false.
15537	F	A bug is fixed, which prevented some cases of forward goto jumping into loop from
		being detected.
		2752: This '%1s' results in the function being too complex. Dataflow analysis continues
45500	_	with the next function.
15538	F	Messages 1477 and 1478 are no longer classified as obsolete.
		1477: Object of enum type is being implicitly compared against zero in a controlling
		expression.  1478: Object of an enum type which does not include a zero value, is being implicitly
		compared against zero in a controlling expression.
15547	F	This new constraint error message terminates dataflow analysis: 1048.
100 //	'	This new constraint error message terminates dataflow analysis: 1040.  This existing constraint error message now terminates dataflow analysis: 430.
		These new minor error messages terminate dataflow analysis: 1333, 3319.
		This existing minor error message now terminates dataflow analysis: 658.
		These new constraint error messages do not terminate dataflow analysis: 1047, 3236,
		3244.
		These existing constraint error messages no longer terminate dataflow analysis: 232,
		233, 261, 338, 427, 431, 436, 437, 446, 447, 448, 449, 450, 452, 454, 458, 466, 467,





CR	Т	Resolution
		476, 477, 478, 481, 483, 484, 487, 495, 496, 513, 541, 546, 547, 550, 558, 559, 580,
		588, 589, 590, 591, 616, 619, 620, 622, 627, 628, 629, 631, 638, 641, 644, 646, 649,
		650, 651, 653, 655, 656, 659, 664, 665, 673, 675, 677, 683, 684, 690, 699, 708, 709,
		736, 737, 738, 746, 747, 757, 766, 767, 768, 774, 775, 940, 941, 943, 944, 1023, 1024,
		1025, 1033.
		The "DF^2 - Deep Flow Dataflow for QA·C 8.1 – Reference Manual" provides the
		details of all the messages that terminate dataflow analysis.
15596	F	The Windows GUI will correctly display function parameters of type unsigned char in
		the Relationship diagram.
15612	N	The Windows GUI will support conversion of project's dataflow information from QA·C
		8.0 to QA-C 8.1 format.
15645	С	The format of metrics files is changed: dataflow metrics (STST1, STST2, STST3,
		STAV1, STAV2, STAV3, STRET and STUNR) will be logged separately from other
		metrics. Dataflow metrics will not be logged if dataflow is disabled.
15658	F	Invariant conditions of a top level logical OR or AND operator will be detected also
		when they occur on the right hand side of the operator:
		2995: The result of this logical operation is always 'true'.
		2996: The result of this logical operation is always 'false'.

