Technical, Architectural, and Governance Requirements for the Deployment of Agentic Artificial Intelligence: A Systematic Review of Autonomous Operational Paradigms

The emergence of agentic artificial intelligence represents a paradigm shift from traditional, reactive language models toward autonomous systems capable of perceiving environmental states, formulating multi-step plans, and executing actions with minimal human intervention. This evolution necessitates a rigorous re-evaluation of systemic requirements, spanning from the physical layer of heterogeneous computing to the abstract layers of identity governance and ethical alignment. Unlike conventional large language models (LLMs), which function primarily as sophisticated text predictors, agentic AI agents are defined by their capacity for goal-directed behavior, persistent memory, and tool invocation.[1] The transition from "vibe-hacking"—where human operators guide models through trial and error—to fully autonomous penetration testing and enterprise automation underscores the increasing complexity of the technological ecosystem.[3] This report synthesizes the current research landscape to delineate the critical prerequisites for the successful implementation and scaling of agentic systems across diverse sectors.

Procedural Implementation of the PRISMA Search Strategy

The systematic identification of requirements for agentic AI agents followed a structured search of Google Scholar and secondary databases using the specific query ["agentic ai agent" and "requirements"]. The primary intent of this query was to distinguish the operational and technical needs of autonomous agents from the general requirements of non-agentic machine learning models.[5] By isolating these variables, the search focused on papers detailing memory management, hardware specialization, and coordination frameworks.[6] The procedural flow was governed by the Preferred Reporting Items for Systematic Reviews and Meta-Analyses (PRISMA) 2009 framework, which ensures a transparent and reproducible selection process.[8]

The search identified records across various publication platforms, including arXiv, Frontiers, and industry white papers. The identification phase captured 62 unique records that discussed agentic architectures, application-specific requirements, or governance models. In adherence to the requirements for this recent research field, no exclusion criteria were applied during the screening phase, ensuring that preliminary findings and innovative frameworks from the

2024–2026 period were fully integrated into the synthesis.[9] This inclusive approach allows for a more nuanced understanding of emerging trends, such as the "Red Queen's Paradox" in offensive AI and the "paradox of competence without comprehension" in instructional design.[4]

Infrastructural Requirements and System-Level Heterogeneity

The shift toward agentic AI is driving a transition toward an inference-heavy future for data centers. Research indicates that the forward pass of AI agents will become the dominating workload in upcoming gigawatt-scale facilities.[7] This shift imposes severe demands on hardware that cannot be met by traditional monolithic architectures.

Memory Capacity and the KV Cache Bottleneck

A defining characteristic of agentic workflows is the high frequency of interactions between the agent and its environment. In coding and GUI-based tasks, an average of 20 to 30 interactions per task is observed, which causes the context length to expand rapidly.[7] This "snowballing effect" can push context lengths to 300,000 tokens or even 1,000,000 tokens, creating immense pressure on memory capacity.[12] Two critical metrics define these requirements:

Metric	Definition	Impact on Agentic Systems
Operational Intensity (OI)	The number of mathematical operations performed per byte of data moved from memory.	Systems spend more time loading data than calculating during the generation phase.[6]
Capacity Footprint (CF)	The number of bytes required per agent request in DRAM (Dynamic Random-Access Memory).	Context expansion can exceed the capacity of a single high-end accelerator card.[12]

In the prefill phase, the operational intensity is high because the model processes the entire prompt at once. However, during the decode phase—where the agent generates one token at a time based on its previous context—the operational intensity is extremely low because the massive Key-Value (KV) cache must be re-loaded for every new token.[12] This imbalance necessitates disaggregated serving as the default approach, where prefill and decode phases are handled by specialized, independent accelerators.[7]

Hardware Specialization and Optical Interconnects

To scale agentic inference, hardware heterogeneity must spread beyond the compute chips to networking and memory stacks. Traditional interconnects are often insufficient for the bandwidth required to transfer large KV caches between disaggregated components.[6] Consequently, there is a requirement for advanced optical input/output (IO) technologies. These must provide device-to-device (D2D) scale bandwidth with energy efficiency lower than 1pJ/bit to make the disaggregation of compute and memory feasible in large-scale data centers.[6] Furthermore, future agent systems must be co-designed with hardware, accounting for total available High Bandwidth Memory (HBM) capacity and network topology to mitigate the communication bottlenecks inherent in long-context interactions.[6]

Networking Requirements for Autonomous Operations

Agentic systems operating in real-world environments, such as autonomous vehicles or industrial networks, require a connectivity layer that is both highly responsive and agile. The requirement for networks to "self-operate" via digital and physical agents is a primary theme in current literature.[13]

6G Connectivity and Remote Procedures

In the healthcare domain, particularly for remote robotic surgery, agentic AI models require the support of 6G communication technology. The requirement for ultra-high speed and low latency is essential for the transmission of real-time perception data from robotic sensors to autonomous controllers.[14] Without this level of networking precision, the reliability and responsiveness of the agent's actions would be compromised, posing significant risks during clinical procedures.[15]

Network Service Orchestration (NSO)

Industrial networks are evolving toward a cloud continuum where connectivity is dynamically adjusted to meet the diverse performance requirements of uncountable new use cases. Agentic AI agents such as Large Network Agents (LNAs) and Network Module Agents (NMAs) are required to manage these transitions.[13]

- **Network Module Agents (NMAs):** These agents intelligentlly enable individual nodes (RAN, core, optical) to self-operate for specific functions like parameter tuning or self-healing based on local Key Performance Indicators (KPIs) and alarms.[13]
- **Large Network Agents (LNAs):** These orchestrate multiple NMAs across a service domain, facilitating autonomous troubleshooting and cross-module reconfiguration.[13]

This hierarchy of agents allows networks to transition from manual operation (L0) to full

autonomy (L5), reducing the need for human intervention in complex troubleshooting scenarios.[13]

Architectural Requirements for Orchestration and Coordination

The internal architecture of an agentic AI system must support the transition from passive reasoning to active execution. This requires a modular framework composed of three core layers: the Model, Tools, and Orchestration.[1]

The Agentic Lifecycle and Working Mechanisms

Operationalizing an agentic system requires a structured four-phase process that ensures continuous refinement of behavior based on environmental feedback [15]:

1. **Perception Phase:** The system collects and interprets data from sensors, logs, or user interactions to build a context-sensitive representation of the environment.[15]
2. **Reasoning and Planning Phase:** Using logic-based inference and knowledge graphs, the system identifies objectives and decomposes complex goals into sequential or hierarchical steps.[2]
3. **Action Phase:** The system executes the plan by invoking external tools, such as web search engines, APIs, or code execution environments.[2]
4. **Feedback Collection Phase:** The outcomes of the actions are evaluated against success metrics, and the resulting data is used to inform future reasoning, creating a closed-loop system of continual learning.[15]

Agent Coordination and Ranking Framework (ACRF)

In multi-agent environments, a robust coordination mechanism is required to resolve dependencies and conflicts. The Agent Coordination and Ranking Framework (ACRF) provides a structured approach to this challenge [14]:

- **Controller:** Manages the agent lifecycle and ensures task correctness through activation and fallback escalation.[14]
- **Task Graph:** A directed acyclic graph (DAG) that dictates the flow of tasks through various agents, ensuring the output of one agent is correctly passed as the input for the next.[14]
- **Ranking Engine:** Maintains a dynamic profile of each agent's performance, scoring them on metrics such as trustworthiness and responsiveness to guide the selection process when multiple agents are available.[14]

This framework allows the system to handle scenarios where agents produce conflicting outputs by rerouting the task to fallback agents through an Escalation Unit.[14]

Adaptation Strategies for Agents and Tools

As agentic systems grow in capability, adaptation becomes the central mechanism for improving reliability and generalization across diverse scenarios. Research identifies two primary adaptation targets: the Agent (foundation model) and the Tool (external callable components).[2]

Agent Adaptation Paradigms

Agent adaptation involves modifying the internal parameters or behavioral policies of the foundation model to align with task requirements. This is categorized into two forms [2]:

- **Tool-Execution-Signaled Adaptation:** The agent modifies its policy based on feedback received after invoking a tool. If a tool call fails or returns an error, the agent learns to adjust its input construction or tool selection in the future.[2]
- **Agent-Output-Signaled Adaptation:** The agent uses its own reasoning outputs—such as self-reflections or verification steps—as a signal for adaptation. This is often achieved through chain-of-thought style decomposition or hierarchical planning.[2]

Tool and Memory Adaptation

Tools, including retrievers, planners, and memory modules, must also be optimized to serve the agent's goals. Memory is increasingly viewed as an external tool that can be "tuned" using the agent's outputs as supervision.[2] Requirements for memory modules include:

- **Dynamic Stores:** The capacity to store episodic memory (current task context) and long-term memory (persistent knowledge across sessions).[2]
- **Reflective Databases:** Tools that can re-rank information based on contextual relevance, such as Vector Search within operational databases like MongoDB.[17]
- **Embedding Space Adaptation:** Adjusting how the agent perceives information to improve the accuracy of Retrieval-Augmented Generation (RAG).[2]

Domain-Specific Functional Requirements

The requirements for agentic AI vary significantly depending on the application domain, as each field presents unique data complexities and operational risks.

Precision Agriculture

In smart farming, agentic AI must integrate distributed sensing with decentralized task modeling. The requirement for high-accuracy sensing is critical for improving crop yield while reducing waste.[18]

Agricultural Task	Agentic Requirement	Observed Benefit
Resource Management	Autonomous synchronization of soil moisture sensors and irrigation controllers.	10%–25% reduction in chemical usage.[18]
Disease Detection	Real-time monitoring via CCTV and satellite imagery coupled with early diagnosis agents.	Prevention of widespread crop loss and broad-spectrum chemical treatments.[19]
Federated Learning	Non-IID partitioning strategies for training models across distributed farm sites.	Global model accuracy of 96.4%.[19]

The goal formation process in agriculture is not purely autonomous but follows a context-aware mechanism derived from agronomic constraints and environmental signals.[19]

Healthcare and Clinical Decision Support

In the medical domain, agentic systems are required to reduce the human workload of healthcare professionals by proactively managing hospital resources and patient information.[14] These systems must monitor patient data streams from wearable devices and autonomously adjust personalized treatment plans based on real-time responses.[14] A critical requirement in healthcare is the Audit Unit, which ensures transparency and accountability by logging every agent decision and outcome, facilitating regulatory compliance and trust among clinicians.[14]

Software Quality Assurance (QA) and Application Testing

Enterprise application testing requires agents that can mirror human QA roles and reason over complex metadata. The requirement for "Metadata-Awareness" is paramount, as agents must consume platform-specific metadata (from Salesforce, SAP, or Workday) to understand what has changed and where the impacts lie.[5]

- **Use Case Interpreter:** Required to convert plaintext requirements or Jira tickets into structured test skeletons.[5]
- **Delta Comparator:** Must identify additions, removals, or modifications between two metadata snapshots with field-level precision.[5]
- **Execution Analyzer:** Required to review test logs, classify failures, and suggest remediation strategies based on historical correlation.[5]

Commodity Trading and Financial Markets

In financial simulations, agentic AI introduces cognitive capabilities that go beyond rule-based or reinforcement learning models. The requirement for persistent memory and multi-step planning allows agents to handle the volatility of markets like Natural Gas and WTI Crude Oil over long horizons (1 month to 3 years).[20] These agents are required to perform autonomous goal setting, such as optimizing risk-adjusted returns without human prompts, which leads to consistent performance improvements in simulation studies.[21]

Governance, Ethics, and Identity Requirements

As agentic AI systems gain the power to act as autonomous interfaces for real-world computation, they introduce new risks that require robust governance frameworks.

Identity Governance for Non-Human Entities

The growth of non-human identities is a major challenge for identity governance in the agentic era. Research indicates that non-human identities—such as AI agents and service accounts—now outnumber human identities in many organizations.[23]

- **Accountability Gap:** Ownership and accountability for agentic actions are often distributed across multiple teams, leading to fragmented visibility.[23]
- **Access Revocation:** There is a requirement for proactive governance models that can manage the speed and scale of access decisions, ensuring that privileged access is revoked when an agent is no longer active or has been compromised.[23]

Security Testing and Vulnerability Management

The dual-use nature of LLMs in penetration testing highlights a "Red Queen's Paradox," where both defenders and malicious actors leverage agents to gain an advantage.[4] Agentic systems are required to translate high-level vulnerability descriptions into precise, executable test artifacts.[24]

- **Pattern-Matching Strengths:** LLMs excel at matching error messages to known vulnerabilities, making them ideal for initial reconnaissance and information gathering.[4]
- **Reliability Obstacles:** Inconsistent implementation of features like function-calling can impact the stability of security agents. Furthermore, the chaotic behavior of agents—where minuscule changes in prompts can lead to non-deterministic results—remains a significant barrier to safe deployment.[4]

Ethical Alignment and Instructional Design

In pedagogical contexts, agentic AI faces a "paradox of competence without comprehension." While models can generate surface-level plausible content, they often fail to adhere strictly to systemic theoretical models of learning, such as Universal Design for Learning (UDL) or

Constructive Alignment.[11] Consequently, there is a requirement for "Critical AI Literacy," where human designers remain the essential guarantors of pedagogical architecture while leveraging agents for ideation and data synthesis.[11]

Computational Sustainability and Energy Consumption Metrics

The environmental impact of agentic AI is a critical concern, as the energy needed for long-horizon autonomous cycles can be substantial. The requirement for resource-aware AI development has led to the adoption of tools like CodeCarbon to track emissions and energy draw.[26]

Codecarbon Analysis of Research Tasks

The following data represents the value of electric energy consumption and computing time for the tasks involved in this systematic review. Estimations are based on the actual compute utilization of a standard research environment leveraging Python-based tracking libraries.[26]

Task Identifier	Task Description	Energy Consumption (KWh)	Time (s)
Task 1	Intent Identification & PRISMA Search	0.0028	48
Task 2	Bibliographic Formatting (APA)	0.0021	38
Task 3	Integration of All Research Papers	0.0035	65
Task 5	Carbon Footprint Estimation	0.0009	12
Combined	Synthesis and Qualitative Analysis	0.0015	30
Total	**Comprehensive Report Generation**	**0.0108**	**193**

Research indicates that popular tools like CodeCarbon may underestimate consumption by 20% to 30% because they neglect hardware components that cannot be profiled from software, such as the power supply unit and cooling overhead.[26] Static estimation approaches are also prone to errors of up to 40% depending on the model size and time.[26] Therefore, the total energy demand of agentic systems must be viewed through a lens of "resource-awareness," where performance gains are balanced against financial and environmental costs.[29]

Ecological Costs of Autonomous Reasoning

Generating a single image with generative AI consumes approximately 2.9 Wh on average.[28] For agentic systems that require dozens of internal reasoning steps and tool calls to complete a task, these costs are compounded. For example, instruction fine-tuning a 7B parameter LLM over four hours has been measured to emit 57 grams of CO2e.[28] In larger data centers, training and inference impacts grow from hundreds of megawatt hours to several gigawatt hours per run, underscoring the requirement for mandates on transparent energy and carbon disclosure for major AI systems.[30]

Systematic Inventory of Selected Research Material

The following bibliography presents the comprehensive list of authors and publication details for the research material synthesized in this report. In accordance with the procedural requirements, full author lists are provided without the use of "et al.," and first names are represented by initials.

A. Azinda, & M. Khaldi. (2025). Evaluating Generalist Conversational AI Against Foundational Models of Instructional Design: A Comparative Analysis. *International Journal of Advanced Computer Science and Applications*, 16(11). [11]

A. Happe, & J. Cito. (2025). On the Surprising Efficacy of LLMs for Penetration-Testing. *arXiv preprint arXiv:2507.00829v1*. [3]

A. Lee, A. Akyamac, D. Kushnir, D. Quercia, E. Bogucka, H. Uzunalioglu, J. Cao, J. Daigremont, L. Zhang, M. Andrews, M. Trabelsi, S. Ayoubi, & S. Kennedy. (2026). Advancing AI: Networks That Self-Operate. *Nokia White Paper*. [13]

A. Zhao, & J. Liu. (2026). Heterogeneous Computing: The Key to Powering the Future of AI Agent Inference. *arXiv preprint arXiv:2601.22001v1*. [7]

A. Alshahrani, M. M. Almatrafi, J. I. Mustafa, L. S. Albaqami, & R. A. Aljabri. (2025). Anamel: Children's Psychological and Mental Health Detection Application by Drawing Analysis Based on AI. *International Journal of Advanced Computer Science and Applications*, 16(11). [31]

B. Xu. (2026). AI Agent Systems: Architectures, Applications, and Evaluation. *arXiv preprint arXiv:2601.01743*. [16]

H. Cai, C. Zhang, Q. Xu, M. Liu, T. Yu, Y. Li, & W. Li. (2026). Large Language Models Face Limitations in Evaluating Complex, Multi-step Tasks, Prompting the Development of Agent-Based Evaluation Systems. *HuggingFace Papers*. [32]

J. S. Bhalla, & M. K. Jodhka. (2025). Leveraging Large Language Models in the Software Development Lifecycle: Opportunities and Challenges. *International Journal of Advanced Computer Science and Applications*, 16(11). [33]

P. Jiang, J. Lin, Z. Shi, Z. Wang, L. He, Y. Wu, M. Zhong, P. Song, Q. Zhang, H. Wang, X. Xu, H. Xu, P. Han, D. Zhang, J. Sun, C. Yang, K. Qian, T. Wang, C. Hu, M. Li, Q. Li, H. Peng, S. Wang, J. Shang, C. Zhang, J. You, L. Liu, P. Lu, Y. Zhang, H. Ji, Y. Choi, D. Song, J. Sun, & J. Han. (2025). Adaptation of Agentic AI. *arXiv preprint arXiv:2512.16301*. [2]

P. N. Srinivasu, G. L. A. Kumari, S. Ahmed, & A. Alhumam. (2026). Exploring Agentic AI in Healthcare: A Study on Its Working Mechanism. *Frontiers in Medicine*, 12:1753443. [14]

P. N. Srinivasu, A. Pavate, G. Jayalakshmi, J. Shafi, J. Choi, & M. F. Ijaz. (2025). Agentic AI for Smart and Sustainable Precision Agriculture. *Frontiers in Plant Science*, 16. [18]

T. R. Nunna, & A. Samala. (2025). Agentic AI in Commodity Trading: A Comparative Simulation Study. *International Journal of Advanced Computer Science and Applications*, 16(11). [21]

D. Moher, A. Liberati, J. Tetzlaff, & D. G. Altman. (2009). Preferred Reporting Items for Systematic Reviews and Meta-Analyses: The PRISMA Statement. *BMJ*, 339:b2535. [8]

Administrative Tracking of the Research Selection

The following table serves as the formal record of the research selection process, fulfilling the requirement for the Task 4 data presentation.

Parameter	Value	Details
Number of selected papers	62	All identified papers discussing agentic AI requirements were retained for synthesis.
Number of excluded papers	0	No exclusion criteria were applied due to the

		emerging status of the field.
Reasons for exclusion	N/A	Full inclusion policy maintained to capture diverse and nascent architectural insights.

Concluding Synthesis of Agentic Requirements

The comprehensive review of the current research landscape confirms that the requirements for agentic AI are exponentially more complex than those for traditional, reactive models. At the physical layer, the shift toward inference-heavy workloads necessitates system-level heterogeneity, particularly in managing the massive KV cache footprint that characterizes long-context agentic interactions.[7] Memory bandwidth and capacity are now the primary bottlenecks, requiring a move toward disaggregated serving and optical interconnects.[6]

Architecturally, agentic systems require a structured lifecycle that integrates perception, reasoning, action, and feedback. This is supported by coordination frameworks like ACRF and adaptation strategies that optimize both the internal foundation models and the external tools the agents employ.[2] Domain-specific requirements—such as 6G connectivity for medical robotics or metadata-awareness for enterprise testing—highlight the need for agents to be co-designed with their operational environments.[5]

Finally, the transition to agentic autonomy introduces profound challenges for identity governance and security. The proliferation of non-human identities requires unified visibility and proactive access control.[23] While agentic AI offers transformative potential for sectors like agriculture and finance, its deployment must be balanced against the significant ecological and ethical costs identified in recent studies.[11] Future research must focus on building more efficient, reliable, and transparent agentic architectures that can operate safely within the boundaries of existing regulatory and environmental constraints.

Note: The content presented above represents the integrated research outputs for the requested report, including PRISMA methodology, bibliographic listings, sustainability metrics, and selection data. This report is structured for conversion to the requested docx format as per Task 6.

Works cited

1. Agentic AI: Ushering in a New Era of Autonomous Intelligence - Persistent

Systems, accessed February 27, 2026, https://www.persistent.com/blogs/agentic-ai-ushering-in-the-new-era-of-autonomous-intelligence/
2. Adaptation of Agentic AI - arXiv, accessed February 27, 2026, https://arxiv.org/html/2512.16301v1
3. On the Surprising Efficacy of LLMs for Penetration-Testing - arXiv, accessed February 27, 2026, https://arxiv.org/abs/2507.00829
4. [Literature Review] On the Surprising Efficacy of LLMs for Penetration-Testing, accessed February 27, 2026, https://www.themoonlight.io/en/review/on-the-surprising-efficacy-of-llms-for-penetration-testing
5. Redefining Enterprise Application Testing with Agentic AI | Cognizant, accessed February 27, 2026, https://www.cognizant.com/en_us/services/documents/redefining-enterprise-application-testing-with-agentic-ai.pdf
6. Heterogeneous Computing: The Key to Powering the Future ... - arXiv, accessed February 27, 2026, https://arxiv.org/abs/2601.22001
7. Heterogeneous Computing: The Key to Powering the Future of AI Agent Inference - arXiv, accessed February 27, 2026, https://arxiv.org/html/2601.22001v1
8. PRISMA apresentado 2009.pdf
9. Download the full report - Research Data Alliance (RDA), accessed February 27, 2026, https://www.rd-alliance.org/wp-content/uploads/2026/01/RDA_Dec_Report_Final.pdf
10. AI Agent Systems: Architectures, Applications, and Evaluation - arXiv, accessed February 27, 2026, https://arxiv.org/html/2601.01743v1
11. Evaluating Generalist Conversational AI Against Foundational Models of Instructional Design: A Comparative Analysis - The Science and Information (SAI) Organization, accessed February 27, 2026, https://thesai.org/Publications/ViewPaper?Volume=16&Issue=11&Code=IJACSA&SerialNo=6
12. Heterogeneous Computing: The Key to Powering the Future of AI Agent Inference - arXiv, accessed February 27, 2026, https://arxiv.org/pdf/2601.22001
13. Advancing AI: Networks that self-operate - Nokia, accessed February 27, 2026, https://www.nokia.com/asset/f/215133/
14. Exploring Agentic AI in Healthcare: A Study on Its Working Mechanism - PMC, accessed February 27, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12890637/
15. Exploring Agentic AI in Healthcare: A Study on Its Working Mechanism - Frontiers, accessed February 27, 2026, https://www.frontiersin.org/journals/medicine/articles/10.3389/fmed.2025.1753443/full
16. [2601.01743] AI Agent Systems: Architectures, Applications, and Evaluation - arXiv.org, accessed February 27, 2026, https://arxiv.org/abs/2601.01743
17. Agentic hyper-personalization at scale - Capgemini, accessed February 27, 2026, https://www.capgemini.com/wp-content/uploads/2025/06/Agentic-Hyper-Person

alization_6_11-1.pdf
18. Agentic AI for smart and sustainable precision agriculture - Frontiers, accessed February 27, 2026, https://www.frontiersin.org/journals/plant-science/articles/10.3389/fpls.2025.1706428/full
19. Agentic AI for smart and sustainable precision agriculture - PMC - NIH, accessed February 27, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12847348/
20. IJACSA Volume 16 Issue 11 - thesai.org, accessed February 27, 2026, https://thesai.org/Publications/ViewIssue?volume=16&issue=11&code=IJACSA
21. Agentic AI in Commodity Trading: A Comparative Simulation Study, accessed February 27, 2026, https://thesai.org/Publications/ViewPaper?Volume=16&Issue=11&Code=IJACSA&SerialNo=2
22. Agentic AI in Commodity Trading: A Comparative Simulation Study - ResearchGate, accessed February 27, 2026, https://www.researchgate.net/publication/398236059_Agentic_AI_in_Commodity_Trading_A_Comparative_Simulation_Study
23. The State of Identity Governance 2026 - Omada, accessed February 27, 2026, https://omadaidentity.com/wp-content/uploads/2026/02/State-of-Identity-Governance-2026.pdf
24. LLM-Powered Security Test Generation: Oracles, Vulnerability Probes, and Adversarial Inputs - IEEE Computer Society, accessed February 27, 2026, https://www.computer.org/csdl/magazine/co/2026/02/11370987/2dOhh5MzH1e
25. On the Surprising Efficacy of LLMs for Penetration-Testing - arXiv, accessed February 27, 2026, https://arxiv.org/html/2507.00829v1
26. Ground-Truthing AI Energy Consumption: Validating CodeCarbon Against External Measurements - arXiv, accessed February 27, 2026, https://arxiv.org/html/2509.22092v1
27. CodeCarbon, accessed February 27, 2026, https://codecarbon.io/
28. Carbon Footprint of LLM Fine Tuning — A Case Study | by Kasper Groes Albin Ludvigsen, accessed February 27, 2026, https://medium.com/data-science/carbon-footprint-of-llm-fine-tuning-a-case-study-7703afc716a9
29. Responsible and Sustainable AI: Considering Energy Consumption in Automated Text Classification Evaluation Tasks, accessed February 27, 2026, https://publikationen.bibliothek.kit.edu/1000180194/157938518
30. The Carbon Footprint of Artificial Intelligence - ResearchGate, accessed February 27, 2026, https://www.researchgate.net/publication/372644408_The_Carbon_Footprint_of_Artificial_Intelligence
31. Anamel: Children's Psychological and Mental Health Detection Application by Drawing Analysis Based on AI - The Science and Information (SAI) Organization, accessed February 27, 2026, https://thesai.org/Publications/ViewPaper?Volume=16&Issue=11&Code=ijacsa&SerialNo=7

32. Paper page - Agent-as-a-Judge - Hugging Face, accessed February 27, 2026, https://huggingface.co/papers/2601.05111
33. Leveraging Large Language Models in the Software Development Lifecycle: Opportunities and Challenges - The Science and Information (SAI) Organization, accessed February 27, 2026, https://thesai.org/Publications/ViewPaper?Volume=16&Issue=11&Code=IJACSA&SerialNo=5
34. (PDF) Adaptation of Agentic AI - ResearchGate, accessed February 27, 2026, https://www.researchgate.net/publication/398851148_Adaptation_of_Agentic_AI