

Dynamic Software Updates: A VM-Centric Approach

Suriya Subramanian

Intel Corporation

Feb 26, 2013

Motivation

- Software applications change all the time
- Deployed systems must be updated with bug fixes, new features
- Updating typically involves: stop, apply patch, restart








Your request could not be processed at this time




The service is currently unavailable.



Please try again in a few minutes. If this problem persists, report an issue to eBay support.




Your request could not be processed

 **The service is currently unavailable.**
Please try again in a few minutes. If

Dynamic Software Updating in the real world




Dynamic Software Updating in the real world



The fundamental problem is losing state
because of downtime.

Dynamic software updating



Key contribution

JVOLVE - a DSU-enabled Java Virtual Machine

Safe Guarantees type-safe updates
Relies on programmer for semantic-correctness

Flexible Supports method body and signature changes
across class hierarchies


Efficient No overhead during normal execution

Easy to use The stock application is DSU-ready
No rewriting/recompilation required

Outline

- Introduction
- An example of an update
- Update Timing and Safety
- Updating State
 - Object Transformers Model
 - Object Transformers VM Implementation
 - Automating state transformer generation
- Evaluation
- My research vision

JVOLVE - System overview



Supported updates

- Changes within the body of a method

```
public static void main(String args[]) {  
    System.out.println("Hello, World.");  
+   System.out.println("Hello again, World.");  
}
```

- Class signature updates



- Add, remove, change the type signature of fields and methods

```
public class Line {  
-   private final Point2D p1, p2;  
+   private final Point3D p1, p2;  
    ...  
}
```

- Signature updates require an object transformer function
- Changes can occur at any level of the class hierarchy

Unsupported changes

- Renaming classes
- Changes to class hierarchy



Example of an update (JavaEmailServer)

```
public class User {
    private final String username, domain, password;
-   private String[] forwardAddresses;
+   private EmailAddress[] forwardAddresses;
    public User(...) {...}
    public String[] getForwardedAddresses() {...}

    public void setForwardedAddresses(String[] f) {...}

}

public class ConfigurationManager {
    private User loadUser(...) {
        ...
        User user = new User(...);
        String[] f = ...;

        user.setForwardedAddresses(f);
        return user;
    }
}
```

Example of an update (JavaEmailServer)

```
public class User {
    private final String username, domain, password;
-   private String[] forwardAddresses;
+   private EmailAddress[] forwardAddresses;
    public User(...) {...}
-   public String[] getForwardedAddresses() {...}
+   public EmailAddress[] getForwardedAddresses() {...}
-   public void setForwardedAddresses(String[] f) {...}
+   public void setForwardedAddresses(EmailAddress[] f) {...}
}

public class ConfigurationManager {
    private User loadUser(...) {
        ...
        User user = new User(...);
-       String[] f = ...;
+       EmailAddress[] f = ...;
        user.setForwardedAddresses(f);
        return user;
    }
}
```


Example of an update (JavaEmailServer)

```
public class v131_User {
    private final String username, domain, password;
    private String[] forwardAddresses;
}

public class JvolveTransformers {
    ...
    public static void jvolveClass(User unused) {}
    public static void jvolveObject(User to, v131_User from) {
        to.username = from.username;
        to.domain = from.domain;
        to.password = from.password;
        // to.forwardAddresses = null;
        int len = from.forwardAddresses.length;
        to.forwardAddresses = new EmailAddress[len],
        for (int i = 0; i < len; i++) {
            to.forwardAddresses[i] =
                new EmailAddress(from.forwardAddresses[i]);
        }
    }
}
```

Stub generated by UPT
for the old version

Default transformer copies
old fields, initializes new
ones to null


Example of an update (JavaEmailServer)

```
public class v131_User {
    private final String username, domain, password;
    private String[] forwardAddresses;
}

public class JvolveTransformers {
    ...
    public static void jvolveClass(User unused) {}
    public static void jvolveObject(User to, v131_User from) {
        to.username = from.username;
        to.domain = from.domain;
        to.password = from.password;
        // to.forwardAddresses = null;
        int len = from.forwardAddresses.length;
        to.forwardAddresses = new EmailAddress[len];
        for (int i = 0; i < len; i++) {
            to.forwardAddresses[i] =
                new EmailAddress(from.forwardAddresses[i]);
        }
    }
}
```

Stub generated by UPT
for the old version


Update process



- Offline Update Preparation Tool
- JvOLVE VM
 - Reach a DSU safe point
 - Install new classes
 - Update state
 - Resume execution


Safe point for the update

- Updates happen at “safe points”
- Safe points are VM yield points, and restrict what methods can be on stack
- Extend the thread scheduler to suspend all application threads
- If any stack has a restricted method, delay the update




Safe point for the update

- Updates happen at “safe points”
- Safe points are VM yield points, and restrict what methods can be on stack
- Extend the thread scheduler to suspend all application threads
- If any stack has a restricted method, delay the update




Safe point for the update

- Updates happen at “safe points”
- Safe points are VM yield points, and restrict what methods can be on stack
- Extend the thread scheduler to suspend all application threads
- If any stack has a restricted method, delay the update



Restrict changed methods (activeness safety)

- Update happens atomically
- Only old code runs before update, only new after update
- Do not allow changed methods to be active on stack
- Guarantees type safety
- Old and new version methods are independently type-safe



Restricted methods

- (1) Methods changed by the update
- (2) Methods identified by the user as unsafe based on semantic information about the application

Install return barriers that trigger DSU upon unsafe method's return

- (3) Methods whose bytecode is unchanged, but compiled representation is changed by the update
 - Offsets of fields and methods hard-coded in machine code
 - Inlined callees may have changed

Utilize on-stack replacement to recompile base-compiled methods

Restricted methods


- (1) Methods changed by the update
- (2) Methods identified by the user as unsafe based on semantic information about the application

Install return barriers that trigger DSU upon unsafe method's return

- (3) Methods whose bytecode is unchanged, but compiled representation is changed by the update
 - Offsets of fields and methods hard-coded in machine code
 - Inlined callees may have changed

Utilize on-stack replacement to recompile base-compiled methods

Reaching a safe point



Install a return barrier for d(). Wait till it returns. On-stack replace new machine code for c().


Outline

- Introduction
- An example of an update
- Update Timing and Safety
- Updating State
 - Object Transformers Model
 - Object Transformers VM Implementation
 - Automating state transformer generation
- Evaluation
- My research vision

Object Transformers Model


Old version

```
class X { Y y; }  
class Y { int i; }
```



New version

```
class X { Y y; int z; }  
class Y { int i; int j; }
```




```
1 Transformer for X:  
2   to.y = from.y;  
3   to.z = 0;  
4 Transformer for Y:  
5   to.i = from.i;  
6   to.j = 0;
```

Object Transformers Model


Old version

```
class X { Y y; }  
class Y { int i; }
```



New version

```
class X { Y y; int z; }  
class Y { int i; int j; }
```



Old version stub

```
class oldX { Y y; }  
class oldY { int i; }
```

Object Transformers Model


- Simple to reason about
- Transformers written in the source language
- All references are to the newest version
- Ensure that an object is transformed before reading its fields

Transforming objects in the GC


Happens in two steps

- Garbage collector creates an additional empty copy for updated objects
- Walk through and transform all these objects

Example



Singly-linked to doubly-linked list




From space


To space

To space (old version objects)


Singly-linked to doubly-linked list



Singly-linked to doubly-linked list




Singly-linked to doubly-linked list




```
jvolveObject(Node to,
               old_Node from) {
    to.data = from.data;
    to.next = from.next;
    if (to.next != null)
        to.next.prev = to;
}
```

Singly-linked to doubly-linked list




```
jvolveObject(Node to,  
              old_Node from) {  
    to.data = from.data;  
    to.next = from.next;  
    if (to.next != null)  
        to.next.prev = to;  
}
```

Singly-linked to doubly-linked list




```
jvolveObject(Node to,  
              old_Node from) {  
    to.data = from.data;  
    to.next = from.next;  
    if (to.next != null)  
        to.next.prev = to;  
}
```

Singly-linked to doubly-linked list




```
jvolveObject(Node to,  
               old_Node from) {  
    to.data = from.data;  
    to.next = from.next;  
    if (to.next != null)  
        to.next.prev = to;  
}
```


Singly-linked to doubly-linked list



Singly-linked to doubly-linked list




Singly-linked to doubly-linked list




Finding the list's tail

```
Node prev = null;
Node current = from.head;
while (current != null) {
    prev = current;
    if (! VM.is_transformed(current)) {
        r0_Node current_old = VM.old_version_object(current);
        current = current_old.next;
    } else {
        current = current.next;
    }
}
to.tail = prev;
```


Singly-linked to doubly-linked list



Singly-linked to doubly-linked list



Singly-linked to doubly-linked list



Outline

- Introduction
- An example of an update
- Update Timing and Safety
- Updating State
 - Object Transformers Model
 - Object Transformers VM Implementation
 - Automating state transformer generation
- Evaluation
- My research vision

Automating state transformer generation

Goal: Robust, trustworthy handling of simple transformers

- Leave programmer to concentrate on more difficult cases

Approach

- Capture state (ver. 1 and ver. 2) using JVM heap snapshot capability
- Compare states. Matching process produces input/output examples
- Synthesize valid state transformer from the examples

Azureus memory leak fix

```
1 void
2 transform(PEPeerControlImpl to,
3           old_PEPeerControlImpl from)
4 {
5     if (from.bContinue == false) {
6         to.s.adapter = null;
7     } else {
8         to.s.adapter = from.s.adapter;
9     }
10 }
```


Outline

- Introduction
- An example of an update
- Update Timing and Safety
- Updating State
 - Object Transformers Model
 - Object Transformers VM Implementation
 - Automating state transformer generation
- Evaluation
- My research vision

Application Experience

- Jetty webserver
 - 11 versions, 5.1.0 through 5.1.10, 1.5 years
 - 45 KLOC
- JavaEmailServer
 - 10 versions, 1.2.1 through 1.4, 2 years
 - 4 KLOC
- CrossFTP server
 - 4 versions, 1.05 through 1.08, more than a year
 - 18 KLOC

Support 20 of 22 updates

- 13 updates change class signature by adding new fields
- Several updates require On-stack replacement support
- Two versions update an infinite loop, postponing the update indefinitely

Unsupported updates

- JavaEmailServer 1.2.4 to 1.3
 - Update reworks the configuration framework of the server
 - Many classes are modified to refer to the configuration system
 - Including infinite loops in SMTP and POP threads
- Jetty 5.1.2 to 5.1.3
 - The application would never reach a safe point
 - Modified method `ThreadedServer.acceptSocket()` that waits for connections is nearly always on stack
 - Return barrier not sufficient since the main method in other threads `PoolThread.run()` is itself modified

Outline

- Introduction
- An example of an update
- Update Timing and Safety
- Updating State
 - Object Transformers Model
 - Object Transformers VM Implementation
 - Automating state transformer generation
- Evaluation
- My research vision

Make web-applications better

- Seamlessly distribute computing between client/proxy/server
 - Adaptively move compute to offer best user(s) experience
 - Customized solutions exist
 - Amazon Silk runs part of the browser on the cloud
 - Netflix video codec variation by device/bandwidth
- Going from prototype to scale
 - Productivity always wins over performance
 - PHP, Python, and Ruby have won the productivity war
 - Performance comes later: Twitter moves to Scala, Facebook compiles PHP
 - Establish JVM as the instruction set of webapps?

Conclusion


- Jvolve, a Java VM with support for Dynamic Software Updating
- Most-featured, best-performing DSU system for Java
- Naturally extends existing VM services
- Supports about two years worth of updates

Dynamic software updating in managed languages can be achieved in a safe, flexible and efficient manner.

Backup slides

JVOLVE performance

No overhead during steady-state execution



Jetty webserver performance

- Used `httperf` to issue requests
- Both client and server on a the same machine, an Intel Core 2 Quad
- Report throughput and latency, median of 21 runs

DSU pause times

- Jvolve performs a GC to transform objects
- Pause time determined by
 - Heap size
 - # of objects transformed
- Simple microbenchmark varying the fraction of objects transformed in a 1GB heap


Update pause time

- No apriori overhead during normal execution (before and after the update)
- Only effect on execution time is the update pause time
 - Comparable to GC pause time

Update pause time


$$\begin{aligned} \text{DSU Pause Time} &\cong \text{Regular GC Time} + \\ &\quad \text{Time to allocate upd. objects} + \\ &\quad \text{Time to transform objects} \\ &\propto \text{Upd. objects fraction} \\ &\quad \text{Heap size} \end{aligned}$$

DSU pause times (microbenchmark)




Update correctness

Version 1



Version 2



Atomic Update

- Single program step
- - - Multiple program steps
- ➡ State transformation

Correct update semantics

Update correctness depends on semantics of application and state transformers

- Transformer that initializes all variables to “unknown” is equivalent to restarting the program. Not useful.
- When going from an 8-bit to 16-bit counter, no correct transformer exists

Safety Guarantees

- Correctness
 - Showing an update correct is undecidable
 - Rely on programmer and testing process for semantics and safety of update
- Well-formed updates
 - All data accesses and method calls in the program respect language semantics.
 - Type safety