Dynamic Software Updates in Java: A VM-centric approach

Suriya Subramanian Advisor: Kathryn S. McKinley

Department of Computer Sciences The University of Texas at Austin

> July 21, 2008 Ph.D. Oral Proposal

The only thing that is constant is change.

Heraclitus of Ephesus

Motivation

- ▶ Software applications change all the time
- Deployed systems must be updated with bug fixes, new features
- The straightforward approach is to stop and restart applications
- ► Stopping not desirable
 - Safety concerns
 - Revenue loss
 - Inconvenience

Slide 3

Solutions to updating software

- ► Move state out of the process
 - State stored externally, for instance databases
 - ▶ Redundant systems: start a new process and stop this one
 - ▶ Not always possible
- ► Dynamic Software Updating (DSU)
 - ▶ Update process state without restarting application
 - ► Non-redundant systems benefit as well
 - ▶ Decouples fault-tolerance from software updating

Slide F

State of the art

Significant progress for C

- ► Server feature upgrades
 - ► Ginseng [Neamtiu et al., 2006]
 - ▶ POLUS [Chen et al., 2007]
- ► Security patches: OPUS [Altekar et al., 2005]
- ► Operating system upgrades
 - K42 [Soules et al., 2003]
 - DynAMOS [Makris and Ryu, 2007]
 - LUCOS [Chen et al., 2006]
 - ► Ksplice [ksplice, 2008]

Applications

- ▶ Personal operating system
- ▶ LinkedIn.com architecture¹
 - "The Cloud": In memory representation of the LinkedIn network graph
 - Network size 22M nodes, 120M edges
 - ▶ Rebuilding an instance takes 8 hours

Slide

DSU requirements

A Dynamic Software Updating solution should *ideally* be

Safe Updating is as correct as starting from scratch Flexible Be able to support changes encountered in practice

Efficient No performance impact on the original application

Slide

Opportunities for managed languages

Solutions for C typically

- ▶ Require special compilation
- ▶ Statically/dynamically insert indirection for function calls
- ► Restrict structure updates, require extra allocation
- ▶ Impose space/time overheads on normal execution
- ► Make type-safety for updates difficult
- ► Not multi-threaded

Slide

Slide

http://hurvitz.org/blog/2008/06/linkedin-architecture

Existing solutions for managed languages

- ► VM-based solutions
 - ► JDrums [Ritzau and Andersson, 2000], DVM [Malabarba et al., 2000]
 - ▶ Not well evaluated
 - \blacktriangleright Provide an interface similar to $\mathrm{J}\mathrm{VOLVE}$
 - ► Perform lazy updates
 - Overheads during normal execution
- ► Standard VM with DSU support
 - DJVCS [Barr and Eisenbach, 2003], DUSC [Orso et al., 2002], [Milazzo et al., 2005]
 - ► Special classloaders, compilers
 - Very restrictive
 - ► Space/time overheads

Slide 9

Thesis

Dynamic software updating in managed languages can be achieved in a safe, flexible and efficient manner by naturally extending existing VM services.


We propose to affirm this claim by building a JVM with DSU support and studying updates to real world applications.

Corollary

DSU support should be a standard feature of future VMs.

Slide 11

Developer's view of $\ensuremath{\mathrm{JVOL\!VE}}$



Slide 13

Supported updates

- ► Changes within the body of a method
- ► Class signature updates
 - Add, remove, change the type signature of fields and methods
- ▶ Changes can occur at any level of the class hierarchy

Our solution

- ▶ JVOLVE a Java Virtual Machine with DSU support
- ▶ Key insight: Naturally extend existing VM services
 - Classloading
 - ► Bytecode verification
 - Thread synchronization
 - ► Garbage collection
 - On-stack replacement
- ▶ No DSU-related overhead during normal execution
- ▶ Support updates to real world applications

Slide :

Outline

Introduction

Motivation

Thecic

JVOLVE

Developer's view Implementation Experience

Conclusion

Slide 1

Division of Labor

- Developer
 - ► Write the old and new versions
 - Write class/object transformation functions for classes that changed (optional)
 - ► Testing (both the application and the update)
- ▶ JVOLVE system
 - Update Preparation Tool (UPT) compares versions and presents the update to the JVOLVE VM.
 - \blacktriangleright $\ensuremath{\mathrm{JVOLVE}}$ VM handles the update

Slide 1

Example of an update (JavaEmailServer)

```
public class User {
    private String Username, domain, password;
    private String[] forwardAddresses;
    public String[] getForwardedAddresses() {...}
    public void setForwardedAddresses(String[] f) {...}
}

public class ConfigurationManager {
    private User loadUser(...) {
        ...
        User user = new User(...);
        String[] f = ...;
        user.setForwardedAddresses(f);
        return user;
    }
}
```

Example of an update (JavaEmailServer) public class User { private String username, domain, password; private String[] forwardAddresses; public String[] getForwardedAddresses() {...} public void setForwardedAddresses(String[] f) {...} private EmailAddress[] forwardAddresses: public EmailAddress[] getForwardedAddresses() {...} public void setForwardedAddresses(EmailAddress[] f) {...} public class ConfigurationManager { private User loadUser(...) { User user = new User(...); String[] f = EmailAddress[] f = ...; user.setForwardedAddresses(f); return user;

```
Object Transformers
```

```
public class old_User {
  public String username, domain, password;
  public String[] forwardAddresses;
public class User {
  public static void jvolve_class() { ... }
  public static void jvolve_object(User to, old_User from) {
    to.username = from.username;
    to.domain = from.domain;
    to.password = from.password;
    to.forwardAddresses = null;
    int 1 = from.forwardAddresses.length;
    to.forwardAddresses = new EmailAddress[1];
    for (int i = 0; i < 1; i++)
      to.forwardAddresses[i] =
       new EmailAddress(from.forwardAddresses[i]);
}}
```

Update model

- ► Update happens in one fell swoop
- ► Simple to reason about
- ► Code
 - ▶ Old code before the update
 - ▶ New code after the update
- Data
 - Representation consistency (all values of a type correspond to the latest version)
 - Support a transformation function to convert objects to the new type

Slide 2

Slide 23

Update Preparation Tool



- ▶ Uses jclasslib², a bytecode library
- ► Compares bytecode of the two versions
- ► Categorizes changes into

Class updates Classes that add, remove, change signature of fields or methods

Method updates Changes within a method body. Only the method has to be loaded/updated

Indirect updates No change to method, but refers to changed classes

▶ Generates old version stubs and default object transformers

²http://jclasslib.sourceforge.net

Object Transformers

- ▶ "Transform" objects to correspond to the new version
- ▶ A function specified as part of the new version of a class
- ► Accepts old object and new object as parameters
- VM runs a default transformer that copies old fields and initializes new ones to null

Outline

Introduction

Motivation

Solutions

Thesis

JVOLVE

Developer's view

Implementation

Experience

Conclusion

Slide

Update process



- ▶ Offline Update Preparation Tool (UPT)
- ▶ JVOLVE VM
 - Reach a safe point in the VM (thread synchronization)
 - ► Load new classes (classloader)
 - ► Transform objects to new definition (garbage collector)
 - Resume execution
 - Update active methods on stack (On-stack replacement)

Slide 2

Safe point for the update




- ▶ Update must be atomic
- Updates happen at "safe points" (VM yield points with restriction on what methods can be on stack)
- ▶ Uses a simple, non-deterministic timer retry
- ▶ Supported only on a single processor
- On-stack replacement support to allow more methods to remain on stack

Restricted methods



- ▶ Identified by UPT
 - ► All methods in updated classes
 - Methods with new implementations
 - ▶ Methods that refer to updated classes (have to be recompiled since field/method offsets might have changed)
- ▶ Identified by the VM
 - ▶ With inlining, transitive closure of callers of methods identified

VM Datastructures



Transforming objects



- ▶ Built on top of a semi-space copying collector
- ▶ Allocate additional space and run object transformers as part of the collector's visit

JVOLVE Garbage collector




- ▶ Identical to Semispace for "regular" objects
- ► For objects to be transformed
 - Copy the object to ToSpace (like Semispace)
 - ► Also, allocate an empty object in ToSpace for the new version
- ▶ Forwarding pointers point to the "new version" object
- ▶ No field can point to an "old version" object

Loading new classes




- ▶ Modifications to the classloader
- ▶ Involved a lot of engineering effort
- ► Correctly update metadata maintained by the VM
 - Classes
 - Type information blocks
 - Methods
 - ► Fields
 - Subclass, superclass relations
 - Innerclasses
 - Exceptions
 - Annotations

VM Datastructures




Semi-space copying collector



The heap is divided into two spaces. Only one space is used by the application. The garbage collector copies objects from FromSpace to ToSpace. GC copies A to ToSpace, leaves a forwarding pointer pointing to the new copy A'. GC scans A'. The obiects pointed to by A'

Forwarding pointer

JVOLVE garbage collector




v₁ object

The same heap as before. Objects to be transformed are highlighted. Copy A. Scan A'. Copy B and C. In addition an empty object C'v1 is allocated. A' points to this copy and not the old one. Scan B'. Scan C'. Scan D'

Scan E'. Scan F'.


GC is now complet

JVOLVE Garbage collector



Slide 33

Revisiting transformation functions



We have an ordering problem

(C v_0).field0.field0 might be uninitialized

Slide 34

Revisiting transformation functions



Solutions to the ordering problem

- Programmer can invoke a VM function that will transform objects on demand. Moves burden of safety to the programmer
- ► Insert read barrier code to perform this check when compiling the transformation function
- Perform some static analysis to determine an order to queue objects

Slide 35

Proposed work

- ▶ Improving flexibility: On-stack replacement (OSR) support
- ▶ Improving efficiency: Concurrent collector support

Slide 3

Extending On-stack replacement (OSR)



- ► Some updates cannot be performed because the VM does not reach a DSU safe point
- ► Jikes RVM employs OSR to promote long running methods for optimization
 - Extract compiler-independent state from an activation record
 - ► Generate a *specialized prologue* that sets up local variables
 - ▶ Jump to corresponding program counter in optimized code
- We can utilize this functionality taking into account old and new versions

Slide 37

OSR issues



- ▶ What types of updates can benefit from OSR?
- ▶ How does OSR know where to resume execution?
- What about new local variables and those that need to be transformed?
- OSR in Jikes RVM can only replace the topmost method on stack.
 - ▶ Implement "return barriers"
 - Overwrite return addresses and jump to VM code that will perform OSR for the current top method
 - Some methods might be long running and always belong to some old version

Slide 3

JVOLVE efficiency



- ▶ JVOLVE requires a stop-the-world full-heap GC
- ▶ Update time is dominated by GC time
- Real-time and highly available applications use a concurrent GC

JVOLVE with a concurrent collector



- ▶ Application and collector run concurrently
- ▶ Guard application from accessing an object of the old version
- Collectors already use read/write barriers to guard the application from disrupting the tricolor abstraction. Piggyback on these barriers for DSU
- ▶ What is the additional overhead?
- ► How flexible can object transformers be?

Slide 39

Slide 40

Outline

JVOLVE

Experience

Jetty webserver: Summary of changes


Ver.	#	# changed					
• • • •	classes	classes				fiel	ds
	added		add	del	chg	add	del
5.1.1	0	14	4	1	38/0	0	0
5.1.2	1	5	0	0	12/1	0	0
5.1.3	3	15	19	2	59/0	10	1
5.1.4	0	6	0	4	9/6	0	2
5.1.5	0	54	21	4	112/8	5	0
5.1.6	0	4	0	0	20/0	5	6
5.1.7	0	7	8	0	11/2	9	3
5.1.8	0	1	0	0	1/0	0	0
5.1.9	0	1	0	0	1/0	0	0
5.1.10	0	4	0	0	4/0	0	0

Overhead of DSU

- ▶ No discernible overhead for normal execution (before and after the update)
- ▶ Only effect on execution time is the update pause time
 - Comparable to GC pause time

Jetty webserver: Throughput measurements

Config.	Req. rate (/s)
5.1.5 (JVOLVE)	361.3 +/- 33.2
5.1.6 (Jikes RVM)	352.8 +/- 28.5
5.1.6 (JVOLVE)	366.2 +/- 26.0
5.1.6 (upd. idle)	357.4 +/- 34.9
5.1.6 (upd. midway)	357.5 +/- 41.6



Applications

- ► Jetty webserver
 - ▶ 11 versions, 5.1.0 through 5.1.10, 1.5 years
 - ▶ 45 KLOC
- ▶ JavaEmailServer
 - ▶ 10 versions, 1.2.1 through 1.4, 2 years
 - ▶ 4 KLOC
- ► CrossFTP server
 - ▶ 4 versions, 1.05 through 1.08, more than a year
 - ▶ 18 KLOC

Jetty webserver: Reaching a DSU safe-point

Upd.		Number of			allowed on stack, du	e to	Number of
to	Reached	methods at	class	method body	indirect method		restricted
ver.	safe point?	runtime	updates	updates	updates	Total	methods
5.1.1	always	1378 (376)	26/49	7/12	20/29	53/90 (17)	67
5.1.2	4/5 [†]	1374 (375)	25/25	3/5	35/43	63/73 (35)	67
5.1.3	0/5*	1374 (375)	326/382	4/6	42/45	370/433 (97)	373
5.1.4	always	1384 (374)	82/82	5/6	15/16	101/104 (24)	101
5.1.5	always	1380 (372)	14/80	39/60	13/15	62/155 (17)	62
5.1.6	3/5 [†]	1394 (378)	203/219	3/3	16/19	222/241 (40)	223
5.1.7	always	1394 (380)	186/187	1/2	53/69	239/258 (74)	243
5.1.8	always	1402 (379)	0/0	1/1	0/0	1/1(1)	1
5.1.9	always	1402 (379)	0/0	0/1	0/0	0/1(0)	0
5.1.10	always	1402 (379)	0/0	4/5	0/0	4/5 (2)	6

 † Restricted method HttpConnection.handleNext() was active *Restricted method ThreadedServer.acceptSocket() was (always) active

We propose to extend On-stack replacement to support changes to active methods on stack

Jetty webserver performance

- ▶ Used httperf to issue requests
- ► Create 100 new connections/second (saturation rate)
- ▶ 5 serial requests to 10KB file per connection
- ► Compared versions 5.1.5 and 5.1.6
- Experiments on Dual-P4, 3 GHz, 2GB RAM, running JikesRVM 2.9.1 on Linux 2.6.22.8

DSU pause times

- ▶ JVOLVE performs a GC to transform objects
- ► Pause time determined by
 - ► Heap size
 - # of objects transformed
- ▶ Simple microbenchmark varying the # of objects transformed

DSU pause times (microbenchmark)

# objects	Fraction of Change objects					
	0.00	0.50	1.00			
Total pause (ms)						
1000	381.21	391.21	400.77			
10000	382.62	461.82	544.46			
50000	382.73	779.67	2152.32			
100000	383.64	1276.26	7903.21			
Running transformation functions (ms)						
1000	0.22	4.62	8.89			
10000	0.22	44.05	85.39			
50000	0.22	215.94	1423.34			
100000	0.22	511.02	6809.91			
Garbage collection time (ms)						
1000	376.83	382.47	387.78			
10000	378.25	413.64	454.95			
50000	378.36	559.62	723.43			
100000	379.29	756.01	1089.16			

Conclusion

- ▶ JVOLVE, a Java VM with support for Dynamic Software Updating
- ▶ Most-featured, best-performing DSU system for Java
- Extends existing VM services
- ▶ Supports about two years worth of updates

Dynamic software updating in managed languages can be achieved in a safe, flexible and efficient manner by naturally extending existing VM services.

Thank you

References II

ksplice (2008).

Ksplice: Rebootless Linux kernel security updates. http://web.mit.edu/ksplice/

Makris, K. and Ryu, K. D. (2007)

Dynamic and adaptive updates of non-quiescent subsystems in commodity operating system kernels.

In Proc. EuroSys.

Malabarba, S., Pandey, R., Gragg, J., Barr, E., and Barnes, J. F. (2000).

Runtime Support for Type-Safe Dynamic Java Classes. In Proc. ECOOP.

Milazzo, M., Pappalardo, G., Tramontana, E., and Ursino, G.

Handling run-time updates in distributed applications. In Proc. SAC.

Outline

Conclusion

Schedule

- ▶ Proof-of-concept implementation that supports two years worth of updates
- ▶ On-stack replacement support (by September), a PLDI submission (November)
- ▶ DSU in a concurrent collector (January 2009 May 2009)
- ► More applications (Summer 2009)
- Dissertation (Fall 2009)

References I

Altekar, G., Bagrak, I., Burstein, P., and Schultz, A. (2005). OPUS: Online patches and updates for security. In Proc. USENIX Security.

Barr, M. and Eisenbach, S. (2003). Safe upgrading without restarting. In Proc. ICSM

Chen, H., Chen, R., Zhang, F., Zang, B., and Yew, P.-C.

Live updating operating systems using virtualization. In Proc. VEE

hen, H., Yu, J., Chen, R., Zang, B., and Yew, P.-C. (2007). POLUS: A POwerful Live Updating System. In Proc. ICSE.

References III

Neamtiu, I., Hicks, M., Stoyle, G., and Oriol, M. (2006). Practical dynamic software updating for C. In Proc. PLDI, pages 72-83.

Orso, A., Rao, A., and Harrold, M. J. (2002). A technique for dynamic updating of Java software. In Proc. ICSM.

Ritzau, T. and Andersson, J. (2000). Dynamic deployment of Java applications. In Java for Embedded Systems Workshop, London.

Soules, C., Appavoo, J., Hui, K., Silva, D. D., Ganger, G., Krieger, O., Stumm, M., Wisniewski, R., Auslander, M., Ostrowski, M., Rosenburg, B., and Xenidis, J. (2003). System support for online reconfiguration. In Proc. USENIX ATC.

Slide 55