Dynamic Industrial Semantic-Segmentation-Assisted SLAM:

Object-Centric Map Maintenance and Bounded Dynamic-Mask Frontend Evidence

Thick Manuscript Draft v2 - English
Updated: 2026-05-13 | Thick draft is the active manuscript target | Existing evidence only

Abstract

Long-term visual SLAM in industrial environments faces two related but distinct sources of dynamic-scene risk. First, semantic maps can be contaminated by objects that are real and repeatedly detected, such as forklifts or carts, but should not become durable static landmarks. Second, dynamic regions can in principle degrade visual odometry if frontend features are drawn from moving or transient objects. This manuscript treats the first problem as the primary contribution and the second as a bounded frontend smoke line. We formulate **session-level map admission control** as an explicit object-maintenance layer between open-vocabulary RGB-D perception and durable semantic map update. The layer converts segmentation outputs into observation, tracklet, map-object, and revision records, then admits objects only when multi-session presence, observation support, label consistency, static dominance, and frame coverage are all satisfied. On the TorWIC industrial dataset from POV-SLAM [6], the object-maintenance evidence ladder retains stable infrastructure across same-day Aisle (203 observations / 11 clusters / 5 retained), cross-day Aisle (240/10/5), cross-month Aisle (297/14/7), and a separate Hallway transfer branch (537/16/9). Forklift-like clusters are consistently rejected as dynamic contamination, with dynamic-like rejection shares from 50.0% to 71.4%.

We additionally consolidate the later dynamic-mask frontend evidence. A compact UNet trained on a P217 semantic-mask dataset (237 rows, 156/51/30 split, zero frame overlap, positive pixel rate 0.374176) reaches validation IoU/F1 0.671304/0.803329 and test IoU/F1 0.578580/0.733038 (P218), with held-out precision/recall/F1/IoU 0.556007/0.789669/0.604636/0.443210 (P219). Ground-truth dynamic-region ORB keypoints drop from 4795 to 2192 (54.2857% reduction, P220). Later P225-P228 experiments build a 60-frame Oct. 12, 2022 Aisle_CW raw-vs-masked sequence, reproduce a neutral DROID-SLAM baseline, and add a confidence/coverage-gated mask module. The gated module uses threshold 0.50, 1 px dilation, 128 px minimum component area, and max/target coverage 0.22/0.18; it gives mean coverage 14.127053%, raw/masked APE 0.088496/0.084705, raw/masked RPE 0.076145/0.076224, and ORB gated-region keypoints 8969 -> 5073. These results are a viable story seed for frontend masking and an ORB gated-region proxy. They do not support broader trajectory, navigation, independent-label, or learned map-admission conclusions. P195 remains BLOCKED.

Index Terms

SLAM, semantic segmentation, dynamic object filtering, object-level mapping, map maintenance, industrial robotics, open-vocabulary perception, dynamic masking, long-term autonomy

I. Introduction

I.A. Motivation

Simultaneous Localization and Mapping (SLAM) has matured from a geometric estimation problem into a long-term autonomy problem: maps must remain useful across repeated visits, changing lighting, layout edits, and moving industrial equipment [1]. In warehouses and logistics spaces, stable infrastructure such as barriers, work tables, racks, and pillars coexists with forklifts, carts, and human-operated equipment. A camera revisiting the same aisle may see the same class of forklift many times, sometimes in similar locations, but this does not make the forklift a stable map landmark.

Modern open-vocabulary perception makes this problem sharper. Grounding DINO [7], SAM2 [8], and OpenCLIP [9] can produce dense object candidates from RGB-D frames with little task-specific training. Without a separate map-admission policy, however, a semantic SLAM pipeline may treat "detected object" as equivalent to "map-worthy object." That shortcut creates forklift-shaped phantoms in the persistent map.

I.B. The Admission-Control Gap

Dynamic SLAM methods such as DynaSLAM [2] protect camera tracking and reconstruction by detecting and masking dynamic regions. Object-level SLAM and open-vocabulary mapping methods [3]-[5] attach semantic identity to mapped entities. These directions are complementary, but neither directly answers the durable-map question: after an object has been detected, segmented, and geometrically localized, should it be admitted to the long-term semantic map?

The core claim of this manuscript is that semantic map admission deserves its own auditable layer. Detection confidence, label purity, and geometric support are not enough. Forklifts can be detected confidently and repeatedly, yet still be inadmissible. A stable barrier may have lower per-frame confidence, yet become valuable through multi-session persistence.

I.C. Scope and Contributions

This thick draft is organized around two evidence lines:

1. **Primary contribution: object-centric map maintenance.** We define observation, tracklet, map-object, and revision records; introduce a transparent trust score; and use boolean admission criteria to retain stable infrastructure while rejecting dynamic contamination.
2. **Secondary evidence line: bounded dynamic-mask frontend.** We document P217-P228 segmentation and raw-vs-masked SLAM smoke evidence as a constrained frontend module story. It verifies that learned and gated masks can be generated and evaluated, but it does not yet support broad dynamic-SLAM or navigation claims.

The manuscript deliberately avoids claiming lifelong SLAM, dense dynamic reconstruction, independent dynamic segmentation labels, downstream

navigation effects, or learned persistent-map admission. The contribution is an auditable bridge from segmentation-assisted open-vocabulary perception to revisioned long-term object-map maintenance, with bounded frontend mask evidence as supporting context.

II. Related Work

II.A. Semantic SLAM and Object-Level Mapping

Cadena et al. [1] frame the evolution of SLAM from geometric estimation toward robust perception and long-term autonomy. CubeSLAM [3] demonstrates that object-level representations can support monocular SLAM by fitting cuboids to detected objects. OpenScene [4] and ConceptFusion [5] show that open-vocabulary scene representations can connect language-conditioned semantics with 3D mapping.

These works establish the feasibility of semantic and object-level mapping. Our focus is narrower and complementary: given object candidates from a perception frontend, determine which candidates deserve durable map slots. The question is not whether the object is detectable; it is whether it is persistent, stable, and semantically admissible.

II.B. Dynamic SLAM and Dynamic-Object Suppression

DynaSLAM [2] and related dynamic-SLAM systems suppress moving objects to protect tracking, mapping, and loop closure. Their typical evaluation target is trajectory or reconstruction quality under dynamic-scene disturbance. This paper uses that literature as motivation but changes the level of decision. We reject dynamic-like objects from the semantic map even when they are correctly detected and geometrically localized.

The dynamic-mask frontend section also connects to this literature, but conservatively. The P225-P228 DROID-SLAM runs are bounded smoke tests on a 60-frame sequence. They demonstrate executable raw-vs-masked plumbing and a useful ORB feature proxy; they do not establish general trajectory effects.

II.C. Long-Term Map Maintenance and Stable Landmark Reuse

Long-term SLAM requires deciding what to retain, update, forget, or revise [1]. POV-SLAM [6] provides object-aware SLAM benchmarks and the TorWIC industrial data used here. Our maintenance layer uses TorWIC revisits to aggregate session-level evidence and make explicit map-admission decisions. Unlike map pruning based only on memory, geometry, or information gain, the proposed admission layer records why each semantic object is retained or rejected.

II.D. Segmentation-Assisted and Open-Vocabulary Frontends

Grounding DINO [7], SAM2 [8], and OpenCLIP [9] are used as black-box observation generators for the object-maintenance line. The dynamic-mask line adds a small supervised segmentation route trained from semantic masks. These models provide object candidates and dynamic-region masks; they are not themselves claimed as the paper contribution.

III. Problem Formulation

Let a SLAM session S_k contain RGB-D frames $F_{k,1}, \ldots, F_{k,N_k}$. A perception frontend returns candidate object observations $o_{k,i}^{(j)}$, each with a frame id, session id, box, mask, canonical label, confidence, and state tag when available.

The **map-admission problem** is to construct a durable object map $\mathcal{M} = \{e_1,\ldots,e_M\}$ such that each admitted entity is:

Requirement	Meaning for industrial semantic SLAM
Stability	The object persists physically across revisits rather than appearing as a transient visit.
Consistency	Its label and spatial support remain coherent enough to serve as a semantic landmark.
Static dominance	Dynamic agents and mobile equipment are rejected from the persistent static map.
Auditability	

Requirement	Meaning for industrial semantic SLAM
	Every retain/reject decision can be traced to observations, sessions, and criteria.

This formulation differs from standard detection-to-map insertion. A detected forklift may be a correct perception result and a poor map entity. The proposed layer therefore inserts an explicit maintenance process between perception and durable map update:

`RGB-D frames -> object observations -> session tracklets -> cross-session map objects -> revisioned map update`

The dynamic-mask frontend problem is separate. There, the question is whether learned or gated dynamic masks can suppress dynamic-region visual features and be evaluated against raw inputs in a SLAM backend. The current evidence treats this as a frontend smoke and diagnostic line, not as proof of improved long-horizon SLAM.

IV. System Overview

The system has two cooperating but claim-separated paths.

IV.A. Object-Maintenance Path

The object-maintenance path processes open-vocabulary object observations into revisioned map entities. It is responsible for stable infrastructure retention, dynamic contamination rejection, and per-object provenance. It is the primary paper contribution.

IV.B. Dynamic-Mask Frontend Path

The dynamic-mask frontend path trains or applies a dynamic-region mask generator, post-processes the predicted mask, applies masked RGB inputs or feature-region analysis, and reports bounded raw-vs-masked evidence. This path currently supports a cautious story: learned masks can suppress ORB keypoints in predicted dynamic regions while keeping DROID-SLAM trajectory

smoke neutral. It does not yet admit learned objects to the persistent map and does not unblock P195, which remains BLOCKED.

IV.C. Evidence Separation

The two paths should not be merged into one overclaim. Object-maintenance results evaluate map admission. Dynamic-mask results evaluate frontend masking behavior and bounded backend execution. A future system could connect them, but this draft keeps the evidence boundaries explicit.

V. Object-Centric Maintenance

V.A. Open-Vocabulary Object Observation Extraction

For each RGB-D frame, the observation frontend produces object instances:

1. Grounding DINO [7] proposes boxes from industrial text prompts such as barrier, forklift, work table, warehouse rack, cart, pallet, and pillar.
2. SAM2 [8] generates instance masks from the proposed boxes.
3. OpenCLIP [9] reranks or resolves labels by comparing object crops against the target category vocabulary.
4. Each candidate becomes an `ObjectObservation` with frame id, session id, box, mask polygon, canonical label, confidence, timestamp, and state metadata.

The perception models are treated as replaceable components. The contribution begins when observations are aggregated, scored, and admitted or rejected.

V.B. Session-Level Tracklets

Within a session, observations with compatible label and spatial support are grouped into tracklets. A tracklet records:

Field	Purpose
Session id and temporal extent	Identify where and when the object was observed.

Field	Purpose
Observation count and frame count	Measure support and viewpoint diversity.
Label histogram	Preserve pre-canonicalization ambiguity.
State histogram	Separate static, candidate, and dynamic-agent evidence.
Dynamic ratio	Fraction of observations tagged as `dynamic_agent`.

Tracklets are the unit of within-session evidence. They are not durable map objects until cross-session evidence is sufficient.

V.C. Cross-Session MapObjects

Tracklets from different sessions are matched by canonical label consistency and spatial overlap, using a spatial IoU threshold of 0.1 in the current implementation. A `MapObject` aggregates session support, total observations, total tracklets, dominant label, label purity, dominant state, spatial stability, and per-session provenance.

This record is intentionally verbose. Reviewers and maintainers can inspect why a cluster exists, which frames support it, and which criterion failed if it is rejected.

V.D. Stability and Dynamicity Scoring

Each map object receives an auxiliary trust score:

$$
\tau(O) = \alpha s_{\text{session}}(O) + \beta s_{\text{support}}(O) - \gamma s_{\text{dynamic}}(O)
$$

where s_{session} normalizes session count, s_{support} normalizes observation support, and s_{dynamic} is the object dynamic ratio. The current weights are $\alpha=0.4$, $\beta=0.3$, and

(\gamma=0.5). The score is not an optimized estimator; it is a compact diagnostic that exposes the same intuition as the boolean gate.

V.E. Map Admission Criteria

A candidate is admitted only if all criteria pass:

Criterion	Condition	Rationale
Multi-session presence	sessions >= 2	Single-session objects may be transient.
Minimum support	observations >= 6	Low-support objects are unreliable.
Label consistency	label purity >= 0.70	Mixed labels indicate detector ambiguity.
Static dominance	dynamic ratio <= 0.20	Mobile agents should not enter the static map.
Minimum frames	frames >= 4	Objects seen from too few frames lack spatial support.

Objects that fail are not silently discarded. They are recorded with rejection reasons such as `dynamic_contamination`, `single_session_or_low_session_support`, `label_fragmentation`, and `low_support`.

V.F. Revisioned Map Updates

When a new session arrives, each tracklet either confirms an existing map object, contributes to a new candidate, or is rejected. The map is revisioned rather than rebuilt:

Outcome	Meaning
Confirm	A tracklet matches an admitted object and updates counters/statistics.
Add	A candidate accumulates enough evidence and passes all criteria.
Reject	A candidate fails one or more criteria and is stored with reasons.

This design is lightweight compared with full lifelong SLAM backends, but it provides the missing semantic admission-control layer.

VI. Dynamic-Mask Frontend

VI.A. Dataset and Compact Network Evidence (P217-P220)

The dynamic-mask branch begins with a P217 semantic-mask dataset:

Evidence	Value
Rows	237
Split	156 train / 51 validation / 30 test
Frame overlap	0 across splits
Positive pixel rate	0.374176

P218 trains a compact UNet-style dynamic-mask model on these semantic masks:

Split	IoU	F1
Validation	0.671304	0.803329
Test	0.578580	0.733038

P219 reports held-out precision/recall/F1/IoU as 0.556007/0.789669/0.604636/0.443210. P220 checks downstream feature relevance: ORB keypoints inside ground-truth dynamic regions drop from 4795 to 2192, a 54.2857% reduction. These facts support the feasibility of a learned dynamic-mask frontend, but the labels are derived from semantic-mask evidence and should not be described as independent dynamic segmentation ground truth.

VI.B. P225 Learned-Mask Sequence

P225 packages a 60-frame learned-mask sequence from the Oct. 12, 2022 Aisle_CW run, source indices 480-539. The original P218 checkpoint was unavailable, so the sequence uses a bounded retrained SmallUNet from the

P217 semantic masks. The artifact is trajectory-ready input only. It should not be described as a final model checkpoint recovery or a trajectory claim.

VI.C. P227 DROID Baseline Reproduction

P227 evaluates the P225 learned-mask package with DROID-SLAM [10]. The 60-frame raw/masked APE is 0.088504/0.084529, and raw/masked RPE is 0.076145/0.076226. ORB keypoints in the predicted dynamic region drop from 21030 to 18617. The status is neutral: the trajectory smoke reproduces, but the result is not an improvement claim.

VI.D. P228 Confidence/Coverage-Gated Module

P228 adds a small post-network gate:

Parameter	Value
Probability threshold	0.50
Dilation	1 px
Minimum connected component	128 px
Maximum coverage	0.22
Target coverage	0.18
Mean coverage on 60 frames	14.127053%

The 60-frame raw/masked APE is 0.088496/0.084705, and raw/masked RPE is 0.076145/0.076224. ORB keypoints in the gated predicted region drop from 8969 to 5073. Compared with P227, P228 is trajectory-neutral and provides a lower ORB gated-region proxy. This is the current viable story seed for the dynamic-mask frontend.

VII. Experimental Protocol

VII.A. Object-Maintenance Protocols

The object-maintenance evidence uses TorWIC industrial RGB-D revisits from the POV-SLAM release [6]. All object-maintenance protocols use the same

criteria: min_sessions=2, min_frames=4, min_support=6, max_dynamic_ratio=0.2, min_label_purity=0.7. No protocol-specific tuning is performed.

Protocol	Sessions	Observations	Candidate Clusters	Retained MapObjects	Role
Same-day Aisle	3 sessions from 2022-06-15	203	11	5	Primary ladder start
Cross-day Aisle	2022-06-15 + 2022-06-23	240	10	5	8-day revisit
Cross-month Aisle	June + Oct. 2022	297	14	7	4-month revisit
Hallway	first 8 executed sessions	537	16	9	Secondary scene transfer

The Aisle ladder is the main evidence sequence. Hallway is retained as a separate broader-validation branch rather than merged into a single aggregate score.

VII.B. Dynamic-Mask Protocols

The dynamic-mask line uses two protocol families:

Phase range	Protocol	Claim status
P135-P143	64-frame dynamic-mask backend diagnostics on available TorWIC Aisle windows	Negative-result boundary: available forklift masks occupy too little image area to affect trajectory.
P217-P220	Compact learned dynamic-mask dataset/model/ORB sanity	Feasibility evidence for semantic-mask-supervised dynamic masking.
P225-P228		Bounded frontend story seed.

Phase range	Protocol	Claim status
	60-frame Oct. 12, 2022 Aisle_CW learned-mask and gated-mask DROID smoke	

P225-P228 are included only as bounded frontend evidence, separate from the object-maintenance contribution.

VIII. Results

VIII.A. Primary Aisle Evidence Ladder

Protocol	Observations	Clusters	Retained	Main Retained Categories	Main Rejection Pattern
Same-day Aisle	203	11	5	2 work tables, 2 racks, 1 barrier	3 forklift-like dynamic, 3 single-session
Cross-day Aisle	240	10	5	Same stable categories	3 forklift-like dynamic, 2 single-session
Cross-month Aisle	297	14	7	Additional barriers/racks reach support	5 forklift-like dynamic, 2 single-session

The ladder shows that longer revisits increase the opportunity for stable infrastructure to accumulate support, while forklift-like objects remain rejected because their dominant state remains dynamic. The cross-month row adds two retained objects, illustrating the value of longer observation windows for map completeness.

VIII.B. Stable Subset Composition

Category	Same-day	Cross-day	Cross-month	Hallway
Barrier	1	1	3	1
Work table	2	2	2	3
Warehouse rack	2	2	2	4
Cart	0	0	0	1
Total retained	5	5	7	9
Forklift-like rejected	3/6	3/5	5/7	5/7

Barriers, work tables, and racks dominate the retained map. The Hallway cart is retained because it satisfies the static-dominance and multi-session criteria; the system does not reject the label “cart” by category alone.

VIII.C. Rejection Profile

Rejection Reason	Count	Interpretation
dynamic_contamination	16	Forklift-like clusters detected consistently but dominated by dynamic-agent state.
single_session_or_low_session_support	13	Insufficient revisit evidence for durable admission.
label_fragmentation	3	Mixed labels indicate detector ambiguity.
low_support	2	Too few observations for reliable map insertion.

Dynamic-like rejection shares are 50.0% for Same-day Aisle, 60.0% for Cross-day Aisle, 71.4% for Cross-month Aisle, and 71.4% for Hallway. The important point is not simply that forklifts are removed; it is that they are removed with explicit, auditable reasons while stable infrastructure is retained.

VIII.D. Admission Criteria Defense (P154-P157)

The admission policy is checked against ablations, baselines, and category-level profiles.

Test	Finding
Parameter ablation (P154)	min_sessions and min_frames are sensitive filters; max_dynamic_ratio is saturated by data bimodality because infrastructure has dynamic_ratio=0.00 and forklifts are >=0.83.
Baseline comparison (P155)	Naive-all-admit keeps 20 clusters and 4 forklifts (20.0% phantom risk). Purity/support heuristic keeps 19 clusters and still keeps 4 forklifts (21.1% phantom risk). Full policy keeps 5 clusters and 0 forklifts.
Map-composition visualization (P156)	Before/after map and lifecycle figures make the admission decision visually inspectable.
Per-category analysis (P157)	Forklift retention is 0/4; infrastructure retention is selective: yellow barriers 40%, work tables 50%, warehouse racks 33%.

The P155 B1 result is a useful warning: label purity and support alone cannot reject forklifts because forklifts can be consistently detected and supported. Static dominance and session evidence are necessary.

VIII.E. Dynamic-Mask Frontend Results (P217-P228)

Evidence	Main Result	Conservative Interpretation
P217 dataset	237 rows, 156/51/30 split, zero frame overlap, positive pixel rate 0.374176	Clean split for semantic-mask-supervised dynamic-mask training.
P218 compact UNet	val IoU/F1 0.671304/0.803329; test IoU/F1 0.578580/0.733038	Feasible compact frontend, not independent GT proof.

Evidence	Main Result	Conservative Interpretation
P219 held-out	precision/recall/F1/IoU 0.556007/0.789669/0.604636/0.443210	Recall-oriented behavior with moderate precision.
P220 ORB GT-region proxy	4795 -> 2192 keypoints, 54.2857% reduction	Dynamic-region feature suppression is plausible.
P225 sequence	60 frames, Oct. 12 2022 Aisle_CW indices 480-539; bounded retrained SmallUNet	Trajectory-ready input only.
P227 baseline	APE 0.088504 -> 0.084529; RPE 0.076145 -> 0.076226; ORB predicted-region 21030 -> 18617	Neutral DROID baseline reproduction.
P228 gated module	APE 0.088496 -> 0.084705; RPE 0.076145 -> 0.076224; ORB gated-region 8969 -> 5073; mean coverage 14.127053%	Viable frontend story seed; lower gated-region ORB proxy, trajectory-neutral.

The dynamic-mask result should be phrased as follows: P228 keeps a bounded DROID-SLAM trajectory smoke effectively neutral relative to P227 while reducing the ORB gated-region proxy.

IX. Failure and Boundary Analysis

IX.A. Why Earlier Dynamic-SLAM Runs Were Trajectory-Neutral

The P135-P143 diagnostic chain shows that available TorWIC forklift masks are too small in the tested Aisle windows to measurably affect DROID-SLAM trajectory accuracy. In the 64-frame chain, forklift coverage remains below 1.39% per frame, and all raw-vs-masked configurations remain below meaningful trajectory-effect thresholds. DROID-SLAM’s internal flow-consistency filtering likely suppresses many small dynamic outliers already.

This is a negative result, not a pipeline failure. It defines a boundary: trajectory-improvement claims require data where dynamic objects occupy a

larger image fraction, plausibly above 5%, or an evaluation target other than short-window APE/RPE.

IX.B. P225-P228 Boundary

P225-P228 improve the frontend story but do not erase the boundary:

Boundary	Status
Broad dynamic-SLAM evaluation	Not claimed.
Navigation or planning effects	Not claimed.
Independent dynamic segmentation ground truth	Not claimed.
Learned persistent-map admission	Not claimed.
P195	Still BLOCKED.
60-frame DROID smoke	Executable and trajectory-neutral.
ORB predicted/gated-region suppression	Supported as a proxy.

The correct claim is a bounded frontend smoke: learned and gated masks can be generated for a fixed industrial sequence, evaluated through DROID-SLAM, and used to suppress ORB features in predicted dynamic regions.

IX.C. Object-Maintenance Failure Modes

The object-maintenance layer is intentionally conservative. False negatives can occur when a stable object appears in only one session or too few frames. Label fragmentation can reject a real object if open-vocabulary labels are inconsistent. Spatial-IoU association may fail under strong viewpoint changes or object relocation. These are acceptable first-draft limitations because rejected candidates remain auditable and can be revisited when more evidence arrives.

X. Discussion

X.A. Why Not Confidence-Only Admission?

Confidence-only admission confuses detector certainty with map worthiness. A forklift can be confidently detected and still be a poor static landmark. The P155 purity/support baseline demonstrates this failure mode: it admits all 4 forklift clusters. The full policy needs dynamic ratio and multi-session criteria to separate stable infrastructure from mobile agents.

X.B. Why Keep Object Maintenance and Dynamic Masking Separate?

Object maintenance and dynamic masking operate at different levels. Map admission decides which semantic entities persist in a durable map. Dynamic masking decides which pixels or features should influence frontend/backend estimation. A future integrated system may use learned dynamic masks as one signal in map admission, but the current evidence does not justify that integration claim.

X.C. Lightweight Design Trade-Off

The maintenance layer is simple: thresholded criteria, interpretable counters, and revision records. That simplicity makes the method easy to audit and reproduce, but it also limits robustness under severe viewpoint change, partial observation, or category ambiguity. A learned association or admission policy could improve recall, but it would need the same or better auditability to be acceptable for long-term map maintenance.

X.D. Aisle and Hallway Roles

The Aisle ladder is the main protocol because it gives same-day, cross-day, and cross-month structure. Hallway is a separate transfer branch. Keeping them separate avoids hiding scene-specific behavior behind a single aggregate number.

XI. Limitations

1. **Not a complete lifelong SLAM backend.** The object-maintenance layer does not perform loop closure, pose optimization, map compression, or full lifelong map management.
2. **No downstream task evaluation.** The evidence does not measure navigation success, relocalization improvement, planning quality, or task completion.
3. **Rule-based association can fail.** Spatial-IoU and label matching are transparent but may be brittle under major viewpoint shifts, occlusion, and object relocation.
4. **Open-vocabulary perception remains a dependency.** Grounding DINO [7], SAM2 [8], and OpenCLIP [9] are black-box components whose errors propagate into observation records.
5. **Dynamic-mask supervision is not independent GT.** P217-P220 use semantic-mask-supervised dynamic labels; these support a frontend route but not independent dynamic segmentation validation.
6. **P225-P228 are bounded smoke tests.** The 60-frame Oct. 12, 2022 Aisle_CW evidence is a constrained frontend check, and its DROID trajectory metrics are neutral.
7. **P195 remains BLOCKED.** The current work does not solve learned persistent-map admission.
8. **Venue formatting is deferred.** Reference punctuation, repository placement, and final citation style should be finalized after target venue selection.

XII. Conclusion

This manuscript presents a thick, paper-shaped account of dynamic industrial semantic-segmentation-assisted SLAM centered on object-centric map maintenance. The primary contribution is a session-level admission-control layer that turns open-vocabulary RGB-D observations into auditable map-object decisions. On TorWIC, the evidence ladder retains stable infrastructure across same-day, cross-day, cross-month, and Hallway protocols while consistently rejecting forklift-like dynamic contamination.

The manuscript also integrates the newer P217-P228 dynamic-mask frontend evidence. Compact learned masks, a 60-frame learned-mask package, DROID-SLAM raw-vs-masked reproduction, and the P228 confidence/coverage gate provide a bounded story seed: ORB counts decrease inside predicted and gated dynamic regions while trajectory smoke remains neutral. This strengthens the paper as a dynamic-scene SLAM manuscript without crossing the evidence boundary into unsupported broad-evaluation, navigation, independent-GT, or learned map-admission claims.

The resulting claim is conservative but useful: semantic map maintenance should be an explicit, auditable layer between perception and long-term maps, and dynamic-mask frontends can be evaluated as bounded supporting modules until stronger independent labels and larger dynamic-scene evidence are available.

References

[1] C. Cadena, L. Carlone, H. Carrillo, Y. Latif, D. Scaramuzza, J. Neira, I. Reid, and J. J. Leonard, "Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age," IEEE Trans. Robot., vol. 32, no. 6, pp. 1309-1332, 2016. DOI: 10.1109/TRO.2016.2624754.

[2] B. Bescos, J. M. Facil, J. Civera, and J. Neira, "DynaSLAM: Tracking, mapping, and inpainting in dynamic scenes," IEEE Robot. Autom. Lett., vol. 3, no. 4, pp. 4076-4083, 2018. DOI: 10.1109/LRA.2018.2860039.

[3] S. Yang and S. Scherer, "CubeSLAM: Monocular 3-D object SLAM," IEEE Trans. Robot., vol. 35, no. 4, pp. 925-938, 2019. DOI: 10.1109/TRO.2019.2909168.

[4] S. Peng, K. Genova, C. Jiang, A. Tagliasacchi, M. Pollefeys, and T. Funkhouser, "OpenScene: 3D scene understanding with open vocabularies," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2023, pp. 815-824. DOI: 10.1109/CVPR52729.2023.00085.

[5] K. M. Jatavallabhula, A. Kuwajerwala, Q. Gu, M. Omama, T. Chen, S. Li, G. Iyer, S. Saryazdi, N. Keetha, A. Tewari, J. B. Tenenbaum, C. M. de Melo, M. Krishna, L. Paull, F. Shkurti, and A. Torralba, "ConceptFusion: Open-set

multimodal 3D mapping," in Proc. Robot.: Sci. Syst. (RSS), 2023. DOI: 10.15607/RSS.2023.XIX.066.

[6] D. Barath, B. Bescos, D. Mishkin, D. Rozumnyi, and J. Matas, "POV-SLAM: Probabilistic object-aware SLAM with semantic mapping benchmarks," in Proc. Robot.: Sci. Syst. (RSS), 2023. DOI: 10.15607/RSS.2023.XIX.069. TorWICDataset repository: github.com/dbarath/POV-SLAM.

[7] S. Liu, Z. Zeng, T. Ren, F. Li, H. Zhang, J. Yang, Q. Jiang, C. Li, J. Yang, H. Su, J. Zhu, and L. Zhang, "Grounding DINO: Marrying DINO with grounded pre-training for open-set object detection," in Proc. Eur. Conf. Comput. Vis. (ECCV), 2024. arXiv: 2303.05499.

[8] N. Ravi, V. Gabeur, Y.-T. Hu, R. Hu, C. Ryali, T. Ma, H. Khedr, R. Radle, C. Rolland, L. Gustafson, E. Mintun, J. Pan, K. V. Alwala, N. Carion, C.-Y. Wu, R. Girshick, P. Dollar, and C. Feichtenhofer, "SAM 2: Segment anything in images and videos," arXiv:2408.00714, 2024.

[9] M. Cherti, R. Beaumont, R. Wightman, M. Wortsman, G. Ilharco, C. Gordon, C. Schuhmann, L. Schmidt, and J. Jitsev, "Reproducible scaling laws for contrastive language-image learning," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2023, pp. 2818-2829. arXiv: 2212.07143.

[10] Z. Teed and J. Deng, "DROID-SLAM: Deep visual SLAM for monocular, stereo, and RGB-D cameras," in Proc. Adv. Neural Inf. Process. Syst. (NeurIPS), vol. 34, 2021. arXiv: 2108.10869.

Software. M. Grupp, "evo: Python package for the evaluation of odometry and SLAM," 2017. [Online]. Available: https://github.com/MichaelGrupp/evo

---

Table Captions and Evidence Notes

Table 1. Object-maintenance protocol ladder. Same-day Aisle (203/11/5), Cross-day Aisle (240/10/5), Cross-month Aisle (297/14/7), and Hallway transfer (537/16/9).

Table 2. Admission criteria. Multi-session presence, minimum support, label consistency, static dominance, and minimum frames.

Table 3. Rejection taxonomy. dynamic_contamination 16, single_session_or_low_session_support 13, label_fragmentation 3, low_support 2.

Table 4. Admission-defense summary. P154 ablation, P155 baseline comparison, P156 visualization, and P157 per-category retention/rejection.

Table 5. Dynamic-mask frontend evidence. P217-P228 dataset, compact model, ORB proxy, learned-mask sequence, DROID baseline, and confidence/coverage gate.

Table 6. P225-P228 bounded DROID smoke. P227 learned-mask baseline and P228 confidence/coverage-gated module. Report as neutral trajectory evidence with ORB predicted/gated-region suppression.

Figure Captions

Fig. 1. Semantic-segmentation-assisted SLAM maintenance pipeline. [File: `paper/figures/torwic_paper_result_overview.png`]

Fig. 2. Primary Aisle evidence ladder: same-day (203/11/5), cross-day (240/10/5), cross-month (297/14/7). [File: `paper/figures/torwic_real_session_overlays.png`]

Fig. 3. Map-admission selectivity across retained and rejected objects. [File: `paper/figures/torwic_hallway_composite.png`]

Fig. 4. Bounded DROID-SLAM 64-frame raw-vs-masked backend diagnostic. [File: `paper/figures/torwic_dynamic_slam_backend_p134.png`]

Fig. 5. Dynamic-mask coverage diagnostic for existing semantic frontend masks. [File: `paper/figures/torwic_dynamic_mask_coverage_p135.png`]

Fig. 6. Temporal-mask propagation stress test. [File: `paper/figures/torwic_dynamic_mask_temporal_stress_p136.png`]

Fig. 7. Optical-flow mask propagation stress test. [File: `paper/figures/torwic_dynamic_mask_flow_stress_p137.png`]

Fig. 8. First-eight real semantic mask backend diagnostic. [File: `paper/figures/torwic_dynamic_mask_first8_real_p138.png`]

Fig. 9. First-sixteen real semantic mask backend diagnostic. [File: `paper/figures/torwic_dynamic_mask_first16_real_p139.png`]

Fig. 10. First-thirty-two real semantic mask backend diagnostic. [File: `paper/figures/torwic_dynamic_mask_first32_real_p140.png`]

Fig. 11. Before/after map composition: B0 naive-all-admit vs B2 richer admission policy. [File: `paper/figures/torwic_before_after_map_composition_p156.png`]

Fig. 12. Object lifecycle: stable barrier admission vs forklift rejection. [File: `paper/figures/torwic_object_lifecycle_p156.png`]

Fig. 13. Map-admission decision space: dynamic ratio vs session count. [File: `paper/figures/torwic_admission_decision_space_p156.png`]

Fig. 14. Per-category retention/rejection bar chart. [File: `paper/figures/torwic_per_category_retention_p157.png`]

Fig. 15. Rejection reason distribution. [File: `paper/figures/torwic_rejection_reason_distribution_p157.png`]

Fig. 16. Per-category by rejection-reason heatmap. [File: `paper/figures/torwic_rejection_reason_heatmap_p157.png`]

Appendix: Archived Evidence Pointers

- Object-maintenance closure and package indexes remain in `outputs/` and the P154-P157 export/evidence chain.
- P225 package: `paper/export/temporal_masked_sequence_p225.md`.
- P227 baseline reproduction: `paper/export/p225_baseline_reproduction_p227.md`.
- P228 module: `paper/export/confidence_gated_mask_module_p228.md`.
- P228 story table: `paper/export/p228_paper_story_results.md`.
- Current reorganization summary: `paper/export/thick_manuscript_reorganization_p229.md`.