Dynamic Industrial Semantic-Segmentation-Assisted SLAM:

Object-Centric Map Maintenance via Open-Vocabulary Object-Instance Filtering

Thick Manuscript Draft v1 - English
Generated: 2026-05-09 | Existing-data-only | No new experiments

Abstract

Long-term visual SLAM in industrial environments faces a principled bottleneck that neither geometric SLAM nor object-level semantic mapping directly addresses: which detected objects deserve durable map slots, and which should be rejected as transient or dynamic contamination? Open-vocabulary detection pipelines produce candidate object instances from every frame, but naively inserting all geometrically consistent detections contaminates the map with forklifts, carts, and single-visit phantoms - a dynamic contamination problem recognized in dynamic SLAM literature [2] but not resolved at the semantic map-admission level. This paper formulates **session-level map admission control** as a distinct methodological contribution: an explicit object-maintenance layer between perception and the map that transforms open-vocabulary RGB-D segmentation outputs into observation, tracklet, map-object, and revision layers, then applies auditable boolean criteria (multi-session presence, minimum observation support, label consistency, static dominance) to admit stable semantic landmarks and reject dynamic contamination. We evaluate the framework on the TorWIC dataset (POV-SLAM provenance [6]), reporting a reproducible evidence ladder across same-day (203 observations / 11 candidate clusters → 5 retained), cross-day (240/10→5), and cross-month (297/14→7) richer Aisle protocols (§ VII.A), with a separate Hallway scene-transfer branch (537/16→9, § VII.C). Forklift-like evidence is consistently rejected as dynamic contamination (50.0%-71.4% rejection share across all four protocols, § VII.D). We validate the admission

policy itself through parameter ablation (§ VII.G), showing that min_sessions and min_frames are sensitive filters while max_dynamic_ratio is naturally saturated by data bimodality (infrastructure at 0.00, forklifts at ⩾0.83). Baseline comparison against naive-all-admit and purity/support-heuristic strategies (§ VII.G) demonstrates that simpler heuristics cannot reject forklifts (phantom risk 20.0%→0.0% with the full policy), while per-category retention/rejection analysis (§ VII.G, P157) confirms forklift rejection is universal and infrastructure retention is selective but interpretable. The contribution is bounded: not a lifelong SLAM benchmark, not dense dynamic reconstruction, and not a downstream navigation-gain claim, but a principled, auditable, and evidence-backed session-level map admission control methodology [1][2][6].

Index Terms

SLAM, semantic segmentation, dynamic object filtering, object-level mapping, map maintenance, industrial robotics, open-vocabulary perception, long-term autonomy

---

I. Introduction

I.A. Motivation

Simultaneous Localization and Mapping (SLAM) has matured to the point where short-horizon geometric maps can be reliably constructed in real time [1]. The next frontier - long-term SLAM and map reuse across weeks or months - shifts the burden from geometric consistency to semantic persistence: which detected objects should enter the map, and which should be discarded as transient or dynamic contamination?

Industrial environments amplify this question. Warehouses and logistics centers contain stable infrastructure (barriers, work tables, racks, pillars) alongside mobile agents (forklifts, carts, human operators). An open-vocabulary detector such as Grounding DINO [7] combined with a segmenter such as SAM2 [8] can propose bounding boxes and masks for dozens of object instances per frame, but without an explicit admission-control policy, the map

quickly accumulates forklift-shaped phantom objects that are re-detected in revisits but should never have been admitted in the first place.

I.B. The Admission-Control Gap

Existing dynamic SLAM pipelines [2] are designed to mask, track, and remove dynamic pixels and objects from the geometric reconstruction, ensuring that visual odometry and loop closure operate on clean static geometry. Object-level SLAM approaches [3]-[5] assign semantic identities to geometric entities and can reason about object categories. However, neither paradigm directly addresses the question of which detected objects deserve a durable slot in the semantic map: detection output is treated as fact once geometric consistency is confirmed, but in practice, repeated detections of forklifts in roughly the same location can appear geometrically consistent without being semantically admissible.

Our key observation is that the pipeline from open-vocabulary detection to durable semantic landmarks requires an explicit maintenance layer - an admission-control policy that scores each candidate object on stability (how long it persists across sessions), consistency (label agreement and spatial coherence), and dynamicity (whether its dominant state is dynamic_agent). This paper describes such a layer.

I.C. Scope and Contribution Boundaries

We deliberately limit the contribution to stable-object retention, dynamic-contamination rejection, and map-admission selectivity in industrial revisits. We do not claim to solve lifelong SLAM, dense dynamic reconstruction, or downstream navigation gain. The paper offers an auditable bridge from perception to map maintenance, with reproducible evidence on the TorWIC dataset.

II. Contributions

We position the paper as a **principled session-level map admission control methodology** for long-term industrial SLAM, supported by the following contributions:

1. **An explicit object-maintenance architecture** (§ V) with observation (§ V.A), tracklet (§ V.B), map-object (§ V.C), and revision (§ V.F) layers that separates detection from map admission. Each layer carries frame-level provenance, stability counters, and dynamicity scores, providing full auditability per candidate object.

2. **A transparent trust-score formulation** (§ V.D) for map admission that combines session-level stability, cross-session persistence, and dominant-state dynamicity. The score is intentionally simple and auditable rather than presented as an optimal estimator, enabling per-component inspection (Appendix Y).

3. **A reproducible evidence ladder** (§ VII.A-VII.C) on the TorWIC dataset [6] across three Aisle protocols (same-day, cross-day, cross-month) and a Hallway scene-transfer branch, all reported with invariant selection criteria (§ VI.C) and cluster-ID-level traceability.

4. **A rejection-profile analysis** (§ VII.D) showing that forklift-like dynamic contamination is the primary rejection driver (50.0%-71.4% share) across all four protocols, with insufficient session coverage and label purity as secondary/tertiary drivers.

5. **Admission-criteria defense through parameter ablation and baseline comparison** (§ VII.G): (i) parameter sweep across min_sessions$\in\{1,2,3\}$, min_frames$\in\{2,4,6\}$, and max_dynamic_ratio$\in\{0.10,0.20,0.30\}$ demonstrates that the policy exploits natural data bimodality rather than hyperparameter tuning - max_dynamic_ratio is insensitive across [0.01,0.82] because infrastructure (dynamic_ratio=0.00) and forklifts ($\geqslant$0.83) are cleanly separated; (ii) comparison against naive-all-admit and purity/support-heuristic baselines shows that cross-session evidence (session_count, dynamic_ratio) provides indispensable discrimination - purity/support alone fails to reject any forklift (phantom risk 21.1% vs 0.0% with the full policy).

6. **Per-category retention and rejection analysis** (§ VII.G, P157): forklift rejection is universal (0/4 retained, all rejected for dynamic_contamination), while infrastructure retention is selective and interpretable - yellow barriers 40% retention (single-session coverage is the main barrier rejector), work tables 50% retention (frame undersampling is the main table rejector), warehouse racks 33% retention (label fragmentation and single-session coverage are the main rack rejectors). Multi-reason rejection is common but criteria are complementary rather than redundant.

7. **Map-composition visualization** (§ VII.G, P156): before/after maps, object lifecycle plots, and admission-decision-space diagrams that make the admission-control effect visually inspectable.

8. **An open-source release** of the object-maintenance layer with TorWIC protocol configuration (§ VI) and invariant selection criteria (§ V.E), supporting auditable reproduction.

III. Related Work

III.A. Semantic SLAM and Object-Level Mapping

Cadena et al. [1] survey the SLAM landscape from geometric to semantic, establishing that map reuse requires semantic understanding. CubeSLAM [3] introduced object-level representations by fitting cuboids to detected objects in monocular SLAM, demonstrating that object identity improves loop closure and relocalization. OpenScene [4] extended open-vocabulary semantic mapping to 3D scenes, showing that language-conditioned feature fields can carry concept-level semantics. ConceptFusion [5] further developed the open-vocabulary 3D mapping paradigm by fusing multiple foundation model outputs into a shared 3D representation.

Our relationship: These works establish that object-level and open-vocabulary semantic mapping is feasible. We build on this tradition but focus on a complementary problem: once objects are detected and semantically labeled, which ones deserve permanent map representation? The answer is not simply "all objects with high detection confidence" - a forklift detected

with 0.95 confidence across five sessions is still a forklift, and it should not enter the static map.

III.B. Dynamic SLAM and Dynamic-Object Suppression

DynaSLAM [2] demonstrated that masking dynamic objects (people, vehicles) from geometric reconstruction improves camera tracking accuracy in dynamic scenes. The key insight - that dynamic pixels degrade visual odometry - has been extended by numerous follow-up works using semantic segmentation, optical flow, and multi-view geometry to identify and suppress dynamic regions.

Our relationship: Dynamic SLAM removes dynamic content to protect geometric reconstruction. We complement this by rejecting dynamic-like objects from the semantic map layer even when they are geometrically well-localized. The geometric reconstruction may correctly estimate the 3D position of a forklift; our maintenance layer independently decides that the forklift should not become a durable map entity.

III.C. Long-Term Map Maintenance and Stable Landmark Reuse

Long-term SLAM has been studied primarily in the context of lifelong mapping and map summarization [1]. The problem of which landmarks to keep across sessions has been addressed through information-theoretic pruning, memory-budget constraints, and change detection. POV-SLAM [6] introduced object-aware semantic SLAM and released the TorWIC dataset, which provides RGB-D revisits of industrial environments with ground-truth object annotations.

Our relationship: We use TorWIC/POV-SLAM [6] as the data provenance anchor. Our maintenance layer operates on top of any detection pipeline and uses session-level evidence aggregation rather than geometric heuristics to decide map admission. The framework is complementary to existing long-term mapping systems - it can be inserted as a filter between perception and the map backend.

III.D. Segmentation-Assisted Filtering and Open-Vocabulary 3D Mapping

Recent advances in foundation models - Grounding DINO [7] for open-vocabulary detection, SAM2 [8] for mask generation, and OpenCLIP [9] for label reranking - have made it practical to extract semantically labeled object instances from RGB-D frames without task-specific training. These models are used as back-end components in our framework but are not the subject of our contribution. The maintenance layer is agnostic to the specific detection/segmentation pipeline.

IV. Problem Formulation

IV.A. Formal Statement

Let a SLAM session S_k produce a sequence of RGB-D frames $\{F_{k,1}, \ldots, F_{k,N_k}\}$. For each frame, an open-vocabulary detection-segmentation-labeling pipeline outputs a set of candidate object instances $\{o_{k,i}^{(j)}\}$, each with a bounding box, a segmentation mask, a canonical label, and a confidence score.

The **map-admission problem** (motivated by the dynamic-contamination gap identified in § I.B and [2]) is: given candidate observations across one or more sessions, produce a map $\mathcal{M}$ consisting of durable object entities $\{e_1, \ldots, e_M\}$ such that:

1. **Stability:** Each e_m corresponds to a physically persistent object in the environment (not a transient or dynamic agent).
2. **Consistency:** The label and spatial extent of e_m are consistent across revisits.
3. **Completeness:** No persistent object that appears across multiple sessions with sufficient evidence is omitted.
4. **Admission control:** Dynamic agents (forklifts, carts) and transient objects (single-session detections with low support) are explicitly rejected rather than silently suppressed (cf. [2], which masks dynamic

pixels for geometric reconstruction but does not reject dynamic objects at the map-admission level).

IV.B. Key Distinction from Standard SLAM

Standard SLAM treats map updates as: detection → geometric verification → map insertion [1]. Our framework inserts an intermediate maintenance layer (cf. object-level SLAM architectures [3][4][5] which assign semantics but lack explicit admission control): detection → observation (§ V.A) → tracklet within-session (§ V.B) → map-object cross-session (§ V.C) → revisioned map update (§ V.F). Each transition applies criteria that filter, aggregate, and score candidate evidence before map insertion.

V. Method

Fig. 1 illustrates the full pipeline: open-vocabulary RGB-D masks flow through observation, tracklet, map-object, and revision layers rather than being inserted directly into the map.

V.A. Open-Vocabulary Object Observation Extraction

For each RGB-D frame, we apply an open-vocabulary detection pipeline (inspired by the open-vocabulary 3D mapping paradigm [4][5] but used here purely as a front-end observation generator):

1. **Grounding DINO [7]** proposes bounding boxes from text prompts corresponding to common industrial object categories (barrier, forklift, work table, warehouse rack, cart, pallet, pillar).
2. **SAM2 [8]** generates instance masks from the proposed boxes.
3. **OpenCLIP [9]** reranks and resolves label assignments by comparing mask crops to text embeddings of the target category set.
4. Each resulting candidate becomes an **ObjectObservation** with frame ID, session ID, bounding box, mask polygon, canonical label, confidence score, and detection timestamp.

The detection pipeline is used as a black-box front end; our contribution begins at the observation layer (§ I.C).

V.B. Session-Level Tracklet Records

Within a single session (S_k), observations with the same canonical label and overlapping spatial extent are grouped into **tracklets**. A tracklet (T) aggregates:

- **Session ID** and temporal extent (first/last frame)
- **Observation count** and spatial extent statistics
- **Label histogram** (raw detector outputs before canonicalization)
- **State histogram** (detector-reported state: static, candidate, dynamic_agent)
- **Dynamic ratio** (\rho_T) = fraction of observations with state = `dynamic_agent`

Tracklets are the within-session evidence unit. Multiple tracklets with the same label from different sessions are candidates for cross-session merging.

V.C. Cross-Session MapObjects

Tracklets from different sessions are matched by spatial overlap and canonical label consistency to form **MapObjects**. A MapObject (O) aggregates:

- **Session support:** number of distinct sessions in which the object appears
- **Total observations** and total tracklets
- **Dominant label** and **label purity** (fraction of observations with the dominant label)
- **Dominant state** (most frequent state across all observations)
- **Spatial stability:** variance of mean center across sessions
- **Meta-evidence:** session lists, frame counts, support counts

The cross-session matching uses a spatial IoU threshold (0.1) with canonical label agreement. Objects that appear in only one session with low support are candidates for rejection.

V.D. Stability and Dynamicity Scoring

Each MapObject (O) receives a **trust score** (\tau(O)) defined as (following the stable-landmark selection philosophy of long-term SLAM [1][6]):

$$
\tau(O) = \alpha \cdot s_{\text{session}}(O) + \beta \cdot s_{\text{support}}(O) - \gamma \cdot s_{\text{dynamic}}(O)
$$

where:
- $s_{\text{session}}(O)$ = normalized session count (min 0, max 1 at ⩾3 sessions)
- $s_{\text{support}}(O)$ = normalized observation support (min 0, max 1 at ⩾20 observations)
- $s_{\text{dynamic}}(O)$ = dynamic ratio ρ_O (0 for fully static, 1 for fully dynamic)
- $\alpha = 0.4$, $\beta = 0.3$, $\gamma = 0.5$ (configurable, not optimized; see § VI.C for protocol-wide consistency)

This score is **not** presented as an optimal estimator. It is a transparent, auditable formulation designed to be inspectable: each component has a clear semantic interpretation, and the weights can be adjusted per deployment domain. The score is used as an auxiliary signal; the primary map-admission gate is the boolean criteria set in § V.E. In practice, across the TorWIC protocols reported in § VII, all retained MapObjects satisfy $\tau(O) \geq 0.4$ and all rejected objects fall below $\tau(O) \leq 0.15$ (see Appendix Y for per-cluster scores).

V.E. Map Admission Criteria

A MapObject O is admitted to the durable map $\mathcal{M}$ if and only if it satisfies **all** of the following criteria:

Criterion	Condition	Rationale
Multi-session presence	sessions ⩾ 2	Single-session observations may be transient
Minimum support	observations ⩾ 6	Low-support objects are likely spurious
Label consistency	label purity ⩾ 0.7	Mixed-label objects indicate detector ambiguity
Static dominance	dynamic ratio ⩽ 0.2	Dynamic agents should not enter the map

Criterion	Condition	Rationale
Minimum frames	frames $\geqslant 4$	Objects seen in only 1-2 frames are likely detection noise

These criteria are the primary admission-control mechanism. Objects that fail any criterion are recorded as **rejected** with specific rejection reasons, providing auditable traceability.

V.F. Revisioned Map Updates

When a new session revisits the environment, its tracklets are matched against existing MapObjects in (\mathcal{M}). Three outcomes are possible:

1. **Confirm:** A tracklet matches an existing MapObject within spatial and label thresholds → increment session/support/observation counters, update statistics.
2. **Add:** A tracklet forms a new candidate MapObject that passes admission criteria after sufficient session evidence → admit.
3. **Reject:** A tracklet does not match any existing object and fails admission criteria → record as rejected with reasons.

The map (\mathcal{M}) is thus **revisioned** rather than rebuilt: stable objects accumulate confirming evidence across revisits (analogous to the long-term map maintenance paradigm [1]), while new candidates are admitted only after meeting the multi-session threshold (§ V.E).

VI. Experimental Protocol

VI.A. Dataset and Provenance

We use the **TorWIC dataset** from the POV-SLAM release [6], which provides RGB-D sequences of industrial warehouse aisles with revisits under varying conditions. The dataset provenance is explicitly tied to POV-SLAM’s object-aware semantic SLAM evaluation setup.

VI.B. Protocol Design

We define four protocols spanning increasing temporal gaps and a scene-transfer branch:

Primary Aisle Ladder (TorWIC TorWIC_s1_d45)

Protocol	Sessions	Observations	Candidate Clusters	Retained MapObjects	Key Challenge
Same-day	3 (2022-06-15, runs 1-3)	203	11	5	Same-day viewpoint variation
Cross-day	4 (2022-06-15 + 2022-06-23)	240	10	5	8-day gap, lighting change
Cross-month	4 (2022-06-15, 2022-06-23, 2022-10-12)	297	14	7	4-month gap, seasonal variation

The primary ladder uses a "richer" bundle configuration covering a specific aisle section. Each protocol processes all RGB-D frames in the bundle, extracts observations via Grounding DINO + SAM2 + OpenCLIP, forms tracklets, merges into MapObjects, and applies admission criteria.

Hallway Broader-Validation Branch

Protocol	Sessions	Observations	Candidate Clusters	Retained MapObjects	Key Feature
Hallway	10 (first 8 executed)	537	16	9	Scene transfer to warehouse hallway

The Hallway branch uses a different scene (warehouse hallway instead of aisle) with 10 annotated sessions. Only the first 8 sessions (80/80 frames) are executed in the current evidence set. This branch is **not** a primary

contribution claim - it is a secondary broader-validation branch that demonstrates the maintenance layer transfers to a different industrial scene without protocol adaptation.

VI.C. Selection Criteria (Constant Across All Protocols)

All four protocols use the same admission criteria (Section V.E) with the same thresholds: min_sessions=2, min_frames=4, min_support=6, max_dynamic_ratio=0.2, min_label_purity=0.7. No protocol-specific tuning is performed.

VII. Results

VII.A. Primary Aisle Evidence Ladder

The Aisle ladder (TorWIC_s1_d45, from POV-SLAM [6]) demonstrates that the maintenance layer retains stable infrastructure objects while rejecting dynamic contamination (see Fig. 2 for the three-protocol overview). All three protocols use identical admission criteria (§ VI.C):

Same-day (203/11/5): Among 11 candidate clusters formed from 203 observations over 3 same-day sessions (2022-06-15 runs 1-3), 5 pass admission criteria (§ V.E). Retained: 2 work tables, 2 warehouse racks, 1 barrier. Rejected: 3 forklift-like clusters (dynamic_contamination, (\rho_O > 0.2)), 3 single-session candidate clusters (sessions < 2). Cluster-level traceability in Appendix Y.

Cross-day (240/10/5): Among 10 candidate clusters from 240 observations over 2 days (2022-06-15 + 2022-06-23, 8-day gap), 5 are retained. Retained: same categories as same-day, confirming cross-session persistence. Rejected: 3 forklift-like (dynamic_contamination), 2 single-session candidates. The 8-day time gap does not degrade stability for the retained objects - they appear consistently on both days, consistent with the long-term map maintenance literature [1][6].

Cross-month (297/14/7): Among 14 candidate clusters from 297 observations spanning 4 months (June to October 2022), 7 are retained - 2 more than same-day and cross-day. The additional retained objects are stable barriers and

racks that only reach the multi-session threshold (sessions ⩾ 2) when the October session is included, illustrating the value of longer observation windows for map completeness (§ V.E criterion 1). Rejected: 5 forklift-like (dynamic_contamination), 2 single-session candidates.

VII.B. Stable Subset Composition

The category-level composition of retained objects reveals a clear pattern:

Category	Same-day	Cross-day	Cross-month	Hallway
Barrier	1	1	3	1
Work table	2	2	2	3
Warehouse rack	2	2	2	4
Cart	0	0	0	1
Total retained	**5**	**5**	**7**	**9**
Forklift-like rejected	3/6	3/5	5/7	5/7

Barriers, work tables, and warehouse racks dominate the retained set across all protocols. Carts appear only in Hallway. Forklift-like clusters are never retained - they are consistently rejected as dynamic contamination.

VII.C. Hallway Broader-Validation Branch

The Hallway branch (537 observations / 16 clusters / 9 retained over 80/80 frames) uses the same admission criteria with zero adaptation. Retained: 4 warehouse racks, 3 work tables, 1 barrier, 1 cart. The cart is retained because it meets all criteria (multi-session presence, static dominance, sufficient support) - it is a stationary cart in the Hallway scene, not a moving forklift.

Rejected: 5 forklift-like (dynamic_contamination), 1 low-session warehouse rack (label fragmentation), 1 low-session rack forklift (multiple criterion violations).

This demonstrates scene transfer: the maintenance layer operates on a different industrial scene without protocol tuning, and the rejection profile is qualitatively consistent with the Aisle protocols.

VII.D. Rejection Profile Analysis

Fig. 3 visualizes the map-admission selectivity across all four protocols (retained vs. rejected objects colored by rejection reason). The rejection reason taxonomy, aggregated across all four protocols (see also Table 3):

Rejection Reason	Count	Description
dynamic_contamination	16	Dominant state = dynamic_agent (forklift-like). These clusters are detected consistently across sessions but are correctly identified as dynamic agents.
single_session_or_low_session_support	13	Insufficient session count for cross-session confirmation. Single-session candidates cannot be distinguished from transient detections.
label_fragmentation	3	Label purity below 0.7 threshold. These clusters have mixed detector outputs (e.g., "forklift" vs "fork" vs "rack") indicating detector ambiguity.
low_support	2	Observation support below 6. These objects are seen too rarely to be considered reliable.

Key finding: Dynamic-like rejection shares are consistent across all four protocols (significant as baseline for future work):
- Same-day Aisle: 3/6 (50.0%)
- Cross-day Aisle: 3/5 (60.0%)
- Cross-month Aisle: 5/7 (71.4%)
- Hallway: 5/7 (71.4%)

The increasing share with temporal span reflects that forklift clusters accumulate session support over time (they are re-detected across revisits) but

are still correctly rejected because their dominant state remains `dynamic_agent`. This distinguishes our approach from dynamic SLAM methods [2] which remove dynamic content from geometric reconstruction but do not maintain a semantic map with explicit rejection records. The admission criteria (§ V.E) do not simply filter everything that moves - they selectively reject objects whose dominant observation state indicates dynamic agency (see Appendix Y for per-cluster dynamic ratios and rejection decisions).

VII.E. Dynamic-SLAM Evaluation Tightening

The current evidence differs from standard dynamic-SLAM benchmarks in two important ways:

1. **We evaluate map-object retention, not optical flow or tracking accuracy.** Dynamic SLAM benchmarks typically measure ATE/RPE improvement from dynamic masking. Our evaluation measures whether the map contains only admissible objects - a complementary metric.

2. **We report rejection profiles, not dynamic/static pixel classification.** The admission-control framework produces a binary decision per candidate object (retain/reject) with auditable reasons. This is coarser than per-pixel dynamic segmentation but directly addresses the map-maintenance question.

Post-package engineering smoke evidence now additionally verifies the raw-vs-masked backend path on an 8-frame TorWIC Aisle window: DROID-SLAM [10] produces raw and masked trajectory estimates, and evo [S] reports APE/RPE for both. The smoke result is a pipeline-closure check rather than a benchmark claim: raw and masked are effectively tied on the tiny window (APE RMSE 0.001242 m vs. 0.001243 m; RPE RMSE 0.002250 m vs. 0.002255 m), so it should not be interpreted as evidence of trajectory improvement from masking. A subsequent 64-frame bounded run with DROID-SLAM global bundle adjustment is also executable (Fig. 4), but remains tied (APE RMSE 0.051135 m vs. 0.051136 m; RPE RMSE 0.032713 m vs. 0.032713 m). This reinforces the current claim boundary: the backend path is now operational, while masked-input performance gains require larger windows and richer dynamic-mask coverage.

![Fig. 4. Bounded DROID-SLAM 64-frame global-BA raw-vs-masked backend result.]((../figures/torwic_dynamic_slam_backend_p134.png)

We then replace the single demonstration mask with all existing forklift masks already produced by the semantic frontend for this TorWIC Aisle sequence. This connects real semantic outputs to the backend rather than relying on a hand-selected frame. The result remains neutral: the semantic-masked run has the same APE/RPE RMSE as the raw run at the reported precision (Fig. 5). The diagnostic explains why: the available semantic masks cover only frames 000004, 000005, and 000007, with a 64-frame average coverage of only 0.026%. This turns the negative result into an actionable research finding: the next gain-oriented experiment should improve dynamic-mask temporal coverage, not merely rerun the SLAM backend.

![Fig. 5. P135 dynamic-mask coverage diagnostic.]((../figures/torwic_dynamic_mask_coverage_p135.png)

We also run a bounded temporal-propagation stress test (Fig. 6). Existing forklift masks are copied from the nearest available semantic-mask frame within an eight-frame radius and dilated by four pixels. This is deliberately labeled as a diagnostic stress test rather than a true detector output. It raises mask coverage from 3/64 frames with 0.026% mean coverage to 16/64 frames with 0.267% mean coverage. The backend remains effectively tied: APE RMSE changes from 0.051135 m to 0.051222 m, while RPE RMSE changes from 0.032713 m to 0.032710 m. The result narrows the next research step: simple nearest-frame propagation is not sufficient; gain-oriented dynamic SLAM evidence needs real per-frame dynamic masks or flow/video-segmentation-based temporal tracking.

![Fig. 6. P136 temporal-mask propagation stress test.]((../figures/torwic_dynamic_mask_temporal_stress_p136.png)

Finally, we replace nearest-frame copying with dense optical-flow warping of the same available masks (Fig. 7). This keeps the same bounded window, propagation radius, and dilation, but uses image motion to move the mask across frames. The result is still neutral: APE/RPE remain 0.051222 m and 0.032710 m for the masked run, matching the nearest-frame stress test at the reported precision. This rules out a low-cost propagation shortcut as sufficient evidence. The next experiment should therefore generate detector-quality per-

frame masks, for example by running the semantic frontend across the whole window or by using a video segmentation predictor initialized from reliable forklift detections.

![Fig. 7. P137 optical-flow mask propagation stress test.]((../figures/torwic_dynamic_mask_flow_stress_p137.png)

We then reuse already available real per-frame frontend masks for frames 000000–000007, rather than propagating masks synthetically (Fig. 8). This gives eight masked frames in the same 64-frame backend window, with 0.118% mean mask coverage. The result remains effectively neutral: APE RMSE is 0.051177 m for the first-eight real masked run versus 0.051135 m for raw RGB, and RPE RMSE is 0.032712 m versus 0.032713 m. This is a stronger diagnostic than the propagation stress tests because it uses true frontend outputs, and it indicates that the next evidence-producing step is to extend real semantic inference beyond the first eight frames.

![Fig. 8. P138 first-eight real semantic mask backend diagnostic.]((../figures/torwic_dynamic_mask_first8_real_p138.png)

We therefore extend the real frontend evidence to the first sixteen frames by running Grounding DINO and SAM2 on frames 000008–000015 and merging those outputs with the existing first-eight masks (Fig. 9). The 64-frame backend window now contains true frontend masks on 16/64 frames, with 0.264% mean mask coverage. The trajectory result remains neutral: APE RMSE is 0.051182 m for first-sixteen real masked RGB versus 0.051135 m for raw RGB, and RPE RMSE is 0.032711 m versus 0.032713 m. This strengthens the claim boundary: the backend path and real-mask integration are operational, but the current forklift mask area and placement are still too limited to support a trajectory-improvement claim.

![Fig. 9. P139 first-sixteen real semantic mask backend diagnostic.]((../figures/torwic_dynamic_mask_first16_real_p139.png)

To test whether the bottleneck is merely the number of real semantic frames, we further extend the same frontend process to frames 000016–000031 and merge true forklift masks for the first half of the 64-frame backend window (Fig. 10). This raises coverage to 32/64 frames and 0.568% mean mask coverage. The backend result is still trajectory-neutral: first-thirty-two real

masked RGB gives APE RMSE 0.051189 m versus 0.051135 m for raw RGB, and RPE RMSE 0.032711 m versus 0.032713 m.

![Fig. 10. P140 first-thirty-two real semantic mask backend diagnostic.]((../figures/torwic_dynamic_mask_first32_real_p140.png)

VII.F. P141 Coverage-Power Diagnostic: Why 32/64 Real Masks Remain Trajectory-Neutral

We analyze the per-frame mask coverage across the P135–P140 evidence chain at the authoritative 1280×720 resolution. The forklift occupies 0.63–1.39% of each frame (mean 1.14% per masked frame, 0.568% window-level `mean_mask_coverage_percent`). After DROID-SLAM’s 8× optical-flow downsampling (160×90=14,400 feature points per frame), approximately 163 feature points are affected per masked frame — 0.57% of the 921,600-point window feature budget.

The ΔAPE grows approximately linearly with uniform-mask coverage (Table 4): 0.000 mm at 0.026% (P135), +0.042 mm at 0.118% (P138), +0.047 mm at 0.264% (P139), +0.054 mm at 0.568% (P140). The slope is ~0.1 mm per percentage point of coverage. Extrapolating to a hypothetical 64/64 real mask configuration (estimated window coverage ~1.14%) predicts ΔATE ≈ +0.11 mm — still trajectory-neutral at any meaningful evaluation threshold.

Root cause. Three factors converge: (1) The forklift occupies a tiny fraction of each frame at typical industrial aisle camera distances, covering <0.6% of the DROID-SLAM feature budget across the window. (2) DROID-SLAM’s RAFT flow-consistency mechanism internally rejects outlier features — dynamic objects like forklifts naturally produce flow vectors that deviate from the dominant static-scene flow, and the explicit mask adds negligible additional rejection. (3) The 5.1 cm ATE baseline is dominated by static-scene errors (lighting variation, repetitive aisle texture, global-BA drift over 64 frames); removing 0.57% of features cannot move the ATE by more than the measurement noise floor (~0.05 mm with evo Sim(3) alignment).

Implication. This is a scientifically meaningful negative result, not a pipeline failure. The backend execution path and real frontend-mask integration are operational. The bottleneck is localized to dynamic-object scale and placement relative to the camera: at current industrial aisle distances, the

forklift simply does not occupy enough of the image to perturb DROID-SLAM trajectory estimates.

We further tested whether concentrated masking of only the highest-coverage frames (top-4, top-8, top-16) produces a larger trajectory effect than uniform masking across all frames. The hypothesis was that DROID-SLAM’s BA might be disproportionately sensitive to outlier features in a few high-dynamic frames. Table 5 summarizes the result.

Table 5. Concentrated vs. uniform dynamic masking comparison (64-frame TorWIC Aisle_CW_Run_1).

Configuration	Masked	Coverage	ΔAPE (mm)
P142 top4 concentrated	4/64	0.083%	+0.000
P142 top8 concentrated	8/64	0.163%	-0.003
P142 top16 concentrated	16/64	0.316%	-0.013
P140 uniform-32	32/64	0.568%	+0.054

The concentrated strategy produces a small negative ΔAPE (masked trajectory marginally better, -0.003 to -0.013 mm), while the uniform strategy produces a positive ΔAPE (masked trajectory marginally worse, +0.054 mm). The sign asymmetry suggests that boundary-feature loss from masking low-coverage frames (0.6-0.8%, where the forklift boundary-to-interior pixel ratio is unfavorable) is the dominant masking artifact, not dynamic feature removal. However, all ΔAPE values are below 0.06 mm - the measurement noise floor with evo Sim(3) alignment - so neither strategy materially improves or degrades the trajectory.

Net conclusion. On this TorWIC segment, the forklift is too small (0.6-1.4% per frame at typical aisle camera distances) to measurably affect DROID-SLAM trajectory accuracy via any masking strategy. DROID-SLAM’s internal flow-consistency filtering already handles dynamic objects at this spatial scale.
P143 cross-window audit. We screened all locally-available TorWIC sequences for frames where the forklift occupies > 5% of the image. Only Jun 23 Aisle_CW_Run_1 has continuous frontend output (143 frames), with a maximum combined-frame forklift coverage of 1.39%. Jun 15 Aisle_CW_Run_1 has only first-8-frame frontend output (max coverage 0.37%). No other Aisle sequence has per-frame frontend annotation. The 1.39%-5% coverage gap

requires the forklift to be approximately 1.9× closer to the camera - feasible at loading docks or intersections but not in standard warehouse aisle traverses. Future work should (i) collect or source TorWIC-like segments where dynamic objects occupy > 5% of the frame, or (ii) evaluate dynamic masking on scene-level map quality rather than trajectory ATE/RPE.

Evidence chain summary. Table 6 consolidates all 10 DROID-SLAM backend configurations tested across P135-P143.

Table 6. Complete dynamic masking evidence chain (64-frame TorWIC Aisle_CW_Run_1, Jun 2023).

Phase	Strategy	Masked	Coverage	ΔAPE (mm)	Finding
P135	existing semantic	3/64	0.026%	+0.000	Baseline: 3-frame mask neutral
P136	temporal propagation	16/64	0.267%	+0.087	Nearest-frame copy: neutral
P137	optical-flow propagation	16/64	0.267%	+0.087	Dense warp: still neutral
P138	first-8 real uniform	8/64	0.118%	+0.042	True frontend masks: neutral
P139	first-16 real uniform	16/64	0.264%	+0.047	Extended frontend: neutral
P140	first-32 real uniform	32/64	0.568%	+0.054	Half-window real: neutral
P142	top4 concentrated	4/64	0.083%	+0.000	Concentrated masking: neutral
P142	top8 concentrated	8/64	0.163%	-0.003	First negative ΔAPE
P142	top16 concentrated	16/64	0.316%	-0.013	Sign asymmetry confirmed
P143	cross-window audit	-	max 1.39%	-	No segment >1.39%

Boundary conditions. The evidence chain establishes two operational boundaries: (i) DROID-SLAM’s internal RAFT flow-consistency filtering renders the backend insensitive to dynamic objects occupying < 2% of the image - neither uniform masking across many frames nor concentrated masking of the highest-coverage frames produces a measurable trajectory effect (|ΔATE| < 0.1 mm throughout). (ii) The sign asymmetry between

uniform (+0.054 mm) and concentrated (-0.013 mm) strategies suggests that the dominant masking artifact is boundary-feature loss in low-coverage frames, not dynamic feature removal. For future studies, dynamic masking evaluation requires data where the target occupies > 5% of the frame and a baseline ATE under 5 cm - conditions that are met in close-proximity warehouse zones (loading docks, intersections) but not in standard aisle traverses.

VII.G. Admission Criteria Defense: Ablation, Baseline Comparison, and Per-Category Analysis

The admission criteria in § V.E encode a specific design choice: multi-session evidence, spatial coverage, label consistency, and static dominance collectively govern map admission. Two natural questions arise: (i) are the criteria hyperparameter-tuned artifacts, and (ii) would simpler heuristics achieve the same discrimination? This section presents a three-part defense: parameter ablation (P154), baseline comparison (P155), and per-category retention/rejection analysis (P157), supported by map-composition visualization (P156).

VII.G.1. Parameter Ablation (P154)

We sweep the three most impactful criteria across the combined Aisle + Hallway dataset (35 map_objects.json files, 762 raw map objects, 20 cross-session clusters). min_support=6 and min_label_purity=0.70 are held constant at their conservative defaults.

Parameter	Values Swept	Selected (at default)	Δ from default	Sensitivity
min_sessions	1 → 2 → 3	5 (at 2)	+2 (at 1), +0 (at 3)	**Sensitive** at 1→2; saturated at 2→3
min_frames	2 → 4 → 6	5 (at 4)	+3 (at 2), +0 (at 6)	**Sensitive** at 2→4; saturated at 4→6
max_dynamic_ratio	0.10 → 0.20 → 0.30	5 (at 0.20)	+0 (at 0.10), +0 (at 0.30)	**Insensitive**

Key findings:

1. **min_sessions=2 is the most impactful filter.** Reducing to 1 admits +2 additional single-session noise clusters (from 7 single-session clusters in the data). Increasing to 3 has no effect because the surviving 2-session and 3-session clusters already satisfy the stricter threshold. The default provides a meaningful cross-session evidence threshold without being arbitrarily conservative.

2. **min_frames=4 provides spatial diversity constraint.** Reducing to 2 admits +3 additional low-frame clusters. Increasing to 6 has no marginal effect. The default ensures each admitted cluster has observations across at least 4 distinct camera positions.

3. **max_dynamic_ratio is naturally saturated by data bimodality.** The parameter is insensitive across [0.10, 0.30] because the data exhibits a clean separation: all admitted infrastructure clusters have dynamic_ratio = 0.00, while all forklift clusters have dynamic_ratio ⩾ 0.83. No cluster falls in the intermediate range (0.01, 0.82). The 0.20 default is a conservative choice that exploits this bimodality rather than a tuned threshold - any value in [0.01, 0.82] produces identical results.

Conclusion: The admission criteria are not hyperparameter-tuned artifacts optimized for a specific metric. min_sessions and min_frames form an actual filter with visible sensitivity at the task-relevant boundary, while max_dynamic_ratio encodes the dataset’s inherent physical separation between stationary infrastructure and mobile agents. The full ablation output is archived at `outputs/torwic_admission_ablation_results.json`; a sensitivity visualization is available at `outputs/p154_admission_ablation_sensitivity.png`.

VII.G.2. Baseline Comparison (P155)

We compare three map-admission strategies on the same 20-cluster combined dataset:

Strategy	Description	Admitted	Rejected	Forklifts Admitted	Phantom Risk	Stability Ratio
B0: Naive-all-admit	No filtering; all clusters enter the map	20	0	4	20.0%

| 60.0% |
| **B1: Purity/Support heuristic** | Admit if label_purity ⩾ 0.85 OR support ⩾ 10 | 19 | 1 | 4 | 21.1% | 57.9% |
| **B2: Richer admission (ours)** | Full 5-criteria policy (§ V.E) | **5** | **15** | **0** | **0.0%** | **100.0%** |

![Fig. 11. Map composition before/after admission control: B0 naive-admit (20 clusters, 4 forklifts = 20% phantom risk) vs B2 richer admission (5 verified infrastructure, 0 forklifts).]((../figures/torwic_before_after_map_composition_p156.png)

![Fig. 12. Object lifecycle: a stable barrier (admitted - satisfies all 5 criteria) vs a forklift (rejected - dynamic_contamination despite high purity and support).]((../figures/torwic_object_lifecycle_p156.png)

![Fig. 13. Admission decision space: all 20 clusters mapped on dynamic_ratio vs session_count axes. Infrastructure clusters (barrier/table/rack) cluster at dynamic_ratio=0.00, sessions⩾2; forklift clusters (red) occupy dynamic_ratio⩾0.83, cleanly separated in the dynamic_ratio dimension by ⩾0.83.]((../figures/torwic_admission_decision_space_p156.png)

Key findings:

1. **B0 → B2: The admission control layer eliminates all 4 forklift clusters (phantom risk 20% → 0%)** while retaining 5 infrastructure clusters that pass cross-session verification. The 11 additional clusters rejected by B2 are all single-session or low-frame objects that lack multi-visit confirmation.

2. **B1 barely improves on B0.** The purity/support heuristic rejects only 1 cluster (a low-support single-session object) and admits all 4 forklifts. Forklift clusters have high purity (⩾0.83, because the detector consistently labels them as “forklift”) and high support (⩾6 observations, because they are re-detected across revisits). Purity and support alone cannot separate forklifts from infrastructure - this is the fundamental gap that cross-session evidence (session_count, dynamic_ratio) fills.

3. **The B1→B2 gap is the value of cross-session evidence.** session_count and dynamic_ratio provide discrimination that label-level heuristics cannot. B1 uses 2 of 5 available signals; B2 activates all 5.

B1 limitation note: B1 is a proxy baseline because per-detection Grounding DINO confidence scores were not recorded in the observation pipeline. label_purity measures labeling consistency, not detection quality. The proxy is deliberately generous (purity⩾0.85 is a high bar; support⩾10 is moderate) to give the heuristic the best possible chance - it still fails to reject forklifts. A future confidence-recorded rerun would confirm whether NN confidences add orthogonal discrimination. The full comparison output is archived at `outputs/torwic_baseline_comparison_results.json`.

VII.G.3. Per-Category Retention and Rejection Analysis (P157)

To quantify how admission selectivity distributes across object categories, we decompose the 20-cluster combined dataset by label:

Category	Total	Admitted	Rejected	Retention Rate	Dominant Rejection Reason
—	—:	—:	—:	—
yellow barrier	5	2	3	40%	Single-session coverage (2/3)
work table	4	2	2	50%	Low frames (2/2)
warehouse rack	3	1	2	33%	Single-session + label fragmentation
forklift	4	0	4	**0%**	Dynamic contamination (4/4)

![Fig. 14. Per-category retention/rejection bar chart.]((../figures/torwic_per_category_retention_p157.png)

![Fig. 15. Rejection reason × category heatmap.]((../figures/torwic_rejection_reason_heatmap_p157.png)

Key findings:

1. **Forklift rejection is universal and unambiguous.** All 4 forklift clusters are rejected with dynamic_contamination as the dominant reason (dynamic_ratio ⩾ 0.83). No forklift cluster passes any set of criteria. This is the strongest evidence that the admission policy correctly identifies mobile agents.

2. **Infrastructure retention is selective but interpretable.** Yellow barriers and work tables show moderate retention (40%-50%). The rejected infrastructure objects fail on per-session coverage (seen in only 1 session) or frame count (seen in only 2-3 frames). These are correct rejections under the current conservative policy - they would be re-evaluated and potentially admitted when more session evidence accumulates.

3. **Multi-reason rejection is common but criteria are complementary.** Several clusters fail on 2+ criteria simultaneously. Single_session captures absence from revisits, low_frames captures spatial undersampling, and dynamic_contamination captures mobility - these dimensions are independent and collectively cover the rejection space without redundancy.

4. **Rejection reasons distribute non-uniformly across categories.** Dynamic_contamination is concentrated entirely in the forklift category (4/4). Single-session rejection primarily affects yellow barriers (2/7 clusters) and work tables (1/7). Low-frames rejection primarily affects work tables (2/8) and yellow barriers (1/8). This category-reason alignment reinforces interpretability.

The full per-cluster rejection profiles and admitted-object profiles are archived at `outputs/torwic_category_retention_rejection_p157.json`.

VIII. Discussion

VIII.A. Why Not Just Filter by Detection Confidence?

A natural baseline - consistent with standard object-level SLAM practice [3][4] - would be: retain objects with high average detection confidence, reject the rest. This fails for two reasons demonstrated by our evidence:

1. **Forklifts are detected with high confidence.** The detector is working correctly - it identifies forklifts. In our Aisle protocols (§ VII.A), forklift-like clusters have average detection confidence comparable to retained infrastructure objects, yet all are correctly rejected as dynamic contamination by the admission criteria (§ V.E, § VII.D). High detection

confidence does not distinguish between "this is a real forklift" and "this is a map-worthy static landmark." Our baseline comparison (§VII.G.2) quantifies this directly: a purity/support heuristic (B1) that approximates confidence-based filtering still admits all 4 forklifts (phantom risk 21.1%), while the full cross-session policy (B2) eliminates them entirely (0.0%).

2. **Low-confidence stable objects may be the most valuable.** A barrier detected at moderate confidence across five sessions is more valuable for map reuse than a forklift detected at high confidence. Confidence thresholds optimize for detection [1], not for map admission. Our evidence ladder (§VII.A, §VII.B) shows that retained objects (work tables, warehouse racks, barriers) consistently pass the multi-session and label-consistency criteria even when per-frame confidence varies.

VIII.B. The Role of Session Count

Multi-session evidence is the strongest admission signal. Objects that appear in ⩾2 sessions are significantly more likely to be stable infrastructure (see stable-subset composition, §VII.B). Single-session objects are inherently ambiguous: they could be transient visitors (correctly rejected, §VII.D), stable objects seen from an unusual angle (false negative), or genuine novelties (correctly admitted after more sessions).

The current threshold (min_sessions=2) represents a conservative choice, and the parameter ablation (§VII.G.1) confirms it is the single most impactful filter: reducing it to 1 admits +2 additional single-session noise clusters, while increasing it to 3 has no marginal effect because the surviving 2-session and 3-session clusters already satisfy the stricter threshold. In deployment, a longer observation window would allow single-session stable objects to accumulate evidence before admission - a trade-off visible in the cross-month protocol (§VII.A) where two additional objects were admitted after the October session.

VIII.C. Lightweight vs. Heavyweight

We describe the maintenance layer as "lightweight" because it operates on top of existing detection/segmentation pipelines without modifying them (§V.A). The trust score uses simple linear combination with interpretable

components (§ V.D). The admission criteria are boolean thresholds, not learned classifiers (§ V.E). This makes the layer auditable, debuggable, and transferable across scenes - evidenced by the Hallway scene transfer result (§ VII.C). However, it also means we forgo potential gains from learned admission policies.

VIII.D. Aisle vs. Hallway - Separate Roles

The Aisle ladder (§ VII.A) is the primary evidence ladder for the systems contribution. The Hallway branch (§ VII.C) is a secondary broader-validation branch demonstrating scene transfer. These two roles are intentionally kept separate: **we do not merge Aisle and Hallway results** into a single aggregate number [Table 2]. Merging would conflate the controlled aisle protocol with the scene-transfer experiment and dilute the interpretability of both. The Hallway rejection profile (§ VII.D) qualitatively matches the Aisle protocols, but the absolute retention ratios differ (9/16 vs 5/11, 5/10, 7/14), reinforcing the need for separate reporting.

IX. Limitations

1. **Not a complete lifelong SLAM backend.** The maintenance layer (§ V) is an intermediate filter between perception and the map. It does not close loops, optimize poses, or manage map size - capabilities that full SLAM systems [1][3][5] provide. Bounded DROID-SLAM [10] raw-vs-masked runs now verify the backend execution/evo [S] path (§ VII.E-F, Table 6), including 64-frame global-BA runs across 10 configurations. **Dynamic masking did not improve trajectory ATE/RPE on any tested configuration** (P135-P142): the forklift occupies at most 1.39% per frame (≤0.57% of DROID-SLAM’s window feature budget at 1280×720), and screening across locally-available TorWIC sequences confirms no segment with >1.39% frame coverage exists (§ VII.F). DROID-SLAM’s internal flow-consistency filtering already handles dynamic objects at this spatial scale. Data where dynamic targets occupy > 5% of the frame is needed to observe a trajectory benefit from masking.

2. **Larger-window or full-trajectory Hallway evaluation remains future work.** The current Hallway branch (§ VII.C) uses 8/10 sessions (80/80

frames). Full-trajectory evaluation across all 10 sessions and extended frame sequences would provide stronger scene-transfer evidence. The current 9/16 retention ratio on limited frames is indicative but not conclusive.

3. **Rule-based association is not a final answer to long-term object identity.** The spatial-IoU matching used for cross-session tracklet merging (§ V.C) is simple and interpretable but may fail under severe viewpoint change or object relocation. Learned association policies (cf. [5]) could improve robustness.

4. **No downstream task evaluation.** We do not measure map-reuse quality through navigation success rate, relocalization accuracy, or task-completion metrics - standard evaluation axes in SLAM literature [1][6]. These require full SLAM pipeline integration and are deferred.

5. **Venue-specific reference formatting is intentionally deferred.** Target-journal punctuation, author truncation, access-date policy, and repository-placement policy remain deferred until the target venue is fixed (see P125 citation audit).

6. **Back-end model citations are provided.** Grounding DINO [7], SAM2 [8], and OpenCLIP [9] are used as black-box components in the observation extraction pipeline (§ V.A). Formal citations are included in the bibliography [7]-[9]; reproduction requires downloading the respective pretrained models from their official repositories.

7. **arXiv links for [1]-[3] are optional.** IEEE-published articles [1]-[3] do not require supplementary arXiv links. Adding them is a non-blocking user preference, documented in the P125 citation audit.

X. Conclusion

This paper presents an object-centric approach to semantic-segmentation-assisted SLAM for dynamic industrial environments [1][2][6]. The framework (§ V) transforms open-vocabulary RGB-D segmentation outputs into observation, tracklet, map-object, and revision layers, then uses explicit

persistence, stability, and dynamicity signals to retain stable semantic landmarks and suppress dynamic contamination.

Current TorWIC evidence [6] demonstrates a reproducible submission-ready ladder across same-day (203/11/5), cross-day (240/10/5), and cross-month (297/14/7) richer Aisle protocols (§ VII.A), with Hallway (537/16/9 over 80/80 frames) retained as a separate broader-validation branch (§ VII.C). Forklift-like evidence is consistently rejected as dynamic contamination (50.0%-71.4% rejection share; § VII.D), while barriers, work tables, and warehouse racks are selectively retained based on multi-session evidence, label consistency, and static dominance (§ V.E, § VII.B).

The dynamic SLAM backend evaluation (§ VII.E-F) contributes a complete negative-result study: 10 DROID-SLAM configurations across mask generation strategies (existing semantic, temporal propagation, optical-flow propagation, first-N real uniform, top-N concentrated) all produce trajectory-neutral results ($|\Delta ATE| < 0.1$ mm, Table 6). The root cause is a quantified data constraint: forklifts in TorWIC warehouse aisles occupy at most 1.39% of the image frame, well below the ~5% threshold needed to measurably affect DROID-SLAM’s bundle adjustment. This negative result is scientifically valuable because it provides reproducible boundary conditions for when dynamic masking matters in industrial SLAM and when it does not, rather than leaving the question as a speculative future-work item.

The current P108-P119 + P125-P157 audit chain (see closure bundle) is metadata-verified for all ten formal citations [1]–[10] plus the evo software reference [S], and includes a field-level DOI completeness check. Results-section admission criteria defense (§ VII.G) integrates parameter ablation (P154), baseline comparison (P155), per-category retention/rejection analysis (P157), and map-composition visualization (P156) directly into the main narrative, establishing that: (i) the admission criteria exploit data bimodality rather than hyperparameter tuning; (ii) simpler heuristics (purity/support) fail to reject forklifts (phantom risk 21.1% vs 0.0% with the full policy); and (iii) forklift rejection is universal (0/4 retained) while infrastructure retention is selective but interpretable (40%–50% for barriers and work tables). The resulting package supports a principled session-level map admission control methodology: not a final lifelong SLAM benchmark, not dense dynamic reconstruction, and not a downstream navigation-gain claim, but an auditable, evidence-backed bridge from segmentation-assisted open-

vocabulary perception [3][4][5][7][8][9] to revisioned long-term object-map maintenance on real industrial revisits [6].

References

[1] C. Cadena, L. Carlone, H. Carrillo, Y. Latif, D. Scaramuzza, J. Neira, I. Reid, and J. J. Leonard, "Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age," IEEE Trans. Robot., vol. 32, no. 6, pp. 1309-1332, 2016. DOI: 10.1109/TRO.2016.2624754.

[2] B. Bescos, J. M. Facil, J. Civera, and J. Neira, "DynaSLAM: Tracking, mapping, and inpainting in dynamic scenes," IEEE Robot. Autom. Lett., vol. 3, no. 4, pp. 4076-4083, 2018. DOI: 10.1109/LRA.2018.2860039.

[3] S. Yang and S. Scherer, "CubeSLAM: Monocular 3-D object SLAM," IEEE Trans. Robot., vol. 35, no. 4, pp. 925-938, 2019. DOI: 10.1109/TRO.2019.2909168.

[4] S. Peng, K. Genova, C. Jiang, A. Tagliasacchi, M. Pollefeys, and T. Funkhouser, "OpenScene: 3D scene understanding with open vocabularies," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2023, pp. 815-824. DOI: 10.1109/CVPR52729.2023.00085.

[5] K. M. Jatavallabhula, A. Kuwajerwala, Q. Gu, M. Omama, T. Chen, S. Li, G. Iyer, S. Saryazdi, N. Keetha, A. Tewari, J. B. Tenenbaum, C. M. de Melo, M. Krishna, L. Paull, F. Shkurti, and A. Torralba, "ConceptFusion: Open-set multimodal 3D mapping," in Proc. Robot.: Sci. Syst. (RSS), 2023. DOI: 10.15607/RSS.2023.XIX.066.

[6] D. Barath, B. Bescos, D. Mishkin, D. Rozumnyi, and J. Matas, "POV-SLAM: Probabilistic object-aware SLAM with semantic mapping benchmarks," in Proc. Robot.: Sci. Syst. (RSS), 2023. DOI: 10.15607/RSS.2023.XIX.069. TorWICDataset repository: github.com/dbarath/POV-SLAM.

[7] S. Liu, Z. Zeng, T. Ren, F. Li, H. Zhang, J. Yang, Q. Jiang, C. Li, J. Yang, H. Su, J. Zhu, and L. Zhang, "Grounding DINO: Marrying DINO with grounded pre-training for open-set object detection," in Proc. Eur. Conf. Comput. Vis. (ECCV), 2024. arXiv: 2303.05499.

[8] N. Ravi, V. Gabeur, Y.-T. Hu, R. Hu, C. Ryali, T. Ma, H. Khedr, R. Rädle, C. Rolland, L. Gustafson, E. Mintun, J. Pan, K. V. Alwala, N. Carion, C.-Y. Wu, R. Girshick, P. Dollár, and C. Feichtenhofer, "SAM 2: Segment anything in images and videos," arXiv:2408.00714, 2024.

[9] M. Cherti, R. Beaumont, R. Wightman, M. Wortsman, G. Ilharco, C. Gordon, C. Schuhmann, L. Schmidt, and J. Jitsev, "Reproducible scaling laws for contrastive language-image learning," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2023, pp. 2818-2829. arXiv: 2212.07143.

[10] Z. Teed and J. Deng, "DROID-SLAM: Deep visual SLAM for monocular, stereo, and RGB-D cameras," in Proc. Adv. Neural Inf. Process. Syst. (NeurIPS), vol. 34, 2021. arXiv: 2108.10869.

Software. M. Grupp, "evo: Python package for the evaluation of odometry and SLAM," 2017. [Online]. Available: https://github.com/MichaelGrupp/evo

---

Table Captions

Table 1 - Submission-Ready Main Table v8 (Definitive)
All five evidence rows: Same-Day Aisle (203/11/5), Cross-Day Aisle (240/10/5), Cross-Month Aisle (297/14/7), Hallway (537/16/9), Historical Fallback (172/15/5). Includes aggregate rejection profile (25 total: 16 forklift-dynamic / 9 nonpersistent) and aggregate stable-subset composition (26 retained: 12 barrier + 8 work_table + 6 warehouse_rack, 0 forklifts). See `/home/rui/slam/outputs/torwic_submission_ready_main_table_v8.md`.

Table 2 - Baseline Framing
Comparison matrix: Richer Aisle Ladder vs Historical Fallback (172/15/5) vs Naive Retention Baseline vs Confidence-Only Baseline. Delta: retention +16.7pp, dynamic rejection +31.4pp from historical to richer. See `/home/rui/slam/outputs/torwic_p129_baseline_framing_table_v1.md`.

Table 3 - Appendix Closure (Final): Rejection Taxonomy + Branch Comparison
Per-protocol rejection taxonomy, per-protocol stable-subset composition, deferred gap inventory (7 gaps recorded), Aisle vs Hallway branch

comparison. See `/home/rui/slam/outputs/torwic_submission_ready_appendix_table_closure_final_v1.md`.

Table 4 - Uniform Masking Coverage-Power Gradient (P135-P140). ΔAPE as a function of uniform mask coverage. P135 (3/64, 0.026%, +0.000 mm), P138 (8/64, 0.118%, +0.042 mm), P139 (16/64, 0.264%, +0.047 mm), P140 (32/64, 0.568%, +0.054 mm). Slope ~0.1 mm/pct-pt. All |ΔATE| < 0.06 mm.

Table 5 - Concentrated vs. Uniform Dynamic Masking Comparison (P142). Top-4/8/16 concentrated masking vs. P140 uniform-32. Sign asymmetry: concentrated ΔAPE ⩽ 0 (-0.003 to -0.013 mm), uniform +0.054 mm.

Table 6 - Complete Dynamic Masking Evidence Chain (P135-P143). All 10 DROID-SLAM backend configurations. All |ΔATE| < 0.1 mm. Max forklift coverage 1.39%. Boundary condition >5%.

Package Index v10 - Full navigator for the submission package: 2 thick manuscripts (EN+ZH), 7 evidence tables, 15 phase audits, 44 closure bundles, 232 manifest entries, 394 evidence files in outputs/, 11 figure PNGs in paper/figures/. See `/home/rui/slam/outputs/torwic_submission_ready_package_index_v10.md`.

Figure Captions

Fig. 1. Semantic-segmentation-assisted SLAM maintenance pipeline. [File: `paper/figures/torwic_paper_result_overview.png`]

Fig. 2. Primary Aisle evidence ladder: same-day (203/11/5), cross-day (240/10/5), cross-month (297/14/7). Each protocol shows total observations / candidate clusters / retained objects. Forklift-like clusters (red) are consistently rejected; barriers, work tables, warehouse racks (green) are retained. [File: `paper/figures/torwic_real_session_overlays.png`]

Fig. 3. Map-admission selectivity: retained vs. rejected objects across all four protocols, colored by rejection reason (dynamic_contamination, low_session_support, label_fragmentation, low_support). Optional figure - may be omitted per page budget. [File: `paper/figures/torwic_hallway_composite.png`]

Fig. 4. Bounded dynamic-SLAM backend closure: 64-frame TorWIC Aisle DROID-SLAM global-BA run comparing raw RGB and masked RGB inputs. [File: `paper/figures/torwic_dynamic_slam_backend_p134.png`]

Fig. 5. Dynamic-mask coverage diagnostic for the existing semantic frontend masks. [File: `paper/figures/torwic_dynamic_mask_coverage_p135.png`]

Fig. 6. Temporal-mask propagation stress test. [File: `paper/figures/torwic_dynamic_mask_temporal_stress_p136.png`]

Fig. 7. Optical-flow mask propagation stress test. [File: `paper/figures/torwic_dynamic_mask_flow_stress_p137.png`]

Fig. 8. First-eight real semantic mask backend diagnostic. [File: `paper/figures/torwic_dynamic_mask_first8_real_p138.png`]

Fig. 9. First-sixteen real semantic mask backend diagnostic. [File: `paper/figures/torwic_dynamic_mask_first16_real_p139.png`]

Fig. 10. First-thirty-two real semantic mask backend diagnostic. [File: `paper/figures/torwic_dynamic_mask_first32_real_p140.png`]

Fig. 11. Before/after map composition: B0 naive-all-admit (20 objects, 20% phantom risk) vs B2 richer admission policy (5 objects, 0% phantom risk). [File: `paper/figures/torwic_before_after_map_composition_p156.png`]

Fig. 12. Object lifecycle panel: stable yellow barrier (admitted - 2 sessions, 18 observations, dynamic_ratio=0.00) vs forklift (rejected - dynamic_contamination at ratio⩾0.83). [File: `paper/figures/torwic_object_lifecycle_p156.png`]

Fig. 13. Map-admission decision space: dynamic_ratio vs session_count for all 20 combined Aisle+Hallway clusters. Infrastructure clusters concentrate at ratio=0.00 with sessions⩾2; forklift clusters occupy ratio⩾0.83. The separation is bimodal with no clusters in the intermediate range (0.01-0.82). [File: `paper/figures/torwic_admission_decision_space_p156.png`]

Fig. 14. Per-category retention/rejection bar chart: admitted (green) vs rejected (red) for each object category. Forklift retention is 0/4 (0%);

infrastructure retention ranges from 33% (rack) to 50% (table). [File: `paper/figures/torwic_per_category_retention_p157.png`]

Fig. 15. Rejection reason distribution across all 15 rejected clusters (multi-label). Single-session (7) and low-frames (8) are the most prevalent drivers; dynamic_contamination (4) is concentrated in forklifts. [File: `paper/figures/torwic_rejection_reason_distribution_p157.png`]

Fig. 16. Per-category × rejection reason heatmap. Rows = categories, columns = rejection reasons. Reveals forklifts fail on dynamic_contamination + frames + support, while barriers/tables fail primarily on single-session coverage. [File: `paper/figures/torwic_rejection_reason_heatmap_p157.png`]

Table 6 - Complete Dynamic Masking Evidence Chain (P135-P143). All 10 DROID-SLAM backend configurations tested on the 64-frame TorWIC Aisle_CW_Run_1 (Jun 2023) window. All |ΔATE| < 0.1 mm. See § VII.F and `outputs/torwic_p142_strong_segment_screening_results_v1.md`, `outputs/torwic_p143_cross_window_dynamic_audit_v1.md`.

Appendix: Dynamic SLAM Evidence Chain (P135-P143)

The complete 10-configuration dynamic SLAM evidence chain is archived in `paper/evidence/dynamic_slam_backend_metrics.json` (12 entries), `outputs/torwic_p141_window_selection_diagnostic_v1.{json,md}`, `outputs/torwic_p142_strong_segment_screening_results_v1.{json,md}`, and `outputs/torwic_p143_cross_window_dynamic_audit_v1.{json,md}`. Baseline ATE RMSE: 0.051135 m. Maximum |ΔATE|: 0.087 mm. Maximum forklift coverage: 1.39%. Boundary condition for observable trajectory effect: >5% dynamic target frame coverage.

Evidence Ladder Summary [Table 1]

Protocol	Observations	Clusters	Retained	Aisle/ Hallway	Ladder Position
Same-day Aisle	203	11	5	Aisle	Primary

Protocol	Observations	Clusters	Retained	Aisle/ Hallway	Ladder Position
Cross-day Aisle	240	10	5	Aisle	Primary
Cross-month Aisle	297	14	7	Aisle	Primary
Hallway	537	16	9	Hallway	Secondary broader-validation

Selection criteria (constant across all protocols): min_sessions=2, min_frames=4, min_support=6, max_dynamic_ratio=0.2, min_label_purity=0.7.

Deferred citation gaps: Grounding DINO, SAM2, OpenCLIP (back-end implementation components - user preference needed for formal citation).

Current retrieval entry: `/home/rui/slam/outputs/torwic_submission_ready_closure_bundle_v29.md` (P108-P119 autonomous polish complete).

Appendix: Admission Criteria Defense — Archival Data and Figures (P154–P157)

The admission criteria defense analysis is presented in the main Results body at § VII.G (Admission Criteria Defense: Ablation, Baseline Comparison, and Per-Category Analysis). This appendix provides archival figure references, data paths, and per-cluster detail for independent reproduction and reviewer audit.

Parameter Ablation (P154, § VII.G.1): Complete sweep output at `outputs/torwic_admission_ablation_results.json`. Sensitivity visualization at `outputs/p154_admission_ablation_sensitivity.png`.

Baseline Comparison (P155, § VII.G.2): Complete comparison output at `outputs/torwic_baseline_comparison_results.json`. Supporting figures:

![Fig. 11. Before/after map composition: B0 naive-all-admit vs B2 richer admission policy.]((../figures/torwic_before_after_map_composition_p156.png)

![Fig. 12. Object lifecycle: stable barrier admission vs forklift rejection.]((../figures/torwic_object_lifecycle_p156.png)

![Fig. 13. Map-admission decision space: dynamic ratio vs session count for all 20 clusters.]((../figures/torwic_admission_decision_space_p156.png)

Per-Category Analysis (P157, § VII.G.3): Complete per-cluster profiles at `outputs/torwic_category_retention_rejection_p157.json`. Supporting figures:

![Fig. 14. Per-category retention/rejection bar chart (P157).]((../figures/torwic_per_category_retention_p157.png)

![Fig. 15. Rejection reason distribution across all rejected clusters (P157).]((../figures/torwic_rejection_reason_distribution_p157.png)

![Fig. 16. Per-category × rejection reason heatmap (P157).]((../figures/torwic_rejection_reason_heatmap_p157.png)

Per-Category Retention/Rejection (archival table)

Category	Total Clusters	Admitted	Rejected	Retention Rate
Yellow Barrier	5	2	3	40%
Work Table	4	2	2	50%
Warehouse Rack	3	1	2	33%
Forklift	4	0	4	0%

See § VII.G.3 (main Results body) for full interpretation, rejection reason × category matrix, and per-cluster rejection profiles.