

HOLE TABLE (BASIC, FROM THE PITCH AXIS) POSITION $\emptyset.005$ A B C

HOLE	SIZE	X	Z
H1	ø.281 THRU (TIE)	17.353	4.391
H2	ø.281 THRU (TIE)	18.710	4.734
C	ø.281 THRU (SPACER)	14.600	-8.600
H4	ø.281 THRU (SPACER)	17.000	-8.650
H5	1/4-20 x .75 DP (EDGE)	14.200	-9.100
H6	1/4-20 x .75 DP (EDGE)	15.600	-9.100
H7	1/4-20 x .75 DP (EDGE)	17.400	-9.100

ϕ	$\phi.005$	A	B	C
--------	------------	---	---	---

2X ARC SLOT .752 +.002/-.000 WIDE
FULL R ENDS

$\frac{1}{2}$	.002	A	B	C
---------------	------	---	---	---

PITCH AXIS (BMC)
CENTRE OF ALL ARCS

FRONT VIEW 1:2.2

SIDE

NOTES:

1. QTY 2, IDENTICAL (+Y AND -Y). PROFILE AND SLOTS: CNC MILL (OR WATERJET + FINISH MILL THE SLOTS).
2. THE TWO ARC SLOTS ARE THE CAM-FOLLOWER TRACKS: THEIR CENTRE IS THE PITCH AXIS (BMC). MACHINE BOTH CHEEKS STACKED AND PINNED IN ONE SETUP. SLOT FACES Ra 32 μ m, NO STEPS AT TOOL ENTRY.
3. PITCH-AXIS ORIGIN: 9.100 ABOVE DATUM B AND 14.600 FORWARD OF HOLE C (BASIC). HOLE TABLE COORDINATES ARE FROM THE PITCH AXIS, X AFT, Z UP.
4. BOTTOM EDGE: 3X 1/4-20 UNC-2B .75 DEEP FOR THE BASE PLATE BOLTS (WT-6C-403).

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES

TOLERANCES:

.X $\pm$.03 .XX $\pm$.010

.XXX ±.005 .XXXX ±.0005

ANGLES $\pm 0^{\circ}30'$

BREAK SHARP EDGES .005-.015

SURFACE FINISH 63 $\mu\text{in Ra MAX}$

INTERPRET PER ASME Y14.5-2018

UNDIMENSIONED GEOMETRY PER STEP MODEL



NEXT ASSY: WT-6C-400 PITCH SECTOR ASSY

PROJECT					DRAWN / DATE		
Wind tunnel - motorized 6-component sting balance					Claude (AI-generated) 2026-10-02		
TITLE					CHECKED		APPROVED
CHEEK, PITCH SECTOR (QTY 2)							
MATERIAL					FINISH		
6061-T6 ALUMINUM, .500 PLATE					CLEAR ANODIZE TYPE II		
DWG NO.		REV	SIZE	SCALE	WEIGHT		SHEET
WT-6C-401		A	B	1:2.2	2.59 lb		25 OF 36