

What is the purpose of Data Hiding?

- Data hiding is mistaken as data security.
- By hiding data a programmer can avoid mishandling of data by the code outside the class.
- Data is accessible only within a class.
- Only the functions of a class, knows what processing should be done on that data

Encapsulation vs Abstraction

- A Class is used for Encapsulation as well as Abstraction
- **Encapsulation** means combining related data members and functions together.
- Encapsulation is achieved using a class.
- **Abstraction** means hiding data and showing required functions.
- Abstraction is achieved using encapsulation and data hiding.
Private and public.

structure vs class

- C++ supports both structure and class
- **structure** in C++ can have data members and member functions.
- All members of a structure are public by default.
- **class** can contain data members and member functions
- All members of a class are private by default.

What is “this” pointer?

- It represents current object.
- It is useful in avoiding variable name conflict.

Example for current object.

```
class Test{
    private:
        int value;
    public:
        void fun(int x){
            this->value=x;
        }
};

int main(){
    Test t1,t2; // both t1 and t2 are having “value”
    t1.fun(10); // “this” inside fun means “value” of t1.
    t2.fun(20); // “this” inside fun means “value” of t2.
}
```

Example for variable name conflict.

```
class Test{
    private:
        int value;
    public:
        void fun(int value){
            // here parameter name and data member name is same
            “value” to access data member “this” is used.
            this->value=value;
        }
}
```

};