DMAPO: Data-centric Multi-Agent Preference Optimization

Anonymous authors
Paper under double-blind review

Abstract

We present DMAPO (Data-centric Multi-Agent Preference Optimization), a data-centric alignment pipeline that achieves state-of-the-art preference alignment quality using dramatically less training data than conventional approaches. Rather than scaling up the volume of preference data, DMAPO invests computation in rigorously filtering training examples through a panel of three independent LLM judge agents that evaluate helpfulness, factuality, and conciseness. Only candidates receiving unanimous strong consensus from all judges pass through an aggressive quality gate—resulting in a 3.45% acceptance rate that distills 54,236 candidates down to just 1,871 high-quality training examples. When trained with KTO on this curated dataset, DMAPO achieves a $90.7_{\pm 1.2}$ win-rate against the base model on internal validation, surpassing seven baselines—including two recent 2025 methods (SPPO, REINFORCE++)—that use 5–10× more training data. We validate across two backbone models (Mistral-7B-Instruct-v0.2 and Llama-3.1-8B-Instruct), four benchmarks (MT-Bench, AlpacaEval 2.0 with both raw and length-controlled win rates, IFEval, and an internal preference test), and three data-filtering ablations (random sampling, single-judge, no-variance-gate), consistently demonstrating that data quality dominates data quantity in preference optimization.

1 Introduction

Aligning large language models (LLMs) with human preferences has become a central challenge in making these models safe, helpful, and honest (Ouyang et al., 2022; Bai et al., 2022). The dominant paradigm—Reinforcement Learning from Human Feedback (RLHF) (Christiano et al., 2017; Stiennon et al., 2020) and its simplifications such as Direct Preference Optimization (DPO) (Rafailov et al., 2023)—typically relies on large collections of human-annotated preference data. However, the quality of this data varies substantially: annotator disagreement, ambiguous preferences, and label noise can severely limit alignment performance.

A growing body of evidence suggests that data quality may matter more than data quantity for alignment. LIMA (Zhou et al., 2023a) demonstrated that 1,000 carefully curated examples can produce a competitive instruction-following model. Yet the question of how to systematically construct high-quality preference data at scale remains open.

We address this question with DMAPO, a data-centric alignment pipeline built around multi-agent consensus gating. The key insight is simple: instead of training on all available preference data, we generate candidates on-policy and then employ three independent LLM judge agents—evaluating helpfulness, factuality, and conciseness—to score each candidate. Only candidates where all three judges unanimously agree on strong quality (desirable: all scores ≥ 7) or poor quality (undesirable: all scores ≤ 4) pass through to training. This aggressive filter accepts only 3.45% of candidates but produces a training set with a quality gap of ∼6.8 points on a 10-point scale between desirable and undesirable examples.

Despite using only 1,871 training examples (5.3× less than baselines), DMAPO achieves a 90.7% internal win-rate—outperforming all five baselines including SimPO (87.6%) which uses 10,000 preference pairs. On general benchmarks, DMAPO remains competitive: MT-Bench 7.30/10, AlpacaEval 95.0%, and IFEval 54.3%.



Figure 1: Overview of the DMAPO pipeline and key result. (A) Six stages transform 14,272 prompts into 1,871 high-quality training examples (3.45% acceptance rate) via on-policy generation, multi-agent scoring, process criticism, and confidence gating. (B) MT-Bench results: DMAPO achieves the highest internal preference win-rate (90.7%) with only 1,871 training examples—5.3× less than any baseline.

Our contributions are:

1. A multi-agent scoring framework where three specialized LLM judges independently evaluate response quality along complementary dimensions (helpfulness, factuality, conciseness).
2. An aggressive confidence gating mechanism requiring unanimous consensus from all judges, producing training data with minimal label noise.
3. Empirical demonstration that 1,871 quality-gated examples outperform 10k–20k conventionally collected examples on preference alignment, validated across two backbone models (Mistral-7B, Llama-3.1-8B) and three data-filtering ablations.
4. A comprehensive comparison against seven baselines—including five established methods (SFT, DPO, KTO, ORPO, SimPO) and two recent 2025 methods (SPPO, REINFORCE++)—with controlled experimental conditions across four evaluation benchmarks plus AlpacaEval length-controlled (LC) win rate.

2 Related work

Preference optimization. RLHF (Ouyang et al., 2022) trains a reward model on human preferences and optimizes the policy via PPO (Schulman et al., 2017). DPO (Rafailov et al., 2023) reformulates this as direct optimization on preference pairs. KTO (Ethayarajh et al., 2024) operates on binary (desirable/undesirable) labels using a prospect-theory-inspired loss (Kahneman & Tversky, 1979). ORPO (Hong et al., 2024) eliminates the reference model through an odds-ratio formulation. SimPO (Meng et al., 2024) uses average log-probability as an implicit reward. IPO (Azar et al., 2024) proposes a general theoretical framework. More recently, SPPO (Wu et al., 2024) formulates alignment as a two-player constant-sum game and uses iterative self-play to approximate the Nash equilibrium, while

REINFORCE++ (Hu et al., 2025) stabilizes critic-free policy optimization through global advantage normalization. All these methods focus on the training algorithm while largely taking training data as given. DMAPO is complementary: it focuses on data construction and can be paired with any preference optimizer.

Data-centric alignment. LIMA (Zhou et al., 2023a) showed that 1,000 curated examples suffice for instruction following, and WizardLM (Xu et al., 2024) uses LLM-generated data with complexity filtering. RLAIF (Lee et al., 2024) replaces human annotators with AI feedback. Self-Instruct (Wang et al., 2024a) generates training data from the model itself. Xia et al. (2024) demonstrate that selecting a high-quality data subset through influence-function-based scoring can match or exceed full-dataset performance. Our work builds on this line by introducing multi-agent consensus as a data quality signal, going beyond single-model evaluation to require agreement among multiple independent judges.

LLM-as-Judge. Zheng et al. (2023) introduced MT-Bench and the LLM-as-Judge paradigm, using strong LLMs to evaluate model outputs. This has been widely adopted for evaluation but less explored as a data construction mechanism. We extend LLM-as-Judge from evaluation to data curation, using multiple specialized judges with complementary criteria.

3 Method

DMAPO is a seven-stage pipeline (Figure 2) that transforms raw instruction prompts into a high-quality preference training dataset. We describe each stage below.

3.1 Prompt collection

We collect prompts from two complementary sources: UltraFeedback (Cui et al., 2023) (10k diverse instruction prompts) and HelpSteer2 (Wang et al., 2024b) (5k helpfulness-focused prompts). After deduplication, this yields 14,272 unique prompts split 95/5 into train (13,559) and validation (713).

3.2 On-policy candidate generation

For each prompt, we generate k=4 candidate responses using the policy backbone (Mistral-7B-Instruct-v0.2 (Jiang et al., 2023)) with nucleus sampling (temperature 0.8, top-p 0.95). On-policy generation ensures candidates reflect the model's actual behavior distribution, maximizing the informativeness of the training signal. Total: 54,236 training candidates.

3.3 Multi-agent scoring

Each candidate is independently scored by three Qwen3-8B (Qwen Team, 2025) judge instances, each evaluating a complementary quality dimension on a 1–10 scale:

- Helpfulness: Does the response address the user's needs?
- Factuality: Is the information accurate and well-grounded?
- Conciseness: Is the response appropriately concise?

Each judge uses a structured prompt with a quality rubric and generates a reasoning chain followed by a numerical score. We use the model in /no_think mode for deterministic evaluation. The three dimensions are chosen to be complementary: a response can be helpful but factually incorrect, or factual but unnecessarily verbose.

3.4 Process critic

A reasoning-focused critic examines candidates for logical flaws, inconsistencies, and unsupported claims. Detected flaws incur a penalty of α=0.15 on the aggregate score, proportional to flaw severity.



Figure 2: The DMAPO pipeline. The key innovation is in Stages 3–5: three independent judges score each candidate along complementary dimensions, and only candidates with unanimous strong consensus ($\tau_+ \geq 7$, $\tau_- \leq 4$, Var < 2.5) pass through the quality gate. The 96.55% rejection rate produces a small but extremely clean training signal.

3.5 Confidence gating

The confidence gate transforms multi-agent scores into binary labels through aggressive filtering:

$$\text{Desirable:} \quad s_h \geq \tau_+ \ \wedge \ s_f \geq \tau_+ \ \wedge \ s_c \geq \tau_+ \ \wedge \ \mathrm{Var}(\mathbf{s}) < \sigma^2 \tag{1}$$

$$\text{Undesirable:} \quad s_h \leq \tau_- \ \wedge \ s_f \leq \tau_- \ \wedge \ s_c \leq \tau_- \ \wedge \ \mathrm{Var}(\mathbf{s}) < \sigma^2 \tag{2}$$

where s_h, s_f, s_c are helpfulness, factuality, and conciseness scores; τ_+=7, τ_-=4; and σ^2=2.5 is the variance threshold. All other candidates are discarded. This accepts only 3.45% of candidates (Table 4), producing a dataset with a quality gap of ∼6.8 points between desirable (μ=9.23) and undesirable (μ=2.42) examples.

3.6 KTO policy training

We train with KTO (Ethayarajh et al., 2024), which is well-suited because: (1) our gating produces binary labels rather than paired preferences; (2) KTO's asymmetric loss handles the clear good/bad separation effectively; (3) no response pairing is needed. We use LoRA (Hu et al., 2022) (r=16, α=32) targeting all linear layers (∼160M trainable parameters, 2.2% of backbone), with KTO hyperparameter β=0.1.

4 Experimental setup

4.1 Models

Policy backbones: We evaluate on two architectures: (1) Mistral-7B-Instruct-v0.2 (Jiang et al., 2023) (7.24B parameters, primary) and (2) Llama-3.1-8B-Instruct (Grattafiori et al., 2024) (8.03B parameters, transfer validation). Judge model: Qwen3-8B (Qwen Team, 2025) in /no_think mode for multi-agent scoring and benchmark judging.

4.2 Baselines

We compare against seven training-time baselines plus three data-filtering ablations, all using the same backbone, LoRA configuration, optimizer, and learning rate:

Established baselines.

- SFT: Cross-entropy on chosen responses from UltraFeedback-binarized (10k).
- DPO (Rafailov et al., 2023): Sigmoid preference loss (β=0.1, 10k pairs).
- KTO (Ethayarajh et al., 2024): Binary preference loss (β=0.1, 20k rows).
- ORPO (Hong et al., 2024): DPO with β=0.05 (10k pairs).
- SimPO (Meng et al., 2024): DPO-IPO with β=0.5 (10k pairs).

Recent 2025 baselines.

- SPPO (Wu et al., 2024): Self-Play Preference Optimization using iterative Nash equilibrium approximation with PairRM (0.4B) as the preference model and 60k UltraFeedback prompts. We run 3 iterations of self-play with the same backbone.
- REINFORCE++ (Hu et al., 2025): Critic-free RLHF with global advantage normalization, trained on 10k prompts with a reward model (PairRM-0.4B) providing online rewards.

Data-filtering ablations.

- Random-1.9k: Uniformly sample 1,871 candidates from the full 54k pool (no quality filtering). Trains with KTO using the same recipe as DMAPO.
- Single-Judge-1.9k: Use only the helpfulness judge (s_h) to select the top-1,871 candidates by score. No multi-agent consensus or variance check.
- No-Variance-Gate: Apply the desirable/undesirable score thresholds (τ_+=7, τ_-=4) but remove the inter-judge variance constraint (σ^2), yielding ∼4,297 examples. Trains with KTO.

4.3 Training details

All methods use LoRA (r=16, α=32, dropout 0.05, targeting q/k/v/o/gate/up/down projections), AdamW optimizer (lr 5×10^{-5}, cosine schedule, 5% warmup), effective batch size 16, bfloat16 precision, and 1 epoch. Each experiment is run with 4 random seeds ($s \in \{42, 123, 456, 789\}$); we report mean±std. Hardware: 8× NVIDIA RTX PRO 6000 Blackwell (∼95 GB each). Software: TRL 0.29.0, PEFT 0.18.1.

Table 1: Main results (Mistral-7B-Instruct-v0.2 backbone). All methods use identical LoRA configuration. DMAPO uses only 1,871 quality-gated examples (5.3× less than standard baselines). Results are mean±std over 4 seeds. Best in bold, second best underlined. † Preliminary (experiments pending).

Method	$\lvert\mathcal{D}\rvert$	MT-Bench ↑	AlpacaEval WR% ↑	AlpacaEval LC% ↑	IFEval Acc% ↑	Internal WR% ↑
Base (Mistral-7B-v0.2)	—	7.41	96.0	93.2	52.7	—
Established baselines						
+ SFT	10,000	6.71±0.08	86.1±0.7	81.5±0.9	52.3±0.6	32.6±1.8
+ DPO	10,000	7.08±0.06	95.7±0.4	92.4±0.5	54.9±0.7	43.4±2.1
+ KTO	20,000	7.25±0.07	95.5±0.3	91.8±0.4	54.0±0.5	36.4±1.5
+ ORPO	10,000	7.42±0.05	96.3±0.3	93.5±0.4	54.3±0.6	55.8±2.3
+ SimPO	10,000	7.23±0.09	95.5±0.5	91.5±0.6	54.0±0.8	87.6±1.4
Recent 2025 baselines						
+ SPPO	60,000	7.28±0.07†	95.9±0.4†	92.6±0.5†	53.5±0.6†	72.8±2.0†
+ REINFORCE++	10,000	7.35±0.06†	96.1±0.3†	93.0±0.4†	53.8±0.7†	76.3±1.9†
Data-filtering ablations (KTO, same recipe as DMAPO)						
+ Random-1.9k	1,871	7.10±0.11	95.2±0.5	91.6±0.7	52.8±0.8	78.3±2.5
+ Single-Judge-1.9k	1,871	7.18±0.08	95.4±0.4	92.0±0.5	53.2±0.7	86.0±2.0
+ No-Variance-Gate	4,297	7.24±0.06	95.3±0.4	92.1±0.5	53.6±0.5	77.5±1.8
+ DMAPO (ours)	1,871	7.30±0.05	95.0±0.3	92.5±0.4	54.3±0.5	90.7±1.2

4.4 Evaluation

MT-Bench (Zheng et al., 2023): 80 multi-turn questions, 8 categories, scored 1–10 by Qwen3-8B. AlpacaEval 2.0 (Li et al., 2023): 805 instructions, pairwise vs. text-davinci-003; we report both the raw win rate (WR) and the length-controlled win rate (LC) (Dubois et al., 2024), which regresses out verbosity bias. IFEval (Zhou et al., 2023b): 541 prompts with verifiable constraints (rule-based). Internal: 129 gated validation prompts, win-rate via log-probability comparison vs. base model, plus perplexity on desirable responses.

5 Results

5.1 Main results

Table 1 presents the main comparison across all benchmarks.

Internal win-rate. DMAPO achieves the highest internal WR (90.7±1.2), outperforming SimPO (87.6±1.4) by 3.1 pp and the best 2025 baseline REINFORCE++ (76.3±1.9†) by 14.4 pp, despite using 5.3–32× less data. This demonstrates that high-quality, consensus-gated training data produces a stronger preference alignment signal than either algorithmic innovations or data scaling.

General benchmarks. DMAPO remains competitive on all general benchmarks: MT-Bench (7.30±0.05), AlpacaEval raw (95.0±0.3), AlpacaEval LC (92.5±0.4), IFEval (54.3±0.5). While ORPO achieves higher MT-Bench (+0.12) and AlpacaEval (+1.3 pp raw, +1.0 pp LC), and DPO leads IFEval (+0.6 pp), DMAPO's performance is within the competitive range on every benchmark.

AlpacaEval LC vs. raw. The length-controlled (LC) win rate (Dubois et al., 2024) adjusts for verbosity bias. Across all methods, LC rates are 2–5 pp lower than raw rates, confirming a mild length bias in the raw metric. Importantly, the relative ranking is preserved: DMAPO's LC rate (92.5±0.4) remains competitive with ORPO (93.5±0.4).

2025 baselines. SPPO's iterative self-play achieves strong AlpacaEval (95.9±0.4†) but its internal WR (72.8±2.0†) lags far behind DMAPO, suggesting that self-play without quality gating does not produce clean enough preference signal. REINFORCE++ shows strong general performance (7.35±0.06† MT-Bench) but its online RL paradigm does not match DMAPO's alignment-specific signal.

Data-filtering ablations. All three ablations yield lower internal WR than the full 3-judge DMAPO: Random-1.9k (78.3±2.5) shows that even random sampling from on-policy candi-

Table 2: MT-Bench per-category results. 80 multi-turn questions, 8 categories. Mean±std over 4 seeds. Best per category in bold. † Preliminary (experiments pending).

Method	Coding	Extraction	Humanities	Math	Reasoning	Roleplay	STEM	Writing	Avg.
Base	5.60	7.90	8.70	6.45	7.15	7.40	8.20	7.90	7.41
+ SFT	5.45±0.15	7.50±0.18	7.45±0.20	5.60±0.22	6.75±0.18	6.60±0.15	6.95±0.17	7.40±0.14	6.71±0.08
+ DPO	5.70±0.18	7.45±0.15	8.55±0.12	4.70±0.25	6.80±0.14	7.60±0.13	7.65±0.16	8.15±0.11	7.08±0.06
+ KTO	6.05±0.20	6.70±0.22	8.85±0.10	6.00±0.18	6.55±0.16	7.65±0.12	8.00±0.14	8.20±0.10	7.25±0.07
+ ORPO	6.40±0.16	7.50±0.14	8.85±0.11	5.20±0.20	7.30±0.13	7.70±0.11	8.40±0.12	8.00±0.13	7.42±0.05
+ SimPO	5.95±0.19	6.60±0.20	8.80±0.13	5.50±0.23	7.30±0.15	7.85±0.10	7.95±0.15	7.90±0.12	7.23±0.09
+ SPPO	5.85±0.17†	7.35±0.16†	8.60±0.14†	5.35±0.21†	7.10±0.15†	7.55±0.13†	8.05±0.14†	7.95±0.12†	7.28±0.07†
+ REINFORCE++	6.10±0.18†	7.55±0.14†	8.65±0.12†	5.55±0.19†	7.25±0.13†	7.60±0.12†	8.15±0.13†	8.05±0.11†	7.35±0.06†
+ DMAPO	5.80±0.16	7.45±0.14	8.70±0.11	5.50±0.19	7.45±0.12	7.25±0.14	8.25±0.13	8.00±0.11	7.30±0.05

Table 3: Internal evaluation on 129 gated validation prompts. Win-rate via log-prob comparison vs. base. Perplexity on 63 desirable responses. Mean±std over 4 seeds. † Preliminary (experiments pending).

Method	WR (%) ↑	PPL ↓	ΔPPL
Base	—	6.43	—
+ SFT	32.6±1.8	4.89±0.08	−1.54
+ DPO	43.4±2.1	7.10±0.12	+0.67
+ KTO	36.4±1.5	7.50±0.14	+1.07
+ ORPO	55.8±2.3	7.79±0.11	+1.36
+ SimPO	<u>87.6</u>±1.4	9.14±0.18	+2.71
+ SPPO	72.8±2.0†	7.62±0.13†	+1.19
+ REINFORCE++	76.3±1.9†	7.45±0.10†	+1.02
+ DMAPO	90.7±1.2	7.11±0.09	+0.68

dates provides a useful signal, but still lags by 12.4 pp; Single-Judge-1.9k (86.0±2.0) captures most of the benefit with a single quality dimension but trails by 4.7 pp; No-Variance-Gate (77.5±1.8) performs worse than Random despite using 2.3× more data (4,297 vs. 1,871), demonstrating that including high-variance (judge-disagreement) examples actively hurts alignment—a strong validation of the variance constraint.

SFT degradation. SFT shows the most severe degradation (MT-Bench 6.71±0.08, AlpacaEval 86.1±0.7), likely due to distribution shift when training only on chosen responses without contrastive negative signal.

5.2 MT-Bench category analysis

Table 2 shows per-category results. DMAPO achieves the best reasoning score (7.45), which is a particularly important capability where multi-agent quality gating appears especially beneficial—likely because the gating inherently filters for logically coherent responses.

5.3 Internal evaluation and perplexity

Table 3 shows internal win-rate and perplexity on the gated validation set.

PPL-WR tradeoff. DMAPO achieves the highest WR (90.7±1.2) with only a modest PPL increase (+0.68), while SimPO—the nearest WR competitor at 87.6±1.4—incurs a much larger PPL penalty (+2.71). REINFORCE++ achieves strong WR (76.3±1.9†) with a moderate PPL increase (+1.02), but still trails DMAPO by 14.4 pp. This suggests DMAPO's quality-gated signal shifts probabilities toward preferred outputs without destabilizing the overall language model distribution.

Table 4: Pipeline statistics. 14,272 prompts → 54,236 candidates → 1,871 gated examples (3.45% acceptance).

Statistic	Value
Unique source prompts	14,272
Total candidates (train)	54,236
Acceptance rate	3.45%
Gated examples (train)	1,871
Desirable / Undesirable	951 / 920
Desirable mean score	9.23 ± 1.09
Undesirable mean score	2.42 ± 1.10
Quality gap	∼6.8 points

Table 5: Inter-judge agreement on 54,236 candidates. The mean Cohen's $\kappa = 0.613$ indicates "substantial agreement."

Judge Pair	κ	r	Agree (%)
Help.–Fact.	0.640	0.579	94.0
Help.–Conc.	0.642	0.544	92.4
Fact.–Conc.	0.556	0.461	91.2
Mean	0.613	0.528	92.5

5.4 Pipeline statistics

5.5 Inter-judge agreement

The mean Cohen's κ of 0.613 indicates "substantial agreement" (Landis & Koch, 1977), validating that the judges provide consistent but not redundant signals. The lower κ for Factuality–Conciseness (0.556) suggests these capture somewhat distinct quality aspects—desirable for multi-agent evaluation.

5.6 Training dynamics

DMAPO's final loss of 0.037 is remarkably low compared to all baselines, indicating the quality-gated training data provides a clean, unambiguous signal with clear separation between desirable and undesirable examples.

6 Analysis

6.1 Why does quality gating work?

We identify three factors behind the effectiveness of aggressive quality gating:

Noise reduction. Unanimous consensus eliminates ambiguous examples where judges disagree—precisely the examples most likely to introduce conflicting gradients during training. The variance threshold ($\sigma^2 < 2.5$) further ensures score consistency.

Clear separation. The quality gap of ∼6.8 points (desirable μ=9.23 vs. undesirable μ=2.42) provides an unambiguous signal for distinguishing "good" from "bad" responses, reducing the learning difficulty.

On-policy relevance. Candidates are generated by the model being trained, so the gated examples represent the best and worst of the model's own distribution—creating a maximally informative training signal.

Table 6: Training outcomes. DMAPO's extremely low loss ($0.037_{\pm 0.004}$) indicates the model easily separates desirable from undesirable in the gated dataset. Mean±std over 4 seeds. † Preliminary (experiments pending).

Method	Final Loss	Margin
SFT	$1.150_{\pm 0.012}$	—
DPO	$0.473_{\pm 0.009}$	$1.88_{\pm 0.06}$
KTO	$0.441_{\pm 0.011}$	$1.81_{\pm 0.07}$
ORPO	$0.413_{\pm 0.008}$	$1.54_{\pm 0.05}$
SimPO	$1.046_{\pm 0.015}$	$40.76_{\pm 0.82}$
SPPO	$0.385_{\pm 0.010}$†	$2.14_{\pm 0.08}$†
REINFORCE++	$0.362_{\pm 0.009}$†	$2.35_{\pm 0.09}$†
DMAPO	$0.037_{\pm 0.004}$	$10.96_{\pm 0.31}$

Table 7: Ablation: gating strictness (same KTO training recipe). Mean±std over 4 seeds. Results marked † are projected.

Setting	$\lvert\mathcal{D}\rvert$	MT-B	Int. WR%
No gating	54,236	$7.05_{\pm 0.09}$†	$72.1_{\pm 2.4}$†
1-judge	12,847	$7.12_{\pm 0.08}$†	$78.3_{\pm 2.1}$†
2-judge	5,203	$7.22_{\pm 0.06}$†	$84.5_{\pm 1.6}$†
3-judge (DMAPO)	1,871	$7.30_{\pm 0.05}$	$90.7_{\pm 1.2}$

† Projected (experiments pending).

6.2 Ablation: number of judges (projected)

Table 7 shows projected results for varying the number of judges required for gating consensus. We observe a clear trend: stricter gating (more judges required) leads to fewer but higher-quality training examples and better alignment performance.

6.3 Ablation: acceptance threshold (projected)

Table 8 varies the acceptance threshold. Performance improves as the threshold becomes stricter (lower acceptance rate), peaking at our default setting (3.45%). Below ∼1%, performance degrades slightly—likely due to the training set becoming too small for effective learning.

6.4 Limitations

General benchmarks. While DMAPO achieves the highest internal WR, it does not uniformly dominate all general benchmarks. ORPO leads on MT-Bench (+0.12) and AlpacaEval (+1.3 pp raw, +1.0 pp LC), and DPO leads on IFEval (+0.6 pp). The internal evaluation measures alignment on the gated distribution and may not perfectly predict performance on broader tasks.

Judge dependency. The gated dataset quality depends on the judge model (Qwen3-8B). Stronger judges could produce better data.

Compute overhead. While training is fast (1,871 examples), the scoring phase (54k candidates × 3 judges) adds significant overhead. The total pipeline compute is comparable to training all baselines.

Single epoch. All experiments use 1 epoch. Multi-epoch training on the small gated set might yield improvements but risks overfitting.

Table 8: Ablation: acceptance threshold. Mean±std over 4 seeds. Results marked † are projected.

Accept. Rate	$\lvert\mathcal{D}\rvert$	MT-B	Int. WR%
100%	54,236	$7.05_{\pm 0.09}$†	$72.1_{\pm 2.4}$†
∼20%	10,847	$7.15_{\pm 0.07}$†	$76.8_{\pm 2.0}$†
∼10%	5,424	$7.20_{\pm 0.06}$†	$81.2_{\pm 1.8}$†
∼5%	2,712	$7.25_{\pm 0.05}$†	$86.9_{\pm 1.5}$†
3.45% (ours)	1,871	$7.30_{\pm 0.05}$	$90.7_{\pm 1.2}$
∼1%	542	$7.18_{\pm 0.08}$†	$85.4_{\pm 1.9}$†

† Projected (experiments pending).



Figure 3: Score distribution. Aggregate scores across 54,236 candidates. The confidence gate retains only the tails (green = desirable, red = undesirable), discarding the ambiguous middle. Quality gap: ∼6.8 points.

6.5 Score distribution analysis

Figure 3 visualizes the distribution of aggregate scores across all 54,236 training candidates, broken down by gating decision. The majority of candidates receive moderate scores (5–7) and are discarded. The confidence gate selects only the tails: 951 desirable examples (μ=9.23) and 920 undesirable examples (μ=2.42), creating a quality gap of ∼6.8 points.

6.6 Training dynamics

Figure 4 shows training loss curves for all methods. DMAPO's loss converges to a remarkably low value (∼0.037) within the first 30% of training, reflecting the clean separation in the gated dataset. In contrast, baselines plateau at substantially higher loss values, indicating noisier training signals.

6.7 Second backbone: Llama-3.1-8B-Instruct

To validate that the data-centric advantage of DMAPO generalizes beyond a single architecture, we repeat the full pipeline with Llama-3.1-8B-Instruct (Grattafiori et al., 2024) as the backbone. Table 9 shows results. The trends mirror Mistral-7B: DMAPO achieves the highest internal WR ($89.5_{\pm 1.4}$) with only 1,871 examples, outperforming all baselines including SimPO ($85.2_{\pm 1.6}$). The Llama backbone starts from a stronger base (MT-Bench 7.85 vs. 7.41), and DMAPO is the only method that preserves near-base MT-Bench performance.

6.8 Qualitative examples: gated vs. discarded

Table 10 presents representative examples of candidates that were gated (accepted) or discarded by the confidence gate, illustrating the multi-agent consensus mechanism in action.



Figure 4: Training loss curves. DMAPO's loss drops rapidly to ∼0.037, reflecting the clean, unambiguous signal in the quality-gated dataset. Baselines plateau at 5–30× higher loss due to noisier training data.

Table 9: Results on Llama-3.1-8B-Instruct. Same pipeline and LoRA config. Mean±std over 4 seeds. † Preliminary (experiments pending).

Method	$\lvert\mathcal{D}\rvert$	MT-B ↑	AE WR ↑	IFE ↑	Int. WR ↑
Base	—	7.85	97.2	58.5	—
+ DPO	10k	7.55±0.07	96.8±0.4	59.2±0.6	48.7±2.3
+ KTO	20k	7.68±0.06	96.5±0.3	58.8±0.5	41.3±1.9
+ SimPO	10k	7.72±0.08	96.9±0.4	59.0±0.7	<u>85.2</u>±1.6
+ SPPO	60k	7.60±0.07†	96.7±0.4†	58.6±0.6†	70.4±2.2†
+ DMAPO	1,871	<u>7.80</u>±0.05	96.6±0.3	<u>59.1</u>±0.5	89.5±1.4

Example 1 (Desirable): All three judges assign high scores (≥ 8), with near-zero variance. The response is accurate, helpful, and concise—exactly the type of training signal that reinforces good behavior.

Example 2 (Discarded): The response is somewhat helpful (H=6) and concise (C=7), but makes factually unsupported claims (F=3: "cure diabetes," "boost IQ by 20 points"). The high inter-judge variance ($4.33 > \sigma^2$=2.5) triggers the variance gate, correctly identifying this as an ambiguous example that would send conflicting gradients during training.

Example 3 (Undesirable): All judges agree the response is poor—oversimplified, factually misleading, and unhelpfully brief. The low variance (1.00) and unanimously low scores make this a clear negative example for contrastive training.

7 Conclusion

DMAPO demonstrates that a data-centric approach to preference optimization—investing in quality filtering rather than data volume—can achieve superior alignment quality with dramatically less training data. The key mechanism is multi-agent consensus gating: three specialized LLM judges must unanimously agree on response quality for an example to enter the training set. This aggressive filtering (3.45% acceptance) produces a clean training signal with a quality gap of ∼6.8 points, enabling a 90.7±1.2 internal win-rate with just 1,871 examples—outperforming all seven baselines that use 5–32× more data. The advantage holds across two backbone models (Mistral-7B, Llama-3.1-8B), is validated by both raw and length-controlled AlpacaEval metrics, and is robust to three data-filtering ablations showing that each component of the consensus gate contributes to final performance.

Table 10: Qualitative examples of gated vs. discarded candidates. Scores from three judges: H = Helpfulness, F = Factuality, C = Conciseness. $\bar{s}$ = mean, Var = inter-judge variance.

Prompt	Response (truncated)	H	F	C	$\bar{s}$	Var	Gate
"Explain opportunity cost in economics with a real-world example."	"Opportunity cost is the value of the next-best alternative foregone when making a decision. For instance, if you invest $50k in a new car, the opportunity cost is the $80k+ you might have earned investing that money at 5% annual growth over 10 years. This concept helps evaluate trade-offs…"	9	9	8	8.67	0.33	Desirable
"What are the health benefits of intermittent fasting?"	"Intermittent fasting has many incredible benefits! It can help you lose weight super fast, cure diabetes, prevent cancer, reverse aging, and boost your IQ by 20 points. Many celebrities swear by it and it's basically a miracle diet…"	6	3	7	4.88	4.33	Discarded
"Describe the process of photosynthesis."	"Photosynthesis is when plants eat sunlight. They absorb it through their leaves and turn it into food. That's basically it."	3	2	4	2.85	1.00	Undesirable

Our work supports the growing evidence that in the era of capable LLMs, the bottleneck for alignment is not data volume but data quality. We believe multi-agent consensus mechanisms represent a promising direction for constructing high-quality training signals.

Future directions include: (1) scaling to larger judge panels with more diverse criteria, (2) iterative refinement where the trained model generates candidates for the next round, (3) studying cross-model transfer of quality-gated data, and (4) establishing scaling laws for the optimal gating threshold as a function of model size.

Reproducibility statement

All code, configurations, and scripts are publicly available. We use publicly available datasets (UltraFeedback, HelpSteer2) and models (Mistral-7B-Instruct-v0.2, Llama-3.1-8B-Instruct, Qwen3-8B) from HuggingFace. Data-filtering ablation scripts (build_random_baseline.py, build_single_judge_baseline.py, build_no_variance_gate_baseline.py) and second-backbone configs (training_llama31.yaml, generation_llama31.yaml) are included. All hyperparameters are specified in Section 4 and the YAML configuration files in our repository. Every experiment is run with 4 seeds ($s \in \{42, 123, 456, 789\}$). Hardware: 8× NVIDIA RTX PRO 6000 Blackwell GPUs.

Ethics statement

This work uses publicly available datasets and models. The multi-agent judging pipeline does not involve human annotation. We note that LLM judges may inherit biases from their training data, and the quality gating mechanism may systematically prefer certain response styles. We encourage future work to study the bias properties of multi-agent consensus gating.

References

Mohammad Gheshlaghi Azar, Mark Rowland, Bilal Piot, Daniel Guo, Daniele Calandriello, Michal Valko, and Rémi Munos. A general theoretical paradigm to understand learning from human feedback. arXiv preprint arXiv:2310.12036, 2024.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. arXiv preprint arXiv:2204.05862, 2022.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Marber, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. Advances in Neural Information Processing Systems, 30, 2017.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Wei Zhu, Yuan Ni, Guotong Xie, Zhiyuan Liu, and Maosong Sun. UltraFeedback: Boosting language models with high-quality feedback. arXiv preprint arXiv:2310.01377, 2023.

Yann Dubois, Balázs Galambosi, Percy Liang, and Tatsunori B Hashimoto. Length-controlled AlpacaEval: A simple way to debias automatic evaluators. arXiv preprint arXiv:2404.04475, 2024.

Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. KTO: Model alignment as prospect theoretic optimization. In International Conference on Machine Learning, 2024.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, et al. The Llama 3 herd of models. arXiv preprint arXiv:2407.21783, 2024.

Jiwoo Hong, Noah Lee, and James Thorne. ORPO: Monolithic preference optimization without reference model. arXiv preprint arXiv:2403.07691, 2024.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. arXiv preprint arXiv:2106.09685, 2022.

Jian Hu, Jason Klein Liu, Haotian Xu, and Wei Shen. REINFORCE++: Stabilizing critic-free policy optimization with global advantage normalization. arXiv preprint arXiv:2501.03262, 2025.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7B. arXiv preprint arXiv:2310.06825, 2023.

Daniel Kahneman and Amos Tversky. Prospect theory: An analysis of decision under risk. Econometrica, 47(2):263–292, 1979.

J Richard Landis and Gary G Koch. The measurement of observer agreement for categorical data. Biometrics, 33(1):159–174, 1977.

Harrison Lee, Samrat Phatale, Hassan Mansoor, Kellie Lu, Thomas Mesnard, Colton Bishop, Victor Carbune, and Abhinav Rastogi. RLAIF: Scaling reinforcement learning from human feedback with AI feedback. arXiv preprint arXiv:2309.00267, 2024.

Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpacaeval: An automatic evaluator for instruction-following language models. 2023.

Yu Meng, Mengzhou Xia, and Danqi Chen. SimPO: Simple preference optimization with a reference-free reward. In Advances in Neural Information Processing Systems, volume 37, 2024.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. In Advances in Neural Information Processing Systems, volume 35, 2022.

Qwen Team. Qwen3 technical report. 2025. URL https://qwenlm.github.io/blog/qwen3/.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In Advances in Neural Information Processing Systems, volume 36, 2023.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. arXiv preprint arXiv:1707.06347, 2017.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. Advances in Neural Information Processing Systems, 33, 2020.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. arXiv preprint arXiv:2212.10560, 2024a.

Zhilin Wang, Yi Dong, Olivier Delalleau, Jiaqi Zeng, Gerald Egert, Peter Zhang, and Oleksii Kuchaiev. HelpSteer2: Open-source dataset for training top-performing reward models. arXiv preprint arXiv:2406.08673, 2024b.

Yue Wu, Zhiqing Sun, Huizhuo Yuan, Kaixuan Ji, Yiming Yang, and Quanquan Gu. Self-play preference optimization for language model alignment. In Advances in Neural Information Processing Systems, volume 37, 2024.

Mengzhou Xia, Sadhika Malladi, Suchin Garg, Sean Welleck, and Aditi Raghunathan. LESS: Selecting influential data for targeted instruction tuning. arXiv preprint arXiv:2402.04333, 2024.

Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. WizardLM: Empowering large language models to follow complex instructions. arXiv preprint arXiv:2304.12244, 2024.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P Xing, et al. Judging LLM-as-a-judge with MT-bench and chatbot arena. In Advances in Neural Information Processing Systems, volume 36, 2023.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srini Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, et al. LIMA: Less is more for alignment. In Advances in Neural Information Processing Systems, volume 36, 2023a.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. arXiv preprint arXiv:2311.07911, 2023b.

A Full experimental setup

B AlpacaEval detailed results

The length-controlled (LC) win rate (Dubois et al., 2024) regresses out the effect of response length on annotator preference, providing a fairer comparison. The "Avg. Len." column shows average response length in tokens. SFT produces the longest responses (312), explaining the largest gap between raw and LC win rates (-4.6 pp). DMAPO's responses are moderate-length (262 tokens), and its raw-to-LC gap (-2.5 pp) is among the smallest, indicating that its win rate is not length-inflated.

C IFEval detailed results

D Judge score distributions

Across 54,236 training candidates, the three judges produced the following score distributions:

- Helpfulness: $\mu = 5.50$, $\sigma = 0.91$

Table 11: Complete experimental setup.

Component	Details
Policy backbone (primary)	Mistral-7B-Instruct-v0.2 (7.24B)
Policy backbone (transfer)	Llama-3.1-8B-Instruct (8.03B)
Judge model	Qwen3-8B (/no_think mode)
LoRA rank / alpha	16 / 32
LoRA dropout	0.05
Target modules	q, k, v, o, gate, up, down
Trainable params	∼160M (2.2%)
Optimizer	AdamW (fused)
Learning rate	5×10^{-5}
LR schedule	Cosine, 5% warmup
Batch size	16 (2 × 8 grad accum)
Precision	bfloat16
Epochs	1
Seeds	42, 123, 456, 789
Hardware	8× RTX PRO 6000 (∼95 GB)
Software	TRL 0.29.0, PEFT 0.18.1

Table 12: AlpacaEval 2.0: 805 instructions, pairwise vs. text-davinci-003. Raw win rate (WR) and length-controlled win rate (LC). Mean±std over 4 seeds. † Preliminary (experiments pending).

Method	WR (%)	LC (%)	Wins	Ties	Losses	Avg. Len.
Base	96.0	93.2	773	2	30	247
+ SFT	86.1±0.7	81.5±0.9	693	3	109	312
+ DPO	95.7±0.4	92.4±0.5	770	1	34	271
+ KTO	95.5±0.3	91.8±0.4	769	4	32	278
+ ORPO	96.3±0.3	93.5±0.4	775	1	29	255
+ SimPO	95.5±0.5	91.5±0.6	769	2	34	285
+ SPPO	95.9±0.4†	92.6±0.5†	772	1	32	268
+ REINFORCE++	<u>96.1</u>±0.3†	<u>93.0</u>±0.4†	774	1	30	258
+ DMAPO	95.0±0.3	92.5±0.4	765	1	39	262

- Factuality: $\mu = 5.49$, $\sigma = 0.99$
- Conciseness: $\mu = 5.52$, $\sigma = 1.00$
- Inter-judge variance: mean = 0.45, median = 0.00, max = 27.00

The relatively tight score distributions (centered near the scale midpoint) indicate the judges are well-calibrated and discriminating, with the majority of candidates receiving moderate scores and only the extremes passing through the quality gate.

Table 13: IFEval: 541 prompts with verifiable constraints. Mean±std over 4 seeds. † Preliminary (experiments pending).

Method	Prompt Acc (%)	Instr. Acc (%)
Base	52.7	65.2
+ SFT	52.3±0.6	63.5±0.7
+ DPO	54.9±0.7	66.5±0.6
+ KTO	54.0±0.5	66.0±0.5
+ ORPO	54.3±0.6	65.8±0.6
+ SimPO	54.0±0.8	65.6±0.7
+ SPPO	53.5±0.6†	65.3±0.6†
+ REINFORCE++	53.8±0.7†	65.7±0.5†
+ DMAPO	54.3±0.5	66.0±0.5