

# Discrete Laplacian for Bounded Biharmonic Weights

## Supplementary Material for HW3

October 2020

The goal of this cheetsheet is to derive the discrete version of laplacian operator for tetrahedral meshes, so that we can compute the bounded biharmonics weights for a mesh based on:

$$\min_{\omega} \sum_{j=1}^m \frac{1}{2} \int_{\Omega} \|\Delta \omega_j\|^2 dV$$

where  $\omega_j \in \mathcal{R}^n$ . As the energy for each  $\omega_j$  is independent, we use  $\omega$  instead of  $\omega_j$  in the following text.

## 1 Weak Formulation

First we change the problem setting to that we want to solve the following equation:

$$f = \Delta \omega$$

We want to compute  $f$  for each point in the space to be the laplacian of our weight function. Because we are going to solve it in a discrete domain, we have to take some weak formulation for that.

Instead of solving  $f = \Delta \omega$ , we try to find a function  $f$ , so that for any function  $v$ ,

$$\int_{\Omega} v f = \int_{\Omega} v \Delta \omega \quad (1)$$

By Green's Identity:

$$\int_{\Omega} v \Delta \omega = \int_{\partial \Omega} v \nabla \omega - \int_{\Omega} \nabla \omega \nabla v$$

We assume the function  $v$  has zero value on the boundary of the domain, so that

$$\int_{\Omega} v \Delta \omega = - \int_{\Omega} \nabla \omega \nabla v$$

By discretizing the space with first order finite element, we choose the linear hat function as basis function. The value of a point inside each triangle can be approximate by a linear combination of the values on three vertices. For example, if we know the value of  $f(x)$  on each vertex,  $f(v_i) = a_i$ , we can approximate the function value inside the triangle as  $f(x) = \sum_i a_i \phi_i(x)$ , where  $\phi_i(x)$  is the coefficient. We can do such finite element descritization for our weight function  $\omega$ , function  $v$  and our goal function  $f$ .

For the left hand of equation (1), we discretize it as

$$\int_{\Omega} v f = \int_{\Omega} \sum_i v_i \phi_i \sum_j f_j \phi_j = \int_{\Omega} \sum_i \sum_j v_i f_j \phi_i \phi_j = v^{\top} M f$$

where  $M_{ij} = \int_{\Omega} \phi_i \phi_j dV$ .

For the right hand of equation (2), we discretize it as

$$\int_{\Omega} v \Delta \omega = - \int_{\Omega} \nabla \omega \nabla v = - \int_{\Omega} (\sum_i \omega_i \nabla \phi_i) (\sum_j v_j \nabla \phi_j) = v^{\top} L \omega$$

where  $L_{ij} = - \int_{\Omega} \nabla \phi_i \nabla \phi_j dV$

Because this hold for any function  $v$ , we have

$$Mf = L\omega \Rightarrow f \approx M^{-1}L\omega$$

(Note: this is an approximating way to derive the laplacian operator, strictly derivation needs a much more complicated technique called mixed finite element).

So given the discretization basis functions  $\phi$  and the weights  $\omega$ , we can compute the laplacian as

$$\Delta\omega = M^{-1}L\omega$$

Now, let's look at how to compute the matrices  $M$  and  $L$ .

## 2 Triangle Surface Mesh

For triangle surface mesh, the derivation for laplacian operator can be found in [laplacian operator]. Please read it before deriving for tetrahedral mesh.

## 3 Tetrahedral Mesh

### 3.1 Mass Matrix $M$

As  $M_{ij} = \int_{\Omega} \phi_i \phi_j dV$ , it involved the product of  $h_i$  and  $h_j$ , which would be quadratic. We usually approximate the mass matrix by a diagonal lumped mass matrix instead of compute the exact matrix.


The most simple approach is that the value of the  $i$ th diagonal element is the surrounding volume of  $i$ th vertex.

$$M_{ii} = \sum_{T \in \mathcal{N}(v_i)} \frac{1}{4} V_T$$

where  $\mathcal{N}(v_i)$  is the tetrahedron set in the  $i$ th vertex's neighbourhood and  $V_T$  is the volume of that tetrahedron.

### 3.2 Cotangent Laplacian Matrix $L$

The matrix  $L_{ij} = - \int_{\Omega} \nabla \phi_i \nabla \phi_j dV$  is well defined. Since  $\phi_i$  are piecewise linear functions in a tetrahedron,  $\nabla \phi_i$  is a constant vector inside a tetrahedron, and thus  $\int_{\Omega} \nabla \phi_i \nabla \phi_j$  yields one scaler per element.



Let's define some notation first. We label the four faces ( $F$ ) of the tet from 0 to 4. The face 0 is opposite to vertex  $i$  and the face 3 is opposite to vertex  $j$ .  $S_k$  represents the area of the face  $k$  and  $\theta_{ij}$  is the dihedral angle between face  $i$  and face  $j$ .  $l_{ij}$  is the length of the edge between face  $i$  and face  $j$ .

By following the derivation for the triangle mesh, we first evaluate the gradient  $\nabla\phi_i$  in this tetrahedron. we know  $\phi_i(i) = 1$  and  $\phi_i(j) = \phi_i(k) = \phi_i(l) = 0$ . Because  $\nabla\phi_i$  is constant inside the tet, we have

$$\begin{aligned}\nabla\phi_i \cdot (v_i - v_j) &= 1 \\ \nabla\phi_i \cdot (v_i - v_k) &= 1 \\ \nabla\phi_i \cdot (v_i - v_l) &= 1\end{aligned}$$

This yields:

$$\begin{aligned}\nabla\phi_i \cdot (v_j - v_k) &= 0 \\ \nabla\phi_i \cdot (v_l - v_k) &= 0\end{aligned}$$

which means  $\nabla\phi_i \perp F_0$ , which is the direction of the gradient.

Then we compute the magnitude:

$$\begin{aligned}1 &= \nabla\phi_i \cdot (v_i - v_k) \\ &= \|\nabla\phi_i\| \cdot (\text{height on } F_0) \\ &= \|\nabla\phi_i\| \cdot \frac{3V}{S_0}\end{aligned}\tag{2}$$

So we get

$$\|\nabla\phi_i\| = \frac{S_0}{3V}\tag{3}$$

Now let's compute the element of matrix  $L$ . There are two cases, the first case is  $i \neq j$  and  $i$  and  $j$  is connected by an edge. And the second case is  $i = j$ . We consider the contribution from one tet to  $L_{ij}$ .

For the first case,  $i \neq j$ .

$$\begin{aligned}\int_{tet} \nabla\phi_i \nabla\phi_j dV &= V \nabla\phi_i \cdot \nabla\phi_j \\ &= -V \|\nabla\phi_i\| \|\nabla\phi_j\| \cos \theta_{03} \\ &= -V \left(\frac{S_0}{3V}\right) \left(\frac{S_3}{3V}\right) \cos \theta_{03} \\ &= -\frac{1}{9V} S_0 S_3 \cos \theta_{03} \\ &= -\frac{1}{6} l_{03} \cot \theta_{03}\end{aligned}\tag{4}$$

The last step is derived by applying the volume formula from Wolfram.

$$V = \frac{2}{3l_{03}} S_0 S_3 \sin \theta_{03}$$

For the second case,  $i = j$ .

$$\begin{aligned}\int_{tet} \nabla\phi_i \nabla\phi_j dV &= V \|\nabla\phi_i\|^2 \\ &= V \left(\frac{S_0}{3V}\right)^2 \\ &= \frac{S_0^2}{9V} \\ &= \frac{1}{9V} S_0 (S_1 \cos \theta_{01} + S_2 \cos \theta_{02} + S_3 \cos \theta_{03}) \\ &= \frac{1}{6} (l_{01} \cot \theta_{01} + l_{02} \cot \theta_{02} + l_{03} \cot \theta_{03})\end{aligned}\tag{5}$$

By combining equation (4) and (5), and considering all tets, we can get:

$$L_{ij} = \begin{cases} \sum_{e \in \mathcal{O}(ij)} \frac{1}{6} l_e \cot \theta_e & \text{if edge } ij \text{ exists} \\ -\sum_{i \neq j} L_{ij} & i = j \\ 0 & \text{otherwise} \end{cases}\tag{6}$$

$e \in \mathcal{O}(ij)$  means the edge  $e$  is opposite to edge  $ij$  in a tetrahedron.

## 4 Bounded Biharmonic Weights Optimization

Once we have the matrices ready, we can discretize our energy formula as

$$\begin{aligned}\min_{\omega} \sum_{j=1}^m \frac{1}{2} \int_{\Omega} \|\Delta \omega_j\|^2 dV &= \min_{\omega} \sum_{j=1}^m \frac{1}{2} \int_{\Omega} (M^{-1} L \omega_j)^{\top} M (M^{-1} L \omega_j) \\ &= \min_{\omega} \frac{1}{2} \sum_{j=1}^m \omega_j^{\top} (L M^{-1} L) \omega_j\end{aligned}\tag{7}$$