

Problem Set #3

[返回第 3 周课程](#)

4/5 得分 (80%)

未认证 本次测验未认证。您必须以认证方式重新完成测验，才有资格获得课程证书。



让您的成就得到认可。“课程证书帮助您得到求职所需的认可，教学内容帮助您”掌握工作所需技能。您不仅能提升自己的价值，而且能让自己的价值得到认可。” -

Peter B., 美国, 软件开发人员

展示你的成就！获取课程证书！ \$79 USD >



1 / 1 分

1.

Which of the following is true for our dynamic programming algorithm for computing a maximum-weight independent set of a path graph? (Assume there are no ties.)

- ☐ If a vertex is excluded from the optimal solution of a subproblem, then it is excluded from the optimal solutions of all bigger subproblems.
- ☐ The algorithm always selects the maximum-weight vertex.
- ☐ As long as the input graph has at least two vertices, the algorithm never selects the minimum-weight vertex.
- ☒ If a vertex is excluded from the optimal solution of two consecutive subproblems, then it is excluded from the optimal solutions of all bigger subproblems.



正确答案

By induction, since the optimal solution to a subproblem depends only on the solutions of the previous two subproblems.



0 / 1 分

2.

Consider a variation of the Knapsack problem where we have two knapsacks, with integer capacities W_1 and W_2 . As usual, we are given n items with positive values and positive integer weights. We want to pick subsets S_1, S_2 with maximum total value (i.e., $\sum_{i \in S_1} v_i + \sum_{i \in S_2} v_i$) such that the total weights of S_1 and S_2 are at most W_1 and W_2 , respectively. Assume that every item fits in either knapsack (i.e., $w_i \leq \min\{W_1, W_2\}$ for every item i). Consider the following two algorithmic approaches. (1) Use the algorithm from lecture to pick a max-value feasible solution S_1 for the first knapsack, and then run it again on the remaining items to pick a max-value feasible solution S_2 for the second knapsack. (2) Use the algorithm from lecture to pick a max-value feasible solution for a knapsack with capacity $W_1 + W_2$, and then split the chosen items into two sets S_1, S_2 that have size at most W_1 and W_2 , respectively. Which of the following statements is true?

- ☐ Neither algorithm is guaranteed to produce an optimal feasible solution to the original problem.
- ☐ Algorithm (1) is guaranteed to produce an optimal feasible solution to the original problem but algorithm (2) is not.
- ☐ Algorithm (2) is guaranteed to produce an optimal feasible solution to the original problem but algorithm (1) is not.
- ☒ Algorithm (1) is guaranteed to produce an optimal feasible solution to the original problem provided $W_1 = W_2$.



不正确回答

There's a counterexample with 4 items.



1 / 1 分

3.

Recall our dynamic programming algorithm for computing the maximum-weight independent set of a path graph. Consider the following proposed extension to more general graphs. Consider an undirected graph with positive vertex weights. For a vertex v , obtain the graph $G'(v)$ by deleting v and its incident edges from G , and obtain the graph $G''(v)$ from G by deleting v , its neighbors, and all of the corresponding incident edges from G . Let $OPT(H)$ denote the value of a maximum-weight independent set of a graph H . Consider the formula $OPT(G) = \max\{OPT(G'(v)), w_v + OPT(G''(v))\}$, where v is an arbitrary vertex of G of weight w_v . Which of the following statements is true?

- ☐ The formula is correct in path graphs but is not always correct in trees.
- ☒ The formula is always correct in trees, and it leads to an efficient dynamic programming algorithm.



正确答案

Indeed. What running time can you get?

- ☐ The formula is always correct in trees, but does not lead to an efficient dynamic programming algorithm.
- ☐ The formula is always correct in general graphs, and it leads to an efficient dynamic programming algorithm.



1 / 1 分

4.

Recall the dynamic programming algorithms from lecture for the Knapsack and sequence alignment problems. Both fill in a two-dimensional table using a double-for loop. Suppose we reverse the order of the two for loops. (I.e., cut and paste the second for loop in front of the first for loop, without otherwise changing the text in any way.) Are the resulting algorithms still well defined and correct?

- ☐ The Knapsack algorithm remains well defined and correct after reversing the order of the for loops, but the sequence alignment algorithm does not.
- ☒ Both algorithms remain well defined and correct after reversing the order of the for loops.

正确回答

The necessary subproblem solutions are still available for constant-time lookup.

- ☐ Neither algorithm remains well defined and correct after reversing the order of the for loops.
 - ☐ The sequence alignment algorithm remains well defined and correct after reversing the order of the for loops, but the Knapsack algorithm does not.
-



1 / 1 分

5.

Consider an instance of the optimal binary search tree problem with 7 keys (say 1,2,3,4,5,6,7 in sorted order) and frequencies

$w_1 = .05$, $w_2 = .4$, $w_3 = .08$, $w_4 = .04$, $w_5 = .1$, $w_6 = .1$, $w_7 = .23$.

What is the minimum-possible average search time of a binary search tree with these keys?

☒ 2.18



正确回答

☐ 2.42

☐ 2.08

☐ 2.9