Problem Set #1

返回第1周课程



5/5 得分(100%)

未认证 本次测验未认证。您必须以认证方式重新完成测验,才有资格获得课程证书。



让您的成就得到认可。"课程证书帮助您得到求职所需的认可,教学内容帮助您"掌握工作所需技能。您不仅能提升自己的价值,而且能让自己的价值得到认可。"-

Peter B., 美国, 软件开发人员

展示你的成就! 获取课程证书! \$79 USD >



1/1分

1.

We are given as input a set of n requests (e.g., for the use of an auditorium), with a known start time s_i and finish time t_i for each request i. Assume that all start and finish times are distinct. Two requests conflict if they overlap in time --- if one of them starts between the start and finish times of the other. Our goal is to select a maximum-cardinality subset of the given requests that contains no conflicts. (For example, given three requests consuming the intervals [0,3], [2,5], and [4,7], we want to return the first and third requests.) We aim to design a greedy algorithm for this problem with the following form: At each iteration we select a new request i, including it in the solution-so-far and deleting from future consideration all requests that conflict with i.

Which of the following greedy rules is guaranteed to always compute an optimal solution?



At each iteration, pick the remaining request with the fewest number of conflicts with other remaining requests (breaking ties arbitrarily).

0	At each iteration, pick the remaining request with the earliest finish time.
indu	回答 R_j denote the requests with the j earliest finish times. Prove by ction on j that this greedy algorithm selects the maximumber of non-conflicting requests from S_j .
	At each iteration, pick the remaining request which requires the least time (i.e., has the smallest value of $t_i - s_i$) (breaking ties arbitrarily).
	At each iteration, pick the remaining request with the earliest start time.
~	1/1分
and a control video let the late that the	given as input a set of n jobs, where job j has a processing time p_j deadline d_j . Recall the definition of completion times C_j from the ectures. Given a schedule (i.e., an ordering of the jobs), we define eness l_j of job j as the amount of time C_j-d_j after its deadline e job completes, or as 0 if $C_j \leq d_j$. Our goal is to minimize the um lateness, $\max_j l_j$.
the ma	of the following greedy rules produces an ordering that minimizes ximum lateness? You can assume that all processing times and nes are distinct.
	Schedule the requests in increasing order of processing time p_j
	Schedule the requests in increasing order of the product $d_j \cdot p_j$
	None of the other answers are correct.

正确回答

Proof by an exchange argument, analogous to minimizing the weighted sum of completion times.

Schedule the requests in increasing order of deadline $d_{\it j}$



3

Consider an undirected graph G=(V,E) where every edge $e\in E$ has a given cost c_e . Assume that all edge costs are positive and distinct. Let T be a minimum spanning tree of G and P a shortest path from the vertex s to the vertex t. Now suppose that the cost of every edge e of G is increased by 1 and becomes c_e+1 . Call this new graph G'. Which of the following is true about G'?

T must be a minimum spanning tree but P may not be a shortest s-t path.

正确回答

The positive statement has many proofs (e.g., via the Cut Property). For the negative statement,

think about two different paths from s to t that contain a different number of edges.

- T is always a minimum spanning tree and P is always a shortest s-t path.
- T may not be a minimum spanning tree and P may not be a shortest s-t path.
- T may not be a minimum spanning tree but P is always a shortest s-t path.



1/1分

4.

Suppose T is a minimum spanning tree of the connected graph G. Let H be a connected induced subgraph of G. (I.e., H is obtained from G by taking some subset $S \subseteq V$ of vertices, and taking all edges of E that have both endpoints in S. Also, assume H is connected.) Which of the following is true about the edges of T that lie in H? You can assume that edge costs are distinct, if you wish. [Choose the strongest true statement.]

	For every ${\cal G}$ and ${\cal H}$, these edges form a spanning tree (but not necessary minimum-cost) of ${\cal H}$
	For every G and H and spanning tree T_H of H , at least one of these edges is missing from T_H
0	For every ${\cal G}$ and ${\cal H}$, these edges are contained in some minimum spanning tree of ${\cal H}$
	回答 $oxedsymbol{f}$ via the Cut Property (cuts in G correspond to cuts in H with fewer crossing edges).
	For every ${\cal G}$ and ${\cal H}$, these edges form a minimum spanning tree of ${\cal H}$
~	1/1分
A <i>minir</i> the ma	er an undirected graph $G=(V,E)$ where edge $e\in E$ has cost c_e and c_e and c_e and c_e and c_e and c_e and c_e are that minimizes c_e and c_e are distinct. So where c_e are distinct.
	A minimum bottleneck spanning tree is always a minimum spanning tree but a minimum spanning tree is not always a minimum bottleneck spanning tree.
	A minimum bottleneck spanning tree is not always a minimum spanning tree, but a minimum spanning tree is always a minimum bottleneck spanning tree.
正确回	

For the positive statement, recall the following (from correctness of Prim's algorithm): for every edge e of the MST, there is a cut (A,B) for which e is the cheapest one crossing it. This implies that every other spanning tree has maximum edge cost at least as large. For the negative statement, use a triangle with one extra high-cost edge attached.

A minimum bottleneck spanning tree is not always a minimum spanning tree and a minimum spanning tree is not always a minimum bottleneck spanning tree.
A minimum bottleneck spanning tree is always a minimum spanning tree and a minimum spanning tree is always a minimum bottleneck spanning tree.

