

Runyang Tian

📍 San Diego, CA 📩 r3tian@ucsd.edu ☎ 858-405-7762 🌐 Homepage

Education

University of California San Diego	<i>09/2024-06/2026</i>
◦ M.S. in Electrical Engineering, GPA: 3.5/4.0	
◦ Courses: Computer Architecture, VLSI for ML, VLSI Physical Design, VLSI Testing, CMOS IC Lab	
Xi'an Jiaotong University	<i>09/2020-06/2024</i>
◦ B.E. in Microelectronic, GPA: 3.5/4.0	
◦ Courses: Digital Integrated Circuits, Analog Integrated Circuits, C Programming, Computer Architecture	

Skills

Languages: Verilog, System Verilog, Python, C/C++, MATLAB, SPICE, TCL

Tools: Cadence Virtuoso, Cadence Innovus, Synopsys DC, Altium, Xcelium, Vivado, HSpice, Linux

Publications

- Y. Chen*, R. Tian*, Y. Pan, Z. Li, W. Xu, T. Rosing, “CHIME: Chiplet-based Heterogeneous Near-Memory Acceleration for Edge Multimodal LLM Inference,” DATE, 2026.
- Y. Chen*, Z. Li*, K. Fan, R. Tian, J. Hsu, M. Zhou, T. Rosing, “RAPID-Graph: Recursive All-Pairs Shortest Paths Using Processing-in-Memory for Dynamic Programming on Graph,” DATE, 2026.

Research Experience

- Heterogeneous Near-Memory Acceleration for Edge LLM Inference** Advisor: Tajana Rosing
◦ Proposed a compiler-supported near-memory accelerator that integrates monolithic 3D DRAM (low-latency, high-endurance) and 3D RRAM (high-density, low-refresh-energy) chiplets.
◦ Proposed a mapping and scheduling framework for heterogeneous near-memory kernels.
◦ Built a in-house cycle- and energy-accurate simulator to evaluate performance.
- Sparse-Aware LUT-Based NMP Acceleration for Edge LLM Inference** Advisor: Tajana Rosing
◦ Simulated and analyzed performance of MAC-basd/LUT-basd NMP/PIM acceleration methods.
◦ Developed LUT-based Processing Engine (LUT-PE) in NMP accelerator that leverages mixed-precision lookup to avoid redundant operations.
◦ Designed Progressive Token Elimination Unit (PTEU) to dynamically prune tokens during inference.
- Recursive All-Pairs Shortest Paths Using PIM on Graph** Advisor: Tajana Rosing
◦ Developed RTL modules and synthesized using 40nm CMOS technology, including a custom permutation unit, min-comparator tree, and controller.
◦ Contributed to a PIM-based system for all-pairs shortest paths with algorithm–architecture co-optimization.
- In-Storage Database Search Using HDC on Ferroelectric NAND Flash** Advisor: Tajana Rosing
◦ Design peripherals to implement binding (XOR) and arithmetic operations (SUM, AVG, MIN, MAX).
◦ Modeled and optimized the energy efficiency of the peripherals.
- Design and Optimization of Optoelectronic Interface Driver** Advisor: Prof. Dan Li
◦ Designed a MZI-based optical DAC with binary-weighted phase control and LUT-based linearity optimization unit
◦ Developed a linear driver array driving an 8-bit optical DAC to operate at 1GHz, while achieving electronic-optical speed matching with TSMC 28nm CMOS process.
◦ Reduced linearity from 10.8% to 1.8%, improved INL from 26 to 5 LSB, the power was 9.81mW.
◦ Outstanding Graduation Thesis Nomination.

Projects

9-bit SAR ADC Design and Tape-Out	03/2025-05/2025, 09/2025-11/2025
<ul style="list-style-type: none">○ Designed the schematic and layout applying dummy devices, common centroid pattern, and power shielding to minimize mismatch and noise. Monte Carlo simulation showed 2mV offset and 0.01% capacitor mismatch.○ Developed the SAR controller in Verilog, synthesized using Genus and PnR with Innovus.○ Designed PCB for testing the chip, includes a Anti-Alias Filter, SE to DE converter.	
Reconfigurable 2D Systolic-Array NPU Design	01/2025-03/2025
<ul style="list-style-type: none">○ FIFO, SRAM, and special function unit (SFU), supporting convolution, matrix multiplication, normalization, and ReLU operators.○ FIFOs, and developed control logic to switch between weight-stationary and output-stationary modes.○ Completed synthesis, STA, and place-and-route (PnR) in TSMC 65 nm technology, optimizing PPA through multi-cycle paths, pipelining, and clock gating.	
TinyCPU: Single-Stage Single-Issue 9-bit Microprocessor	03/2025-06/2025
<ul style="list-style-type: none">○ Developed an accumulator-based architecture to meet compact 9-bit instruction encoding constraint.○ Defined a custom ISA that supports arithmetic, logic, branch, jump and load-store operations in six instruction formats (SR, LS, SI, DR, RI, J).○ Designed control logic and datapath, implementing floating-point to fixed-point conversion program on TinyCPU.	
FAST-9 Corner Detection Algorithm Accelerator	07/2023-08/2023
<ul style="list-style-type: none">○ Developed RTL design for buffer, detection and non-maximum suppression modules to process image.○ Designed corner detection as a 4-stage pipeline (difference value, absolute value, threshold compare, result) to improve throughput.	