6.

```
const http = require('http');

const server = http.createServer((req, res) => {
 res.writeHead(200, { 'Content-Type': 'text/plain' });
 res.end('Hello, World!');
});

const PORT = 3000;

server.listen(PORT, () => {
 console.log(` Server running at http://localhost:${PORT}` );
});
```

7.

```
const express = require('express');
const app = express();
const port = 3000;
app.use(express.json());

let users = [
 { id: 1, name: 'Alice', age: 30 },
 { id: 2, name: 'Bob', age: 25 }
];

// Create user
app.post('/addusers', (req, res) => {
 const newUser = { id: users.length + 1, ...req.body };
 users.push(newUser);
 res.status(201).json(newUser);
});

// Get all users
app.get('/allusers', (req, res) => {
 res.json(users);
});
app.listen(port, () => console.log(` Server running on port ${port}` ));
```

8.

```
const express = require('express');
const app = express();
const port = 3000;

// Middleware to parse incoming JSON data in requests
app.use(express.json());

// Simple in-memory data set
let users = [
  { id: 1, name: 'John Doe', age: 30 },
  { id: 2, name: 'Jane Doe', age: 25 },
  { id: 3, name: 'Jim Brown', age: 35 },
];

// **GET** - Fetch all users
app.get('/users', (req, res) => {
  res.status(200).json(users);
});

// **PUT** - Update user by ID
app.put('/users/:id', (req, res) => {
  const userId = parseInt(req.params.id);
  const updatedData = req.body;

  // Find the user by ID
  let user = users.find(u => u.id === userId);

  if (!user) {
    return res.status(404).send({ error: 'User not found' });
  }

  // Update user data
  user.name = updatedData.name || user.name;
  user.age = updatedData.age || user.age;

  res.status(200).json(user);
});

// **DELETE** - Delete user by ID
app.delete('/users/:id', (req, res) => {
  const userId = parseInt(req.params.id);

  // Find the index of the user
```

```
  const userIndex = users.findIndex(u => u.id === userId);

  if (userIndex === -1) {
    return res.status(404).send({ error: 'User not found' });
  }

  // Remove the user from the array
  const deletedUser = users.splice(userIndex, 1);

  res.status(200).json({ message: 'User deleted successfully', deletedUser });
});

// Start the server
app.listen(port, () => {
  console.log(`Server running on http://localhost:${port}`);
});
```

9.

(index.js)

```
// Import the express module
const express = require('express');

// Create an instance of an Express application
const app = express();

// Set the port for the server to listen on
const PORT = process.env.PORT || 3000;

// Serve static files from the "public" directory
app.use(express.static('public'));

// Set up basic routing
app.get('/', (req, res) => {
  res.send('Welcome to the homepage!');
});

app.get('/about', (req, res) => {
  res.send('This is the About page');
});

// Start the server
app.listen(PORT, () => {
```

```
  console.log(`Server is running on http://localhost:${PORT}`);
});
```

(Index.html)

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Express Server</title>
</head>
<body>
  <h1>Welcome to the Express Server!</h1>
  <p>This is a static HTML file served by Express.js</p>
</body>
</html>
```

4.

```
<!DOCTYPE html>
<html>
<head>
 <title>Button click</title>
</head>
<body>
  <h1>click this button to change colour  </h1>
  <button onclick="show()">change</button>
  <script>
    function show(){
      document.body.style.backgroundColor="red";
    }
  </script>
</body>
</html>
```

1.

```
<html>
  <head>
    <title>My first program</title>
  </head>
  <body>
    <script>
      let x=10;
      let y=2;
      let add=x+y;
      let sub=x-y;
      let mul=x*y;
      let div=x/y;
      let rem=x%y;

      document.write("<h1>addition is "+add);
      document.write("<br>subtraction is "+sub);
      document.write("<br>multiplication is "+mul);
      document.write("<br>division is "+div);
      document.write("<br>reminder is "+rem+"</h1>");
     </script>
  </body>
</html>
```

3

```
<!DOCTYPE html>
<html>
<head>
  <title>Document</title>
</head>
<body>
  <script>
    function checkprime() {
      let n = 7;
      for (i = 2; i < n; i++) {
        if (n % i == 0) {
          document.write("Not a prime number....");
          break;
        }
```

```
        }
        if (n == i) {
           document.write("prime");
        }
      }
      checkprime();
   </script>
</body>
</html>
```