

Product Data Sheet

GW63527

IEC 309 HP range





A range of trailing and fixed plugs and socket-outlets for industrial use, complying with the dimensional and performance standards unified at International level (IEC 60309) and assimilated by the European Standards (EN 60309) and Italian Standards (CEI 23-12). Socket-outlets and plugs with a rated current of 63 and 125A are equipped with an extra pilot contact (CP) for creating an electric interlock. The range is completed with 90° fixed plugs and 10° and 90° fixed socket-outlets. Sleeves and pins are obtained from solid brass bar, type Pt. CuZn40Pb2 (Cu 58%, Zn 40%, Pb 2%); anti-loosening terminals with unlosable screws, and built-in cable clamp with anti-abrasion cable gland.

Colour	Red	Rated current (A)	63		
IP degree	IP67	No. of poles	3P+N+E		
Mechanical resistance	IK08	Reference h	6		
Rated voltage	380-415 V	Туре	90° angled surface-mounting socket-outlet		
Frequency	50/60 Hz	Terminal tightening capacity	6-16mm² flexible cables - 6-25mm² rigid cables		
Operating temperature	-25 +55 °C	Type of wiring	With screw		
Electrocod	2211	Glow wire test	850 °C (active parts) - 650 °C (passive parts)		
Total number of operations	> 2000	Breaking capacity at 1.1 Un	79 A		
Insulation resistance	> 10 MΩ	Thermo-pressure with ball	125 °C (active parts) - 80 °C (passive parts)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS													
Saline solution	Acids		Bases		Solvents				Mineral	UV			
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol	oil	rays			
Resistant	Not resistant	L <mark>imited</mark> resistance	L <mark>imited</mark> resistance	Resistant	Resistant	Resistant	Resistant	Resistente	Resistant	Resistant			

DIMENSIONAL





TECHNICAL SYMBOLOGY

IP67

IK08

-25°C ma -25°C -25 +55°C



GWT



With screw

 $\begin{array}{lll} 850~^{\circ}\text{C (active parts)} & 12\overline{5}~^{\circ}\text{C (active parts)} \\ & \text{-} 650~^{\circ}\text{C (passive} & \text{-} 80~^{\circ}\text{C (passive} \\ & \text{parts)} & \text{parts)} \end{array}$

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 19/09/2020 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice