



German standard wall mounting enclosure equipped with bipolar terminal blocks and two interchangeable flanges (1 flange with knock-out elements and 1 flange with quick entry cable glands).

Insulation class	II	Colour	Grey RAL 7035
Outer dim. LxHxD (mm)	298x420x140	IP degree	IP65
Installation	Wall mounting	Mechanical resistance	IK07
Door colour	Smoked Transparent	Terminal block N (mm²)	(3x25)+(10x10)
Terminal block T (mm²)	(3x25)+(10x10)	No. of modules EN 50022	24 (12X2)
Glow Wire Test	750 °C	Standard	IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1
Operating temperature	-25 +60 °C	Electrocod	0321
Thermo-pressure with ball	70 °C	Pole 1 (mm²)	N (3x35) + (10x10)
Pole 2 (mm²)	E (3x35) + (10x10)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

DIMENSIONAL

TECHNICAL SYMBOLOGY



II

IP

IP65

IK

IK07

GWT

750 °C



-25 +60 °C



70 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 10/10/2020

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice