

# **Product Data Sheet**

# GW60079

IEC 309 BTS Range



A range of trailing and fixed plugs and socket-outlets for industrial use, complying with the dimensional and performance standards unified at International level (IEC 60309) and assimilated by the European Standards (EN 60309) and Italian Standards (CEI 23-12). Socket-outlets and plugs with a rated current of 63 and 125A are equipped with an extra pilot contact (CP) for creating an electric interlock. The range is completed with 90° fixed plugs and 10° and 90° fixed socket-outlets. Sleeves and pins are obtained from solid brass bar, type Pt. CuZn40Pb2 (Cu 58%, Zn 40%, Pb 2%); anti-loosening terminals with unlosable screws, and built-in cable clamp with anti-abrasion cable gland.

| Colour                      | Green   | Rated current (A)            | 32  |
|-----------------------------|---|------------------------------|---|
| IP degree                   | IP44  | No. of poles                 | 2P  |
| Mechanical resistance       | IK08  | Reference h                  | 11  |
| Туре                        | Straight plug                                 | Rated voltage                | 20-25V and 40-50 V                                |
| Frequency                   | 401 - 500 Hz                                  | Terminal tightening capacity | 2.5-6mm² flexible cables - 2.5-10mm² rigid cables |
| Operating temperature       | -25 +40 °C                                    | Type of wiring               | With screw  |
| Electrocod                  | 2230  | Glow wire test               | 850 °C (active parts) - 650 °C (passive parts)    |
| Total number of operations  | > 2000  | Permissible overload         | 42 A  |
| Breaking capacity at 1.1 Un | 40 A  | Insulation resistance        | > 10 MΩ   |
| Thermo-pressure with ball   | 125 °C (active parts) - 80 °C (passive parts) |                              |   |

|           | BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS |                                      |                                     |           |           |           |           |            |           |           |  |
|-----------|--|--------------------------------------|-------------------------------------|-----------|-----------|-----------|-----------|------------|-----------|-----------|--|
| Saline    | ne Acids                                       |                                      | Bases                               |           | Solvents  |           |           | Mineral    | UV        |           |  |
| solution  | Concentrated                                   | Diluited                             | Concentrated                        | Diluited  | Hexane    | Benzol    | Acetone   | Alcohol    | oil       | rays      |  |
| Resistant | Not<br>resistant                               | L <mark>imite</mark> d<br>resistance | L <mark>imited</mark><br>resistance | Resistant | Resistant | Resistant | Resistant | Resistente | Resistant | Resistant |  |

#### DIMENSIONAL





### TECHNICAL SYMBOLOGY

IP IP44

IK08





**GWT** 



850 °C (active parts) 125 °C (active parts) - 650 °C (passive - 80 °C (passive parts) parts)

### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 09/10/2020 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice