

Product Data Sheet

GW60404

IEC 309 HP range





A range of trailing and fixed plugs and socket-outlets for industrial use, complying with the dimensional and performance standards unified at International level (IEC 60309) and assimilated by the European Standards (EN 60309) and Italian Standards (CEI 23-12). Socket-outlets and plugs with a rated current of 63 and 125A are equipped with an extra pilot contact (CP) for creating an electric interlock. The range is completed with 90° fixed plugs and 10° and 90° fixed socket-outlets. Sleeves and pins are obtained from solid brass bar, type Pt. CuZn40Pb2 (Cu 58%, Zn 40%, Pb 2%); anti-loosening terminals with unlosable screws, and built-in cable clamp with anti-abrasion cable gland.

| Colour | Blue | Rated current (A) | 16 |
|-----------------------------|---|------------------------------|--|
| IP degree | IP44 | No. of poles | 2P+E |
| Mechanical resistance | IK08 | Reference h | 6 |
| Rated voltage | 200-250 V | Туре | 90° angled surface mounting inlet |
| Frequency | 50/60 Hz | Terminal tightening capacity | 1-2.5mm² flexible cables - 1.5-4mm² rigid cables |
| Operating temperature | -25 +55 °C | Type of wiring | With screw |
| Electrocod | 2230 | Glow wire test | 850 °C (active parts) - 650 °C (passive parts) |
| Total number of operations | > 5000 | Permissible overload | 22 A |
| Breaking capacity at 1.1 Un | 20 A | Insulation resistance | > 10 MΩ |
| Thermo-pressure with ball | 125 °C (active parts) - 80 °C (passive parts) | | |

| BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS | | | | | | | | | | | | | |
|--|------------------|--------------------------------------|--------------------------------------|-----------|-----------|-----------|-----------|------------|-----------|-----------|--|--|--|
| Saline solution | Acids | | Bases | | Solvents | | | Mineral | UV | | | | |
| | Concentrated | Diluited | Concentrated | Diluited | Hexane | Benzol | Acetone | Alcohol | oil | rays | | | |
| Resistant | Not resistant | L <mark>imite</mark> d resistance | L <mark>imite</mark> d resistance | Resistant | Resistant | Resistant | Resistant | Resistente | Resistant | Resistant | | | |

DIMENSIONAL





TECHNICAL SYMBOLOGY

IP IP44

IK IK08

-25 +55 °C

With screw

GWT



850 °C (active parts) 125 °C (active parts) - 650 °C (passive - 80 °C (passive parts) parts)

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 19/09/2020 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice