

## **Product Data Sheet**

## GW50430

44 CE Range



Systems of accessories for electrical installations used for residential, tertiary and industrial applications. The system consists of fasteners for pipes and cables, cable fittings, accessories for rigid pipes (RK Series) and flexible conduit (DF Series). The system include also a wide variety of cable ties (52FS Range) and terminal blocks (44 Range).

Colour	Grey RAL 7035	IP degree	IP55
Material	Flexible polymer	For ext. conduits max (mm)	25
Mounting hole Ø (mm)	29	Description	Cable gland for conduits
Glow Wire Test	960 °C	Operating temperature	-5 +60 °C
Electrocod	36A	Standard	EN 61386-1 - EN 60670-1 (as applicable)

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS							
Saline	Solvents			Mineral	UV		
solution	Hexane	Benzol	Acetone	oil	rays		
Resistant	Not resistant	Limited resistance	Resistant	Resistant	Resistant		

## **DIMENSIONAL**

TECHNICAL SYMBOLOGY







IP55

960 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09 www.gewiss.com sat@gewiss.com Last update 10/10/2020 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice