




Flexible protected conduit system range DF DIFLEX made in thermoplastic PVC, classification 2311. In compliance with IEC 61386-1 (CEI 23/80) e IEC 61386-23 (CEI 23/83). The range includes conduit system available in 14 diameter, from 8 to 60 mm in grey, black and blue colour. Suitable for for the protection of conductors in fixed or mobile installations in residential applications, and on board operating machinery in industrial applications thanks to its flexibility and resistance to mineral oils. Installation type: exposed on walls and ceilings or for applications inside false ceilings and floating floors.

Colour	Black RAL 9005	Material	PVC
Sheath Ø (mm)	22	Glow Wire Test	960 °C
Electrocod	21320	Resistance to compression	2 (Light - 320 N)
Resistance to impact	3 (Medium - 2 J)	Resistance to bending	4 (Flexible)
Electrical characteristics	2 (With electrical insulating characteristics)	Fire resistance	1 (Non-flame propagating)
Classification	2311	Minimum bend radius	10 times the diameter
Insulation resistance	100 MΩ a 500V for 1 minute	Dielectric rigidity	2000 V a 50 Hz for 15 minutes
Protection against ingress of solid objects with revolving and fixed couplings	5	Protection against ingress of solid objects with conduit-sheath unions	6
Protection against ingress of water with revolving and fixed couplings	4	Protection against ingress of water with conduit-sheath unions	5
Tensile strength	1 (Very light)	Suspended load capacity	Not applicable
Standard	EN 61386-1 EN 61386-23	Family	Diflex

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

**GWT**

960 °C



CLASSIFICATION

**2311**

EN 50086  
EN 61386

## STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 10/10/2020

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice