Table III: Native method resolution for SysJava on latest container images (JDK 8–25). JNA and FFI bindings are resolved statically from bytecode call sites.

	Cassandra 5.0.8 JDK 17 Debian 12	Zookeeper 3.9.5 JDK 17 Ubuntu 22.04	Tomcat 11.0 JDK 25 Ubuntu 24.04	Solr 10.0.0 JDK 25 Ubuntu 24.04	Groovy 5.0.6 JDK 21 Ubuntu 24.04	OrientDB 3.2.53 JDK 8 Ubuntu 26.04	Jetty 12.1.10 JDK 25 Ubuntu 26.04	Elasticsearch 7.1.0 JDK 12 CentOS 7	Storm 2.8.8 JDK 17 Ubuntu 26.04	JRuby 10.1.0.0 JDK 21 Ubuntu 24.04
Native Method Resolution										
Native Methods	1675	869	651	722	360	588	183	368	2802	498
SysJava Resolved	1547	808	642	718	300	571	181	352	2698	481
Resolution Breakdown (SysJava)										
JNI Static (Java_*)	786	220	175	132	174	381	93	232	1647	338
Partial (_1/$/__)	31	9	0	4	15	24	0	14	64	4
JNI Dynamic (RegisterNatives)	649	503	50	521	53	122	48	60	918	56
JVM	41	43	42	44	49	44	40	41	48	50
JFR/Netty	26	17	0	17	0	0	0	0	21	0
JNA (Static / Dynamic)	13 / 0	9 / 0	0 / 0	0 / 0	9 / 0	0 / 0	0 / 0	5 / 0	0 / 0	0 / 0
FFI/FFM (incl. JNR-FFI)	1	7	375	0	0	0	0	0	0	33
Platform / Intrinsic	113	61	9	4	60	9	2	16	78	10
Not Found	15	0	0	0	0	8	0	0	26	7
Syscall Allowlist (SysJava only)										
Java Lib Syscalls	133	134	116	138	120	107	121	112	141	107
Container Binary Syscalls	152	113	96	140	121	108	113	94	123	108
Unanalysed Lib Syscalls (Δ)	37	3	27	25	24	9	26	43	10	8
Go Whitelist (Δ)	13	29	26	17	25	33	23	23	23	34
Total Syscalls	229	183	180	217	193	172	193	196	195	173

Note: Native Methods = methods declared native (JNI and JNA direct mapping) + JNA interface and dynamic bindings + JNR-FFI and FFM bindings. The breakdown rows count resolved natives and add up to SysJava Resolved; Platform / Intrinsic = natives and bindings for other operating systems (Windows, macOS, Solaris, BSD), JVM intrinsics, and bindings with no native target (FFM upcall callbacks, vDSO calls). Not Found = natives with no symbol in any available library, and JNA/FFI bindings whose library or symbol is unknown. SysJava Resolved + Platform / Intrinsic + Not Found = Native Methods. Tomcat 11 uses the FFM API extensively (382 FFI bindings), reflecting the move away from JNI in newer Java versions; FFM hits that the detector inferred from a class name in a JAR that never references java.lang.foreign (e.g. clojure.core$abs, EvpHmac$MD5) are not counted. JNA and FFI bindings are resolved statically using SysJava's binding rules and constant propagation to API arguments. Solr and Storm include natives mapped by supplying the library the image does not ship (Solr netty-tcnative 2.0.70: 276; Storm jansi: 9 and netty io˙uring: 62, which adds io_uring_setup/enter/register; Tomcat: 2 commons-daemon natives in jsvc, built from the image's commons-daemon-native source; OrientDB jffi 1.3.11: 37 and Lucene NativePosixUtil: 5; Elasticsearch NativePosixUtil: 5). Unanalysed Lib Syscalls (Δ) are syscalls reachable from native libraries present in the container but without a direct Java binding entry point, not already counted above; the Go Whitelist (Δ) adds the runc entries not already counted. All ten containers run under their generated profiles.