Table III: Native method resolution for SysJava on latest container images (JDK 8–25), RTA call graph (EchoTrace 89bf135). JNA and FFI bindings are resolved statically from bytecode call sites.

	Cassandra 5.0.8 JDK 17 Debian 12	Zookeeper 3.9.5 JDK 17 Ubuntu 22.04	Tomcat 11.0 JDK 25 Ubuntu 24.04	Solr 10.0.0 JDK 25 Ubuntu 24.04	Groovy 5.0.6 JDK 21 Ubuntu 24.04	OrientDB 3.2.53 JDK 8 Ubuntu 26.04	Jetty 12.1.10 JDK 25 Ubuntu 26.04	Elasticsearch 7.1.0 JDK 12 CentOS 7	Storm 2.8.8 JDK 17 Ubuntu 26.04	JRuby 10.1.0.0 JDK 21 Ubuntu 24.04
Native Method Resolution										
Native Methods	2328	1322	996	1335	1014	709	686	589	3373	690
SysJava Resolved	2202	1260	983	1328	951	692	682	573	3283	672
Resolution Breakdown (SysJava)										
JNI Static (Java_*)	1418	650	488	686	790	501	565	432	2208	509
Partial (_1/$/__)	40	15	7	16	28	24	10	16	70	9
JNI Dynamic (RegisterNatives)	657	516	62	555	68	123	58	76	935	68
JVM	47	46	51	54	56	44	49	44	49	53
JFR/Netty	26	17	0	17	0	0	0	0	21	0
JNA (Static / Dynamic)	13 / 0	9 / 0	0 / 0	0 / 0	9 / 0	0 / 0	0 / 0	5 / 0	0 / 0	0 / 0
FFI/FFM (incl. JNR-FFI)	1	7	375	0	0	0	0	0	0	33
Platform / Intrinsic / Dead	126	62	13	7	63	17	4	16	90	18
Not Found	0	0	0	0	0	0	0	0	0	0
Syscall Allowlist (SysJava only)										
Java Lib Syscalls	160	158	149	168	147	131	154	146	168	143
Container Binary Syscalls	152	113	96	140	121	108	113	94	123	108
Unanalysed Lib Syscalls (Δ)	30	3	0	20	3	7	3	29	8	5
Go Whitelist (Δ)	14	27	25	15	28	29	21	23	18	26
Total Syscalls	233	196	180	224	191	183	191	208	207	187

Note: Native Methods = methods declared native (JNI and JNA direct mapping) + JNA interface and dynamic bindings + JNR-FFI and FFM bindings. The breakdown rows count resolved natives and add up to SysJava Resolved; Platform / Intrinsic = natives and bindings for other operating systems (Windows, macOS, Solaris, BSD), JVM intrinsics, bindings with no native target (FFM upcall callbacks, vDSO calls), and Dead natives: declared natives that no library or source implements (jffi Foreign, hawtjni Callback, zstd generateSequences, OpenHFT NativeAffinity.rdtsc0, OpenJDK TransformBlit.Transform, two rocksdbjni 10.10.1.1 natives, JFR setCompressedIntegers). Natives are found on an RTA call graph (virtual and interface calls dispatched to the overrides of every class instantiated in reachable code). Not Found = natives with no symbol in any available library, and JNA/FFI bindings whose library or symbol is unknown. SysJava Resolved + Platform / Intrinsic / Dead + Not Found = Native Methods. Tomcat 11 uses the FFM API extensively (382 FFI bindings), reflecting the move away from JNI in newer Java versions; FFM hits that the detector inferred from a class name in a JAR that never references java.lang.foreign (e.g. clojure.core$abs, EvpHmac$MD5) are not counted. JNA and FFI bindings are resolved statically using SysJava's binding rules and constant propagation to API arguments. Solr and Storm include natives mapped by supplying the library the image does not ship (Solr netty-tcnative 2.0.70: 276; Storm jansi: 9, netty io˙uring: 62, which adds io_uring_setup/enter/register, and rocksdb 5.18.4: 4; Solr and Tomcat: 20 FFM fallback-linker natives in libfallbackLinker built from OpenJDK 25.0.3 source; Cassandra OpenHFT Java-Thread-Affinity 3.23.3: 6; Tomcat: 2 commons-daemon natives in jsvc, built from the image's commons-daemon-native source; OrientDB jffi 1.3.11: 37 and Lucene NativePosixUtil: 5; Elasticsearch NativePosixUtil: 5). Unanalysed Lib Syscalls (Δ) are syscalls reachable from native libraries present in the container but without a direct Java binding entry point, not already counted above; the Go Whitelist (Δ) adds the runc entries not already counted (runc itself is not analysed). Storm's Total includes the supplied io_uring library's syscalls and excludes sync (false FFM hits); Storm runs under that 207-syscall profile. All ten containers run under their generated profiles.