

# Selecting Data with SQL

## Introduction

As a data scientist, the SQL query you'll likely use most often is `SELECT`. This lesson introduces how to use `SELECT` to subset and transform the columns of a database table.

## Objectives

You will be able to:

- Retrieve a `subset of columns` from a table
- Create an `alias` in a SQL query
- Use SQL `CASE` statements to transform selected columns
- Use built-in SQL `functions` to transform selected columns

## The Data

Below, we connect to a SQLite database using the Python `sqlite3` library ([documentation here](#)):

```
# import module
import sqlite3
# create a connection
conn = sqlite3.connect('data.sqlite')
```

The database that you've just connected to is the same database you have seen previously, containing data about orders, employees, etc. Here's an overview of the database:

For this first section we'll be focusing on the `employees` table.

If we want to get all information about the employee records, we might do something like this (\* means all columns):

```
# module
import pandas as pd
# pandas-sql-query
pd.read_sql("""SELECT * FROM employees;""", conn)
```

	employeeNumber	lastName	firstName	extension	\
0	1002	Murphy	Diane	x5800	
1	1056	Patterson	Mary	x4611	
2	1076	Firrelli	Jeff	x9273	
3	1088	Patterson	William	x4871	

4	1102	Bondur	Gerard	x5408
5	1143	Bow	Anthony	x5428
6	1165	Jennings	Leslie	x3291
7	1166	Thompson	Leslie	x4065
8	1188	Firrelli	Julie	x2173
9	1216	Patterson	Steve	x4334
10	1286	Tseng	Foon Yue	x2248
11	1323	Vanauf	George	x4102
12	1337	Bondur	Loui	x6493
13	1370	Hernandez	Gerard	x2028
14	1401	Castillo	Pamela	x2759
15	1501	Bott	Larry	x2311
16	1504	Jones	Barry	x102
17	1611	Fixter	Andy	x101
18	1612	Marsh	Peter	x102
19	1619	King	Tom	x103
20	1621	Nishi	Mami	x101
21	1625	Kato	Yoshimi	x102
22	1702	Gerard	Martin	x2312

	email	officeCode	reportsTo	
jobTitle				
0	dmurphy@classicmodelcars.com	1		
President				
1	mpatterso@classicmodelcars.com	1	1002	
VP Sales				
2	jfirrelli@classicmodelcars.com	1	1002	VP
Marketing				
3	wpatterson@classicmodelcars.com	6	1056	Sales
Manager (APAC)				
4	gbondur@classicmodelcars.com	4	1056	Sale
Manager (EMEA)				
5	abow@classicmodelcars.com	1	1056	Sales
Manager (NA)				
6	ljennings@classicmodelcars.com	1	1143	
Sales Rep				
7	lthompson@classicmodelcars.com	1	1143	
Sales Rep				
8	jfirrelli@classicmodelcars.com	2	1143	
Sales Rep				
9	spatterson@classicmodelcars.com	2	1143	
Sales Rep				
10	ftseng@classicmodelcars.com	3	1143	
Sales Rep				
11	gvanauf@classicmodelcars.com	3	1143	
Sales Rep				
12	lbondur@classicmodelcars.com	4	1102	
Sales Rep				
13	ghernande@classicmodelcars.com	4	1102	

Sales Rep			
14	pcastillo@classicmodelcars.com	4	1102
Sales Rep			
15	lbott@classicmodelcars.com	7	1102
Sales Rep			
16	bjones@classicmodelcars.com	7	1102
Sales Rep			
17	afixter@classicmodelcars.com	6	1088
Sales Rep			
18	pmarsh@classicmodelcars.com	6	1088
Sales Rep			
19	tking@classicmodelcars.com	6	1088
Sales Rep			
20	mnishi@classicmodelcars.com	5	1056
Sales Rep			
21	ykato@classicmodelcars.com	5	1621
Sales Rep			
22	mgerard@classicmodelcars.com	4	1102
Sales Rep			

## Quick Note on String Syntax

When working with strings, you may have previously seen a `'string'`, a `"string"`, a `'''string'''`, or a `"""string"""`. While all of these are strings, the triple quotes have the added functionality of being able to use multiple lines within the same string as well as to use single quotes within the string. Sometimes, SQL queries can be much longer than others, in which case it's helpful to use new lines for readability. Here's the same example, this time with the string spread out onto multiple lines:

```
pd.read_sql("""
SELECT
*
FROM
employees;
""", conn
)
```

	employeeNumber	lastName	firstName	extension	\
0	1002	Murphy	Diane	x5800	
1	1056	Patterson	Mary	x4611	
2	1076	Firrelli	Jeff	x9273	
3	1088	Patterson	William	x4871	
4	1102	Bondur	Gerard	x5408	
5	1143	Bow	Anthony	x5428	
6	1165	Jennings	Leslie	x3291	
7	1166	Thompson	Leslie	x4065	
8	1188	Firrelli	Julie	x2173	
9	1216	Patterson	Steve	x4334	
10	1286	Tseng	Foon Yue	x2248	

11	1323	Vanauf	George	x4102
12	1337	Bondur	Loui	x6493
13	1370	Hernandez	Gerard	x2028
14	1401	Castillo	Pamela	x2759
15	1501	Bott	Larry	x2311
16	1504	Jones	Barry	x102
17	1611	Fixter	Andy	x101
18	1612	Marsh	Peter	x102
19	1619	King	Tom	x103
20	1621	Nishi	Mami	x101
21	1625	Kato	Yoshimi	x102
22	1702	Gerard	Martin	x2312

	email	officeCode	reportsTo	
jobTitle				
0	dmurphy@classicmodelcars.com	1		
President				
1	mpatterso@classicmodelcars.com	1	1002	
VP Sales				
2	jfirrelli@classicmodelcars.com	1	1002	VP
Marketing				
3	wpatterson@classicmodelcars.com	6	1056	Sales
Manager (APAC)				
4	gbondur@classicmodelcars.com	4	1056	Sale
Manager (EMEA)				
5	abow@classicmodelcars.com	1	1056	Sales
Manager (NA)				
6	ljennings@classicmodelcars.com	1	1143	
Sales Rep				
7	lthompson@classicmodelcars.com	1	1143	
Sales Rep				
8	jfirrelli@classicmodelcars.com	2	1143	
Sales Rep				
9	spatterson@classicmodelcars.com	2	1143	
Sales Rep				
10	ftseng@classicmodelcars.com	3	1143	
Sales Rep				
11	gvanauf@classicmodelcars.com	3	1143	
Sales Rep				
12	lbondur@classicmodelcars.com	4	1102	
Sales Rep				
13	ghernande@classicmodelcars.com	4	1102	
Sales Rep				
14	pcastillo@classicmodelcars.com	4	1102	
Sales Rep				
15	lbott@classicmodelcars.com	7	1102	
Sales Rep				
16	bjones@classicmodelcars.com	7	1102	
Sales Rep				

17	afixter@classicmodelcars.com	6	1088
Sales Rep			
18	pmarsh@classicmodelcars.com	6	1088
Sales Rep			
19	tking@classicmodelcars.com	6	1088
Sales Rep			
20	mnishi@classicmodelcars.com	5	1056
Sales Rep			
21	ykato@classicmodelcars.com	5	1621
Sales Rep			
22	mgerard@classicmodelcars.com	4	1102
Sales Rep			

Unlike in Python, whitespace indentation in SQL is not used to indicate scope or any other important information. Therefore this:

```
SELECT *
  FROM employees;
```

(with two spaces in front of `FROM`)

is identical to this:

```
SELECT *
FROM employees;
```

(with zero spaces in front of `FROM`)

as far as SQL is concerned. However we will be aligning the right edge of the SQL keywords, using a "river" of whitespace down the center to improve legibility in this lesson, following [this style guide](#). You will see multi-line SQL written with various different indentation styles, and you will want to check with your employer to learn what their style guide is.

## Retrieving a Subset of Columns

Once we know what the column names are for a given table, we can select specific columns rather than using `*` to select all of them. This is achieved by replacing the `*` with the names of the columns, separated by commas.

For example, if we just wanted to select the last and first names of the employees:

```
pd.read_sql("""
    SELECT
        lastName, firstName
    FROM
        employees;
    """, conn
).head()
```

	lastName	firstName
0	Murphy	Diane
1	Patterson	Mary
2	Firrelli	Jeff
3	Patterson	William
4	Bondur	Gerard

We can also specify the columns in a different order than they appear in the database, in order to reorder the columns in the resulting dataframe:

```
pd.read_sql("""
    SELECT
        firstName, lastName
    FROM
        employees;
""", conn
).head()
```

	firstName	lastName
0	Diane	Murphy
1	Mary	Patterson
2	Jeff	Firrelli
3	William	Patterson
4	Gerard	Bondur

Additionally, we can use **aliases** (AS keyword) to change the column names in our query result:

```
pd.read_sql("""
    SELECT
        firstName AS name
    FROM
        employees;
""", conn
).head()
```

	name
0	Diane
1	Mary
2	Jeff
3	William
4	Gerard

Note: the AS keyword is technically optional when assigning an alias in SQL, so you may see examples that don't include it. In other words, you could just say `SELECT firstName name` and it would work the same as `SELECT firstName AS name`. However we recommend being more explicit and including the AS, so that it's clearer what your code is doing.

## Using SQL CASE Statements

CASE statements appear very frequently in SQL technical interview questions. They are a type of conditional statement, similar to `if` statements in Python. Whereas Python uses the keywords `if`, `elif`, and `else`, SQL uses `CASE`, `WHEN`, `THEN`, `ELSE`, and `END`.

`CASE` indicates that a conditional statement has begun, and `END` indicates that it has ended.

`WHEN` is similar to `if`, and then instead of a colon and an indented block, `THEN` indicates what should happen if the condition is true. After the first `THEN` has executed, it skips to the end, so each subsequent `WHEN` is more like `elif` in Python.

`ELSE` is essentially the same as `else` in Python.

## CASE to Bin Column Values

One of the most common use cases for `CASE` statements is to bin the column values. This is true for both numeric and categorical columns.

In the example below, we use the `jobTitle` field to bin all employees into `role` categories based on whether or not their job title is "Sales Rep":

```
# Trial-test # brian-added
pd.read_sql("""SELECT firstName, lastName, jobTitle From employees
WHERE jobTitle = 'Sales Rep';""", conn).head()
```

	firstName	lastName	jobTitle
0	Leslie	Jennings	Sales Rep
1	Leslie	Thompson	Sales Rep
2	Julie	Firrelli	Sales Rep
3	Steve	Patterson	Sales Rep
4	Foon Yue	Tseng	Sales Rep

```
pd.read_sql("""
SELECT firstName, lastName, jobTitle,
CASE
    WHEN jobTitle = "Sales Rep" THEN "Sales Rep"
    ELSE "Not Sales Rep"
END AS role
FROM employees;
""", conn).head(10)
```

	firstName	lastName	jobTitle	role
0	Diane	Murphy	President	Not Sales Rep
1	Mary	Patterson	VP Sales	Not Sales Rep
2	Jeff	Firrelli	VP Marketing	Not Sales Rep
3	William	Patterson	Sales Manager (APAC)	Not Sales Rep
4	Gerard	Bondur	Sale Manager (EMEA)	Not Sales Rep
5	Anthony	Bow	Sales Manager (NA)	Not Sales Rep
6	Leslie	Jennings	Sales Rep	Sales Rep
7	Leslie	Thompson	Sales Rep	Sales Rep

8	Julie	Firrelli	Sales Rep	Sales Rep
9	Steve	Patterson	Sales Rep	Sales Rep

## CASE to Make Values Human-Readable

Another typical way to use `CASE` is to translate the column values into something that your eventual audience will understand. This is especially true of data that is entered into the database as a "code" or "ID" rather than a human-readable name.

In the example below, we use a `CASE` statement with multiple `WHEN`'s in order to transform the `officeCode` column into an `office` column that uses a more meaningful name for the office:

```
pd.read_sql("""
SELECT firstName, lastName, officeCode,
       CASE
         WHEN officeCode = "1" THEN "San Francisco, CA"
         WHEN officeCode = "2" THEN "Boston, MA"
         WHEN officeCode = "3" THEN "New York, NY"
         WHEN officeCode = "4" THEN "Paris, France"
         WHEN officeCode = "5" THEN "Tokyo, Japan"
       END AS office
FROM employees;
""", conn).head(10)
```

	firstName	lastName	officeCode	office
0	Diane	Murphy	1	San Francisco, CA
1	Mary	Patterson	1	San Francisco, CA
2	Jeff	Firrelli	1	San Francisco, CA
3	William	Patterson	6	None
4	Gerard	Bondur	4	Paris, France
5	Anthony	Bow	1	San Francisco, CA
6	Leslie	Jennings	1	San Francisco, CA
7	Leslie	Thompson	1	San Francisco, CA
8	Julie	Firrelli	2	Boston, MA
9	Steve	Patterson	2	Boston, MA

**Note** that because **we did not specify a name for officeCode "6"**, and did not include an `ELSE`, the associated office value for William Patterson is `NULL` (represented as `None` in Python).

There is also a shorter syntax possible if all of the `WHEN`s are just checking if a value is equal to another value (e.g. in this case where we are repeating `officeCode =` over and over). Instead we can specify `officeCode` right after `CASE`, then only specify the potential matching values:

```
pd.read_sql("""
SELECT firstName, lastName, officeCode,
       CASE officeCode
         WHEN "1" THEN "San Francisco, CA"
         WHEN "2" THEN "Boston, MA"
         WHEN "3" THEN "New York, NY"
       END AS office
FROM employees;
""", conn).head(10)
```



```

        WHEN "4" THEN "Paris, France"
        WHEN "5" THEN "Tokyo, Japan"
        END AS office
FROM employees;
""" , conn).head(10)

```

	firstName	lastName	officeCode	office
0	Diane	Murphy	1	San Francisco, CA
1	Mary	Patterson	1	San Francisco, CA
2	Jeff	Firrelli	1	San Francisco, CA
3	William	Patterson	6	None
4	Gerard	Bondur	4	Paris, France
5	Anthony	Bow	1	San Francisco, CA
6	Leslie	Jennings	1	San Francisco, CA
7	Leslie	Thompson	1	San Francisco, CA
8	Julie	Firrelli	2	Boston, MA
9	Steve	Patterson	2	Boston, MA

## Using Built-in SQL Functions

Similar to the [Python built-in functions](#), SQL also has built-in functions. The available functions will differ somewhat by the type of SQL you are using, but in general you should be able to find functions for:

- String manipulation
- Math operations
- Date and time operations

For SQLite in particular, if you are looking for a built-in function, start by checking the [core functions](#) page, [mathematical functions](#) page, and/or [date and time functions](#) page.

### Built-in SQL Functions for String Manipulation

#### length

Let's start with an example of a SQL built-in function that is very similar to one we have in Python: `length` ([documentation here](#)). This works very similarly to the `len` built-in function in Python. For a string, it returns the number of characters.

If we wanted to find the length of the first names of all employees, that would look like this:

```

pd.read_sql("""
SELECT
    firstName, length(firstName) AS length_of_name
FROM
    employees;
""", conn).head()

```

	firstName	length_of_name
0	Diane	5

1	Mary	4
2	Jeff	4
3	William	7
4	Gerard	6

## upper

Now let's say we wanted to return all of the employee names in all caps. Similar to the Python string method, this SQL function is called **upper** ([documentation here](#)). However, since it's a built-in function and not a method, the syntax looks like:

```
upper(column_name)
```

and not `column_name.upper()`.

As you get more comfortable with Python and SQL, distinctions like this will get more intuitive, but for now don't worry if you have to look it up every time!

Here is an example using **upper**:

```
pd.read_sql("""
SELECT
    firstName, upper(firstName) AS name_in_CAPS
FROM
    employees;
""", conn).head()
```

	firstName	name_in_CAPS
0	Diane	DIANE
1	Mary	MARY
2	Jeff	JEFF
3	William	WILLIAM
4	Gerard	GERARD

## substr

Another form of string manipulation you might need is finding a substring (subset of a string). In Python, we do this with string slicing. In SQL, there is a built-in function that does this instead. For SQLite specifically, this is called **substr** ([documentation here](#)).

Let's say we wanted just the first initial (first letter of the first name) for each employee:

```
pd.read_sql("""
SELECT
    firstName, substr(firstName, 1, 1) AS first_initial,
    length(substr(firstName, 1, 1)) AS Length_of_Substr
FROM
    employees;
""", conn).head()
```

	firstName	first_initial	Length_of_Substr
0	Diane	D	1
1	Mary	M	1
2	Jeff	J	1
3	William	W	1
4	Gerard	G	1

If we wanted to add a `.` after each first initial, we could use the SQLite `||` (concatenate) operator. This works similarly to `+` with strings in Python:

```
pd.read_sql("""
SELECT
    substr(firstName, 1, 1) || "." AS first_initial
FROM
    employees;
""", conn).head()
```

	first_initial
0	D.
1	M.
2	J.
3	W.
4	G.

We can also combine multiple column values, not just string literals. For example, below we combine the first and last name:

```
pd.read_sql("""
SELECT
    firstName || lastName AS full_name
FROM
    employees;
""", conn).head()
```

	full_name
0	DianeMurphy
1	MaryPatterson
2	JeffFirrelli
3	WilliamPatterson
4	GerardBondur

Hmm, that looks a bit odd. Let's concatenate those column values with a space (`" "`) string literal:

```
pd.read_sql("""
SELECT
    firstName || " " || lastName AS full_name
FROM
```

```
employees;
""" , conn).head()
```

	full_name
0	Diane Murphy
1	Mary Patterson
2	Jeff Firrelli
3	William Patterson
4	Gerard Bondur

That looks better!

## Built-in SQL Functions for Math Operations

For these examples, let's switch over to using the `orderDetails` table:

```
pd.read_sql("""SELECT * FROM orderDetails;""", conn).head()
```

	orderNumber	productCode	quantityOrdered	priceEach	orderLineNumber
0	10100	S18_1749	30	136.00	3
1	10100	S18_2248	50	55.09	2
2	10100	S18_4409	22	75.46	4
3	10100	S24_3969	49	35.29	1
4	10101	S18_2325	25	108.06	4

### round

Let's say we wanted to round the price to the nearest dollar. We could use the SQL `round` function ([documentation here](#)), which is very similar to the the Python `round`:

```
pd.read_sql("""
SELECT
    priceEach, round(priceEach) AS rounded_price
FROM
    orderDetails;
""", conn).head()
```

	priceEach	rounded_price
0	136.00	136.0
1	55.09	55.0
2	75.46	75.0
3	35.29	35.0
4	108.06	108.0

### CAST

The previous result looks ok, but it's returning floating point numbers. What if we want integers instead?

In Python, we might apply the `int` built-in function. In SQLite, we can use a `CAST` expression ([documentation here](#)):

```
pd.read_sql("""
SELECT
    CAST(round(priceEach) AS INTEGER) AS rounded_price_int
FROM
    orderDetails;
""", conn).head()
```

	rounded_price_int
0	136
1	55
2	75
3	35
4	108

## Basic Math Operations

Just like when performing math operations with Python, you don't always need to use a function. Sometimes all you need is an operator like `+`, `-`, `/`, or `*`. For example, below we multiply the price times the quantity ordered to find the total price:

```
pd.read_sql("""
SELECT
    priceEach * quantityOrdered AS Total_Price
FROM
    orderDetails;
""", conn).head()
# alternative
## CAST((priceEach * quantityOrdered) AS INTEGER) AS Total_Price
```

	Total_Price
0	4080.00
1	2754.50
2	1660.12
3	1729.21
4	2701.50

## Built-in SQL Functions for Date and Time Operations

For these examples, we'll look at yet another table within the database, this time the `orders` table:

```
pd.read_sql("""SELECT * FROM orders;""", conn).head()
```

	orderNumber	orderDate	requiredDate	shippedDate	status	\
0	10100	2003-01-06	2003-01-13	2003-01-10	Shipped	

1	10101	2003-01-09	2003-01-18	2003-01-11	Shipped
2	10102	2003-01-10	2003-01-18	2003-01-14	Shipped
3	10103	2003-01-29	2003-02-07	2003-02-02	Shipped
4	10104	2003-01-31	2003-02-09	2003-02-01	Shipped

	comments	customerNumber
0		363
1	Check on availability.	128
2		181
3		121
4		141

What if we wanted to know how many days there are between the `requiredDate` and the `orderDate` for each order? Intuitively you might try something like this:

```
pd.read_sql("""
    SELECT
        requiredDate - orderDate
    FROM
        orders;
""", conn)
```

	requiredDate - orderDate
0	0
1	0
2	0
3	0
4	0
..	...
321	0
322	0
323	0
324	0
325	0

[326 rows x 1 columns]

Clearly that didn't work.

It turns out that we need to specify that we want the difference in *days*. One way to do this is using the `julianday` function ([documentation here](#)):

```
pd.read_sql("""
    SELECT
        CAST(julianday(requiredDate) - julianday(orderDate) AS INTEGER)
    AS days_from_order_to_required
    FROM
        orders;
""", conn)
```

	days_from_order_to_required
0	7
1	9
2	8
3	9
4	9
..	...
321	8
322	12
323	6
324	8
325	7

[326 rows x 1 columns]

If we wanted to select the order dates as well as dates 1 week after the order dates, that would look like this:

```
pd.read_sql("""
    SELECT
        orderDate, date(orderDate, "+7 days") AS one_week_later,
        date(orderDate, "+14 days") AS two_week_later
    FROM
        orders;
""", conn)
```

	orderDate	one_week_later	two_week_later
0	2003-01-06	2003-01-13	2003-01-20
1	2003-01-09	2003-01-16	2003-01-23
2	2003-01-10	2003-01-17	2003-01-24
3	2003-01-29	2003-02-05	2003-02-12
4	2003-01-31	2003-02-07	2003-02-14
..	...	...	...
321	2005-05-29	2005-06-05	2005-06-12
322	2005-05-30	2005-06-06	2005-06-13
323	2005-05-30	2005-06-06	2005-06-13
324	2005-05-31	2005-06-07	2005-06-14
325	2005-05-31	2005-06-07	2005-06-14

[326 rows x 3 columns]

You can also use the `strftime` function, which is very similar to the [Python version](#). This is useful if you want to split apart a date or time value into different sub-parts. For example, here we extract the year, month, and day of month from the order date:

```
pd.read_sql("""
    SELECT orderDate,
        strftime("%m", orderDate) AS month,
        strftime("%Y", orderDate) AS year,
```

```
        strftime("%d", orderDate) AS day
FROM orders;
""", conn).head()
```

	orderDate	month	year	day
0	2003-01-06	01	2003	06
1	2003-01-09	01	2003	09
2	2003-01-10	01	2003	10
3	2003-01-29	01	2003	29
4	2003-01-31	01	2003	31

Now that we are finished with our queries, we can close the database connection.

```
conn.close()
```

## Summary

In this lesson, you saw how to execute several kinds of SQL `SELECT` queries. First, there were examples of specifying the selection of particular columns, rather than always using `SELECT *` to select all columns. Then you saw some examples of how to use `CASE` to transform column values using conditional logic. Finally, we walked through how to use built-in SQL functions, particularly for string, numeric, and date/time fields.