(1)

Written Assignment 3

Binomial Coefficients
Input: n, k
Output: C[n][k]
C is the array to store the computed Binomial Coefficients.

Now $C(n_3) = C(n_1, k_1) + C(n_1, k)$ $C(n_3) = C(n_3) = 1 \in Stopping Condition$

procedure Binomial Coy (n,k):

Jor i from O to nJor j from O to k j=0 or j=1: C[i][j]=1

(i)[j] = ([i-1][j-1] + ([i-1][j])

If The Time Complexity of the above algorithm is O(nk). Since times loop rune k k'times and outer loop runs k times


Algorithm to court the number of ways in which the good can be pared Input = n = length of hoad in meters Output = number of ways in which the road can be pared Goodparing [n] = wadparing [n-2] + road paring n-3] + noadparing [n-5] Stopping Condition > hoad pains [0] = 1 & hoadparing [1] = 0 [Sanity Creck] & if n < 0 then road parring[n]=0 dy paringhood (n): pareng road paring [0] = 1 headparing [1] = 0 for 'u from 2 to n: y i is greater than or egul to 2: Sum += readparing [i-2] if i is greater than or equal to 3: Sum += roadparing [i-3) y i is greater than or equal to 5 sum + = noadpany[i-5] hoadparing [1] = sun wadparry n)

Wumber g ways g partitioning a del g n elevants Reference: - en wikipedia org /wiki / Bell_triangle
Array & Bell stores: the bell triangle
It is a 2d matrix [lower tringular
matrix] Input = n = number of elements in a set Output = number of ways they can be partitioned Bell [i) [j] = Bell [i+) [j-1] + Bell [i] [j-1] procedure Partition (n): Bet for i for from 0 to n for j from 0 to i.

y ((i and j are equal to zero)

or (i is equal to one asy and j is equal to zero)) then Bell [i) (i) = 1 // Clement (O,1) and (O,0) are set to I else y jes equal to O

Bell[i][0] = Bell[i-][i-] // y column = 0 then bell provision = Bell provision of 1/, ie, set just element of the now to copyed to 1/ the last element of previous from



procedure path (n,m):

If A(n)[m] >-1 // if theres a value return A[n](m) else if / (n is equal to I and m is equal to zero)_ Or nisequal to o and m is equal to one) return I else if (n isequal to zoro)

A[n](m) = path (n, m-1)

Clse if (m is equal to zero) A[n][m] = path (n+, m) $A[n][m] = path(n,m_1) + path(n_1,m)$ geturn Afrila) Explaination 1. Checks if Am) in filled. If yes return that value 2. Checks if elevent is ABDIT or ACIJO7 gince path from A[0][0] to the elements above is equal to I, This is the stopping constal condition 3 Checks if the denent is in the first column is yes wheak the denent below 1. Checks y the element is in the first away.

If yes check the clement to be left

	5 Else 9thurn the addition of path (n, m.) and path (n.1,m)
1	
	The Court of the state of the state of the
	er Aren OD make the following the contract the first
	CAR PARAMETER TO THE PROPERTY OF THE PARAMETER TO THE PAR
ar a	
(0.0)	
,	and the same of
	THE RELATION OF LAKER HE WAS A STREET OF THE PARTY OF THE
- ALL	Property of the Control of the Contr
	The state of the s
Part of the State of	1840 - Art 1 - British