

NovaLife® Clarus PET 125 SS (Clarus 125)

Premium non-tear film for photo and general commercial applications



Description & Application

NovaLife Clarus PET 125 SS (Clarus 125) is a single side coated PET (Polyethylene Terephthalate) film for Electrophotography, Offset, Flexo and Screen Printing. Ideally suited for special effects in wedding albums, overlays in multi-layered printing and similar applications.

Features & Benefits

- PET Film base provides tear resistance, stiffness and long-term durability
- Optical clarity enables designers to creatively layer multiple printed images, allowing for the combination of elements that create depth and dimension
- This media is compatible with white ink, enabling reverse & sandwich printing
- The carrier sheet at the back helps in sensing the leading edge
- Good anti-static properties for trouble free printing and dust free outputs
- Thermally stable PET Film base allows post print finishing involving heat such as thermal lamination

Specifications

- Base : Polyester Film (PET)
- Total Thickness : 125 ± 10 microns (175 ± 7 gsm)
- Surface Finish : Clear
- Printability : Single side printable
- Available Sizes : 330 x 482 (mm) & other sizes available on request

Printer Compatibility

A Electrophotography - (ElectroInk and Dry toner)

Brand	Model
HP Indigo (ElectroInk)	5500, 5600, 5900, 7500, 7600, 7700, 7800, 7900, 7R, 10000, 12000, 15K
Konica Minolta	C73hc, C83hc, C74hc, C84hc, C3070, C3080, C4085, C4065, C4070, C4080, C6085, C6100, C7100, C12000, C14000,
Xerox	Versant: 180, 280, 2100, 3100, 4100 iGen: 3, 4, 5, 150 Xerox Iridesse Production press
Canon ImagePress	C650, C810, C850, C910, V9000, V1000, V1350, C7011VP, C8000VP, C9010VP, C7000VP, C10000VP
Ricoh	Pro: 5300S, C5310S, C7100, C7200, C7210, C7500, C9200, C9210, C9500
Fuji	Revoria Press: PC1120, Ec1100 ApeosPro: C650, C750, C810

B Other Printing Technologies

Hybrid Printing (Offset + Digital)	For the best results, use UV inks with alcohol dampening system. Do not pre-print / flood coat areas that later need to be digitally printed.
Standard Offset Printing	For best result use Standard/Oxidative inks with aqueous over print varnish.
Flexo Printing	Corona treatment may not be required. Compatible with UV inks.
Screen Printing	Suitable for PVC based inks & UV inks
Inkjet Printing	UV inks (such as KM1) & Latex inks
Laser Printing	Compatible with most of desktop laser printers (A4, A3)
Thermal Printing	Compatible with Dye Diffusion Thermal Transfer (D2T2) printers, involving transfer of solid wax/resin ink from ribbon.

Usage Instructions

- We recommend thorough testing of the substrate for intended application prior to use
- Please refer the user guide of the printing machine for correct printer settings & for best output & media settings please consult the service engineer of the press
- Please ensure the sheets are acclimatized to the printing environment for 24 hours before use. Best print results can be obtained at 20-25°C, 55% ± 10% relative humidity (RH)
- To facilitate jam-free feeding, please fan or jog the sheets before printing
- To extend the print life, (thermal) lamination or varnishing after printing is advisable. The lamination film or varnish must be checked for compatibility with the media
- The durability of the printed images will depend on the fading characteristics of the ink or toner used. Please consult with ink or toner supplier

Storage, Handling & Packaging

- **Storage & Handling** : Hold media by the edges to avoid kink marks. Fingerprints will affect the quality of the image. A fresh pair of cotton gloves should be used while handling unprinted media to avoid sweat, grease and oil transfer on to the media that could affect the print quality. When not in use, store the media in cool & dry place [20-25°C, 55% ±10% RH] away from direct sunlight in its original packing. Keep media in flat position to avoid curling
- **Ecology** : This media can be recycled through appropriate polyester (PET) recycling channels
- **Shelf-life** : For optimum results, use the media within two years from the date of manufacture

Digital Print Media Portfolio

TechNova's expertise lies in coating a variety of substrates to produce a range of Digital Print Media that helps effortless transformation of images into works of art.

TechNova's Digital Print Media range is manufactured in one of the world's most sophisticated coating and converting plants. It is optimised for best results for diversified industry segments like Photo, Signage, Engineering, Architecture, Education and Hospitality.

- **Premium Non-Tear Media** : Non-tear films & papers for photo and general commercial printing using digital production presses
- **Inkjet Photo Media** : Films & papers for photo and proofing applications using dry labs, desktop and large-format inkjet printers
- **Industrial Labels** : Self-Adhesive films & papers for digital production presses
- **Specialty Labels** : Pre-cut A4 size self-adhesive synthetic labels
- **Multipurpose Labels** : Pre-cut A4 size self-adhesive labels for desktop inkjet & laser printers and copiers
- **Wide-format Print Media** : Non-tear films & papers for signage and display applications using wide-format printer
- **Polyester Offset Plates** : Inkjet & Laser imaged polyester offset plates for sheet-fed, small & wide-format printers
- **Positive Films** : Inkjet & Laser imaged polyester films for exposing offset & flexo plates & screens

Corporate Office

TechNova Imaging Systems (P) Limited
2401-2408, Cyber One
Pranav Anandji Marg, Sector 30A
Navi Mumbai 400 703
Phone : +91 22 7183 2463

TechNovaCare

Toll-free (India) : 1800 267 7474
Phone : +91 22 7183 2474
eMail : help@technovaworld.com
Web : www.technovaworld.com



Disclaimer : The information provided in this document is to be used only as a guide. It does not imply any liability and shall not be binding upon the company. In pursuit of constant product improvement, specifications are subject to change without prior notice. All brand names and product names used here are trademarks belonging to their respective owners. Prints are for documentation only and not for diagnostic purposes.

© April 2025. Copyright reserved for design & content. Owner, TechNova Imaging Systems (P) Limited.