

## NovaLife® Matte PET 200 DS (LMO 5508)



Certified for  
HP Indigo

Premium non-tear film for photo & general commercial print applications

### Description & Application

NovaLife Matte PET 200 DS (LMO 5508) is a double-side coated PET (Polyethylene Terephthalate) film for Electrophotography, Offset, Flexo and Screen Printing. Ideally suited for high-quality Photo Books, Menu Cards, Certificates, Mark sheets, Shop- floor Manual Cover, Door Hangers, Metal Tags, Plant Tags, Pharma Visual Aids, Indoor Signage and many more applications.

### Features & Benefits

- PET Film base provides tear resistance, stiffness and thermal stability for long term durability
- PET Film substrate provides superior water resistance & excellent weather ability
- Specially designed coating provides superior chemical resistance
- Good anti-static properties for trouble-free printing and dust-free outputs
- Thermally stable PET Film base allows thermal lamination
- Biaxially oriented polyester film provides dimensional stability in either direction
- Soft silk finish gives a premium luxury paper feel
- HP Indigo certified, no priming required
- Security seals and logos can be incorporated using Hot Foiling
- Writable surface for adding comments & signatures
- Stampable surface enables authentication of documents
- High opacity allows printing on both sides without show through

### Specifications

- Base : Polyester Film (PET)
- Total Thickness :  $200 \pm 7$  microns ( $280 \pm 10$  gsm)
- Surface Finish : White Matte
- Opacity :  $> 97\%$
- Thermal stability : Can withstand from  $-60^{\circ}\text{C}$  to  $180^{\circ}\text{C}$
- Printability : Both side printable
- Available Sizes : Available in various sheet sizes & roll widths

### Printer Compatibility

#### A Electrophotography - (ElectroInk and Dry toner)

| Brand                          | Model                                                                                                                                                                                              |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HP Indigo (ElectroInk)         | 3050, 3500, 3550, 3600, 5000, 5500, 5600, 5900, 5R, 7500, 7600, 7700, 7800, 7900, 7R, 7K, 7Eco, 10000, 12000, 15000                                                                                |
| FujiFilms                      | ApeosPro: C650, C750, C810<br>Revorla: PC1120                                                                                                                                                      |
| Konica Minolta (Accurio Press) | C71 HC, C73HC, C83HC, C1060, C1070, C1085, C1100, C2060, 2070, C2070P, C3070, C3070P, C3080, C4065, C4070, C4080, C6085, C6100, C7090, C7100, C12000, C14000, Accurio Label 190, Accurio Label 230 |
| Xerox                          | Color: C40, C70, C75, J75, 250, 550, 560, 770, 1000, 1000i, Versant: 80, 180, 280, 2100, 3100, 4100<br>iGen: 3, 4, 5, 150<br>Iridesse Production Press                                             |
| Ricoh                          | C751, Pro C5300S, Pro C5310S, Pro C7100, Pro C7100x, Pro C9100, Pro C7200, Pro C7200S, Pro C7200SC, Pro C7200X, Pro C7210SX, Pro C7210X, Pro C9200, Pro C9210                                      |
| Canon (ImagePress)             | C265, C650, C700VP, C710, C810, C850, C910 C7011VP, C10000VP, C8000VP, C9010VP, C10010VP,                                                                                                          |
| Xeikon                         | 3000, 3030, 3300, 3500, 8500, 9600, 9800                                                                                                                                                           |



## B Other Printing Technologies

|                  |                                                                                                                                                                                           |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Offset Printing  | Standard offset ink can be used. For best results, use oxidizing inks with alcohol dampening system. For incorporation of security features, invisible & florescent inks can also be used |
| Flexo Printing   | Corona treatment not required. Compatible with UV & water- based inks                                                                                                                     |
| Screen Printing  | Suitable for PVC based inks & UV inks                                                                                                                                                     |
| Inkjet Printing  | UV inks (such as KM1) & Latex inks                                                                                                                                                        |
| Laser Printing   | Compatible with most of desktop laser printers (A4, A3)                                                                                                                                   |
| Thermal Printing | Compatible with Dye Diffusion Thermal Transfer (D2T2) printers, involving transfer of solid wax / resin ink from ribbon.                                                                  |

### Usage Instructions

- We recommend thorough testing of the substrate for intended application prior to use
- Please refer the user guide of the printing machine for correct printer settings
- For best output & media settings, please consult the service engineer of the press
- Please ensure the sheets are acclimatized to the printing environment for 24 hours before use
- Best print results can be obtained at 20-25°C, 55% ± 10% relative humidity (RH)
- To facilitate jam-free feeding, please fan or jog the sheets before printing
- In addition to extend print life, lamination or varnishing after printing is advisable. The lamination film or varnish must be checked for compatibility with the media
- The durability of the printed images will depend on the fading characteristics of the ink or toner used. Please consult with press manufacturer for technical advice

### Storage, Handling & Packaging

- **Storage & Handling** : Hold media by the edges to avoid kink marks. Fingerprints will affect the quality of the image. A fresh pair of cotton gloves should be used while handling unprinted media to avoid sweat, grease and oil transfer on to the media that could affect the print quality. When not in use, store the media in cool, dry place [20-25°C, 55% ±10% RH] away from direct sunlight in its original packing. Keep media in flat position to avoid curling
- **Ageing** : Almost no deterioration or discoloration under normal environmental conditions when kept away from strong UV light and protected against extreme conditions
- **Ecology** : This media can be recycled through appropriate polyester (PET) recycling channels
- **Shelf-life** : For optimum results, use the media within two years from the date of manufacture
- **Pack Size** : Available in 500 sheets (100 sheets X 5 packs) & 250 sheets (50 sheets X 5 packs)

### Digital Print Media Portfolio

TechNova's expertise lies in coating a variety of substrates to produce a range of Digital Print Media that helps effortless transformation of images into works of art.

TechNova's Digital Print Media range is manufactured in one of the world's most sophisticated coating and converting plants. It is optimised for best results for diversified industry segments like Photo, Signage, Engineering, Architecture, Education, Hospitality and HealthCare.

- **Premium Non-Tear Media** : Non-tear films & papers for photo and general commercial printing using digital production presses
- **Inkjet Photo Media** : Films & papers for photo and proofing applications using dry labs, desktop and large-format inkjet printers
- **Industrial Labels** : Self-Adhesive films & papers for digital production presses
- **Specialty Labels** : Pre-cut A4 size self-adhesive synthetic labels
- **Multipurpose Labels** : Pre-cut A4 size self-adhesive labels for desktop inkjet & laser printers and copiers
- **Medical Imaging Films** : Non-tear films for printing medical imaging reports using inkjet printers
- **Wide-format Print Media** : Non-tear films & papers for signage and display applications using wide-format printer
- **Polyester Offset Plates** : Inkjet & Laser imaged polyester offset plates for sheet-fed, small & wide-format printers
- **Positive Films** : Inkjet & Laser imaged polyester films for exposing offset & flexo plates & screens

#### Corporate Office

TechNova Imaging Systems (P) Limited  
2401-2408, Cyber One  
Pranav Anandji Marg, Sector 30A  
Navi Mumbai 400 703  
Phone : +91 22 7183 2463

#### TechNovaCare

Toll-free (India) : 1800 267 7474  
Phone : +91 22 7183 2474  
eMail : [help@technovaworld.com](mailto:help@technovaworld.com)  
Web : [www.technovaworld.com](http://www.technovaworld.com)



**Disclaimer** : The information provided in this document is to be used only as a guide. It does not imply any liability and shall not be binding upon the company. In pursuit of constant product improvement, specifications are subject to change without prior notice. All brand names and product names used here are trademarks belonging to their respective owners. Prints are for documentation only and not for diagnostic purposes.

© September 2024. Copyright reserved for design & content. Owner, TechNova Imaging Systems (P) Limited.