

SESSION-14:

Tasks

1.

Given the following buggy code meant to calculate the total price of a Zomato order, identify and fix the syntax and runtime errors:

let items = ["Burger", "Pizza", "Fries"];
let prices = [120, 250, 90];
let total = 0;
for (i = 0; i < items.length; i++) {
 total += prices[i]
}
console.log("Total price is: " + total);

Hint: Watch for assignment and loop variable issues.

```
#include <stdio.h>
```

```
int main() {  
    char items[3][20] = {"Burger", "Pizza", "Fries"};  
    int prices[3] = {120, 250, 90};  
    int total = 0;  
  
    for (int i = 0; i < 3; i++) {  
        total += prices[i];  
    }  
  
    printf("Total price is: %d\n", total);  
  
    return 0;  
}
```

```
PS C:\Users\SIDDHI\OneDrive\Desktop\c> gcc session14_task1.c -o session14_task1
PS C:\Users\SIDDHI\OneDrive\Desktop\c> .\session14_task1.exe
Total price is: 460
```

2.

Rewrite the following code to improve its indentation and add comments explaining each step, so that a beginner can understand what it does:

function isEven(num){if(num%2==0){return true;}else{return false;}}

```
#include <stdio.h>
```

```
int isEven(int num) {
    // Check if the number is divisible by 2
    if (num % 2 == 0) {
        return 1;
    } else {
        return 0;
    }
}
```

```
int main() {
    int number = 10;

    // Call the function and display the result
    if (isEven(number)) {
        printf("%d is even.\n", number);
    } else {
        printf("%d is odd.\n", number);
    }
}
```

```
    return 0;
}
PS C:\Users\SIDDHI\OneDrive\Desktop\c> gcc session14_task2.c -o session14_task2
PS C:\Users\SIDDHI\OneDrive\Desktop\c> .\session14_task2.exe
10 is even.
```

3.

Write a function `formatFollowersCount(count)` that takes a number and returns a formatted string like Instagram: 1500 as '1.5K', 1200000 as '1.2M', and numbers below 1000 as-is. Add clear comments and use proper indentation.

```
#include <stdio.h>
```

```
void formatFollowersCount(int count) {
    // Format numbers of 1 million or more
    if (count >= 1000000) {
        printf("%.1fM\n", count / 1000000.0);
    }
    // Format numbers of 1 thousand or more
    else if (count >= 1000) {
        printf("%.1fK\n", count / 1000.0);
    }
    // Display numbers below 1000 as they are
    else {
        printf("%d\n", count);
    }
}
```

```
int main() {
    formatFollowersCount(1500);
    formatFollowersCount(1200000);
    formatFollowersCount(500);

    return 0;
}
```

```
PS C:\Users\SIDDHI\OneDrive\Desktop\c> gcc session14_task3.c -o session14_task3
PS C:\Users\SIDDHI\OneDrive\Desktop\c> .\session14_task3.exe
1.5K
1.2M
500
```

4.

You are given a piece of JavaScript code that should print all even numbers from 1 to 10, but it doesn't work as expected:

for (let i = 1; i <= 10; i++) {
 if (i % 2 = 0) {
 console.log(i)
 }
}

Find and fix the error, then rewrite the code with good indentation and at least one comment explaining the logic.

```
#include <stdio.h>
```

```
int main() {
    // Print numbers from 1 to 10 that are divisible by 2
    for (int i = 1; i <= 10; i++) {
        if (i % 2 == 0) {
            printf("%d\n", i);
        }
    }
}
```

```
return 0;
```

```
}
```

```
PS C:\Users\SIDDHI\OneDrive\Desktop\c> gcc session14_task4.c -o session14_task4
```

```
PS C:\Users\SIDDHI\OneDrive\Desktop\c> .\session14_task4.exe
```

```
2
```

```
4
```

```
6
```

```
8
```

```
10
```