

# SESSION-3:

## Tasks

1.

Declare variables for a Flipkart product: productName (as a string), price (float), and rating (double). Assign sample values and print each variable with its data type.

```
#include <stdio.h>
```

```
int main() {
```

```
    char productName[] = "Samsung Galaxy S24";
```

```
    float price = 74999.50;
```

```
    double rating = 4.5;
```

```
    printf("Product Name: %s (string)\n", productName);
```

```
    printf("Price: %.2f (float)\n", price);
```

```
    printf("Rating: %.1f (double)\n", rating);
```

```
    return 0;
```

```
}
```

```
PS C:\Users\SIDDHI\OneDrive\Desktop\c> gcc session3_task1.c -o session3_task1
PS C:\Users\SIDDHI\OneDrive\Desktop\c> .\session3_task1.exe
Product Name: Samsung Galaxy S24 (string)
Price: 74999.50 (float)
Rating: 4.5 (double)
```

2.

Create a constant variable to store the GST rate (for example, 18%) and use it to calculate the final price of a Zomato order with a given base price.<br><br><em><strong>Constraint:</strong> The GST rate must not be changeable after its initial assignment.</em>

```
#include <stdio.h>
```

```
int main() {
```

```
    const float GST_RATE = 18.0;
```

```
    float basePrice = 500.0;
```

```
    float gstAmount;
```

```
    float finalPrice;
```

```
    gstAmount = basePrice * GST_RATE / 100;
```

```
    finalPrice = basePrice + gstAmount;
```

```
    printf("Base Price: Rs. %.2f\n", basePrice);
```

```
    printf("GST Rate: %.2f%%\n", GST_RATE);
```

```
    printf("GST Amount: Rs. %.2f\n", gstAmount);
```

```
    printf("Final Price: Rs. %.2f\n", finalPrice);
```

```
    return 0;
```

```
}
```

### **3.**

Write a program that stores your favorite Spotify playlist's name (string), total number of songs (int), and average song duration in minutes (float). Print all values in a single formatted sentence.

```
#include <stdio.h>
```

```
int main() {
```

```
    char playlistName[] = "Chill Vibes";
```

```
    int totalSongs = 25;
```

```
float averageDuration = 3.5;
```

```
printf("My favorite Spotify playlist is \"%s\", which has %d songs with an  
average duration of %.1f minutes per song.\n",
```

```
playlistName, totalSongs, averageDuration);
```

```
return 0;
```

```
}
```

```
PS C:\Users\SIDDHI\OneDrive\Desktop\c> gcc session3_task3.c -o session3_task3  
PS C:\Users\SIDDHI\OneDrive\Desktop\c> .\session3_task3.exe  
My favorite Spotify playlist is "Chill Vibes", which has 25 songs with an average duration of 3.5 minutes per  
song.
```

#### 4.

Identify and correct the invalid variable names from this list: 1stPlayer, player\_age, \$score, total-marks, userName.<br><br><em><strong>Hint:</strong> Apply standard variable naming rules for your programming language.</em>

| No. | Given Variable | Valid/Invalid | Correct Variable |
|-----|----------------|---------------|------------------|
| 1   | 1stPlayer      | Invalid       | firstPlayer      |
| 2   | player_age     | Valid         | player_age       |
| 3   | \$score        | Invalid       | score            |
| 4   | total-marks    | Invalid       | total_marks      |
| 5   | userName       | Valid         | userName         |