Атрибут	Описание	Тип данных	Ограничения
payment_id	Payment ID	INTEGER	PK
drive_id	Drive ID	INTEGER	FK → Drive
fare	Fare	DECIMAL(10, 2)	NOT NULL and > 0
tip	Tip	DECIMAL(10, 2)	>=0

Атрибут	Описание	Тип данных	Ограничения
update_id	Update ID	INTEGER	PK
driver_id	Driver ID	INTEGER	FK → Driver
rating	Current rating	DECIMAL(10, 2)	DEFAULT 5 and 0 <= rating <= 5
rating_from	Last rater	INTEGER	This value exists in Person[person_id]
date	Date of the last service rating	TIMESTAMP	Less than current time

Атрибут	Описание	Тип данных	Ограничения
driver_id	Driver ID	INTEGER	PK
car_number	Car number	VARCHAR(20)	NOT NULL and has 3 parts: 3 digits + 2 letters + region code
rating	Current rating	DECIMAL(10, 2)	DEFAULT 5 and 0 <= rating <= 5
license	Driver's license number	VARCHAR(50)	NOT NULL and has 2 parts: 4 digits of the series and 6 digits of the number
full_name	Driver's full name	VARCHAR(100)	NOT NULL and contains only cyrillic
experience_years	Driving experience in years	INTEGER	>=0 and DEFAULT TRUE

Атрибут	Описание	Тип данных	Ограничения
update_id	Update ID	INTEGER	PK
person_id	Passenger ID	INTEGER	FK → Person
rating	Current rating	DECIMAL(10, 2)	DEFAULT 5 and 0 <= rating <= 5
rating_from	Last rater	INTEGER	This value exists in Driver[driver_id]
date	Date of the last service rating	TIMESTAMP	Less than current time

Атрибут	Описание	Тип данных	Ограничения
drive_id	Drive ID	INTEGER	PK
person_id	Passenger ID	INTEGER	FK → Person
driver_id	Driver ID	INTEGER	FK → Driver
start_location	Starting location	VARCHAR(255)	NOT NULL
final_location	Final location	VARCHAR(255)	NOT NULL
from_pas_to_driver	Driver rating by passenger	INTEGER	0 <= from_pas_to_driver <= 5
from_driver_to_pas	Passenger rating by driver	INTEGER	0 <= from_pas_to_driver <= 5
comment	Passenger comment	VARCHAR(150)	

Атрибут	Описание	Тип данных	Ограничения
person_id	Passenger ID	INTEGER	PK
full_name	Passenger's full name	VARCHAR(100)	NOT NULL and contains only cyrillic
number	Passenger's number	VARCHAR(20)	NOT NULL and has 11 digits
have_premium	Has premium subscription	BOOLEAN	DEFAULT FALSE
email	Email	VARCHAR(100)	has @
rating	Current rating	DECIMAL(10, 2)	DEFAULT 5 and 0 <= rating <= 5