

Software Requirements Specification

MEA-V2G / FreeV2G

Reference Implementation for ISO 15118 EV/EVSE

Development Team

December 18, 2025

Contents

1	Introduction	2
1.1	Purpose	2
1.2	Scope	2
1.3	Definitions and Acronyms	2
2	Overall Description	3
2.1	Product Perspective	3
2.2	System Functions	3
2.3	Use Case Diagram	3
2.4	System Architecture	3
3	Specific Requirements	5
3.1	External Interfaces	5
3.1.1	Communication Interfaces	5
3.1.2	User Interfaces	5
3.2	Functional Requirements	5
3.2.1	FR-01: Protocol Negotiation	5
3.2.2	FR-02: Authorization	5
3.2.3	FR-03: Charging Control	5
3.3	Communication Flow	6
3.4	EV State Machine	6
3.5	EVSE State Machine	7
3.6	State Synchronization	8
3.7	Charger Simulation	8
3.8	Battery Simulation	9

Chapter 1

Introduction

1.1 Purpose

The purpose of this document is to define the software requirements for the MEA-V2G (FreeV2G) project. This system serves as a reference implementation for controlling the 8 devices WHITE-beet-EI (EVSE) and WHITE-beet-PI (EV) ISO 15118 modules using an Ethernet host control interface (HCI).

1.2 Scope

The MEA-V2G software encompasses:

- Parsing of the protocol used to communicate with the WHITE-beet modules.
- Simulation of EVSE and EV behaviors.
- Handling of charging parameters (Voltage, Current, Power).
- Implementation of basic Control Pilot (CP) and SLAC sequences.
- High-level V2G communication management.

1.3 Definitions and Acronyms

EV Electric Vehicle

EVSE Electric Vehicle Supply Equipment (Charging Station)

HCI Host Control Interface

SLAC Signal Level Attenuation Characterization

V2G Vehicle-to-Grid

PNC Plug & Charge

EIM External Identification Means

Chapter 2

Overall Description

2.1 Product Perspective

The software interacts directly with the WHITE-beet hardware modules via Ethernet or SPI. It acts as the "Host" controller, managing the logic while the WHITE-beet module handles the low-level PLC (Power Line Communication) and ISO 15118 framing.

2.2 System Functions

The system enables the following core functions:

1. **Control Pilot (CP) implementation:** Detects EV plugin and manages duty cycles.
2. **SLAC:** Automates the matching process between EV and EVSE at the physical layer.
3. **V2G Session Management:** Handles Service Discovery, Parameter Discovery, and Authorization.
4. **Charging Loop:** Monitoring and control of the active energy transfer.

2.3 Use Case Diagram

The following diagram illustrates the primary actors and use cases for the MEA-V2G system.

2.4 System Architecture

The system obeys a modular object-oriented architecture. The core logic handles the state machines for EV and EVSE, while the 'Whitebeet' class abstracts the hardware communication.




Figure 2.1: MEA-V2G High-Level Use Case Diagram




Figure 2.2: MEA-V2G Simplified Class Diagram

Chapter 3

Specific Requirements

3.1 External Interfaces

3.1.1 Communication Interfaces

- **Ethernet:** Main control interface for sending HCI commands and receiving notifications.
- **SPI:** Alternative control interface (e.g., for Raspberry Pi integration).

3.1.2 User Interfaces

- **CLI (Command Line Interface):** Primary mode of operation. Outputs session logs and accepts interactive input (e.g., authorization "yes/no").
- **GUI:** A graphical launcher ('gui_launcher.py') provided for configuration and startup.
- **API:** A REST API (default port 5000) for real-time status monitoring (e.g., for Grafana dashboards).

3.2 Functional Requirements

3.2.1 FR-01: Protocol Negotiation

The system shall support negotiation of ISO 15118 protocol versions.

- The EVSE shall advertise supported protocols.
- The EV shall select a mutually supported protocol (e.g., DIN SPEC 70121 or ISO 15118-2).

3.2.2 FR-02: Authorization

The system shall support multiple authorization modes:

- **EIM (External Identification Means):** Manual authorization via console input.
- **PnC (Plug & Charge):** Automated certificate-based authorization.

3.2.3 FR-03: Charging Control

During the charging loop, the system shall:

- Exchange charging parameters (SOC, Target Voltage, Target Current).

- Terminate the session upon "Stop Charging" request from either side.

3.3 Communication Flow

The following sequence diagram depicts the simplified ISO 15118 charging loop interaction between the EV and EVSE, which is the core logical flow of the application.




Figure 3.1: ISO 15118 Charging Loop Sequence

3.4 EV State Machine

The EV internal logic follows a distinct state machine to manage the charging session lifecycle, as observed in the implementation.

Init Initial state where the EV controller is started and hardware interfaces (SPI/Ethernet) are initialized.

SessionStarted The V2G session has been established. The EV has successfully matched with the EVSE via SLAC.

CableCheck The EV waits for the EVSE to perform the cable check (isolation test) to ensure safety.

PreCharging Pre-charge phase where the EV matches its battery voltage to the DC bus voltage.

Charging The main state where energy transfer occurs. The EV sends *CurrentDemand* requests in a loop.

ChargingStopped The session is terminated, either normally (target SOC reached) or due to an error.




Figure 3.2: EV State Machine

3.5 EVSE State Machine

The EVSE logic complements the EV, acting as the server component that handles session setup, authorization, and power delivery control.

Init Initialization of the Whitebeet module services (CP, SLAC, V2G).

Wait The EVSE waits for an EV to physically plug in (Control Pilot State B).

SLAC Signal Level Attenuation Characterization process to pair the EV and EVSE.

Session High-level communication session established; protocol negotiation occurs.

Authorization Verifying if the EV is authorized to charge (via EIM or Plug & Charge).

Params Exchanging charge parameter limits (Maximum Voltage, Current, Power limits).

Cable Performing cable isolation check to ensure no faults exist.

PreCharge Adjusting DC output voltage to match the EV's reported battery voltage.

Charge Active energy transfer loop responding to the EV's current demand.

Stop Session termination and welding detection sequence.




Figure 3.3: EVSE State Machine

3.6 State Synchronization

The charging process relies on the tight synchronization between the EV and EVSE states. Figure 3.4 illustrates the parallel state progression and key synchronization points.

Discovery Control Pilot signal detection (State A $\rightarrow$ B).

Setup SLAC matching and V2G Session Setup.

Safety Both sides must confirm safety parameters during Cable Check.

Sync Voltage levels must be synchronized during Pre-Charge before the contactors close.

Power The Charging Loop is a lock-step process where the EV requests and the EVSE delivers.

Term Coordinated shutdown to ensure contactors open safely (Welding Detection).

3.7 Charger Simulation

The **Charger** class performs a physical simulation of the power electronics, ensuring realistic behavior during the charging session. Its key functions include:

- **Output Ramping:** Instead of instantaneous jumps, the charger simulates the physical "slewing" of voltage and current over time. It uses defined ΔU and ΔI rates to ramp the output toward the target setpoint.
- **Limit Enforcement:** It strictly enforces hard safety limits for the system (e.g., `evse_max_current`, `evse_max_power`), protecting the modeled hardware.




Figure 3.4: EV-EVSE State Synchronization

- **Setpoint Control:** The EV provides dynamic target values (*Target Voltage*, *Target Current*), which the charger attempts to follow within its safety constraints.
- **Fault Detection:** The class includes methods like `isVoltageLimitExceeded()` and `isPowerLimitExceeded()` to trigger immediate session termination if operating conditions are violated.

3.8 Battery Simulation

The **Battery** class provides a logical model of the EV's energy storage, managing State of Charge (SOC) and physical limits.

- **Energy Tracking:** Maintains the battery capacity (Wh) and current energy level. SOC is dynamically calculated as $\frac{\text{Current Level}}{\text{Capacity}} \times 100$.
- **Charging Process:** The `tickSimulation()` method accumulates energy over time intervals based on the instantaneous input voltage and current ($E = V \times I \times \Delta t$).
- **Configurable Limits:** Supports defining maximum Voltage, Current, and Power constraints specific to the chosen Energy Transfer Mode (AC vs. DC).

- **Status Reporting:** Continuously updates the SOC and charging status ('is_full', 'is_charging'), which are reported back to the EVSE via ISO 15118 messages.

Chapter 4

Configuration and Deployment

4.1 Command Line Interface (CLI)

The system is launched via `Application.py` with several arguments to define its operating mode:

- **-r, -role**: Specifies the mode of operation (EV or EVSE).
- **-i, -interface**: Defines the network interface connected to the Whitebeet module (e.g., `eth0`).
- **-c, -config**: Path to the EV configuration file (default: `ev.json`).
- **-ec, -evse-config**: Path to the EVSE configuration file (default: `evse.json`).
- **-auto**: (EVSE only) Enables automatic authorization for Plug & Charge.
- **-api-port**: Sets the port for the REST API status monitor.

4.2 JSON Configuration

Behavioral parameters are externalized in JSON files to allow run-time customization without code changes.

4.2.1 EV Configuration (`ev.json`)

Defines the characteristics of the Electric Vehicle:

- **ev**: Supported protocols (ISO 15118-2, DIN), payment methods (EIM, PnC), and energy transfer modes.
- **battery**: Physical parameters including capacity, maximum voltage/current, and initial SOC.

4.2.2 EVSE Configuration (`evse.json`)

Defines the characteristics of the Charging Station:

- **charger**: Output limits (Max Voltage/Current/Power) and slew rates ($\Delta V, \Delta I$) for the simulation.
- **schedule**: Defines power delivery schedules (SASchedules) sent to the EV during the Charge Parameter Discovery phase.