

MEA OCPP 1.6 Compliance Test Report

Section 9: MEA-Specific Configuration & V2G/BPT

Vector vSECC.single Board vs MEA CSMS (rddQC4000001)

MEA-V2G Project — Automated Test

2026-06-11 04:48 UTC

Contents

1	Test Configuration	2
2	Section 9 Results	2
3	Notes	3

1 Test Configuration

Device Under Test Vector vSECC.single Board
Device IP 192.168.1.166
OCPP Version 1.6 (JSON)
CP ID rddQC4000001
CSMS wss://ocpp.measandbox.com:2930
Connection Direct TLS (Security Profile 1, no proxy)
Test Date 2026-06-11 04:48 UTC
Results file tex/vsecc_section9_results.json

Test Architecture

The vSECC connects directly to the MEA CSMS at `wss://ocpp.measandbox.com:2930/EV/Srv/JSON/1.6/rddQC4000001` over TLS with no intermediate proxy. OCPP traffic is observed via the vSECC's GET `/api/logging/files/ocpplib.log` REST endpoint (TRACE-level log, raw » sent / « received frames) and via MQTT at 192.168.1.166:1883 (topic `vsecc/#`). The test PC NAT-routes internet access for the vSECC subnet (192.168.1.x via enp3s0).

2 Section 9 Results

Summary: 5 PASS 0 FAIL 3 WARN 0 SKIP (8 total)

Item	Test Description	Detail / Evidence	Result
9.0	CSMS connection probe GetConfiguration HTTP 200	vSECC connected to MEA CSMS	PASS
9.1	ChangeConfiguration V2GMode=true Accepted	HTTP 200	PASS
"			
9.2	ChangeConfiguration MeterValueSampleInterval=10 Accepted	HTTP 200	PASS
"			
9.3	ChangeConfiguration LocalAuthorizeOffline=false Accepted	HTTP 200	PASS
"			
9.4.0	ChangeConfiguration V2GMode=true (pre-condition for power demand)	HTTP 200	PASS
"			
9.4.1	Power Demand -5000 W (BPT discharge from EV to grid)	HTTP 200; <i>metervalues not observed in 15s</i> <i>V2G/BPT requires active charging session and</i> <i>V2G-capable EV</i>	WARN
"			
9.4.2	Power Demand +2000 W (BPT charge EV from grid)	HTTP 200; <i>metervalues not observed in 15s</i> <i>V2G/BPT requires active charging session and</i> <i>V2G-capable EV</i>	WARN
"			
9.4.3	Power Demand 0 W (BPT idle / stop power flow)	HTTP 200; <i>metervalues not observed in 15s</i> <i>V2G/BPT requires active charging session and</i> <i>V2G-capable EV</i>	WARN
"			

3 Notes

V2G/BPT configuration (items 9.1–9.4)

ChangeConfiguration commands (V2GMode, MeterValueSampleInterval, LocalAuthorizeOffline) are issued via MEA REST API and return HTTP 200.

V2G power demand (items 9.4.1–9.4.3)

Require an active ISO 15118 V2G charging session (physical EV with V2G capability). Observed via MQTT MeterValues with V2G measurands or `ocpplib.log`.