


TIUMOR

TRACE

By
Katta Sai Rutvik
kattasairutvik@gmail.com



Problem Statement

- This project aims to address these challenges by leveraging Artificial Intelligence (AI), specifically deep learning techniques, to automate the detection and classification of breast tumors in MRI scans.
- By integrating AI-based models like VGG16, ResNet50, and ResNet18, the project seeks to enhance diagnostic accuracy, reduce manual effort, and support radiologists with reliable predictions for distinguishing between benign and malignant tumors.

Data Set

The dataset used in this project is specifically curated for breast tumor detection and classification using MRI images. It is divided into three subsets: training, validation, and testing.

The training set is used to teach the model patterns associated with benign (non-cancerous) and malignant (cancerous) tumors. The validation set helps in fine-tuning hyperparameters and monitoring the model's performance during training, while the test set evaluates the model's ability to generalize to new, unseen data.

Preprocessing

Involves several steps to prepare the MRI images for effective training and ensure consistency in the dataset. All images are resized to a uniform dimension of 224x224 pixels to standardize input size. Normalization is applied using ImageNet's mean and standard deviation to scale pixel values and facilitate faster model convergence.

Data Augmentation:

- Random horizontal and vertical flips with a 50% probability.
- Random rotations within a range of -20° to $+20^{\circ}$.
- Color jitter to adjust brightness, contrast, saturation, and hue.

Preprocessing

- Sobel edge detection is applied to highlight significant boundaries in the images.
- Feature Extraction:
- Histogram of Oriented Gradients (HOG): Captures structural and shape information.
- Local Binary Pattern (LBP): Encodes local texture features.

- Mean Binary Pattern (MBP): Evaluates pixel patterns based on the mean intensity of a local window.
- Median Binary Pattern: Encodes patterns using the median intensity of a local window.
- Variance Binary Point: Uses variance within a local window to compute binary patterns.
- •Mean-Median-Variance (MMV): Combines mean, median, and variance thresholds to extract comprehensive binary patterns.

Problem Statement Dataset Preprocessing Flow Diagram **Training Dataset** Collection & Preprocessing Model **Training** Testing & **Evaluation** Gradio Deployment



- Selected deep learning models (VGG16, ResNet50, ResNet18).
- Modified the model architecture for binary classification (Benign vs. Malignant).
- Freeze feature extraction layers to train only the classifier layers.

Data Loading & Batching

• Load preprocessed training data in batches using PyTorch DataLoader. Batch size is taken as 32.

() Model Training

- Trained the model using CrossEntropyLoss as the loss function.
- Used optimizers like Adam ,SGD to minimize the loss.
- Performed backpropagation to update the model weights.

Problem Statement

Dataset

Preprocessing

Flow Diagram

Training

Epoch 23/50

24/50: 100% 639/639 [02:39<00:00, 4.01batch/s

Train Accuracy: 99.99%

Specificity: 1.0000, Sensitivity: 0.0005, AUC: 0.8705 Precision: 0.9172, Recall: 0.7913, F1-Score: 0.8496

Test set: Average loss: 0.5942, Accuracy: 77.73%

Confusion Matrix:

[[295 113]

[330 1251]]
Model checkpoint saved to: /kaggle/working/tumor_classification/resnet50/resnet50_epoch_23.pth

EarlyStopping counter: 19 out of 20

Epoch 24/50

Epoch 25/50: 100%| 639/639 [02:37<00:00, 4.06batch/s]

Train Accuracy: 99.99%

Specificity: 1.0000, Sensitivity: 0.0005, AUC: 0.8731 Precision: 0.9147, Recall: 0.7868, F1-Score: 0.8460

Test set: Average loss: 0.5846, Accuracy: 77.22%

Confusion Matrix:

[[292 116]

[337 1244]]

Model checkpoint saved to: /kaggle/working/tumor_classification/resnet50/resnet50_epoch_24.pth

EarlyStopping counter: 20 out of 20

Early stopping

Test set: Average loss: 0.3625, Accuracy: 83.86%

EarlyStopping counter: 19 out of 20

Epoch 26/50: 100% 639/639 [03:52<00:00, 2.75batch/s]

Train Accuracy: 83.13%

Specificity: 1.0000, Sensitivity: 0.0005, AUC: 0.9015 Precision: 0.9353, Recall: 0.8223, F1-Score: 0.8751

Test set: Average loss: 0.3992, Accuracy: 81.35%

EarlyStopping counter: 20 out of 20

Early stopping

DUCH Z4/JW

Epoch 25/50: 100% 639/639 [01:22<00:00, 7.72batch/s]

Train Accuracy: 100.00%

Specificity: 0.9995, Sensitivity: 0.0000, AUC: 0.9161 Precision: 0.9298, Recall: 0.9045, F1-Score: 0.9170

Test set: Average loss: 0.4056, Accuracy: 86.98%

Confusion Matrix:


[[300 108]


[151 1430]]

Model checkpoint saved to: /kaggle/working/tumor_classification/resnet18/resnet18_epoch_24.pth

FarlyStonning counter: 18 out of 20









Specificity: 1.0000, Sensitivity: 0.0000, AUC: 0.7382

Test set: Average loss: 0.7913, Accuracy: 5043/6851 (73.61%)

RESENET50


Testing and Results





Specificity: 1.0000, Sensitivity: 0.0000, AUC: 0.7140

Test set: Average loss: 0.7387, Accuracy: 5174/6851 (75.52%)



RESENET18

VGG16

GRADIO

https://drive.google.com/file/d/11ht-pzUw0-UVsDEjfrOfHMmr55l49B4F/view?usp=sharing

