




postcard

an unreasonably effective tool for machine to machine communication

: @jamesmunns.com

: onevariable.com

: @jamesmunns:beeper.com


: @bitshiftmask

ONE **VARIABLE**

i'm james!

: @jamesmunns.com

: onevariable.com

: @jamesmunns:beeper.com

: [@bitshiftmask](https://twitter.com/bitshiftmask)

ONE **VARIABLE**

ONE

VARIABLE

ONE

VARIABLE

(consulting)

I work on
"embedded systems"

ONE **VARIABLE**

this is a vague term that covers a lot

ONE **VARIABLE**

computers you don't sit in front of

ONE **VARIABLE**



By James086 - Own work, CC BY-SA 4.0,
<https://commons.wikimedia.org/w/index.php?curid=3520225>

ONE **VARIABLE**

or

ONE **VARIABLE**



By Polimerek - Own work, CC BY-SA 4.0,
<https://commons.wikimedia.org/w/index.php?curid=425348>

ONE **VARIABLE**

(one of) my most common tasks:

ONE **VARIABLE**

help computers talk to other computers

ONE **VARIABLE**

sometimes all the decisions are made

ONE **VARIABLE**

other times it's a **paralyzing void** of
options

ONE **VARIABLE**

stare into the void with me

ONE **VARIABLE**

what do you do when the whole plan
looks like this?



ONE **VARIABLE**

by the way: the first demo is in a week,
better start quick

ONE VARIABLE

first blessing: most of my customers
are using Rust for both PCs and MCUs

ONE **VARIABLE**

this makes everything so much easier.

ONE **VARIABLE**

second blessing: we have `serde`

ONE **VARIABLE**

"I want to put Rust data on the wire"

ONE **VARIABLE**

```
pub struct AccelReading {  
    pub x: i16,  
    pub y: i16,  
    pub z: i16,  
}
```

ONE VARIABLE

```
#[derive(Serialize, Deserialize)]
pub struct AccelerReading {
    pub x: i16,
    pub y: i16,
    pub z: i16,
}
```

ONE VARIABLE

solved (halfway)

ONE **VARIABLE**

serde is the "front half":
focused on Rust types

ONE **VARIABLE**

we need the other half:
a "data format"
or, "what we put on the wire"

ONE **VARIABLE**

embedded systems don't always have
things like
operating systems or allocators

ONE **VARIABLE**

```
#![no_std]
```

ONE **VARIABLE**

in 2019, there weren't many serde data formats that worked with `#![no_std]`

ONE **VARIABLE**

postcard

ONE **VARIABLE**

I wrote down five design goals:
(lightly edited)

ONE **VARIABLE**

1

design primarily for `#![no_std]` usage: it
has to work on the tiniest chips

ONE **VARIABLE**

2

make it as easy to use as any other **serde**
format

ONE **VARIABLE**

3

no "special code":
same on your PC and MCU

ONE **VARIABLE**

4

be resource efficient:
memory usage, code size,
developer time, and CPU time;
in that order

ONE **VARIABLE**

5

allow for context-specific
customization options

ONE **VARIABLE**

I made the format as dumb as I could

ONE **VARIABLE**

no bit packing trickery, only bytes

ONE **VARIABLE**

competing against transmuting to/from bytes
and calling memcpy

(don't do that lightly, btw)

ONE **VARIABLE**

"non self-describing":
only send raw values, nothing more

ONE **VARIABLE**

everything is little endian in postcard

ONE **VARIABLE**

structs and tuples just go in lexical order

ONE **VARIABLE**

slices are prefixed by their length

ONE **VARIABLE**

enums are prefixed by their discriminant

ONE **VARIABLE**

originally: slice lengths and discriminants
were "varints" - variable length integers

today: all integers are "varints" for portability
reasons

ONE **VARIABLE**

provide "flavors":
stackable combinators on ser/de

ONE **VARIABLE**

works a lot like iterators

ONE **VARIABLE**

with helper functions to hide the generics:

ONE **VARIABLE**


```
postcard::to_slice(&data, &mut buf)
```

ONE **VARIABLE**

```
postcard::to_slice_cobs(&data, &mut buf)
```

ONE **VARIABLE**

2019-2022: I used `postcard` a lot!

ONE **VARIABLE**

2019-2022: so did other people!

ONE **VARIABLE**

2022: time for 1.0

ONE **VARIABLE**

clean up the last portability issues, stabilize
the wire format

ONE **VARIABLE**

2022-2024: I kept using `postcard` a lot!

ONE **VARIABLE**

it has gotten to the point where *MOST* of my
projects use it somehow

ONE **VARIABLE**

but I had a problem

ONE **VARIABLE**

sometimes good tools can make the wrong
thing **TOO** easy to do

ONE **VARIABLE**

let's look at the stack:

ONE **VARIABLE**




ONE **VARIABLE**




ONE **VARIABLE**



ONE **VARIABLE**




ONE VARIABLE



easy!

ONE VARIABLE

hard!



(at least for nontrivial projects)

ONE VARIABLE

every project required a lot of custom work

ONE **VARIABLE**

not *hard* work, just *tedious* work

ONE VARIABLE


(usually a lot of copy and pasting)

ONE **VARIABLE**

I couldn't figure out how to abstract this

ONE **VARIABLE**

hard!



(at least for nontrivial projects)

ONE VARIABLE

until I realized that I was missing a
defined "protocol" layer

ONE **VARIABLE**

application: "how to behave"
or "business logic"

ONE **VARIABLE**

protocol: "how to communicate"

ONE **VARIABLE**

I was reinventing a protocol
for *every* project


ONE VARIABLE

postcard made it TOO easy to build bespoke protocols - but I had to do it every time

ONE **VARIABLE**


what if there was a protocol available
out of the box?

ONE **VARIABLE**



easy!


ONE VARIABLE



easy!

ONE **VARIABLE**

still custom, but that's life



ONE VARIABLE

meet `postcard-rpc`:
a *protocol* on top of `postcard`

ONE **VARIABLE**

what behaviors does the `postcard-rpc`
protocol have?

ONE **VARIABLE**

1

defined "client" and "server" roles

ONE **VARIABLE**

1



ONE **VARIABLE**

2

rpc: "remote procedure call"

ONE **VARIABLE**

2

"every request gets a response"

ONE **VARIABLE**

2

client initiates, server responds

ONE **VARIABLE**

2



ONE **VARIABLE**

2

```
async fn procedure(Request) -> Response {  
    .....  
}
```

ONE VARIABLE

3

"topics", for streaming or notifications


ONE **VARIABLE**

3


can go in either direction, NO response

ONE **VARIABLE**

3



and/or



ONE **VARIABLE**

how does `postcard-rpc` do it?

ONE **VARIABLE**

every packet gets a **header** with two
things:


ONE **VARIABLE**

1

a sequence number

ONE **VARIABLE**

1



ONE **VARIABLE**

2

a unique *Key*

ONE

VARIABLE

2

a way to identify what KIND of message
this is

ONE **VARIABLE**

2

```
key = hash("path") + hash(schema(Message));
```

ONE **VARIABLE**

2

keys are 8 bytes (for now)

ONE **VARIABLE**

2

keys are generated at compile time

ONE **VARIABLE**

now that the protocol is standard, we can
provide reusable protocol code


ONE **VARIABLE**

USB:

`nusb` on the host side

`embassy-usb` on the target side

ONE **VARIABLE**



ONE VARIABLE

what does the code look like?

ONE **VARIABLE**

defining shared protocol definitions:

ONE **VARIABLE**

```
#[derive(Debug, PartialEq, Serialize, Deserialize, Schema)]
pub struct Sleep {
    ... pub seconds: u32,
    ... pub micros: u32,
}
```

```
#[derive(Debug, PartialEq, Serialize, Deserialize, Schema)]
pub struct SleepDone {
    ... pub slept_for: Sleep,
}
```

```
endpoint!(
    ... SleepEndpoint, ... // This is the NAME of the Endpoint
    ... Sleep, ... // This is the Request type
    ... SleepDone, ... // This is the Response type
    ... "sleep", ... // This is the "path" of the endpoint
);
```

```
///·A·marker·trait·denoting·a·single·endpoint
///
///·Typically·used·with·the·[endpoint]·macro.
pub·trait·Endpoint·{
    ····///·The·type·of·the·Request·(client·to·server)
    ····type·Request:·Schema;
    ····///·The·type·of·the·Response·(server·to·client)
    ····type·Response:·Schema;
    ····///·The·path·associated·with·this·Endpoint
    ····const·PATH:·&'static·str;
    ····///·The·unique·[Key]·identifying·the·Request
    ····const·REQ_KEY:·Key;
    ····///·The·unique·[Key]·identifying·the·Response
    ····const·RESP_KEY:·Key;
}
```

```
#[derive(Debug, PartialEq, Serialize, Deserialize, Schema)]
pub struct AccelReading {
    pub x: i16,
    pub y: i16,
    pub z: i16,
}
```

```
topic!(
    AccelTopic, // This is the NAME of the Topic
    AccelReading, // This is the Topic type
    "acceleration", // This is the "path" of the topic
);
```

```
///·A·marker·trait·denoting·a·single·topic
///
///·Unlike·[Endpoint]s,·[Topic]s·are·unidirectional,·and·can·be·sent
///·at·any·time·asynchronously.·Messages·may·be·sent·client·to·server,
///·or·server·to·client.
///
///·Typically·used·with·the·[topic]·macro.
pub·trait·Topic·{
    ····///·The·type·of·the·Message·(unidirectional)
    ····type·Message:·Schema;
    ····///·The·path·associated·with·this·Topic
    ····const·PATH:·&'static·str;
    ····///·The·unique·[Key]·identifying·the·Message
    ····const·TOPIC_KEY:·Key;
}
```

defining a server's endpoint handlers

ONE **VARIABLE**

```

fn unique_id_handler(
    ... context: &mut AppContext,
    ... header: WireHeader,
    ... _rqst: (),
) -> u64 {
    ... /* ... */
}

async fn set_led_handler(
    ... context: &mut AppContext,
    ... header: WireHeader,
    ... rqst: SingleLed,
) -> Result<(), BadPositionError> {
    ... /* ... */
}

```

```

#[embassy_executor::task]
async fn accelerometer_handler(
    ... context: AppSpawnContext,
    ... header: WireHeader,
    ... rqst: StartAccel,
    ... sender: Sender,
) {
    ... /* ... */
}

```

ONE VARIABLE

defining the "routing" or "dispatching" of
our server

ONE **VARIABLE**


```
define_dispatch! {  
    ... dispatcher: Dispatcher<  
        ... Mutex = ThreadModeRawMutex,  
        ... Driver = usb::Driver<'static', USB>,  
        ... Context = AppContext,  
    ... >;  
    ... PingEndpoint => blocking ping_handler,  
    ... GetUniqueIdEndpoint => blocking unique_id_handler,  
    ... SetSingleLedEndpoint => async set_led_handler,  
    ... SetAllLedEndpoint => async set_all_led_handler,  
    ... StartAccelerationEndpoint => spawn accelerometer_handler,  
    ... StopAccelerationEndpoint => blocking accelerometer_stop_handler,  
}
```

ONE VARIABLE

on the PC side

ONE **VARIABLE**

making an rpc/`Endpoint` request

ONE **VARIABLE**

```
// Connect to the first USB device with the
// product name "ov-twin"
let client = HostClient::new_raw_nusb(
    ... |dev| dev.product_string() == Some("ov-twin"),
    ... ERROR_PATH,
    ... 8,
);

// send a request, and receive a response
let val = client.send_resp::<PingEndpoint>(&id).await?;
```

ONE VARIABLE

subscribing to incoming **Topic** messages

ONE **VARIABLE**

```
//·subscribe·to·a·topic  
let·mut·accel_sub·=·client  
·····subscribe::<AccelTopic>(8).await?;  
  
//·receive·the·next·message  
let·data·=·accel_sub.recv().await?;
```

ONE **VARIABLE**

concerns: separated.

ONE **VARIABLE**

postcard

make getting data from here to there effortless

ONE VARIABLE

postcard-rpc

make a conversation between computers effortless

ONE VARIABLE

no matter how you connect to your devices

ONE **VARIABLE**

they're never more than a postcard away.

ONE VARIABLE




postcard

an unreasonably effective tool for machine to machine communication

: @jamesmunns.com

: onevariable.com

: @jamesmunns:beeper.com

: @bitshiftmask

ONE **VARIABLE**


no matter how you connect to your devices,
they're never more than a **postcard** away.

onevariable.com
docs.rs/postcard
docs.rs/postcard-rpc

ONE **VARIABLE**

Q: where does the name "postcard" come from?

A: The song "Postcards From Hell" by "The Wood Brothers"



ONE **VARIABLE**