

gRPC: a Go server and a Dart client

One unary call, one stream, a deadline, and a cancel

Dinu-Ștefan Rusu

FILS, Universitatea Politehnica București · Week 12

What this lab is for



Call a Go server once

Generate a Dart client from a .proto file, call a unary RPC with a deadline, and read back a DeadlineExceeded status when the server is slow.

TIME

2 hours



Watch a stream live

Subscribe to a server-streaming RPC, show one reading a second on screen, and cancel it cleanly with a button.

SUBMIT

Push to your team repo, branch `lab-6`, before next lab

Install the toolchain

Install these once per machine, then branch the team repository for this lab.

```
brew install protobuf    # or: apt install protobuf-compiler

go install google.golang.org/protobuf/cmd/protoc-gen-go@latest
go install google.golang.org/grpc/cmd/protoc-gen-go-grpc@latest

dart pub global activate protoc_plugin
```

Add them to PATH

The Go plugins land in `GOPATH/bin`, the Dart one in your pub-cache `bin` folder. Neither is on PATH by default.

Where your code goes

1. Branch the team repository:

```
git checkout -b lab-6
```

2. Put the contract in `proto/readings/v1/`.
3. Server code in `server/lab6/main.go`. App code in `lib/lab6/`.
4. Run the server once before writing any Dart code.

Order of work

Contract, then server, then client. Do not write a widget before `go run` prints a listening line in your terminal.

The contract: readings.proto

```
syntax = "proto3";
package readings.v1;
message Reading {
    string device_id    = 1;
    double value        = 2;
    int64  taken_at_unix = 3;
}
message DeviceRequest { string device_id = 1; }
service Readings {
    rpc GetLatest(DeviceRequest) returns (Reading);
    rpc StreamReadings(DeviceRequest) returns (stream Reading);
}
```

GetLatest returns one Reading. StreamReadings returns a stream of them.

Generate the stubs, run the server

1. Run protoc for Go, then for Dart (the commands are next).
2. Add the packages:
`flutter pub add grpc protobuf.`
3. Start the server: `go run ./server/lab6.`
4. Confirm it prints the port it is listening on.

DONE WHEN

- ☐ `gen/readings/v1/` holds two generated Go files.
- ☐ `lib/gen/readings/v1/` holds four Dart files.
- ☐ The server keeps running with no error printed.
- ☐ `flutter pub get` resolves cleanly.

Generated code is build output. Never hand-edit it. Change the .proto file and regenerate instead.

Generating stubs for Go and Dart

Run protoc once per language, against the same .proto file.

```
protoc -Iproto \  
  --go_out=gen      --go_opt=paths=source_relative \  
  --go-grpc_out=gen --go-grpc_opt=paths=source_relative \  
  proto/readings/v1/readings.proto  
  
protoc -Iproto --dart_out=grpc:lib/gen \  
  proto/readings/v1/readings.proto
```

Commit the generated files, or run protoc in CI. Either way, pick one and write it down.

A Go server: struct and GetLatest

```
type server struct {  
    pb.UnimplementedReadingsServer  
    latest *pb.Reading  
}  
  
func (s *server) GetLatest(  
    ctx context.Context, req *pb.DeviceRequest,  
) (*pb.Reading, error) {  
    if s.latest == nil {  
        return nil,  
        status.Error(codes.NotFound, "empty")  
    }  
    return s.latest, nil  
}
```

Embed the Unimplemented type. It gives every method a stub, so the server compiles before GetLatest exists.

No reading yet is an error, not a zero value: NotFound tells the client empty and absent apart.

A Go server: the stream and main

```
func (s *server) StreamReadings(  
    req *pb.DeviceRequest,  
    stream pb.Readings_StreamReadingsServer,  
) error {  
    ctx := stream.Context()  
    for ctx.Err() == nil {  
        time.Sleep(time.Second)  
        stream.Send(s.latest)  
    }  
    return nil  
}
```

```
func main() {  
    lis, _ := net.Listen(  
        "tcp", ":50051")  
    gs := grpc.NewServer()  
  
    pb.RegisterReadingsServer(  
        gs, &server{})  
    gs.Serve(lis)  
}
```

StreamReadings loops until the client's context is done. main wires the implementation to a TCP listener.

A unary call with a deadline

1. Add a debug flag that sleeps 3 seconds before `GetLatest` returns.
2. Call `getLatest` from Flutter with a 2-second `CallOptions` timeout.
3. Catch `GrpcError` and show its status code on screen.
4. Confirm the call fails while the server is still asleep.

DONE WHEN

- ☐ The screen shows an error, not a stuck spinner.
- ☐ The error code is `deadlineExceeded`.
- ☐ Turning off the sleep makes the same call succeed.

A deadline is not optional. Without one, a slow server holds your UI state forever.

A Dart client: the unary call

```
final channel = ClientChannel(  
  '10.0.2.2', port: 50051,  
  options: const ChannelOptions(  
    credentials:  
      ChannelCredentials.insecure()));  
final client = ReadingsClient(channel); try {  
  final r = await client.getLatest(  
    DeviceRequest()..deviceId = id,  
    options: CallOptions(  
      timeout: const Duration(seconds: 2)));  
  setState(() => _value = r.value);  
} on GrpcError catch (e) {  
  setState(() => _error = e.code); }
```

Insecure means plaintext, fine for a lab server on your own machine, never for a real deployment.

10.0.2.2 is the Android emulator's address for your host machine, not `localhost`.

The streaming screen, with a cancel

1. Call `streamReadings` with the device id.
2. Listen on the stream and update the screen on each `Reading`.
3. Add a Cancel button that stops the subscription.
4. Show a stopped label once canceled.

DONE WHEN

- ☐ The value on screen changes about once a second.
- ☐ Cancel stops the updates immediately.
- ☐ Nothing is logged as an error after a clean cancel.

A Dart client: the stream and cancel

```
final call = client.streamReadings(  
  DeviceRequest()..deviceId = id,  
);  
final sub = call.listen(  
  (r) => setState(() => _value = r.value),  
  onError: (_) => setState(() => _live =  
    false),  
);  
  
void _cancel() {  
  call.cancel(); // stop the stream  
  sub.cancel();  
  setState(() => _live = false);  
}
```

call is a ResponseStream.

Canceling it tells the server to stop sending, not only to stop listening locally.

The timeout still applies. Pick a generous one for a stream you plan to keep open for a while.

What the grader will do

THE DEMO

- ☐ The stream updates live, about once a second.
- ☐ Pressing Cancel stops it immediately.
- ☐ A 2-second deadline fails `getLatest` against a server sleeping 3 seconds, with `deadlineExceeded`.

IN THE REPOSITORY

The .proto file, the server, the app code, and a README naming your device id scheme and the port you used.

One commit per task, on branch `lab-6`.

Errors you will meet, and their fixes

`protoc-gen-go: program not found`

Not on PATH. Add both plugin bin folders to PATH.

Target of URI doesn't exist:
`readings.pb.dart`

Match `--dart_out` to where the app imports it.

Connection refused to
`localhost:50051`

Emulator localhost is itself. Use `10.0.2.2`.

UNAVAILABLE: failed to connect

The server isn't running, or the port is wrong.

CLEARTEXT communication not
permitted

Android blocks it. Set `usesCleartextTraffic`.

Push before you leave.

Branch lab-6 · one commit per task · README with device id scheme and port