

Rendering and Optimization

Frame budget, widget trees, optimization, profiling

Lecturer

Dinu-Ștefan Rusu

Course

MEC

What you should leave with

Frame budget

One frame is $1 \div \text{refresh rate}$. See where Impeller and the raster thread spend it.

Optimization techniques

const constructors, builder lists, and when an offscreen buffer or a decoded image is the problem.

Widget, Element and RenderObject trees

Widget, Element and RenderObject, and how reconciliation decides what a rebuild touches.

Profiling

Read the DevTools frame chart, tell a UI-thread problem from a raster-thread one, and fix a real list screen.

1

Speed and efficiency

Startup latency, frame budget

Contents		Page
1	Speed and efficiency	3
2	Flutter rendering	7
3	Optimization techniques	17
4	Profiling	24

Speed versus efficiency

- **Speed:** how fast the app answers. Startup latency, scroll smoothness, the delay between a tap and something moving. The user feels this directly, in milliseconds.
- **Efficiency:** what the app costs to run. Memory footprint, install size, and energy. The user feels this indirectly, as a hot phone and a flat battery.

This lecture

Rendering and optimization are mostly about speed. Lecture 7 and Lecture 14 cover the energy half of efficiency in depth.

A slow app and an expensive app fail differently. Keep the two apart when you read a bug report: "laggy" is speed, "drains the battery" is efficiency.

Startup latency: cold, warm, hot

Start	What the system already has	Vitals flags above
Cold	nothing: process created, runtime initialized, first frame drawn	5 s
Warm	the process, but the screen is rebuilt from scratch	2 s
Hot	process and UI both alive, just brought to the foreground	1.5 s

Measure the one your users hit. Cold start is what a store reviewer sees once. Hot start is what a daily user sees ten times a day.

One frame budget = $1 \div \text{refresh rate}$

16.7 ms

60 Hz: the old assumption, still true on older devices

11.1 ms

90 Hz: many mid-range and older phones

8.3 ms

120 Hz: most 2026 flagships

- A frame budget is not a constant. It is one divided by the refresh rate, and that rate has climbed for a decade.
- Inside it, the UI thread runs build, layout and paint, then hands off to the raster thread and the GPU.
- Jank is variance, not average. A steady 30 fps feels smoother than 55 fps with occasional spikes.

Budget for the fastest panel you support, not the slowest. Lecture 2 introduced this budget for concurrency; this lecture spends it on rendering.

2

Flutter rendering

Three trees, reconciliation, operation costs

Contents	Page
1 Speed and efficiency	3
2 Flutter rendering	7
3 Optimization techniques	17
4 Profiling	24

Flutter rendering and Impeller

- Flutter does not draw the platform's native widgets. It ships a renderer and paints the entire surface itself.
- The renderer is **Impeller**, not Skia. iOS runs Impeller only. Android enables it by default on API 29 and later, and falls back to the legacy OpenGL renderer below that. Flutter on the web still draws with Skia.

💡 Why it exists

Skia compiled a shader the first time an effect appeared: a stutter on first use. Impeller precompiles its shaders when the engine is built.

The pipeline, in order. Your widgets → the framework (layout, paint, layers) → Impeller (precompiled shaders) → Metal or Vulkan.

Shader warm-up under Impeller

- Under Skia, a shader was compiled the first time the GPU needed it, mid-frame. The classic symptom was "first-run jank": an effect that stuttered once, the first time it appeared, then never again.
- The workaround was shader warm-up: bundling a set of SkSL shaders and compiling them during a splash screen, before the user could trigger the expensive first frame.
- Impeller precompiles its shader set when the engine itself is built. The first frame that uses an effect costs the same as the thousandth, so there is no first-run jank left to warm up.

If a tutorial tells you to warm up shaders, it predates Impeller. Treat any Flutter rendering advice written before 2023 as needing a second check against current facts.

The three trees and their costs

ADMD Lectures 3 and 5 introduced the three trees at the developer level. Here is what each one costs to touch.

Widget tree

The blueprint. Immutable, no behavior. Allocating one is a bump-pointer write: constant time.

Element tree

The mediator. Persists across frames, holds your State, decides if the old render object can be kept.

RenderObject tree

The machinery. Layout, paint, hit-testing. Expensive to touch, kept alive as long as possible.

Flutter does not rebuild the whole widget tree every frame. Only dirty subtrees rebuild. “Cheap to rebuild” is about allocation, not permission to rebuild a screen for one changed label.

StatelessWidget rebuilds

- A common misconception: a `StatelessWidget` builds once and stays that way. It does not.
 - It rebuilds whenever its parent rebuilds, or whenever an `InheritedWidget` it depends on notifies a change. "Stateless" describes what it holds, not how often `build()` runs.
-

	Stateless	Stateful
build() runs	on insert, on every parent rebuild	all of that, plus every <code>setState()</code>
holds	no mutable data of its own	a <code>State</code> object, kept across rebuilds

Something above a `StatelessWidget` decides when it rebuilds.

Reconciliation: runtimeType and key

```
// The whole reuse decision:
bool canUpdate(Widget a, Widget b) {
  return a.runtimeType == b.runtimeType
    && a.key == b.key;
}
// true -> Element updated in place,
//       render object REUSED.
// false -> old subtree disposed.
```

- The element tree walks the new children in order and asks this once per child: linear, $O(N)$ in the child count.
- Keeping types and keys stable keeps the answer "true".

Same type, same key: the expensive object survives. Swapping a `Container` for a `SizedBox` in a conditional is a type change, and it silently destroys the state below it.

setState and dirty elements

- `setState` marks exactly one Element dirty and asks for a frame. On that frame, `build()` runs on the dirty subtree, and on nothing else.
 - Sibling subtrees are never visited. Their Elements, State objects and render objects are left untouched.
 - The cost of a `setState` is the size of the subtree beneath it. Push it as far down the tree as you can.
1. `setState(() { ... })`: mutate a field
 2. `markNeedsBuild()`: this Element is dirty
 3. next frame: `build()` on dirty subtrees only
 4. reconcile children: `runtimeType`, then key
 5. layout and paint only what changed

Only dirty subtrees rebuild.

Keys and element identity

- Without a key, children are matched by position. Reorder a list and Flutter hands item three's state to whatever now sits third.
- With a key, Flutter recognizes the move: it relocates the element and its render object instead of rebuilding them.

```
for (final t in todos)
  ListTile(key: ValueKey(t.id), todo: t)
```

💡 Which key

`ValueKey(item.id)` for data you own. `ObjectKey` for identity by instance. `UniqueKey` only for destruction: it never matches.

Delete the first row without a key, and the second row inherits its state. Its scroll offset and its animation jump to the wrong item.

GlobalKey and reparenting

- A GlobalKey can reparent a widget: move a live element under a completely different parent, keeping its state.
- Three costs come with that power, every time it fires.
 1. detach and re-attach, with a lookup in a global registry
 2. layout and paint invalidated in both the old and the new location
 3. every InheritedWidget dependency below it resolved again

Keys are cheap. GlobalKey is not. Use a GlobalKey when you need to reparent or reach a State from outside it, not as a convenient handle to a widget.

Cost of tree operations

Operation	Cost	Why
Building a widget	constant	an allocation in the young heap, nearly free to collect
Reconciling children	linear, $O(N)$	one <code>canUpdate</code> call per child
GlobalKey reparenting	search + re-attach	invalidates layout in two places
Intrinsic sizing (nested)	quadratic, $O(N^2)$	each level walks its subtree again

Layout is one depth-first pass: constraints go down, sizes come up. A relayout boundary stops a dirty flag from propagating upward. A fixed-size box around a busy widget is an optimization.

3

Optimization techniques

const, builder lists, offscreen buffers, and images

Contents		Page
1	Speed and efficiency	3
2	Flutter rendering	7
3	Optimization techniques	17
4	Profiling	24

const constructors

```
// Rebuilt, re-diffed on every build:
Padding(
  padding: EdgeInsets.all(16),
  child: Text('Total'),
)
// The SAME instance, forever:
const Padding(
  padding: EdgeInsets.all(16),
  child: Text('Total'),
)
```

- Dart canonicalizes const expressions: identical const widgets are the same object.
- Reconciliation then returns immediately, and the subtree below is skipped.
- It needs every argument to be compile-time constant, a reason to hoist styles into static fields.

Use const constructors wherever the arguments allow it. Turn on the `prefer_const_constructors` lint and let the IDE add them for you.

Lazy lists with ListView.builder

The eager alternative, `ListView(children: ...)`, builds every child up front.

```
// Lazy: builds only what is visible.  
ListView.builder(  
  itemCount: items.length,  
  itemExtent: 72,          // O(1) scroll math  
  itemBuilder: (context, i) => RowTile(  
    key: ValueKey(items[i].id),  
    item: items[i],  
  ),  
)
```

- **Startup:** frame one skips builds it will never show.
- **Memory:** elements track the viewport, not the data.
- **Scrolling:** `itemExtent` makes it arithmetic.

The eager version's cost grows with the number of rows.

Offscreen buffers and saveLayer

Opacity and ClipRRect can force a saveLayer:

1. allocate an offscreen buffer in GPU memory
2. render the entire child subtree into it
3. apply the alpha or the clip to the finished texture
4. composite the texture back onto the frame

Four GPU steps, every frame, for one faded widget: the classic raster-thread spike.

- Animating a fade: use `AnimatedOpacity`, which drives a compositor layer instead of re-diffing the subtree each frame.
- Hiding something: `Opacity(opacity: 0)` still lays out and paints. Use `Visibility`, or do not build the widget.
- Rounded corners: a `BoxDecoration` paints the shape directly; reach for `ClipRRect` only to clip real content.

RepaintBoundary

- `RepaintBoundary` deliberately creates a layer, so a repaint inside it does not spread to the widgets around it.
- The cost is video memory: width times height times 4 bytes, for RGBA, per boundary.
- Wrapping every row of a list fragments the layer tree and multiplies that cost by the row count.

Wrap the right thing

Wrap the one spinner that animates, not the list around it. A boundary around static content buys nothing.

A layer is a deliberate trade: less repaint spread, for more video memory. Reach for it once you have profiled a repaint problem, not by default.

Image decoding and memory

- Decoding an image allocates a full bitmap at its native pixel dimensions, not at the size it is displayed on screen.
- A large photo decoded to fill a small avatar still allocates the full decoded bitmap first, then Flutter scales it down for display.
- A screen with many such images, a photo grid or a long avatar list, can allocate far more memory than the screen shows, and force needless garbage collection.

The source resolution decides the memory cost, not the layout size. A 4000-pixel-wide photo in a 40-pixel avatar still pays for 4000 pixels of decoded bitmap, unless you tell Flutter otherwise.

cacheWidth and precacheImage

```
// Decodes at the target size:  
Image.network(  
  user.avatarUrl, cacheWidth: 96,  
)  
// Decodes ahead of time:  
precacheImage(  
  NetworkImage(nextUrl), context,  
)
```

- `cacheWidth` cuts decoded memory roughly by the square of the resize ratio.
- Flutter also keeps a small in-memory cache, so a re-shown image does not decode twice.

Decode once, at the size you show. `precacheImage` moves the decode off the frame that would otherwise pay for it, such as after a navigation.

4

Profiling

DevTools performance view, before-and-after example

Contents	Page
1 Speed and efficiency	3
2 Flutter rendering	7
3 Optimization techniques	17
4 Profiling	24

Profile mode builds

```
# Debug builds are JIT and assert-heavy.  
# Never quote a debug-mode number.  
flutter run --profile          # on a real device  
# then open DevTools -> Performance
```

- Profile mode compiles close to release performance but keeps the tracing information DevTools needs.
- Run it on a real device. A simulator has different GPU and thermal behavior, so its numbers do not transfer.

Profile before you change anything.

The DevTools frame chart

- The Performance view's timeline draws one bar per frame, split into a UI-thread segment and a raster-thread segment.
- A bar taller than the budget line, 8.3 ms at 120 Hz, marks a janky frame. The timeline scrolls as the app runs, so a scroll gesture that jumps the line is easy to spot.
- Click a bar to expand it into a flame chart of the calls that ran during that frame: build, layout, paint, and everything beneath them.

A tall, wide band across many frames is a systemic problem. One isolated tall bar is usually a single expensive event, like a navigation.

UI thread versus raster thread

Signal	What it means
Tall UI segment (light blue)	your Dart is slow: an expensive build(), or isolate-bound work
Tall raster segment (dark blue)	the GPU is slow: a saveLayer, an oversized image, too many layers
One widget lights up every frame	seen with "Track widget builds"; a whole screen for one label is the bug
Deep stack under performLayout	layout thrashing, often from nested IntrinsicWidth or Height

The taller half tells you which side of the problem you have. Fix a UI segment with less work in build(); fix a raster segment with fewer or smaller layers.

Example: a list screen that drops frames

```
ListView(children: users.map((u) =>
  Opacity(
    opacity: 1,
    child: ListTile(
      leading: Image.network(u.avatarUrl),
      title: Text(u.name),
    ),
  ),
).toList())
```

- 1,200 users. Every row builds up front, before frame one shows.
- Avatars decode at full source size, not tile size.
- `Opacity(opacity: 1)` still forces a `saveLayer` per row.

The frame chart: a steady band of tall UI segments, plus raster spikes on scroll. Three problems, stacked in one screen.

Example: the fix and its effect

```
ListView.builder(  
  itemCount: users.length,  
  itemExtent: 72,  
  itemBuilder: (context, i) => ListTile(  
    key: ValueKey(users[i].id),  
    title: Text(users[i].name),  
  ),  
)
```

- Only visible rows build. `ValueKey` keeps state with the right user.
- The avatar now loads with `cacheWidth: 96`, and the no-op `Opacity` is gone.

Each fix maps to an earlier slide: builder lists, keys, decoding. The UI band drops under budget, and the raster spikes disappear.

Summary

1. One frame budget is 1 divided by refresh rate. 8.3 ms at 120 Hz, not a fixed 16 ms; the budget itself moves with the display.
2. Reconciliation, not full rebuilds. Same runtimeType and same key keep the render object. const, keys and ListView.builder are how you keep that answer true.
3. Profile before you fix. The taller half of the frame bar tells you whether the problem is your Dart, the UI segment, or the GPU, the raster segment.

Further reading

docs.flutter.dev/perf/best-practices · [DevTools: Performance view](#) · [Rendering performance](#) · [Impeller](#)

Questions?

dinu_stefan.rusu@upb.ro · Microsoft Teams: course channel