

Widgets, UI, and DevTools

Layouts, gestures and debugging

Lecturer

Dinu-Ștefan Rusu

Course

ADMD

Lab objectives

Compose a screen

Build a todo list from layout widgets, then add swipe gestures with Dismissible.

Time
2 hours

Attach the tools

Launch DevTools, plant three bugs, find them with breakpoints and the inspector.

Present
To the lab instructor, at the end of this lab

File layout

1. Open the project from Lab 2.
2. Create `lib/screens/todo_screen.dart`. All three tasks happen there.
3. Run the app once before changing anything. If it does not build, fix that first.
4. Keep the todo app. Task III debugs this app with DevTools.



Hint

Hot reload keeps your list contents between edits. Hot restart drops them: use it after changing `initState` or dependencies.

The todo screen

1. A StatefulWidget that holds todos in State.
2. A ListView.builder with one Card per todo.
3. A checkbox in each Card, bound to `done`.
4. A FloatingActionButton that adds a new todo.
5. Extract the Card into a reusable `TodoTile` component.

Done when

- ☐ Toggling a checkbox rebuilds only that tile.
 - ☐ Adding a todo scrolls smoothly.
 - ☐ `TodoTile` takes data through constructor.
-

Layout widgets

- `Column` and `Row`: arrange children vertically or horizontally.
- `Expanded`: takes remaining space inside a `Row` or `Column`.
- `ListView.builder`: lazy list of items; only builds what is visible.
- `Card` and `ListTile`: Material design containers.
- `Padding`: space around a child; `EdgeInsets` specifies how much.
- `SizeBox`: fixed width or height.
- `Container`: padding, margin, color, border in one widget.
- `Stack`: children drawn on top of each other.
- `Scaffold`: `AppBar`, body, FAB layout.

Stateless and stateful widgets

```
class _TodoState
  extends State<TodoScreen> {
  final _items = <Todo>[];
  final _input = TextEditingController();
  void _add() {
    setState(() {
      _items.add(Todo(_input.text));
    });
    _input.clear();
  }
  // Dispose the controller in dispose()
}
```

1. StatefulWidget for the screen.
2. StatelessWidget for TodoTile.
3. Pass data through constructor.
4. Call `dispose()` on controllers.

Structure of a swipeable row

```
Dismissible(  
  key: ValueKey(todo.id),  
  direction: DismissDirection.endToStart,  
  onDismissed: (_) => setState(() {  
    _items.removeWhere(  
      (t) => t.id == todo.id,  
    );  
  }),  
  background: Container(color: Colors.red),  
  child: TodoTile(todo: todo),  
)
```

1. Wrap each tile in Dismissible.
2. Remove from the list in `onDismissed`.
3. Show a SnackBar for undo.

Watch out

Index as key causes wrong row to vanish.

Launching DevTools

```
# From the IDE (fastest, gives breakpoints)  
# VS Code: F5, then Cmd/Ctrl+Shift+P  
#           -> "Dart: Open DevTools"  
# Android Studio: Run > Debug,  
#           then Flutter Inspector  
  
# From terminal (no debugger):  
flutter run  
# Copy the printed URL into a browser
```

1. Start from the IDE, not bare `flutter run`.
2. Open DevTools Inspector tab.
3. Plant three bugs one at a time.
4. Fix each before the next.

DevTools tabs

Inspector

The live widget tree. Select Widget Mode lets you tap a widget on screen. Track widget rebuilds counts how many times each widget rebuilt after an action.

Debugger

Breakpoints, the call stack, and the Variables pane. Conditional breakpoints stop only when a condition is true.

Logging

Everything `debugPrint` writes, plus framework events. Keep it open during debugging.

Performance

Frame timeline and overlay. Only meaningful in a `--profile` build.

Memory

Heap snapshots. Find controllers you forgot to dispose.

Network

Every HTTP request the app makes. You will need this in Lab 4.

Planted bugs

```
// Bug 1: off-by-one
for (var i = 0; i <= _items.length; i++) {
    done += _items[i].done ? 1 : 0;
}

// Bug 2: no setState
void _toggle(int i) =>
    _items[i].done = !_items[i].done;

// Bug 3: null access
String? _filter;
final visible = _items.where(
    (t) => t.title.contains(_filter!));
```

1. Plant Bug 1, run until it throws.
2. Set breakpoint, watch `i` and length.
3. Fix. Plant Bug 2. Use conditional breakpoint.
4. Plant Bug 3. Fix the null access.

Widget rebuilds

`setState` marks one element dirty. Only that subtree rebuilds on the next frame. The framework reuses the element and State when the new widget has the same `runtimeType` and key.

Your list keeps scroll position when one item changes. Keys matter when items can be reordered or removed from the middle.

One frame

16.7 ms at 60 Hz · 8.3 ms at 120 Hz

The Inspector counts rebuilds, not repaints.

Layout errors and debugging issues

RenderFlex overflowed by 42 pixels

Wrap the growing child in Expanded.

Vertical viewport was given unbounded height

Wrap the ListView in Expanded.

A dismissed Dismissible widget is still part of the tree

Remove the item from the list in `onDismissed`.

Breakpoints are hollow and never hit

Start from the IDE (F5), not bare `flutter run`.

The data changed, the screen did not

You mutated state outside `setState`. No rebuilds.

Presentation

The todo screen running · DevTools open on it