

Lab test

Rules, format, practice specs

Lecturer

Dinu-Ștefan Rusu

Course

ADMD

Lab objectives

Prove four skills, once

Build a small app from a one-page spec in ninety minutes: a screen, a Cubit, a network call, and a route.

Time

90 minutes

Worth 30 points

7.5 points per requirement, graded when you present the app at the end of the test.

Present

To the lab instructor, when the time is up

Rules

1. You work alone. No pair programming, no shared screens, no copying a classmate's code.
2. Ninety minutes, one sitting, starting when you receive the spec.
3. Your own laptop, your existing lab app from Labs 1 to 6.
4. No new packages beyond what Labs 2 to 6 already added, unless the spec names one.

Time lost to a crashed emulator or a broken hot reload is not added back.

Allowed resources

1. Internet access is allowed: official docs, package pages, your own past labs.
2. AI agents are allowed for writing code.
3. You must be able to explain any line the grader points to, in your own words.
4. Asking another person, in the room or online, to write code for you is not allowed.

Watch out

An agent-written line you cannot explain earns no credit for that requirement, even if it compiles.

Test format

One page, handed at the start

An app idea and four requirements, on paper or a shared document. Nothing changes once the clock starts.

Ninety minutes, then you present

Build until time is up, then run the app for the lab instructor. No extensions.

Every spec asks for the same four kinds of requirement, described next.

Requirement types

A screen

Built from the layout widgets: Row, Column, ListView, Card. No hardcoded pixel offsets.

One network call

A single HTTP call parsed into a model class with fromJson. Not a hardcoded map.

State in a Cubit

An Equatable state class, `emit`, and a BlocBuilder. Not a raw setState.

One navigation

A go_router route that carries data and pushes to a second screen.

Rubric

Requirement	Full credit (7.5 p)	Partial credit (3.75 p)
Screen	Matches the spec's widgets, no overflow	Builds, but the layout differs from spec
Cubit state	UI updates through emit, never setState	Cubit exists, but a screen still calls setState
Network + model	Parses the real response into a model	Call runs, but fields come from a raw map
go_router nav	Navigates and returns with the right data	Route exists, but push or data is wrong

Anything not attempted scores zero.

Presentation

1. Stop coding when the ninety minutes end.
2. Run the app on your emulator or device when you are called.
3. Show each requirement working, in the order of the spec.
4. Answer questions on any line of your code.

Watch out

What runs when you are called is what is graded. The test cannot be presented later.

Preparation

Requirement	Taught in
Screen from the layout widgets	Lab 3
State in a Cubit	Lab 5
Network call and a model class	Lab 4
Navigation with go_router	Lab 6

Every requirement was covered in Labs 3 to 6. Re-read the Task slides and the reference code in those four labs. Redo one small screen from memory before you come.

Practice A: habit tracker

An app that lists daily habits the user can check off.

1. A `ListView.builder` of habit cards, each with a checkbox, and a button that opens a dialog to add one.
2. A `HabitsCubit` with an `Equatable` state holding the habit list. Toggling or adding emits a new state.
3. On start, fetch `/users/1` from `JSONPlaceholder` and parse it into a `User` model shown in the AppBar.
4. Routes `/` and `/habit/:id`. Tapping a card pushes to the detail route.

Grader checks

- ☐ The app builds and runs.
- ☐ A checkbox toggle goes through the Cubit, never `setState`.
- ☐ The AppBar name comes from the API, not a hardcoded string.
- ☐ The back button returns from the detail screen to the list.

Practice B: campus events board

An app that lists campus events, with filtering and a detail view.

1. A row of filter chips (All, Today) above a scrollable list of event cards.
2. An `EventsCubit` with a state holding the event list and the selected filter. Picking a chip emits a filtered state.
3. On start, fetch `/posts` from `JSONPlaceholder` and parse each item into an `Event` model.
4. Routes `/` and `/event/:id`. Tapping a card pushes to a detail screen with the full text.

Grader checks

- ☐ A chip filters the list through the Cubit, not a local variable.
 - ☐ Every field on screen comes from the Event model, never a raw map key.
 - ☐ The detail route reads the id from the URL.
 - ☐ The app does not crash when the network call is slow.
-

Common mistakes

Bad state: field does not exist
for the class

The JSON keys do not match the model. Print the raw
response before writing fromJson.

No routes matched location
"/habit/3"

The path pushed is not in the go_router route list, or a name
is misspelled.

A blank screen, nothing in the
console

The Cubit never emitted after the network call finished.
Check that the future completes.

setState() or emit() called after
dispose()

A response arrived after the screen closed. Check
`mounted` before calling either.

Presentation

Each requirement shown running · presented when time is up