

# UI polish and testing

Theming, layout, forms, motion, accessibility, and tests

---

Lecturer

Dinu-Ștefan Rusu

Course

ADMD

# What you should leave with

## Theming and dark mode

Build the app's colors and type once with ThemeData, and get dark mode for free.

## Accessibility and localization

Semantics, contrast, tap targets, text scaling, and localized strings.

## Forms

Validators, focus order, keyboard types, and error messages a user can act on.

## Testing

Unit, widget, bloc, golden and integration tests, all running on every pull request.

## 1

# Theming

ThemeData, Material 3, dark mode, and responsive layout

| Contents |                                | Page |
|----------|--------------------------------|------|
| 1        | <b>Theming</b>                 | 3    |
| 2        | Forms                          | 11   |
| 3        | Implicit animations            | 16   |
| 4        | Accessibility and localization | 21   |
| 5        | Testing                        | 27   |

## Hard-coded colors

```
// Repeated in forty widgets:  
Container(color: const Color(0xFF3F51B5))  
Text('Total', style: TextStyle(  
  fontSize: 16, color: Colors.black87))  
  
// Declared once, read everywhere:  
final cs = Theme.of(context).colorScheme;  
Container(color: cs.primaryContainer)  
Text('Total', style: tt.titleMedium)
```

**The first version has no dark mode.**

Every hard-coded color is a value that cannot change with the platform, the user's settings, or next year's brand.

It is also unsearchable: finding which blue the button uses means reading forty files.

---

**A widget that names a role such as `cs.primary` keeps working when the palette, the mode or the brand changes.**

# ThemeData and ColorScheme.fromSeed

```
ColorScheme _scheme(Brightness b) => ColorScheme.fromSeed(  
    seedColor: const Color(0xFF3F51B5), brightness: b);  
  
ThemeData appTheme(Brightness b) => ThemeData(colorScheme: _scheme(b));  
  
// Read it in any widget, never re-declare it:  
final cs = Theme.of(context).colorScheme;  
final tt = Theme.of(context).textTheme;
```

---

**One seed color produces the whole palette.** Material 3 derives every role from it and keeps the contrast between a color and its `on` pair correct in both modes.

# Common color roles

| Role                | What it paints                       | Text on it         |
|---------------------|--------------------------------------|--------------------|
| primary             | the main action: a filled button     | onPrimary          |
| primaryContainer    | a tinted area for that action        | onPrimaryContainer |
| surface             | page background, cards, sheets       | onSurface          |
| secondary, tertiary | accents that are not the main action | onSecondary        |
| error               | validation and destructive actions   | onError            |
| outline             | borders, dividers, disabled edges    |                    |

Every role has an `on` pair. Paint with one, write with the other, and contrast is already handled.

# Dark mode

```
MaterialApp(  
  theme: appTheme(Brightness.light),  
  darkTheme: appTheme(Brightness.dark),  
  themeMode: ThemeMode.system,    // or the user's saved choice  
  home: const HomeScreen(),  
);  
  
// Rare, and usually a smell:  
final isDark = Theme.of(context).brightness == Brightness.dark;
```

---

**You do not design dark mode twice.** If widgets read roles instead of colors, the same widget tree is already correct in both modes.

# Typography and component themes

```
ThemeData(  
  colorScheme: _scheme(b),  
  fontFamily: 'Inter',  
  appBarTheme: const AppBarTheme(centerTitle: true),  
  inputDecorationTheme: const InputDecorationTheme(  
    border: OutlineInputBorder(),  
  ),  
  filledButtonTheme: FilledButtonThemeData(  
    style: FilledButton.styleFrom(minimumSize: const Size.fromHeight(48)),  
  ),  
);
```

The scale runs from `displayLarge` to `labelSmall`. Most screens need only three of its roles.

# MediaQuery

```
final size = MediaQuery.sizeOf(context);  
final pad = MediaQuery.paddingOf(context);  
final keyboard =  
    MediaQuery.viewInsetsOf(context)  
        .bottom;  
final scaler =  
    MediaQuery.textScalerOf(context);
```

**Ask for one metric, not all of them.**

`MediaQuery.of(context)` rebuilds your widget when any metric changes, including the keyboard opening. The `sizeOf` family rebuilds only on the value you read. `viewInsets` is the keyboard. `padding` is the notch and the home indicator.

---

**MediaQuery describes the window, not your widget.** It reports what the system is doing to the app: the size, the notch, the keyboard, and the user's text scale.

# LayoutBuilder, breakpoints, and SafeArea

```
LayoutBuilder(builder: (context, constraints) {  
  if (constraints.maxWidth < 600) return const TodoList();  
  return const Row(children: [  
    Expanded(flex: 2, child: TodoList()),  
    Expanded(flex: 3, child: TodoDetail()),  
  ]);  
});  
  
SafeArea(child: body); // keeps content clear of notch and gestures
```

---

**Break on the width you were given, not on the device.** A phone in landscape, a tablet, and a split-screen window can all be the same width. Two breakpoints, near 600 and near 840, cover almost everything.

# 2

## Forms

Form, TextFormField, validators, focus, and error display

| Contents |                                | Page |
|----------|--------------------------------|------|
| 1        | Theming                        | 3    |
| <b>2</b> | <b>Forms</b>                   | 11   |
| 3        | Implicit animations            | 16   |
| 4        | Accessibility and localization | 21   |
| 5        | Testing                        | 27   |

# Flutter form structure

```
final _formKey = GlobalKey<FormState>();

Form(
  key: _formKey,
  autovalidateMode: AutovalidateMode.onUserInteraction,
  child: Column(children: [emailField, passwordField, submitButton]),
);

if (_formKey.currentState!.validate()) await _signIn();
```

---

**The Form is a coordinator, not a container.** It finds every descendant field, runs their validators, and reports one boolean. The fields keep their own state.

# Form validation

```
String? validateEmail(String? v) {  
    final s = v?.trim() ?? '';  
    if (s.isEmpty) return 'Enter your email';  
    if (!s.contains('@')) {  
        return 'This address is missing an @';  
    }  
    return null;    // null means valid  
}
```

## Return null when the value is fine.

Any other string becomes the red line under the field. One message, naming the one thing to change. "Invalid input" tells the user nothing. Trim before you check, and never reject a password for containing a space.

---

**A validator is a pure function.** A string in, a string or null out. That makes it the easiest thing in the whole app to unit test, as Part 5 shows.

# Keyboard, focus order, and submit

```
TextFormField(  
  controller: _email,  
  focusNode: _emailFocus,  
  keyboardType: TextInputType.emailAddress,  
  textInputAction: TextInputAction.next,  
  onFieldSubmitted: (_) => _passwordFocus.requestFocus(),  
  decoration: const InputDecoration(labelText: 'Email'),  
);  
  
// In dispose(): _email.dispose(); _emailFocus.dispose();
```

---

**Dispose everything you create.** A controller and a FocusNode belong to your State object, and leak if forgotten.

# Error display

## ❗ Errors under the field

The message sits where the mistake is.

## ☰ Server errors

"Email already registered" is not a validator result. Show it near the button.

## 🔒 Disable submit in flight

Keep a bool in the bloc state. A double tap must not create two accounts.

## ↺ Keep what they typed

On failure, keep every field.

## ↑ Scroll to the error

On a long form the field can be off screen.

`Scrollable.ensureVisible` helps.

## ✅ Say what succeeded

A form that submits silently looks broken. One `SnackBar` is enough.

## 3

# Implicit animations

Implicit animations, Hero, duration, reduced motion

| Contents |                                | Page |
|----------|--------------------------------|------|
| 1        | Theming                        | 3    |
| 2        | Forms                          | 11   |
| <b>3</b> | <b>Implicit animations</b>     | 16   |
| 4        | Accessibility and localization | 21   |
| 5        | Testing                        | 27   |

# Implicit animation widgets

## **AnimatedContainer**

Change size, color, padding or decoration and it tweens between old and new.

## **AnimatedAlign**

Move a child inside its parent. So does AnimatedPadding.

## **AnimatedOpacity**

Fade in or out. An opacity of zero still lays out and still hits tests.

## **AnimatedDefaultTextStyle**

Grow, shrink or recolor text as a state changes.

## **AnimatedSwitcher**

Cross-fades between two children when the child's key changes.

## **TweenAnimationBuilder**

Any value you can tween, animated once, with no State of your own.

# AnimatedContainer and AnimatedSwitcher

```
const d = Duration(milliseconds: 200); // one place, whole app
AnimatedContainer(
  duration: d, curve: Curves.easeOut,
  color: done ? cs.primaryContainer : cs.surface,
  padding: EdgeInsets.all(done ? 8 : 16),
  child: const TodoTitle(),
);
AnimatedSwitcher(duration: d,
  child: loading ? const Spinner(key: ValueKey('spin'))
    : TodoList(key: ValueKey(items.length)));
```

---

**The key is what makes AnimatedSwitcher work.** Without a different key, Flutter reuses the same element and there is nothing to cross-fade.

# Hero transitions

```
// List screen
Hero(
  tag: 'todo-${todo.id}',
  child: TodoThumbnail(todo),
);

// Detail screen, same tag
Hero(tag: 'todo-${todo.id}', child: big);
```

## The tag is the contract.

Flutter finds the widget carrying the same tag on both routes and flies it between the two positions.

A tag must be unique on each screen. Use the record's id, not the list index.

---

**Hero borrows the route transition.** No controller, no duration. The only thing you own is the tag, and duplicate tags throw.

# Animation duration and reduced motion

```
if (MediaQuery.disableAnimationsOf(context)) return child;
```

---

## Length

### Use it for

### Sign you got it wrong

|               |                              |
|---------------|------------------------------|
| 100 to 150 ms | a ripple, a checkbox, a fade |
| 200 to 300 ms | cards, sheets, list items    |
| 300 to 400 ms | a full route transition      |

|                                   |
|-----------------------------------|
| the change is invisible           |
| the app feels slow to a fast user |
| the user waits for the animation  |

---

**If the user notices the animation instead of the result, it is too long.** Never block input until it ends.

## 4

# Accessibility and localization

Semantics, contrast, tap targets, text scaling, ARB files

| Contents                                | Page |
|-----------------------------------------|------|
| 1 Theming                               | 3    |
| 2 Forms                                 | 11   |
| 3 Implicit animations                   | 16   |
| <b>4 Accessibility and localization</b> | 21   |
| 5 Testing                               | 27   |

# Common accessibility barriers

## Unlabeled controls

An icon button with no label is announced as "button" and nothing else by TalkBack and VoiceOver.

## Low contrast

Gray on gray fails outdoors, on a cheap panel, and for anyone over forty.

## Tiny targets

A 24 dp icon is a 24 dp target unless you say otherwise.

## Fixed heights

A row with a hard-coded height overflows the moment the user enlarges text.

## Color as the only signal

Red text alone does not say "error" to a person who cannot see red. Add an icon or a word.

## No focus order

On a keyboard or a switch device, tab order is your layout order. Check it once.

# Semantics and screen readers

```
IconButton(  
  icon: const Icon(Icons.delete),  
  tooltip: 'Delete todo',    // also a label  
  onPressed: _delete,  
);  
  
Semantics(  
  label: '3 of 7 done',  
  child: ExcludeSemantics(child: chart),  
);
```

**Describe the meaning, not the pixels.**

A chart is a picture to the framework. `Semantics` replaces it with the sentence a person needs.

`MergeSemantics` joins a row into one announcement. `LiveRegion: true` makes a status line speak when it changes.

---

**Flutter builds a semantics tree on its own.** Add `Semantics` wherever the pixels do not carry the meaning.

# Contrast, tap targets, and text scaling

---

| Rule                 | Target          | How to satisfy it                    |
|----------------------|-----------------|--------------------------------------|
| Body text contrast   | 4.5 to 1        | an on role over its own surface role |
| Large text and icons | 3 to 1          | the same, plus a design-tool check   |
| Tap target           | 48 dp, 44 pt    | a minimum button size in the theme   |
| Text scaling         | up to 2 times   | no fixed heights, let rows wrap      |
| Focus order          | follows reading | widget order equals visual order     |

---

**Test with the phone's own settings.** Set the font size to the largest step, turn a screen reader on, and open every screen.

# Localized strings in ARB files

```
# pubspec.yaml
flutter:
  generate: true

# l10n.yaml
arb-dir: lib/l10n
template-arb-file: app_en.arb
output-localization-file: app_localizations.dart
```

Add `flutter_localizations` and `intl` as dependencies. Building the app regenerates the `AppLocalizations` class from the ARB files. Pass `AppLocalizations.localizationsDelegates` and `supportedLocales` to `MaterialApp`, then read a string with `AppLocalizations.of(context)`.

# Plurals, dates, and right-to-left layout

```
// lib/l10n/app_en.arb
"totalCount": "{count, plural, =0{No todos} =1{1 todo} other{{count} todos}}",
"@totalCount": { "placeholders": { "count": { "type": "int" } } }

// In the widget
Text(AppLocalizations.of(context)!.totalCount(items.length));
Text(DateFormat.yMMMd(locale).format(todo.due));

// Right to left: start and end, never left and right
padding: const EdgeInsetsDirectional.only(start: 16),
```

Some languages have more than two plural forms, which is why you never build a sentence by concatenation.

# 5

## Testing

Unit, widget, bloc, golden and integration tests

| Contents                         | Page      |
|----------------------------------|-----------|
| 1 Theming                        | 3         |
| 2 Forms                          | 11        |
| 3 Implicit animations            | 16        |
| 4 Accessibility and localization | 21        |
| <b>5 Testing</b>                 | <b>27</b> |

# The testing pyramid

| Layer       | Runs on              | Speed        | What it proves                        |
|-------------|----------------------|--------------|---------------------------------------|
| Unit        | the Dart VM, no UI   | milliseconds | a validator, a model, a repository    |
| Widget      | a headless tree      | milliseconds | a screen builds and reacts to a tap   |
| Bloc        | the Dart VM          | milliseconds | an event produces these states        |
| Golden      | a headless tree      | fast         | the pixels did not change by accident |
| Integration | a device or emulator | seconds      | the whole app, plugins and network    |

**Write many cheap tests and a few expensive ones.** Every layer catches a bug the layer below cannot see, and costs more to write and to run.

# Unit tests

```
// test/validators_test.dart
void main() {
  group('validateEmail', () {
    test('rejects an empty value', () {
      expect(validateEmail(''), 'Enter your email');
    });
    test('accepts a normal address', () {
      expect(validateEmail('ana@example.com'), isNull);
    });
  });
}
```

Files end in `_test.dart` and live under `test/`. Run them all with `flutter test`.

## Widget tests: testWidgets, find, pump

```
testWidgets('adding a todo shows it in the list', (tester) async {  
  await tester.pumpWidget(const MaterialApp(home: TodoScreen()));  
  
  await tester.enterText(find.byType(TextField), 'Buy milk');  
  await tester.tap(find.byIcon(Icons.add));  
  await tester.pump(); // build one new frame  
  
  expect(find.text('Buy milk'), findsOneWidget);  
  expect(find.byType(TodoTile), findsNWidgets(1));  
});
```

Finders: `find.text`, `find.byType`, `find.byIcon`, `find.byKey`. Matchers: `findsOneWidget`, `findsNothing`, `findsNWidgets(n)`.

## pump and pumpAndSettle

```
await tester.pump();  
// one frame  
  
await tester.pump(  
  const Duration(milliseconds: 300));  
// advance time by 300 ms  
  
await tester.pumpAndSettle();  
// frames until no animation is left
```

**Test time does not pass on its own.** Nothing animates, no timer fires and no Future completes until you pump, so the test is deterministic.

---

### Watch out

`pumpAndSettle` never returns if something animates forever, such as a spinner. Pump a fixed duration instead.

# Mocking with mocktail

```
class MockTodoRepository extends Mock implements TodoRepository {}

late MockTodoRepository repo;

setUp(() {
  repo = MockTodoRepository();
  when(() => repo.load()).thenAnswer((_) async => [Todo(id: 1)]);
});

test('the cubit asks the repository once', () async {
  await TodoCubit(repo).load();
  verify(() => repo.load()).called(1);
});
```

## Bloc tests

```
blocTest<TodoBloc, TodoState>(  
  'emits loading then loaded when TodosRequested is added',  
  build: () => TodoBloc(repo),           // repo is a mock, see previous slide  
  act: (bloc) => bloc.add(const TodosRequested()),  
  expect: () => [  
    const TodoState.loading(),  
    TodoState.loaded([Todo(id: 1)]),  
  ],  
);
```

---

**This is why state classes carry value equality.** `expect` compares the emitted states to your list. Without `Equatable`, two identical states are not equal and the test fails.

## Golden tests

```
testWidgets('TodoTile matches its golden', (tester) async {  
  await tester.pumpWidget(wrap(const TodoTile(title: 'Buy milk')));  
  await expectLater(  
    find.byType(TodoTile),  
    matchesGoldenFile('goldens/todo_tile.png'),  
  );  
});
```

Create or update the reference images with `flutter test --update-goldens`, then review them in the pull request like any other change.

---

**Commit the golden files.** The diff in the review is a picture, so a designer can review it.

# integration\_test and CI

```
flutter analyze
flutter test           # unit, widget, bloc, golden
flutter test integration_test # on a booted device or emulator
```

An integration test starts with

`IntegrationTestWidgetsFlutterBinding.ensureInitialized()` and then uses the same `testWidgets` API, except that the full app runs on a device with its plugins.

---

**Run analyze and test on every pull request.** A branch that fails the checks cannot be merged. The pipeline itself is Lecture 15.

# Summary

1. Declare colors and type once. A widget that reads a role instead of a hex value already supports dark mode, large text and a rebrand.
2. Keep animations short and error messages specific. Use a 48 dp tap target, and a layout that adapts when the window is twice as wide.
3. Tests are how a refactor stays cheap. Many unit and widget tests, a few golden and integration tests, all of them run by CI.

## Further reading

[docs.flutter.dev/ui/design/material](https://docs.flutter.dev/ui/design/material) · [Accessibility and i18n](#) · [Testing overview](#)

# Questions?

dinu\_stefan.rusu@upb.ro · Microsoft Teams: course channel