

Documentation

The implementation uses the Python language.

For solving the problem statement we shall define:

- a class named **TripleDictGraph** which represents a directed graph,
- a class named **UI** for testing the operations
- and **4** additional **functions** for **reading** from a file and **writing** in a file.

In what follows, an **edge** is considered a **tuple (origin, target)**.

The isolated vertices are marked.

The class TripleDictGraph is initialized with the following data:

self._number_of_vertices

- the number of vertices the graph has

self._number_of_edges

- the number of edges the graph has

self._dictionary_in

- a dictionary for keeping the inbound vertices of each vertex, the vertices are the keys

self._dictionary_out

- a dictionary for keeping the outbound vertices of each vertex, the vertices are the keys

self._dictionary_cost

- a dictionary for keeping the edges and their costs, the edges are the keys

The class TripleDictGraph will provide the following methods:

- `dictionary_cost(self)`
 - returns the dictionary of edges and costs of the graph
- `dictionary_in(self)`
 - returns the dictionary of inbound vertices of the graph
- `dictionary_out(self)`
 - returns the dictionary of outbound vertices of the graph
- `number_of_vertices(self)`
 - returns the number of vertices the graph has
- `number_of_edges(self)`

Homework 1

- returns the number of edges the graph has
- `parse_vertices(self)`
 - iterator for the vertices of the graph
- `parse_inbound(self, x)`
 - iterator for the inbound vertices of the vertex `x`
- `parse_outbound(self, x)`
 - iterator for the outbound vertices of the vertex `x`
- `parse_cost(self)`
 - iterator for the edges of the graph and their costs
- `add_vertex(self, x)`
 - add a new vertex `x` to the graph; returns `False` if it doesn't add it and `True` otherwise. Precondition: the vertex `x` must not already exist
- `remove_vertex(self, x)`
 - remove a vertex `x` from the graph; return `False` if it doesn't remove it and `True` otherwise. Precondition: the vertex `x` must be an existing one
- `in_degree(self, x)`
 - return the in degree of the vertex `x` or `-1` if the vertex does not exist. Precondition: the vertex `x` must be an existing one
- `out_degree(self, x)`
 - return the out degree of a vertex `x` or `-1` if the vertex does not exist. Precondition: the vertex `x` must be an existing one
- `add_edge(self, x, y, cost)`
 - add a new edge `(x, y)` to the graph; returns `False` if it doesn't add and `True` otherwise. Precondition: the edge `(x, y)` must not already exist in the graph
- `remove_edge(self, x, y)`
 - remove an edge `(x, y)` from the graph; returns `False` if it doesn't remove it and `True` otherwise. Precondition: the edge `(x, y)` must already exist in the graph
- `find_edge(self, x, y)`
 - returns the cost of the edge `(x, y)` if it exists and `False` otherwise. Precondition: the edge `(x, y)` must already exist in the graph
- `change_cost(self, x, y, cost)`
 - change the cost of an edge `(x, y)` to be equal to `cost`; returns `True` if it changes, `False` otherwise. Precondition: the edge `(x, y)` must already exist in the graph
- `make_copy(self)`
 - return a copy of the graph

The 4 additional functions for reading/writing from/in a file are:

- `write_graph_to_file(graph, file)`
 - receiving as parameters a graph and a file it writes in a file the graph; if the file does not exist it creates it; if the dictionaries used for printing, dictionary of costs and inbound dictionary, are empty a `ValueError` will be raised and an error will be written in the file
- `read_graph_from_file(filename)`
 - it has as a parameter a file name from which the graph should be read.
Precondition: the file must exist
- `write_modified_graph_to_file(graph, file)`
 - receiving as parameters a graph and a file it writes in a file the graph; if the file does not exist it creates it; if the dictionaries used for printing, dictionary of costs and inbound dictionary, are empty a `ValueError` will be raised and an error will be written in the file
- `read_modified_graph_from_file(filename)`
 - it has as a parameter a file name from which the graph should be read.
Precondition: the file must exist

The UI class is initialized with the following data:

`self._graphs`

- a list that keeps the graphs created, used for switching between the graphs, it is empty initially

`self._current`

- an element that memorizes the current graph with which the user is working it is set to `None` initially

The UI class will provide the following methods:

- `add_empty_graph(self)`
 - creates an empty graph and adds it to the list of graphs available in the program, setting it to be the current graph also
- `create_random_graph_ui(self)`
 - takes as input from the user the number of vertices and edges and creates a random graph, adds it to the list, and sets it to be the current graph
- `generate_random(self, vertices, edges)`
 - the `create_random_graph_ui` function uses it for generating a random graph; it raises a `ValueError` if the user provides too many edges and it returns the new graph
- `read_graph_from_file_ui(self)`
 - takes the filename from the input of the user and creates a new graph using the `read_graph_from_file`, adds it to the list of graphs, and sets it as the current graph

Homework 1

- `write_graph_to_file_ui(self)`
 - writes using the function `write_graph_to_file` the current graph that the program is working within the format: `no_of_vertices no_of_edges x y cost` (this line can be repeated multiple times)
- `read_modified_graph_from_file_ui(self)`
 - takes the filename from the input of the user and creates a new graph using the `read_modified_graph_from_file`, adds it to the list of graphs, and sets it as the current graph
- `write_modified_graph_to_file_ui(self)`
 - writes using the function `write_modified_graph_to_file` the current graph that the program is working within the format: `x y cost` (this line can be repeated multiple times)
- `switch_graph_ui(self)`
 - switch the graphs, the switch is done between available graphs in the `self._graphs` list Precondition: the graph to be switched to has to exist in the list Raises `ValueError` if the graph is not in the list
- `get_number_of_vertices_ui(self)`
 - print the number of vertices the current graph has
- `get_number_of_edges_ui(self)`
 - print the number of edges the current graph has
- `list_all_outbound(self)`
 - lists all the vertices from the current graph with all their outbound vertices
- `list_outbound(self, x)`
 - lists the outbound vertices of the vertex `x`
- `list_all_inbound(self)`
 - lists all the vertices from the current graph with all their inbound vertices
- `list_inbound(self, x)`
 - lists the inbound vertices of the vertex `x`
- `list_all_costs(self)`
 - lists all the edges of the graph with their cost
- `parse_all_vertices(self)`
 - list all the vertices of the graph
- `add_vertex_ui(self)`
 - reads input from the user for the vertex and uses the `add_vertex` function to add a vertex to the graph; prints a corresponding message
- `delete_vertex_ui(self)`
 - reads input from the user for the vertex and uses the `remove_vertex` function to remove a vertex from the graph; prints a corresponding message
- `add_edge_ui(self)`
 - reads input for vertices and cost from the user and uses the `add_edge` function to add an edge with a cost to the graph; prints a corresponding message
- `remove_edge_ui(self)`
 - reads input for vertices from the user and uses the `remove_edge` function to remove an edge from the graph; prints a corresponding message

Homework 1

- `modify_cost_ui(self)`
 - read input from the user for the vertices and the cost and uses the `change_cost` function to change the cost of an edge; prints a corresponding message
- `get_in_degree_ui(self)`
 - prints the in degree of a vertex given by the user; prints a corresponding message
- `get_out_degree_ui(self)`
 - prints the out degree of a vertex given by the user; prints a corresponding message
- `check_if_edge_ui(self)`
 - checks if an edge given by the user exists and if it does it prints its cost
- `copy_current_graph_ui(self)`
 - creates a copy of the graph using the `make_copy` function

In the **UI class** we also have a function to print the menu, for the user to know its options and start the program.

At the beginning, the program initializes the current graph with an empty graph and gives the user various options to modify the elements.

The graph can be stored in an output file and used at another application run.