

# M4GB: An Efficient Gröbner Basis Algorithm

Rusydi H. Makarim<sup>1,2</sup>    Marc Stevens<sup>2</sup>

<sup>1</sup>Mathematics Institute, University Leiden

<sup>2</sup>Cryptology Group, Centrum Wiskunde en Informatica (CWI)

ALGANT-DOC Meeting, 15th May 2017

- 1 Introduction
- 2 Gröbner Basis
- 3 M4GB Algorithm
- 4 Performance Comparison
- 5 Solving MQ Challenges

# Table of Contents

- 1 Introduction
- 2 Gröbner Basis
- 3 M4GB Algorithm
- 4 Performance Comparison
- 5 Solving MQ Challenges

# Problem

- $\mathbb{F}$  - A Field
- $n$  - number of variables
- $m$  - number of equations

# Problem

- $\mathbb{F}$  - A Field
- $n$  - number of variables
- $m$  - number of equations

Problem (Multivariate Quadratic(MQ) problem)

# Problem

- $\mathbb{F}$  - A Field
- $n$  - number of variables
- $m$  - number of equations

## Problem (Multivariate Quadratic(MQ) problem)

- *Given* :  $f_1, \dots, f_m \in \mathbb{F}[x_1, \dots, x_n]$ ,  $\deg(f_i) = 2$

# Problem

- $\mathbb{F}$  - A Field
- $n$  - number of variables
- $m$  - number of equations

## Problem (Multivariate Quadratic(MQ) problem)

- *Given* :  $f_1, \dots, f_m \in \mathbb{F}[x_1, \dots, x_n]$ ,  $\deg(f_i) = 2$
- *Problem* : Find a  $(v_1, \dots, v_n) \in \mathbb{F}^n$  such that

$$f_1(v_1, \dots, v_n) = 0$$

$$\vdots$$

$$f_m(v_1, \dots, v_n) = 0$$

# Why MQ Problem ?

- MQ-problem is NP-complete



# Why MQ Problem ?

- MQ-problem is NP-complete
- Candidate for post-quantum public-key and digital-signature scheme

# Why MQ Problem ?

- MQ-problem is NP-complete
- Candidate for post-quantum public-key and digital-signature scheme
- Need to understand its practical difficulty (How ?)

# Why MQ Problem ?

- MQ-problem is NP-complete
- Candidate for post-quantum public-key and digital-signature scheme
- Need to understand its practical difficulty (How ?)

## Open Public Challenge - MQChallenge

- Initiated at 2015
- Random and dense system
- Various parameters

# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$			
$m \approx 2/3n$			

# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
$m \approx 2/3n$			

# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$			

# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$	IV	V	VI

# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$	IV	V	VI
	$m \geq 55$	$m \geq 16$	$m \geq 16$



# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$	IV	V	VI
	$m \geq 55$	$m \geq 16$	$m \geq 16$

## Parameter Choice

Require at least **one month** for Magma 2.19-9 to solve using **Four 6-cores Intel(R) Xeon(R) CPU E5-4617 @ 2.9GHz** and **1TB of RAM**.

# MQ Challenge Types

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$	IV	V	VI
	$m \geq 55$	$m \geq 16$	$m \geq 16$

## Parameter Choice

Require at least **one month** for Magma 2.19-9 to solve using **Four 6-cores Intel(R) Xeon(R) CPU E5-4617 @ 2.9GHz** and **1TB of RAM**.

<https://www.mqchallenge.org>

# Solving MQ-problem

- Linearization

# Solving MQ-problem

- Linearization
- Extended Linearization (XL)

# Solving MQ-problem

- Linearization
- Extended Linearization (XL)

This talk

## Gröbner basis

# Table of Contents

- 1 Introduction
- 2 Gröbner Basis**
- 3 M4GB Algorithm
- 4 Performance Comparison
- 5 Solving MQ Challenges

# Ordering Monomial in $\mathbb{F}[x_1, \dots, x_n]$

## Definition (Monomial Ordering)

$>$  is a monomial ordering if

# Ordering Monomial in $\mathbb{F}[x_1, \dots, x_n]$

## Definition (Monomial Ordering)

$>$  is a monomial ordering if

- 1 Total (or linear) ordering on  $\mathbb{Z}_{\geq 0}^n$



# Ordering Monomial in $\mathbb{F}[x_1, \dots, x_n]$

## Definition (Monomial Ordering)

$>$  is a monomial ordering if

- ① Total (or linear) ordering on  $\mathbb{Z}_{\geq 0}^n$
- ② Let  $\alpha, \beta, \gamma \in \mathbb{Z}_{\geq 0}^n$  and  $x = (x_1, \dots, x_n)$

$$x^\alpha > x^\beta \Rightarrow x^\gamma x^\alpha > x^\gamma x^\beta$$

# Ordering Monomial in $\mathbb{F}[x_1, \dots, x_n]$

## Definition (Monomial Ordering)

$>$  is a monomial ordering if

- ① Total (or linear) ordering on  $\mathbb{Z}_{\geq 0}^n$
- ② Let  $\alpha, \beta, \gamma \in \mathbb{Z}_{\geq 0}^n$  and  $x = (x_1, \dots, x_n)$

$$x^\alpha > x^\beta \Rightarrow x^\gamma x^\alpha > x^\gamma x^\beta$$

- ③  $>$  is a well-ordering on  $\mathbb{Z}_{\geq 0}^n$

# Monomial Ordering : Examples

## Lexicographic

$x^\alpha >_{\text{lex}} x^\beta \Leftrightarrow$  the leftmost nonzero entry of  $\alpha - \beta$  is positive

# Monomial Ordering : Examples

## Lexicographic

$x^\alpha >_{\text{lex}} x^\beta \Leftrightarrow$  the leftmost nonzero entry of  $\alpha - \beta$  is positive

## Degree-Reverse Lexicographic (degrevlex)

$x^\alpha >_{\text{degrevlex}} x^\beta \Leftrightarrow$

# Monomial Ordering : Examples

## Lexicographic

$x^\alpha >_{\text{lex}} x^\beta \Leftrightarrow$  the leftmost nonzero entry of  $\alpha - \beta$  is positive

## Degree-Reverse Lexicographic (degrevlex)

$x^\alpha >_{\text{degrevlex}} x^\beta \Leftrightarrow$

•  $\sum_i \alpha_i > \sum_i \beta_i$  OR

# Monomial Ordering : Examples

## Lexicographic

$x^\alpha >_{\text{lex}} x^\beta \Leftrightarrow$  the leftmost nonzero entry of  $\alpha - \beta$  is positive

## Degree-Reverse Lexicographic (degrevlex)

$x^\alpha >_{\text{degrevlex}} x^\beta \Leftrightarrow$

- $\sum_i \alpha_i > \sum_i \beta_i$  OR
- $\sum_i \alpha_i = \sum_i \beta_i$  and the rightmost nonzero entry of  $\alpha - \beta$  is negative

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$$



# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$

- $\text{LM}(f)$  (the largest monomial of  $f$  w.r.t  $>$ )

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$

- $\text{LM}(f)$  (the largest monomial of  $f$  w.r.t  $>$ )
- $\text{LC}(f)$  (the coefficient correspond to  $\text{LM}(f)$ )

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$

- $\text{LM}(f)$  (the largest monomial of  $f$  w.r.t  $>$ )
- $\text{LC}(f)$  (the coefficient correspond to  $\text{LM}(f)$ )
- $\text{LT}(f) = \text{LC}(f) \cdot \text{LM}(f)$

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$

- $\text{LM}(f)$  (the largest monomial of  $f$  w.r.t  $>$ )
- $\text{LC}(f)$  (the coefficient correspond to  $\text{LM}(f)$ )
- $\text{LT}(f) = \text{LC}(f) \cdot \text{LM}(f)$
- $\text{Tail}(f) = f - \text{LT}(f)$

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$

- $\text{LM}(f)$  (the largest monomial of  $f$  w.r.t  $>$ )
- $\text{LC}(f)$  (the coefficient correspond to  $\text{LM}(f)$ )
- $\text{LT}(f) = \text{LC}(f) \cdot \text{LM}(f)$
- $\text{Tail}(f) = f - \text{LT}(f)$
- $\text{Term}(f), \text{Mono}(f)$

# Notations

$\mathbb{F}[x_1, \dots, x_n]$  together with  $>$

## Notations

$f \in \mathbb{F}[x_1, \dots, x_n], f \neq 0$

- $\text{LM}(f)$  (the largest monomial of  $f$  w.r.t  $>$ )
- $\text{LC}(f)$  (the coefficient correspond to  $\text{LM}(f)$ )
- $\text{LT}(f) = \text{LC}(f) \cdot \text{LM}(f)$
- $\text{Tail}(f) = f - \text{LT}(f)$
- $\text{Term}(f), \text{Mono}(f)$

$$F \subseteq \mathbb{F}[x_1, \dots, x_n] \begin{cases} \text{Tail}(F) = \cup_{f \in F} \{\text{Tail}(f)\} \\ \text{Term}(F) = \cup_{f \in F} \text{Term}(f) \\ \text{Mono}(F) = \cup_{f \in F} \text{Mono}(f) \end{cases}$$

# Gröbner Basis : Definition

## Definition

# Gröbner Basis : Definition

## Definition

$I \neq \{0\}$  be an ideal of  $\mathbb{F}[x_1, \dots, x_n]$



# Gröbner Basis : Definition

## Definition

$I \neq \{0\}$  be an ideal of  $\mathbb{F}[x_1, \dots, x_n]$

$G \subseteq I$ ,  $|G| < \infty$  that generates  $I$  is a Gröbner basis of  $I$  if,

# Gröbner Basis : Definition

## Definition

$I \neq \{0\}$  be an ideal of  $\mathbb{F}[x_1, \dots, x_n]$   
 $G \subseteq I$ ,  $|G| < \infty$  that generates  $I$  is a Gröbner basis of  $I$  if,

for any  $f \in I$ ,  $\exists g \in G$  s.t.  $\text{LT}(g) \mid \text{LT}(f)$

# Gröbner Basis and Solving System of Equations

# Gröbner Basis and Solving System of Equations

## Lexicographic Ordering

$$\begin{aligned} &g_1(x_1), \dots, \\ &g_2(x_1, x_2), \dots, g_{k_1}(x_1, x_2) \\ &g_{k_1+1}(x_1, x_2, x_3), \dots, \\ &g_{k_n}(x_1, \dots, x_n) \end{aligned}$$

# Gröbner Basis and Solving System of Equations

## Lexicographic Ordering

$$\begin{aligned} g_1(x_1), \dots, \\ g_2(x_1, x_2), \dots, g_{k_1}(x_1, x_2) \\ g_{k_1+1}(x_1, x_2, x_3), \dots, \\ g_{k_n}(x_1, \dots, x_n) \end{aligned}$$

## Unique Solution in the Base Field

$$\begin{aligned} g_1 &= x_1 + c_1, \\ &\vdots \\ g_n &= x_n + c_n \end{aligned}$$



## Question

Given  $f_1, \dots, f_m \in \mathbb{F}[x_1, \dots, x_n]$ , how to compute the Gröbner basis  $G$  of  $\langle f_1, \dots, f_m \rangle$  ?

## Question

Given  $f_1, \dots, f_m \in \mathbb{F}[x_1, \dots, x_n]$ , how to compute the Gröbner basis  $G$  of  $\langle f_1, \dots, f_m \rangle$  ?

How to obtain new element in the ideal ?



## Question

Given  $f_1, \dots, f_m \in \mathbb{F}[x_1, \dots, x_n]$ , how to compute the Gröbner basis  $G$  of  $\langle f_1, \dots, f_m \rangle$  ?

How to obtain new element in the ideal ?

- 1 Generate polynomials of higher degree

## Question

Given  $f_1, \dots, f_m \in \mathbb{F}[x_1, \dots, x_n]$ , how to compute the Gröbner basis  $G$  of  $\langle f_1, \dots, f_m \rangle$  ?

How to obtain new element in the ideal ?

- ① Generate polynomials of higher degree
- ② Division algorithm in  $\mathbb{F}[x_1, \dots, x_n]$  (computing remainder)

# Generate higher degree polynomial : S-Polynomial

# Generate higher degree polynomial : S-Polynomial

- $f, g \in \mathbb{F}[x_1, \dots, x_n]$  with  $f \neq 0, g \neq 0$

# Generate higher degree polynomial : S-Polynomial

- $f, g \in \mathbb{F}[x_1, \dots, x_n]$  with  $f \neq 0, g \neq 0$
- $x^\gamma = \text{LCM}(\text{LM}(f), \text{LM}(g))$

# Generate higher degree polynomial : S-Polynomial

- $f, g \in \mathbb{F}[x_1, \dots, x_n]$  with  $f \neq 0, g \neq 0$
- $x^\gamma = \text{LCM}(\text{LM}(f), \text{LM}(g))$

## Definition

$$\text{Spoly}(f, g) = \frac{x^\gamma}{\text{LT}(f)} \cdot f - \frac{x^\gamma}{\text{LT}(g)} \cdot g.$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$xy + z \mid x^2y^2 + z^4 + xy$$

---



---



---



---



---



---

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$xy + z \overline{\begin{array}{r} xy \\ x^2y^2 + z^4 + xy \end{array}}$$

---



---



---



---



---



---



# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$xy + z \overline{\begin{array}{r} xy \\ x^2y^2 + z^4 + xy \\ x^2y^2 + xyz \end{array}}$$

---



---



---



---



---

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \end{array}} \\
 \hline
 \\
 \hline
 \\
 \hline
 \\
 \hline
 \\
 \hline
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$xy + z \overline{\begin{array}{r} xy \\ x^2y^2 + z^4 + xy \\ x^2y^2 + xyz \\ \hline z^4 - xyz + xy \end{array}} \quad r$$

---



---



---



---



---

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy \\ x^2y^2 + z^4 + xy \\ x^2y^2 + xyz \\ \hline z^4 - xyz + xy \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array}
 \end{array}$$

---



---



---



---



---

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy \\ x^2y^2 + z^4 + xy \\ x^2y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array} \\
 \hline
 \end{array}$$

---



---



---



---

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy \\ x^2y^2 + z^4 + xy \\ x^2y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array} \\
 \hline \\
 \hline \\
 \hline \\
 \hline
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array} \\
 \hline
 \\
 \hline
 \\
 \hline
 \\
 \hline
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline \end{array} } \quad \begin{array}{l} r \\ \\ z^4 \end{array} \\
 \hline
 \\
 \hline
 \\
 \hline
 \\
 \hline
 \end{array}$$



# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array} \\
 \hline \\
 \hline \\
 \hline
 \end{array}$$

Division Algorithm in  $\mathbb{F}[x_1, \dots, x_n]$  : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array} \\
 \hline \\
 \hline \\
 \hline
 \end{array}$$

Division Algorithm in  $\mathbb{F}[x_1, \dots, x_n]$  : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline \hline \hline \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \end{array}
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \end{array}} \quad \begin{array}{l} r \\ \\ \\ z^4 \\ \\ \\ \end{array} \\
 \hline \\
 \hline
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \\ \\ \\ z^4 + z^2 \end{array} \\
 \hline \\
 \hline
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \\ z^2 \\ \hline \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \\ \\ \\ z^4 + z^2 \end{array}
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \\ z^2 \\ \hline -z \\ \hline \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \\ \\ \\ z^4 + z^2 \end{array}
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \\ z^2 \\ \hline -z \end{array}} \\
 \hline
 \end{array}
 \begin{array}{l}
 r \\
 \\
 z^4 \\
 \\
 \\
 \\
 z^4 + z^2 \\
 \\
 z^4 + z^2 - z
 \end{array}$$



Division Algorithm in  $\mathbb{F}[x_1, \dots, x_n]$  : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \\ z^2 \\ \hline -z \\ -z \\ \hline \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \\ \\ \\ z^4 + z^2 \\ z^4 + z^2 - z \end{array}
 \end{array}$$

# Division Algorithm in $\mathbb{F}[x_1, \dots, x_n]$ : Example

$$\begin{array}{r}
 xy + z \overline{) \begin{array}{l} xy - z + 1 \\ x^2 y^2 + z^4 + xy \\ x^2 y^2 + xyz \\ \hline z^4 - xyz + xy \\ z^4 \\ \hline -xyz + xy \\ -xyz - z^2 \\ \hline xy + z^2 \\ xy + z \\ \hline z^2 - z \\ z^2 \\ \hline -z \\ -z \\ \hline 0 \end{array}} \quad \begin{array}{l} r \\ \\ z^4 \\ \\ \\ z^4 + z^2 \\ z^4 + z^2 - z \end{array}
 \end{array}$$

# Division Algorithm / Polynomial Reduction

$$G = (g_1, \dots, g_t) \subseteq \mathbb{F}[x_1, \dots, x_n]$$

# Division Algorithm / Polynomial Reduction

$$G = (g_1, \dots, g_t) \subseteq \mathbb{F}[x_1, \dots, x_n]$$

## Theorem (Division Algorithm)

Every  $f \in \mathbb{F}[x_1, \dots, x_n]$  can be written as

$$f = q_1 g_1 + \dots + q_t g_t + r$$

and

$$r = \begin{cases} 0 \\ \text{none of terms of } r \text{ is divisible by any of } \text{LT}(g_i) \end{cases}$$

# Division Algorithm / Polynomial Reduction

$$G = (g_1, \dots, g_t) \subseteq \mathbb{F}[x_1, \dots, x_n]$$

## Theorem (Division Algorithm)

Every  $f \in \mathbb{F}[x_1, \dots, x_n]$  can be written as

$$f = q_1 g_1 + \dots + q_t g_t + r$$

and

$$r = \begin{cases} 0 \\ \text{none of terms of } r \text{ is divisible by any of } \text{LT}(g_i) \end{cases}$$

$$r \leftarrow \text{FULLREDUCE}(f, G)$$

# Buchberger's Algorithm

**Input:** A finite ordered subset  $F \subseteq \mathbb{F}[x_1, \dots, x_n]$

**Result:** A Gröbner basis  $G$  such that  $\langle G \rangle = \langle F \rangle$

$G \leftarrow F$

**repeat**

$G' \leftarrow G$

**forall**  $(p, q) \in G' \times G', p \neq q$  **do**

$r \leftarrow \text{FULLREDUCE}(\text{Spoly}(p, q), G')$

**if**  $r \neq 0$  **then**

$G \leftarrow G \cup \{r\}$

**until**  $G = G'$ ;

**return**  $G$

# Table of Contents

- 1 Introduction
- 2 Gröbner Basis
- 3 M4GB Algorithm**
- 4 Performance Comparison
- 5 Solving MQ Challenges

- Gröbner bases algorithms follows the same principle



- Gröbner bases algorithms follows the same principle
- Differs in reduction techniques

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering



# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2 \quad \left| \quad G = \{g_1, g_2, g_3\} \right.$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2 \quad \left| \quad G = \{g_1, g_2, g_3\} \right.$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$



# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3, g_4\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$g_4 = x_1 g_2 - g_3 = x_1 x_2^3 x_4 + 1$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = \textcolor{red}{x_1 x_2^3 x_4} + x_1^3 x_4 + x_2 x_3^2$$

$$G = \{g_1, g_2, g_3, g_4\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$g_4 = x_1 g_2 - g_3 = \textcolor{red}{x_1 x_2^3 x_4} + 1$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$f = f - g_4 = x_1^3 x_4 + x_2 x_3^2 + 1$$

$$G = \{g_1, g_2, g_3, g_4\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$g_4 = x_1 g_2 - g_3 = x_1 x_2^3 x_4 + 1$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$

# Example : Standard Reduction vs M4GB Reduction

$\mathbb{F}_2[x_1, x_2, x_3, x_4]$  with *degrevlex* ordering

$$f = x_1^2 x_2^3 + x_1 x_2^3 x_4 + x_1 x_3^3 + x_1^3 x_4 + x_2 x_3^2 + x_4^2$$

$$f = f - g_1 = x_1 x_2^3 x_4 + x_1^3 x_4 + x_2 x_3^2$$

$$f = f - g_4 = x_1^3 x_4 + x_2 x_3^2 + 1$$

$$G = \{g_1, g_2, g_3, g_4\}$$

$$g_1 = x_1^2 x_2^3 + x_1 x_3^3 + x_4^2$$

$$g_2 = x_2^3 x_4 + x_2 x_3 + x_3 + 1$$

$$g_3 = x_1 x_2 x_3 + x_1 x_3$$

$$g_4 = x_1 g_2 - g_3 = x_1 x_2^3 x_4 + 1$$

$$x_1 g_2 = x_1 x_2^3 x_4 + x_1 x_2 x_3 + x_1 x_3 + x_1$$

$$r = x_1^3 x_4 + x_2 x_3^2 + 1$$

## M4GB Main Strategy

Maintain tail-reduced polynomials

# M4GB Reduction

MULFULLREDUCE( $G, u, f$ )

```

 $r \leftarrow 0$ 
forall  $t \in \text{Term}(f)$  do
   $t' \leftarrow u \cdot t$ 
  if  $\exists g \in G : \text{LT}(g) \mid t'$  then
     $(G, g) \leftarrow \text{GETREDUCTOR}(G, t')$ 
     $r \leftarrow r - (t' / \text{LT}(g)) \cdot \text{Tail}(g)$ 
  else
     $r \leftarrow r + t'$ 
return  $(G, r)$ 

```



# M4GB Reduction

$\text{MULFULLREDUCE}(G, u, f)$

```

 $r \leftarrow 0$ 
forall  $t \in \text{Term}(f)$  do
   $t' \leftarrow u \cdot t$ 
  if  $\exists g \in G : \text{LT}(g) \mid t'$  then
     $(G, g) \leftarrow \text{GETREDUCTOR}(G, t')$ 
     $r \leftarrow r - (t' / \text{LT}(g)) \cdot \text{Tail}(g)$ 
  else
     $r \leftarrow r + t'$ 
return  $(G, r)$ 

```

$\text{GETREDUCTOR}(G, t)$

```

if  $\exists g \in G : \text{LM}(g) = \text{LM}(t)$  then
  return  $(G, g)$ 
 $h \leftarrow \text{SELECTREDUCTOR}(G, t)$ 
 $(G, h) \leftarrow$ 
   $\text{MULFULLREDUCE}(G, t / \text{LT}(h), \text{Tail}(h))$ 
 $g \leftarrow t + h$ 
return  $(G \cup \{g\}, g)$ 

```

# UPDATEREDUCE( $G, f$ )

$$H \leftarrow \{LC(f)^{-1} \cdot f\}$$

$$Q \leftarrow \text{Mono}(\text{Tail}(G \cup H)) \setminus \text{LM}(H)$$
**while**  $\exists u \in Q : \text{LM}(f) \mid u$  **do**

$$\begin{array}{l} u \leftarrow \max\{m \in Q : \text{LM}(f) \mid m\} \\ (G, h) \leftarrow \text{MULFULLREDUCE}(G, u/\text{LT}(f), \text{Tail}(f)) \\ H \leftarrow H \cup \{u + h\} \\ Q \leftarrow \text{Mono}(\text{Tail}(G \cup H)) \setminus \text{LM}(H) \end{array}$$
**while**  $H \neq \{\}$  **do**

$$\begin{array}{l} \text{Select } h \in H \text{ such that } \text{LM}(h) = \min \text{LM}(H) \\ H \leftarrow H \setminus \{h\} \\ H \leftarrow \{g - ch : g \in H, c \text{ is a coefficient of } \text{LM}(h) \text{ in } \text{Tail}(g)\} \\ G \leftarrow \{g - ch : g \in G, c \text{ is a coefficient of } \text{LM}(h) \text{ in } \text{Tail}(g)\} \\ G \leftarrow G \cup \{h\} \end{array}$$

# Table of Contents

- 1 Introduction
- 2 Gröbner Basis
- 3 M4GB Algorithm
- 4 Performance Comparison**
- 5 Solving MQ Challenges

- Implemented using C++11

- Implemented using C++11
- Comparison with existing implementations
  - ① FGb C Interface - Implementation by Jean Charles Faugere<sup>1</sup>
  - ② Magma v2.20-6
  - ③ OpenF4 v1.0.1 - Open source implementation by Coladon, Vitse and Joux<sup>2</sup>.

---

<sup>1</sup>Available at <http://www-polsys.lip6.fr/~jcf/FGb/C/index.html>

<sup>2</sup>Available at <https://github.com/nauotit/openf4>

- Implemented using C++11
- Comparison with existing implementations
  - ① FGb C Interface - Implementation by Jean Charles Faugere<sup>1</sup>
  - ② Magma v2.20-6
  - ③ OpenF4 v1.0.1 - Open source implementation by Coladon, Vitse and Joux<sup>2</sup>.
- Test cases
  - ① Dense polynomials with coefficients in  $\mathbb{F}_{31}$
  - ②  $m = 2n$  and  $m = n + 1$ .

---

<sup>1</sup>Available at <http://www-polsys.lip6.fr/~jcf/FGb/C/index.html>



<sup>2</sup>Available at <https://github.com/nauotit/openf4>

# Benchmark for $m = 2n$

		Total CPU time (sec)			
$n$	$m$	M4GB	OpenF4	Magma	FGb
20	40	57	206	232	470
21	42	170	472	500	1002
22	44	424	1145	1617	3118
23	46	1060	2274	3185	6849
24	48	2556	10293	31168	64700
25	50	5575	-	77679	151653
26	52	15517	-	183629	360055
27	54	46548	-	409452	767543

		Memory (MB)			
$n$	$m$	M4GB	FGb	Magma	OpenF4
20	40	73	112	362	4240
21	42	121	165	577	6640
22	44	226	525	859	14368
23	46	395	918	1324	26135
24	48	663	1561	8873	161945
25	50	1471	2765	19719	-
26	52	3328	4607	25197	-
27	54	6799	8180	39845	-

# Graph for $m = 2n$







# Benchmark for $m = n + 1$

		Total CPU time (sec)			
$n$	$m$	M4GB	OpenF4	Magma	FGb
10	11	0.98	2.99	3.29	5
11	12	2.6	8.73	11.172	21
12	13	13.92	36.76	59.08	134
13	14	58.18	172.49	286.4	642
14	15	393.19	1258	2810.75	5850
15	16	2424	7225	17265.5	36361

		Memory (MB)			
$n$	$m$	M4GB	FGb	Magma	OpenF4
10	11	17	33	32	101
11	12	16	50	64	341
12	13	31	112	114	1463
13	14	74	323	281	7622
14	15	250	1098	1104	33460
15	16	837	4118	3320	117396

# Graph for $m = n + 1$



# Table of Contents

- 1 Introduction
- 2 Gröbner Basis
- 3 M4GB Algorithm
- 4 Performance Comparison
- 5 Solving MQ Challenges**

## Solved MQ Challenges

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$	IV	V	VI
	$m \geq 55$	$m \geq 16$	$m \geq 16$

## Solved MQ Challenges

	$\mathbb{F}_2$	$\mathbb{F}_{2^8}$	$\mathbb{F}_{31}$
$m = 2n$	I	II	III
	$n \geq 55$	$n \geq 35$	$n \geq 34$
$m \approx 2/3n$	IV	V	VI
	$m \geq 55$	$m \geq 16$	$m \geq 16$

# Solving Strategy

# Solving Strategy

- Hybrid approach

# Solving Strategy

- Hybrid approach
- Idea :



# Solving Strategy

- Hybrid approach
- Idea :
  - 1 Randomly select  $(a_1, \dots, a_{n-m}) \in \mathbb{F}_q^{n-m}$

# Solving Strategy

- Hybrid approach
- Idea :
  - 1 Randomly select  $(a_1, \dots, a_{n-m}) \in \mathbb{F}_q^{n-m}$
  - 2 Construct

$$\tilde{F} = \{f(x_1, \dots, x_m, a_1, \dots, a_{n-m}) : \forall f \in F\}$$

# Solving Strategy

- Hybrid approach

- Idea :

- 1 Randomly select  $(a_1, \dots, a_{n-m}) \in \mathbb{F}_q^{n-m}$

- 2 Construct

$$\tilde{F} = \{f(x_1, \dots, x_m, a_1, \dots, a_{n-m}) : \forall f \in F\}$$

- 3 Select small positive integer  $k$  (e.g. 1 or 2)

# Solving Strategy

- Hybrid approach

- Idea :

- 1 Randomly select  $(a_1, \dots, a_{n-m}) \in \mathbb{F}_q^{n-m}$

- 2 Construct

$$\tilde{F} = \{f(x_1, \dots, x_m, a_1, \dots, a_{n-m}) : \forall f \in F\}$$

- 3 Select small positive integer  $k$  (e.g. 1 or 2)

- 4 Generate  $q^k$  subsystems

$$\{\tilde{F}(x_1, \dots, x_{n-k}, v_1, \dots, v_k) : (v_1, \dots, v_k) \in \mathbb{F}_q^k\}$$

# Solving Strategy

- Hybrid approach

- Idea :

- 1 Randomly select  $(a_1, \dots, a_{n-m}) \in \mathbb{F}_q^{n-m}$

- 2 Construct

$$\tilde{F} = \{f(x_1, \dots, x_m, a_1, \dots, a_{n-m}) : \forall f \in F\}$$

- 3 Select small positive integer  $k$  (e.g. 1 or 2)

- 4 Generate  $q^k$  subsystems

$$\{\tilde{F}(x_1, \dots, x_{n-k}, v_1, \dots, v_k) : (v_1, \dots, v_k) \in \mathbb{F}_q^k\}$$

- 5 Compute Gröbner basis of each subsystem

# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)

# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration
V	24/16			
V	25/17			
V	27/18			

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)

# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration
V	24/16	A	1	$\approx 9.3$ hours
V	25/17			
V	27/18			

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)



# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration
V	24/16	A	1	$\approx 9.3$ hours
V	25/17	B	1	$\approx 46.33$ hours
V	27/18	B	2	$\approx 10.9$ days

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)

# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration
V	24/16	A	1	$\approx 9.3$ hours
V	25/17	B	1	$\approx 46.33$ hours
V	27/18	B	2	$\approx 10.9$ days
VI	24/16			
VI	25/17			
VI	27/18			
VI	28/19			

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)

# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration
V	24/16	A	1	$\approx 9.3$ hours
V	25/17	B	1	$\approx 46.33$ hours
V	27/18	B	2	$\approx 10.9$ days
VI	24/16	A	1	$\approx 1.2$ hours
VI	25/17			
VI	27/18			
VI	28/19			

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)

# Summary of Solved Challenges

Type	$n/m$	Machine Used	# Node	Duration
V	24/16	A	1	$\approx 9.3$ hours
V	25/17	B	1	$\approx 46.33$ hours
V	27/18	B	2	$\approx 10.9$ days
VI	24/16	A	1	$\approx 1.2$ hours
VI	25/17	B	1	$\approx 9.87$ hours
VI	27/18	B	1	$\approx 31.48$ hours
VI	28/19	B	2	$\approx 7.61$ days

A) Intel(R) Core(TM) i7-2600K CPU @3.40GHz and 16GB RAM (Desktop)

B) Intel(R) Xeon(R) CPU E5-2650 v3 @ 2.30GHz and 128GB RAM (NUMA)

<https://github.com/cr-marcstevens/m4gb>

Question ?