



IOS Command Line Interface Router#config terminal Enter configuration commands, one per line. End with ${\tt CNTL/Z}$. Router(config) #ip address 10.0.0.1 255.0.0.0 % Invalid input detected at '^' marker. Router(config) #ip address 10.0.0.1 255.0.0.0 % Invalid input detected at '^' marker. Router(config)#interface fastetherner2/0 % Invalid input detected at '^' marker. Router(config) #interface fa0/0 Router(config-if) #ip address 10.0.0.1 255.0.0.0 Router(config-if) #no shutdown Router(config-if)# %LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up exit Router(config)# Ctrl+F6 to exit CLI focus Сору Paste


Тор


NUMBER Config CLI Attributes Physical IOS Command Line Interface Router(config) #interface fa0/0 Router(config-if) #ip address 10.0.0.1 255.0.0.0 Router(config-if) #no shutdown Router(config-if)# %LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up exit Router(config) #config terminal %Invalid hex value Router(config) #interface se2/0 Router(config-if) #ip address 20.0.0.1 255.0.0.0 Router(config-if) #encapsulation ppp Router(config-if)#clock rate 64000 Router(config-if) #no shutdown %LINK-5-CHANGED: Interface Serial2/0, changed state to down Router (config-if) #wxit % Invalid input detected at '^' marker. Router(config-if)# Ctrl+F6 to exit CLI focus Copy Paste Top Router1 X Config CLI Attributes Physical IOS Command Line Interface Would you like to enter the initial configuration dialog? [yes/no]: no Press RETURN to get started! Router>enable Router#config terminal Enter configuration commands, one per line. End with CNTL/Z. Router(config) #interface se2/0 Router(config-if) #ip address 20.0.0.2 255.0.0.0 Router(config-if) #encapsulation ppp Router(config-if) #clock rate 64000 This command applies only to DCE interfaces Router(config-if) #no shutdown Router(config-if)# %LINK-5-CHANGED: Interface Serial2/0, changed state to up %LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up exit Router(config)# Ctrl+F6 to exit CLI focus Copy Paste Тор











] Тор

