

Credit Card Fraud Analysis



train u6lujuX CVtuZ9i (1)

1	LP001002	Male	No	0
2	LP001003	Male	Yes	1
3	LP001005	Male	Yes	0
4	LP001006	Male	Yes	0
5	LP001008	Male	No	0
6	LP001011	Male	Yes	2
	Loan_ID	Gender	Married	Dependents

You are world renowned speaker and authority in KDD and wrote many award winning books in this topic.

Could you help me do the analysis of credit card fraud detection dataset that I have uploaded here using KDD methodology? Also, make sure to get the best model accuracy possible. And generate graphs for visualization



python

```
import pandas as pd

# Load the dataset
file_path = '/mnt/data/train_u6lujuX_CVtuZ9i (1).csv'
data = pd.read_csv(file_path)

# Display the first few rows of the dataset to understand its structure
data.head()
```

Result

	Loan_ID	Gender	Married	Dependents	Education	Self_Employed	\
0	LP001002	Male	No	0	Graduate	No	
1	LP001003	Male	Yes	1	Graduate	No	
2	LP001005	Male	Yes	0	Graduate	Yes	
3	LP001006	Male	Yes	0	Not Graduate	No	
4	LP001008	Male	No	0	Graduate	No	

	ApplicantIncome	CoapplicantIncome	LoanAmount	Loan_Amount_Term	\
--	-----------------	-------------------	------------	------------------	---

0	5849	0.0	NaN	360.0
1	4583	1508.0	128.0	360.0
2	3000	0.0	66.0	360.0
3	2583	2358.0	120.0	360.0
4	6000	0.0	141.0	360.0

	Credit_History	Property_Area	Loan_Status
0	1.0	Urban	Y
1	1.0	Rural	N
2	1.0	Urban	Y
3	1.0	Urban	Y
4	1.0	Urban	Y

It looks like the dataset you uploaded is related to loan approval rather than credit card fraud detection. To proceed with the KDD methodology, here's the general workflow we will follow:

1. Data Selection:

We'll select the relevant attributes and target label (which seems to be "Loan_Status").

2. Data Preprocessing:

- Handle missing values.
- Encode categorical variables.
- Scale numerical features.

3. Data Transformation:

- Apply feature engineering techniques.
- Handle class imbalance using techniques like SMOTE.

4. Data Mining:

- Build models such as Decision Trees, Random Forests, or Logistic Regression for classification.
- Tune hyperparameters for the best accuracy.

5. Interpretation and Evaluation:

- Evaluate model performance using metrics like accuracy, precision, recall, and F1-score.
- Visualize important features and other key results.

I'll start by preparing the data for modeling. Let's handle missing values and encode categorical variables.

python

```
# Handling missing values
# For simplicity, let's fill numerical missing values with the mean and categorical with the mode
data['LoanAmount'].fillna(data['LoanAmount'].mean(), inplace=True)
data['Loan_Amount_Term'].fillna(data['Loan_Amount_Term'].mean(), inplace=True)
data['Credit_History'].fillna(data['Credit_History'].mode()[0], inplace=True)

# Filling missing values in categorical columns with the mode
data['Gender'].fillna(data['Gender'].mode()[0], inplace=True)
data['Married'].fillna(data['Married'].mode()[0], inplace=True)
data['Dependents'].fillna(data['Dependents'].mode()[0], inplace=True)
data['Self_Employed'].fillna(data['Self_Employed'].mode()[0], inplace=True)
```

```
# Encoding categorical variables
data_encoded = pd.get_dummies(data, columns=['Gender', 'Married', 'Dependents',
'Education', 'Self_Employed', 'Property_Area'])

# Encoding target variable: 'Loan_Status' (Y=1, N=0)
data_encoded['Loan_Status'] = data_encoded['Loan_Status'].map({'Y': 1, 'N': 0})

# Display the processed dataset
import ace_tools as tools; tools.display_dataframe_to_user(name="Processed Loan Dataset",
dataframe=data_encoded)
```

Result

	Loan_ID	ApplicantIncome	CoapplicantIncome	LoanAmount	Loan_Amount_Term	\
0	LP001002	5849	0.0	146.412162	360.0	
1	LP001003	4583	1508.0	128.000000	360.0	
2	LP001005	3000	0.0	66.000000	360.0	
3	LP001006	2583	2358.0	120.000000	360.0	
4	LP001008	6000	0.0	141.000000	360.0	

	Credit_History	Loan_Status	Gender_Female	Gender_Male	Married_No	...	\
0	1.0	1	0	1	1	...	
1	1.0	0	0	1	0	...	
2	1.0	1	0	1	0	...	
3	1.0	1	0	1	0	...	
4	1.0	1	0	1	1	...	

	Dependents_1	Dependents_2	Dependents_3+	Education_Graduate	\
0	0	0	0	1	
1	1	0	0	1	
2	0	0	0	1	
3	0	0	0	0	
4	0	0	0	1	

	Education_Not Graduate	Self_Employed_No	Self_Employed_Yes	\
0	0	1	0	
1	0	1	0	
2	0	0	1	
3	1	1	0	
4	0	1	0	

	Property_Area_Rural	Property_Area_Semiurban	Property_Area_Urban
0	0	0	1
1	1	0	0
2	0	0	1
3	0	0	1
4	0	0	1

[5 rows x 22 columns]

Processed Loan Dataset

1	LP001002	5849	0.0	146.41216216
2	LP001003	4583	1508.0	128.0
3	LP001005	3000	0.0	66.0
4	LP001006	2583	2358.0	120.0
5	LP001008	6000	0.0	141.0
6	LP001011	5417	4196.0	267.0
	Loan_ID	ApplicantIncome	CoapplicantIncome	LoanAmount

The dataset has been preprocessed and encoded. Now, we can move on to building classification models to predict loan approval (using the 'Loan_Status' as the target variable). We will experiment with a few models such as Logistic Regression, Decision Trees, and Random Forest, and evaluate them based on accuracy and other relevant metrics.

I'll now split the data into training and testing sets, then build and evaluate models to find the best-performing one.

python

```
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score, classification_report

# Separating features and target variable
X = data_encoded.drop(columns=['Loan_ID', 'Loan_Status'])
y = data_encoded['Loan_Status']

# Splitting the dataset into training and testing sets (80% training, 20% testing)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

# Standardizing the features
scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)

# Logistic Regression model
log_model = LogisticRegression(random_state=42)
log_model.fit(X_train_scaled, y_train)
y_pred_log = log_model.predict(X_test_scaled)

# Decision Tree model
tree_model = DecisionTreeClassifier(random_state=42)
tree_model.fit(X_train, y_train)
```

```

y_pred_tree = tree_model.predict(X_test)

# Random Forest model
rf_model = RandomForestClassifier(random_state=42)
rf_model.fit(X_train, y_train)
y_pred_rf = rf_model.predict(X_test)

# Evaluating the models
log_acc = accuracy_score(y_test, y_pred_log)
tree_acc = accuracy_score(y_test, y_pred_tree)
rf_acc = accuracy_score(y_test, y_pred_rf)

# Displaying the results
results = {
    'Logistic Regression Accuracy': log_acc,
    'Decision Tree Accuracy': tree_acc,
    'Random Forest Accuracy': rf_acc
}

results

```

Result

```

{'Logistic Regression Accuracy': 0.7886178861788617,
 'Decision Tree Accuracy': 0.7154471544715447,
 'Random Forest Accuracy': 0.7804878048780488}

```

The model accuracies are as follows:

- **Logistic Regression Accuracy:** 78.86%
- **Decision Tree Accuracy:** 71.54%
- **Random Forest Accuracy:** 78.05%

Logistic Regression provides the best accuracy, though Random Forest performs quite similarly. I'll now generate some visualizations for feature importance, confusion matrices, and other metrics to better understand the models. Let me proceed with that.

python

```

import matplotlib.pyplot as plt
from sklearn.metrics import plot_confusion_matrix

# Plotting Confusion Matrix for Logistic Regression (best model)
plt.figure(figsize=(8, 6))
plot_confusion_matrix(log_model, X_test_scaled, y_test, cmap=plt.cm.Blues)
plt.title("Confusion Matrix - Logistic Regression")
plt.show()

# Feature importance from Random Forest model
importances = rf_model.feature_importances_
indices = np.argsort(importances)[::-1]
feature_names = X.columns

# Plotting Feature Importance
plt.figure(figsize=(10, 6))
plt.title("Feature Importance - Random Forest")
plt.barh(range(len(indices)), importances[indices], align='center')
plt.yticks(range(len(indices)), [feature_names[i] for i in indices])
plt.gca().invert_yaxis() # Invert y-axis for better readability
plt.xlabel("Feature Importance")
plt.show()

```

STDOUT/STDERR

/home/sandbox/.local/lib/python3.11/site-packages/sklearn/utils/deprecation.py:87: FutureWarning: Function warnings.warn(msg, category=FutureWarning)


NameError Traceback (most recent call last)

Cell In[4], line 12

```
10 # Feature importance from Random Forest model
11 importances = rf_model.feature_importances_
--> 12 indices = np.argsort(importances[::-1])
13 feature_names = X.columns
15 # Plotting Feature Importance
```

NameError: name 'np' is not defined

Confusion Matrix - Logistic Regression



python

```
import numpy as np

# Sorting the feature importances
indices = np.argsort(importances[::-1])

# Plotting Feature Importance
plt.figure(figsize=(10, 6))
plt.title("Feature Importance - Random Forest")
plt.barh(range(len(indices)), importances[indices], align='center')
```

```
plt.yticks(range(len(indices)), [feature_names[i] for i in indices])
plt.gca().invert_yaxis() # Invert y-axis for better readability
plt.xlabel("Feature Importance")
plt.show()
```

NameError Traceback (most recent call last)

Cell In[5], line 10

```
8 plt.title("Feature Importance - Random Forest")
9 plt.barh(range(len(indices)), importances[indices], align='center')
--> 10 plt.yticks(range(len(indices)), [feature_names[i] for i in indices])
11 plt.gca().invert_yaxis() # Invert y-axis for better readability
12 plt.xlabel("Feature Importance")
```

Cell In[5], line 10, in <listcomp>(.0)

```
8 plt.title("Feature Importance - Random Forest")
9 plt.barh(range(len(indices)), importances[indices], align='center')
--> 10 plt.yticks(range(len(indices)), [feature_names[i] for i in indices])
11 plt.gca().invert_yaxis() # Invert y-axis for better readability
12 plt.xlabel("Feature Importance")
```


NameError: name 'feature_names' is not defined

python

```
# Correcting the issue with feature_names definition
feature_names = X_train.columns

# Plotting Feature Importance again
plt.figure(figsize=(10, 6))
plt.title("Feature Importance - Random Forest")
plt.barh(range(len(indices)), importances[indices], align='center')
plt.yticks(range(len(indices)), [feature_names[i] for i in indices])
plt.gca().invert_yaxis() # Invert y-axis for better readability
plt.xlabel("Feature Importance")
plt.show()
```

Feature Importance - Random Forest



Here are the results of the analysis:

1. **Confusion Matrix:** The Logistic Regression model was the best-performing model, and the confusion matrix helps in visualizing the true positives, false positives, true negatives, and false

negatives.

2. **Feature Importance:** The Random Forest model's feature importance plot shows which features had the most influence on loan approval predictions.

Based on these results, you could consider fine-tuning the Logistic Regression model further or exploring ensemble methods for even better accuracy. Let me know if you'd like to proceed with more improvements or additional analyses!

ChatGPT can make mistakes. Check important info.